



**FrontRunner™**

# THE EXMARK FRONTRUNNER™.

FRONT-MOUNT PERFORMANCE, EXMARK® QUALITY AND PROVEN TECHNOLOGY FROM THE LEADER IN PROFESSIONAL MOWING EQUIPMENT.

- **Hydraulic, push-button, power deck-fold system:** With one push of a button, the deck lifts to an upright position, giving you access to the underside for easy maintenance and cleaning.
- **Full-floating UltraCut™ deck:** Floats over uneven terrain to deliver a superior cut.
- **Superior weight-transfer system:** Keeps the weight on drive tires to maintain traction and reduce turf damage.

## FRONTRUNNER™

MODEL	ENGINE	CUTTING WIDTH
FR23 KC	23 hp Kohler® Command™ SP	
FR27 KC	27 hp Kohler Command SP	
FR31 BV	31 hp Vanguard™	
FR25 KD	25 hp Kubota® Diesel	
FR524		52" (132 cm)
FR604		60" (152 cm)
FR724		72" (183 cm)



BEST-SELLING BRAND OF MOWING EQUIPMENT FOR THE LANDSCAPE PROFESSIONAL.

[WWW.EXMARK.COM](http://WWW.EXMARK.COM)

# OF COURSE, IT'S AN EXMARK®

Since opening our doors, we've been busy making high-quality, professional-grade mowers. And the FrontRunner™ is no exception. We take pride in the fact that anything bearing the Exmark® name is an exceptional piece of equipment. You can feel confident knowing that it's the brand landscape pros choose 2 to 1 over any other. Visit [exmark.com](http://exmark.com)

## DECK CONSTRUCTION

5.5" deep UltraCut™ Deck  
7-gauge sides joined by a continuous bead weld to a 10-gauge top  
4-point suspension, full-floating deck with six adjustable anti-scalp rollers

## CUTTING WIDTH

52", 60" or 72"

## CUTTING HEIGHTS

1.5" to 5.0" hydraulic cut height adjustment

## PTO ENGAGEMENT

MagStop Electromagnetic 200 ft-lbs clutch with spot brake. 2 year warranty.

## DECK LIFT AND FOLD

Standard hydraulic deck-fold, to approximately 70° (full-fold position)

## FRONT CASTER TIRES

9 x 3.5-4, semi-pneumatic

## FRONT CASTERS

3/8" thick double-yoke, smooth tread caster wheel assembly with pre-installed needle roller bearings

## REAR CASTER TIRE

13 x 6.50-6, semi-pneumatic

## REAR CASTERS

23 hp model single tail wheel—standard  
25 hp diesel, 27 and 31 hp models dual tail wheel—standard  
1/2" thick double-yoke, smooth tread caster wheel assembly with pre-installed bearing cups

## DRIVE TIRES

23 hp model 23 x 10.50-12, 4-ply Turf Mate® turf tread  
25 hp diesel, 27 and 31 hp models 24 x 12-12, 4-ply AT101 bar lug tread

## TRACTOR

TRACTOR	WEIGHT
23 hp Kohler® Command™ SP	906 lbs
27 hp Kohler Command SP	925 lbs
31 hp Vanguard™	960 lbs
25 hp Kubota® Diesel	1099 lbs

## DECK

DECK	WEIGHT
52"	360 lbs
60"	430 lbs
72"	lbs

## TRACTOR WIDTH

Turf Mate® tires, 49.2" AT101 tires, 53.1"

## LENGTH

Single tail wheel, 112.5" Dual Tail Wheel, 109.5"

## HEIGHT

68.8"

## ROLL OVER PROTECTION

Standard

## SEAT BELT

Standard

## 2-YEAR WARRANTY\*

Standard



BEST-SELLING BRAND OF MOWING EQUIPMENT FOR THE LANDSCAPE PROFESSIONAL.

[WWW.EXMARK.COM](http://WWW.EXMARK.COM)

EXMARK MANUFACTURING COMPANY INC. • 2101 ASHLAND AVENUE • P.O. BOX 808 • BEATRICE, NE 68310-0808 • CALL 402.223.6300 • FAX 402.223.6384

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations.

\*See your dealer for details on all of our warranties. Exmark® is a registered trademark, and FrontRunner™ is a trademark of Exmark Mfg. Co., Inc. ©2007 Exmark Manufacturing Company, Inc. All rights reserved. Printed in the U.S.A. 2007