



THE EXMARK LAZER Z[®] XS

HIGH HORSEPOWER PERFORMANCE IN THE
TOP-OF-THE-LINE, HEAVY-DUTY COMMERCIAL Z.

- 29 hp Liquid-Cool Kawasaki[®] DFI
- 25 hp Kubota[®] Diesel
- 35 hp Vanguard[™] V-Twin
- Triton[®] High-Capacity Cutting Deck
- Twin 21cc Hydro-Gear variable displacement pumps:
High performance mechanical cooling fans located on front
of each pump
- Hydro-Gear high-torque wheel motors for
increased performance
- Easy access hood release for liquid-cooled and
diesel models



BEST-SELLING BRAND OF MOWING EQUIPMENT FOR THE LANDSCAPE PROFESSIONAL.

WWW.EXMARK.COM

OF COURSE, IT'S AN EXMARK®

Since opening our doors, we've been busy making high-quality, professional-grade mowers. And the Lazer Z® XS is no exception. We take pride in the fact that anything bearing the Exmark® name is an exceptional piece of equipment. You can feel confident knowing that it's the brand landscape pros choose 2 to 1 over any other. Visit exmark.com

DECKS

STYLE — Triton® High-Capacity Cutting Deck side-discharge standard with option to bag or mulch.

WIDTHS AVAILABLE

60", 66" and 72" 10-gauge top that is formed and continuously seam welded, with 10-gauge top reinforcement plate, 7-gauge side skirt and 7-gauge reinforcement rings at spindle assembly. 6" deep, 4-point suspension full-floating deck with 6 adjustable cone-shaped anti-scalp rollers.

CUTTING HEIGHTS

1.0" (2.5 cm) to 5" (12.7 cm) in 0.25" (0.64 cm) increments and adjustable from operator's seat.

TRACTOR FRAME

Welded, heavy-duty tubular steel.

STEERING & MOTION CONTROL

Hydraulically dampened twin levers adjust fore and aft.

FRONT CASTER TIRES

13 x 6.50-6, smooth tread, semi-pneumatic tires.

DRIVE TIRES

26 x 12-12, 4-ply Multi-Trac®.

TURNING RADIUS

True zero-turn.

PARKING BRAKE

Lever-actuated drum and band integrated with transmission-neutral interlock.

SEAT

Deluxe, low-profile, full-suspension seat adjusts to individual operator weight and features padded armrests.

ENGINES AVAILABLE

29 hp Kawasaki® Liquid-Cooled V-Twin w/digital fuel injection, 35 hp air-cooled Vanguard™ V-Twin, governed to 3750 rpm; 25 hp Kubota® 3-Cylinder Liquid-Cooled Diesel, governed to 3850 rpm.

DRIVE SYSTEM

Two Hydro-Gear 21cc/rev pumps with integral SCR (System Check Relief) valves (in forward), powering two Hydro-Gear wheel motors with 1.25" (3.18 cm) diameter tapered shafts.

SPEED

Infinitely variable speed selection from 0-12 mph (19.3 kmph) forward, 0-8.0 mph (12.9 kmph) reverse.

PTO ENGAGEMENT

MagStop Electromagnetic 200 ft-lbs clutch with spot brake on 29 hp. MagStop Electromagnetic 250 ft-lbs clutch with spot brake on 35 hp and 25 hp diesel models. 2-year warranty.

FUEL CAPACITY

15.5-gal. (58.7-L) twin fuel tanks.

LAZER Z® XS

MODEL	ENGINE	CUTTING WIDTH
LXS29LKA605	29 hp Kawasaki DFI	60" Triton
LXS29LKA725	29 hp Kawasaki DFI	72" Triton
LXS25KD605	25 hp Kubota Diesel	60" Triton
LXS25KD665	25 hp Kubota Diesel	66" Triton
LXS25KD725	25 hp Kubota Diesel	72" Triton
LXS35BV605	35 hp Vanguard	60" Triton
LXS35BV665	35 hp Vanguard	66" Triton
LXS35BV725	35 hp Vanguard	72" Triton



BEST-SELLING BRAND OF MOWING EQUIPMENT FOR THE LANDSCAPE PROFESSIONAL.

WWW.EXMARK.COM

EXMARK MANUFACTURING COMPANY INC. • 2101 ASHLAND AVENUE • P.O. BOX 808 • BEATRICE, NE 68310-0808 • CALL 402.223.6300 • FAX 402.223.6384

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer

for details on all of our warranties. Exmark® and Lazer Z® are registered trademarks, and Triton™ is a trademark of Exmark Mfg. Co., Inc. ©2007 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2007