



AN AMERICAN WORKHORSE SINCE 1916

HARDWORKING, HEAVY IRON, THAT DOESN'T KNOW THE MEANING OF DOWNTIME.



PROFESSIONAL

Accessories/ Attachments

Standard:

FOLDABLE ROPS
SUSPENSION SEAT

Optional:

55" SNOW BLOWER
60" ROTARY SWEEPER
60" SNOW BLADE
3-BUCKET X-TREME FLO™ BAGGER
BAR STYLE TIRE KIT
DISCHARGE COVER KIT
ELECTRIC DECK LIFT KIT
FLEXTEND™ SHOULDER SUPPORT SYSTEM
HEADLIGHT KIT
LIFT MASTER®
MULCHING KIT
OPERATOR CONTROLLED CHUTE BAFFLE
POWERED BAGGER KIT
SOLID FRONT TIRE KIT
STRIPING KIT
VACUUM BAFFLE
WHEEL COVERS

Pro-Master™ 200 XDZ Series

- **Lockable, floating front axle** easily adjusts to uneven terrain for added stability and operator comfort
- **7-Gauge fabricated and welded X-Factor® deck design** assures lasting strength and durability
- **Maintenance-free XL Spindles®** with durable cast iron housings
- **Adjustable anti-scalp rollers** and hardened steel blades efficiently integrate for a beautifully manicured finish.
- **1/2" Wear bar** and two additional gussets guard against leading edge or baffle bending
- **Industry leading 1-1/4" front caster forks** enhance maneuverability
- **Large diameter steering arms** and vibration isolators add operator comfort and control
- **Ergonomically designed cockpit** with comfort-grip handles, easy-access controls
- **Suspension seat** with adjustable armrests elevates operator productivity by minimizing fatigue.
- **Available in several fuel source options** including liquefied petroleum (LP) that burns cleaner which reduces emissions and lowers engine maintenance.
- **Hydraulic or mechanical deck lift** available



PRO-MASTER™ 200 XDZ SERIES

PRODUCT NAME	252M	260M	260H	260H	266H	272H	260H LP	260H	272H	
MODEL NUMBER	992191	992188	992189	992190	992192	992193	992194	992195	992196	
ENGINE	Kawasaki® FX	Kawasaki® FX	Kawasaki® FX	Kohler® Command	Kawasaki® FX	Kawasaki® FX	Generac®	Briggs & Stratton® - Daihatsu®		
	Air-cooled Verticak Twin							Liquid-cooled Horizontal Diesel™		
	Heavy-Duty Air Cleaner									
HORSEPOWER	27	27	27	27	31	31	28	27	31	
DISPLACEMENT (cc)	852	852	852	725	852	852	992	950	950	
DRIVE SYSTEM	Hydro-Gear 21cc Pump with Parker 18 c.i. Wheel motors									
FUEL CAPACITY - Gallons (LITERS)	13 gallon (49L)	13 gallon (49L)	13 gallon (49L)	13 gallon (49L)	13 gallon (49L)	13 gallon (49L)	Twin 33.5 lb LP Tanks (Not Included)	13 gallon (49L)	13 gallon (49L)	
GROUND SPEED (APPROX. Mph) (Forward/Reverse)	13 mph/6 mph	13 mph/6 mph	13 mph/6 mph	13 mph/6 mph	13 mph/6 mph	13 mph/6 mph	13 mph/6 mph	13 mph/6 mph	13 mph/6 mph	
STARTER	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	Electric	
DECK										
DECK MATERIAL	7 ga steel with .25 inch spindle reinforcement									
DECK CONSTRUCTION	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded	
NUMBER OF SPINDLES	3	3	3	3	3	3	3	3	3	
BLADE TIP SPEED (FPM)	18,000	18,000	18,000	18,000	18,000	18,000	18,000	18,000	18,000	
SPINDLE HOUSING MATERIAL	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	
SPINDLE SHAFT	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel	Steel	
SPINDLE BEARINGS	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	Ball Bearing	
DECK DRIVE	Belt	Belt	Belt	Belt	Belt	Belt	Belt	Belt	Belt	
DECK ENGAGEMENT	Ogura GT3.5 Electric Clutch									
DECK LIFT SYSTEM	Foot Operated	Foot Operated	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	
CUTTING WIDTH	52	60"	60"	60"	66"	72"	60"	60"	72"	
CUTTING HEIGHTS	1"-5"	1"-5"	1"-5"	1"-5"	1"-5"	1"-5"	1"-5"	1"-5"	1"-5"	
CUTTING POSITIONS	17	9	17	17	17	17	17	17	17	
WHEELS										
FRONT AXLE	Pivoting/Locking									
FRONT	Ribbed 15 x 6-6									
REAR	Turf 24 x 11.5-12									
FEATURES										
HOOD	Standard									
SEAT	High Back w/ Full Suspension									
HOOR METER	Standard									
MACHINE DIMENSION										
WEIGHT (lbs)	1272	TBD	TBD	TBD	TBD	TBD	TBD	TBD	1677	
LENGTH (inches)	82	82	82	82	82	82	82	83.5	83.5	
WIDTH (inches)	55.5 w/o chute			63 w/o chute	69 w/o chute	75 w/o chute	63 w/o chute	63 w/o chute	75 w/o chute	
HEIGHT W/ ROPS EXT/DOWN (inches)	72/48	72/48	72/48	72/48	72/48	72/48	72/48	72/48	72/48	
WARRANTY										
UNIT	2 Year Limited Commercial									
DECK SHELL & FRAME	Limited Lifetime Deck Shell & Frame									
SPINDLES	3 Year Limited Spindle									