

Rear Blades

RBT45 Series		
	RBT4596	RBT45108
Blade Width	96"	108"
Approximate Weight (lbs.) with hydraulic links	1130	1166
Maximum Engine Horsepower	125	
Maximum G.V.W. (lbs.)	9500	
Hitch Type	Cat. 2 & 3 (Fits Land Pride Quick Hitch)	
Blade Angle	15 positions up to 45 degrees clockwise and counter clockwise forward and same for reverse. (Center, 7 clockwise and 7 counter clockwise)	
Manual Linkage:	Infinite number of positions up to 45 degrees clockwise and counterclockwise forward and same for reverse.	
Hydraulic Cylinder:		
Angle Cylinder	4" X 16"	
Blade Tilt	Up to 15 degrees left and right.	
Manual Ratchet Jack	Infinite number of positions up to 15 degrees left and right.	
Hydraulic Cylinder:		
Tilt Cylinder	3" X 6"	
Blade Offset	15 positions up to 35 inches. (Center, 7 left and 7 right)	
Manual Linkage:	Infinite number of positions up to 35 inches left and right.	
Hydraulic Cylinder:		
Offset Cylinder	4" X 16"	
Moldboard Height	19"	
Moldboard Thickness	5/16" with 1/4" boxed reinforcement	
Cutting Edge	1/2" x 6" Heat treated and reversible	
Main Frame	Fully enclosed welded, formed box	
Parking Stand	Retractable	
Options	Skid Shoes, End Plates, Single or Dual Gauge Wheel, Double Selector Valve, Cushion Valve	

Designs, specifications, features and information are subject to change without notice.