

New Holland 300GM Series Rear-Mounted Finishing Mower Specifications



310GM 320GM 330GM

MODEL	310GM	320GM	330GM
PACKAGE	100	200	300
SIZE, in. (mm)	60 (1524)	72 (1829)	90 (2286)
3-PT mounted, floating hitch		Category I	
Discharge, rear only		Rear	
Discharge safety chain		Standard	
Size, cutting width, in. (mm)	60 (1524)	72 (1829)	90 (2286)
PTO HP rating	up to 30	up to 40	up to 60
Number of blades	3	3	5
Blade speed, rpm	2,630	2,230	2,630
Standard PTO, rpm		540	
V belt drive		Standard	
Cutting height range, in. (mm)		1 to 4 (25 to 102)	
Solid rubber gauge wheels, fully rotating		4	
Weight, lbs. (kg)	435 (197)	500 (227)	683 (310)

Visit our Web site at www.newholland.com/na. Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.