

New Holland G Series Zero-Turn-Radius Mower Specifications



G4010 G4020 G4030 G4035 G4050

MODELS	G4010	G4020	G4030	G4035	G4050
ENGINE					
Horsepower, hp (kW)	19 (14.2)	21 (15.7)	23 (17.2)	25 (18.6)	25 (18.6)
Make	Kohler Courage SV590	Kohler Courage SV610	Kohler Courage SV720	Kohler Courage SV730	Kohler Courage PRO
No. of cylinders	1	1	2	2	2
Cooling system	Air				
Fuel capacity, gal. (L)	3 (11.4)			4 (15.1)	
Full pressure lubrication	Standard				
Starter key w/safety interlock	Standard				
Air cleaner	Standard				

DRIVE SYSTEM

Type	Dual hydrostatic: transaxle with integral pump and motor; one at each wheel				Twin hydro-gear ZT2800 hydrostatic transaxle with charge pumps
Max speed, forward, mph (kph)	7.0 (11.3)				
Max speed, reverse, mph (kph)	3.4 (5.5)	3.4 (5.5)	3.4 (5.5)	5 (8.0)	5 (8.0)
Implement clutch	Electric				

BRAKES

Service brake	Hydrostatic dynamic braking				
Parking brake lock	Automatic engagement with steering levers in neutral				Manual LH lever

ELECTRICAL

Voltage	12 volts				
Charging system (amps)	15				

OPERATOR STATION AND CONTROLS

Steering	Dual padded lever hydrostatic with hydraulic dampening				
Seat type, adjustable fore and aft	Contoured, high back			18" high back	18" high back
Armrests	Optional	Optional	Standard	Standard	Standard
Cup holder	Standard				
Storage bin	Standard				
Front casters	Double yoke				

WHEELS AND TIRES

Front Casters	10 x 4 ribbed	10 x 4 smooth	10 x 4 smooth	10 x 4 smooth	10 x 4 smooth
Rear	18 x 7.5-8, 2-ply	18 x 9.5-8, 2-ply	18 x 9.5-8, 2-ply	18 x 9.5-8, 2-ply	20 x 10, 4-ply

DIMENSIONS, in. (cm)

Length, overall					
with grass catcher	90.0 (228.6)				NA
less grass catcher	73.1 (185.7)				
Width, overall					
with deck deflector down	53.8 (136.7)	63.0 (160.0)	63.0 (160.0)	63.0 (160.0)	65.5 (166.4)
with deck deflector up	46.0 (116.8)	53.5 (135.9)	53.5 (135.9)	53.5 (135.9)	53.0 (134.6)
with grass catcher	52.8 (134.1)	56.8 (144.3)	56.8 (144.3)	56.8 (144.3)	NA
Height, overall, to top of seat	37.2 (94.5)	40.2 (102.1)	40.2 (102.1)	40.2 (102.1)	42.2 (107.2)
Wheelbase	48.1 (122.2)				46.4 (117.9)
Turning radius, inside rear wheel	Zero turn				
Net weight, estimated, lb. (kg)	500 (226.8)	552 (250.4)	565 (256.3)	565 (256.3)	649 (294.4)

New Holland G Series Zero-Turn-Radius Mower Specifications



G4010 G4020 G4030 G4035 G4050

MODELS	G4010	G4020	G4030	G4035	G4050
MOWER DECKS					
(optional mulching kits available)					
42 in. (107 cm) side discharge	Standard	NA	NA	NA	NA
50 in. (127 cm) side discharge	NA	Standard	Standard	Standard	NA
52 in. (132 cm) side discharge	NA	NA	NA	NA	Standard
Spindles	2	3	3	3	3
Anti-scalp gauge wheels	Standard				
ATTACHMENTS & ACCESSORIES					
2-bag grass catcher (8 cu. ft./23 m ³)	Optional	Optional	Optional	NA	Optional
Rear engine guard	Optional	Standard	Standard	Standard	Standard
Engine top cover	Optional				
Foot assist height of cut kit	Optional	Optional	Standard	Standard	Standard
Smooth-tread front tires	Optional	Standard	Standard	Standard	Standard
Sunshade kit	NA				
Hitch kit	Optional				
Front light kit	NA				
Rubber floor mat	Optional	Optional	Optional	Optional	Optional
Mulch kit	Optional				
WARRANTY	3 year limited				

Visit our Web site at www.newholland.com/na. Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.