

New Holland Tedders / Rake Tedder

157 163 H5270 / 255



TEDDER SPECIFICATIONS	157	163 MANUAL FOLD	163 HYDRAULIC FOLD	H5270 HYDRAULIC FOLD
Number of rotors	2	4	4	6
Tines per rotor	6	6	6	7
Overall width in operating position, ft. in. (m)	10' 2" (3.10)	17' 8" (5.38)	17' 8" (5.38)	25' 7" (7.8)
Tedding width, ft. in. (m)	8' 6" (2.60)	16' 5" (5.0)	16' 5" (5.0)	27' 7" (8.4)
Transport width, ft. in. (m)	8' 0" (2.40)	9' 2" (2.79)	9' 2" (2.79)	9' 10" (3)
Weight, lbs. (kg)	441 (200)	986 (447)	950 (431)	1874 (850)
Tires	15 x 6 x 6	15 x 6 x 6	15 x 6 x 6	Two 18 x 8.50 - 8 center/ Four 16 x 16.50 - 8 outer
PTO Tractor requirement, hp (kW)	15 (11)	20 (15)	20 (15)	35 (26.1)
PTO slip clutch	Standard	Standard	Standard	Standard
Tractor attachment	3-point	Towed	Towed	Towed
Tractor remote valves required	none	none	one	one
Safety Tow Chains	N/A	Standard	Standard	Standard

RAKE TEDDER SPECIFICATIONS	255
Number of rotors	2
Arms per rotor	6
Tines per arm	2 double tines
Tedding width, ft. in. (m)	10' 6" (3.20)
Raking width, ft. in. (m)	10' 6" (3.20) to 13' 1-1/2" (4.00)
Transport width, in. (m)	10 (3.05)
Weight, lbs. (kg)	897 (407)
Tires	15 X 6 X 6, 4-ply
Tractor requirement, hp (kW)	30 (22.3) and 540 rpm PTO

Visit our Web site at www.newholland.com/na. Or, call toll-free **866-NEW-HLND (866-639-4563)**.

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.



Safety begins with a thorough understanding of the equipment. Always make sure you and your operators read the Operator's Manual before using the equipment. Pay close attention to all safety and operating decals and never operate machinery without all shields, protective devices and structures in place.