

Extron® Electronics

INTERFACING, SWITCHING AND DISTRIBUTION



**AUDIO VIDEO DISTRIBUTION AMPLIFIERS
MDA 3AV RCA, MDA 5AV RCA, & MDA 5SVA RCA**

Video inputs and outputs on female BNC connectors (composite) or 4-pin mini-DIN connectors (S-video)

Distributes unbalanced stereo audio on RCA connectors

435 MHz (-3db) video bandwidth on composite models

270 MHz (-3db) video bandwidth on S-video models

Metal enclosure
1U high Rack mountable
(half rack width)



www.extron.com

DESCRIPTION

The Extron MDA 3AV RCA, MDA 5AV RCA, and MDA 5SVA RCA Mini Distribution Amplifiers (MDAs) are compact distribution amplifiers for the distribution of a single source input to multiple outputs and are ideal for a wide range of A/V applications including boardrooms, training facilities, home theater, command and control centers, and rental and staging. The MDA 3AV RCA offers one input, three output composite video and unbalanced stereo audio on RCA connectors. The MDA 5AV RCA offers one input, five output composite video on BNC connectors and unbalanced stereo audio on RCA connectors. The MDA 5SVA RCA offers 1x5 S-video on 4-pin mini-DIN and unbalanced stereo audio on RCA connectors. The input on all three models feature a separate, passive loop-through channel that can be used to chain together several MDAs to provide additional outputs. MDAs are housed in half rack width, 1U metal enclosures and include an internal power supply that will accept 100-240VAC.

FEATURES

- Video inputs and outputs on female BNC connectors or 4-pin mini-DIN connectors
- NTSC, PAL, and SECAM compatible
- Accepts and distributes unbalanced stereo audio on RCA connectors
- 435 MHz (-3db) video bandwidth on composite models; 270 MHz (-3db) video bandwidth on S-video models
- Metal enclosure
- 1U high rack mountable (half rack width)

SPECIFICATIONS

Video

Gain	Unity
Bandwidth	
MDA 5SVA RCA	270 MHz (-3dB)
MDA 3AV RCA, MDA 5AV RCA	435 MHz (-3dB)
Differential phase error	0.05°, 0 to 50 MHz
Differential gain error	<0.05%, 0 to 50 MHz
K factor	<0.05%

Video input

Number/signal type	
MDA 5SVA RCA	1 NTSC/PAL S-video
MDA 3AV RCA, MDA 5AV RCA	1 NTSC/PAL composite video

Connectors

MDA 5SVA RCA	1 4-pin mini DIN female
MDA 3AV RCA, MDA 5AV RCA	1 BNC female

Minimum/maximum level(s)

MDA 5SVA RCA	Y: 0.4V to 2.0V p-p with no offset
MDA 3AV RCA, MDA 5AV RCA	0.4V to 2.0V p-p with no offset

Impedance	75 ohms
Return loss	-40dB @ 0 to 10 MHz
Maximum DC offset	1.0V

Video output

Number/signal type	
MDA 5SVA RCA	6 S-video: 5 amplified for distribution, 1 passive loop-through
MDA 3AV RCA	4 composite video: 3 amplified for distribution, 1 passive loop-through

SPECIFICATIONS (Cont.)

MDA 5AV RCA	6 composite video: 5 amplified for distribution, 1 passive loop-through
-------------------	---

Connectors

MDA 5SVA RCA	6 4-pin mini-DIN
MDA 3AV RCA	4 BNC female
MDA 5AV RCA	6 BNC female

Minimum/maximum level(s)	0.4V to 2.0V p-p
--------------------------------	------------------

Impedance	75 ohms
-----------------	---------

Return loss	-30dB @ 5 MHz
-------------------	---------------

DC offset	±5mV maximum with input at 0 offset
-----------------	-------------------------------------

Sync

Standards	NTSC 3.58, NTSC 4.43, PAL & SECAM
-----------------	-----------------------------------

Audio

Gain	Unity
------------	-------

Frequency response	20 Hz to 20 kHz, ±0.05dB
--------------------------	--------------------------

THD + Noise	0.03% @ 1 kHz at rated maximum output drive
-------------------	---

S/N	>90 dB, at rated maximum output drive
-----------	---------------------------------------

Stereo channel separation	>80 dB @ 1 kHz; >60 dB @ 20 kHz
---------------------------------	---------------------------------

CMRR	>75 dB @ 20 Hz to 20 kHz
------------	--------------------------

Audio input

Number/signal type	1 stereo unbalanced
--------------------------	---------------------

Connectors	2 RCA connectors
------------------	------------------

Impedance	>50 kohms unbalanced, DC coupled
-----------------	----------------------------------

Maximum level	+24 dBu (unbalanced) at stated %THD+N
---------------------	---------------------------------------

Audio output

Number/signal type	
--------------------	--

MDA 5SVA RCA	5 stereo, unbalanced
--------------------	----------------------

MDA 3AV RCA	3 stereo, unbalanced
-------------------	----------------------

MDA 5AV RCA	5 stereo, unbalanced
-------------------	----------------------

Connectors

MDA 5SVA RCA	10 RCA connectors
--------------------	-------------------

MDA 3AV RCA	6 RCA connectors
-------------------	------------------

MDA 5AV RCA	10 RCA connectors
-------------------	-------------------

Impedance	50 ohms unbalanced
-----------------	--------------------

Gain error	±0.1dB channel to channel
------------------	---------------------------

Maximum level (Hi-Z)	>+24dBu, unbalanced at stated %THD+N
----------------------------	--------------------------------------

NOTE: 0dBu = 0.775 volts (RMS).

General

Power	1100VAC to 240VAC, 50/60 Hz, 20 watts, internal, auto-switchable
-------------	--

Rack mount	Yes, with optional 1U rack shelf, part #60-190-01
------------------	---

Enclosure type	Metal
----------------------	-------

Enclosure dimensions	1.7" H x 8.75" W x 9.5" D (1U high, half rack width) 4.2 cm H x 22.2 cm W x 24.1 cm D (Depth excludes connectors)
----------------------------	---

Product weight	2.5 lbs (1.1 kg)
----------------------	------------------

Shipping weight	5 lbs (2.3 kg)
-----------------------	----------------

Listings	UL, CUL
----------------	---------

Compliances	CE, FCC Class A, VCCI, AS/NZS, ICES
-------------------	-------------------------------------

MTBF	30,000 hours
------------	--------------

Model

MDA 3AV RCA	60-443-01
-------------------	-----------

MDA 5AV RCA	60-479-01
-------------------	-----------

MDA 5SVA RCA	60-445-01
--------------------	-----------

Part Number



Extron Electronics, USA
1230 South Lewis Street
Anaheim, CA 92805
800.633.9876 714.491.1500
FAX 714.491.1517

Extron Electronics, Europe
Beeldschermweg 6C, 3821 AH Amersfoort
The Netherlands
+800.3987.6673 +31.33.453.4040
FAX +31.33.453.4050

Extron Electronics, Asia
135 Joo Seng Rd. #04-01
PM Industrial Bldg.
Singapore 368363
+65.6383.4400 FAX +65.6383.4664

Extron Electronics, Japan
Daisan DMJ Bldg. 6F, 3-9-1 Kudan Minami
Chiyoda-ku, Tokyo 102-0074
Japan
+81.3.3511.7655 FAX +81.3.3511.7656