

Specifications*

* Specifications and design subject to change without notice.

Model	ST330		ST333	
Drive	4WD		4WD	
Transmission type	Mech.	HST	Mech.	HST
Engine (Diesel)				
Type	N843		N843	
Power (DIN hp/ kW)	30.0/ 22.4		33.4/ 24.6	
No. of cylinders	3		3	
Displacement (cc)	1496		1496	
Rated speed (rpm)	2800		2800	
Battery (V-A)	12 - 55		12 - 55	
Alternator (A)	40		40	
Fuel tank capacity (l)	29.5		29.5	
PTO				
Type	Trans. w/ one way clutch	Live	Trans. w/ one way clutch	Live
Rear PTO power (hp/ kW)	23.7/ 17.7	23.1/ 17.2	26.0/ 19.4	25.5/ 19.0
Rear (rpm)	616	605	616	605
Mid (rpm)	2300 (option)	2300	2300 (option)	2300
Hydraulic System				
Lift control type: position	standard		standard	
Max. lift capacity (kg)	1400		1400	
3-point hitch	cat. 1		cat. 1	
Travelling system				
Power steering	standard		standard	
Brakes	wet disc		wet disc	
Clutch	dry - single		dry - single	
Standard tyres size				
Agricultural Front	6-14		6-14	
Rear	9.5-24		11.2x24	
Turf Front	25x8.50-14		25x8.50-14	
Rear	13.6-16		13.6-16	
Travelling speed - speed range (at rated engine speed)				
Forward	9	3	9	3
first (km/h)	1.25	0 - 6.01	1.3	0 - 6.01
second (km/h)	1.85	0 - 12.48	1.94	0 - 12.48
third (km/h)	2.65	0 - 25.45	2.78	0 - 25.45
fourth (km/h)	3.95		4.14	
fifth (km/h)	5.84		6.11	
sixth (km/h)	8.37		8.78	
seventh (km/h)	10.12		10.58	
eight (km/h)	14.93		15.65	
ninth (km/h)	21.43		23.05	
Reverse	3	3	3	3
first (km/h)	1.84	0 - 4.21	1.94	0 - 4.21
second (km/h)	5.84	0 - 8.74	6.11	0 - 8.74
third (km/h)	14.93	0 - 17.82	15.65	0 - 17.82
Dimensions				
Overall length (with 3-point hitch) (mm)	2830		2830	
Overall width (mm)	1400		1400	
Overall height (with ROPS) (mm)	2490		2490	
Wheelbase (mm)	1600		1600	
Min. ground clearance (mm)	285		300	
Tread front (mm)	1101		1101	
Tread rear (mm)	1115		1115	
Weight incl. ROPS (kg)	1115	1125	1115	1125



SHIBAURA EUROPE BV
 Begonialaan 7
 NL - 6851 TE Huissen
 Tel. (0031) 026 326 9999
 Fax (0031) 026 326 9990
 E-mail: info@shibaura.com
 www.shibaura.com

Dealer: