S P E C I F I C A T I O N S





	and the second se				
Cutting Width	48"	52"	61"		
Cutting Height Range	1.75 - 4.5"	1.75 - 4.5"	1.75 - 4.5"		-
Deck Lift System	Shims, fixed deck	Shims, fixed deck	Shims, fixed deck	R	1
Deck Construction	7 Gauge	7 Gauge	7 Gauge	B	
Blades (1/4" thick, high-lift wings)	(3) 16.5"	(3) 18"	(3) 21"	R R	
Blade Tip Speed (fpm at 3584 rpm)	19,000	19,000	19,000	ΞĔ	
Spindles	Cast Iron Housings	Cast Iron Housings	Cast Iron Housings	ED	1 -
Blade Clutch/Brake Maintenance-Free; Rated Heavy Duty	Warner™	Warner™	Warner™	/ER-SI	
Discharge Systems	Side, Rear & Mulch	Side, Rear & Mulch	Side, Rear & Mulch	б	
Makes Available	Kawasaki™	Kawasaki™	Kawasaki™, Kohler™		
Horsepower	17, 19, 23	17, 19, 23, 25	23, 25	z	
Cylinders	2	2	2	10	
Starting	17 Recoil 17 Recoil & Electric 19, 23 Electric	17 Recoil & Electric 19, 23, 25 Electric	Electric 23, 25 Electric	NSTRUC	
	23	3 & 25 hp equipt w/ heavy duty a	air cleaner		
Hour Meter	Included	Included	Included	DECI	19
Operator Controls	Quad Lever™	Quad Lever [™]	Quad Lever [™]	ga.	
Hydro Pumps	10 cc	10 cc	10 cc		
Fuel Capacity	6.4 Gal.	6.4 Gal.	6.4 Gal.	–	
Drive Tires	20 x 10 - 8	20 x 10 - 8	20 x 10 - 8		
Caster Tires	11 x 4.0 - 5	11 x 4.0 - 5	11 x 4.0 - 5		-
Speed Forward (mph)	8.4	8.4	8.4	Σ	h C
Speed Reverse (mph)	4.3	4.3	4.3	STE	
Overall Length	55"	56.5"	60"		-
Overall Width - Deflector Up (Down)	49" (59")	53" (63")	62" (72")	DR	6
Dry Weight	765	785	835	TWIN HY	
	Cutting Height Range Deck Lift System Deck Construction Blades (1/4" thick, high-lift wings) Blade Tip Speed (fpm at 3584 rpm) Spindles Blade Clutch/Brake Maintenance-Free; Rated Heavy Duty Discharge Systems Makes Available Horsepower Cylinders Starting Hour Meter Operator Controls Hydro Pumps Fuel Capacity Drive Tires Caster Tires Speed Forward (mph) Speed Reverse (mph) Overall Length Overall Length Overall Length	Cutting Height Range1.75 - 4.5"Deck Lift SystemShims, fixed deckDeck Construction7 GaugeBlades (1/4" thick, high-lift wings)(3) 16.5"Blade Tip Speed (fpm at 3584 rpm)19,000SpindlesCast Iron HousingsBlade Clutch/Brake Maintenance-Free; Rated Heavy DutyWarner"Discharge SystemsSide, Rear & MulchMakes AvailableKawasaki""Horsepower17, 19, 23Cylinders2Starting17 Recoil 17 Recoil 17 Recoil & Electric 19, 23 ElectricHour MeterIncludedOperator ControlsQuad Lever"Hydro Pumps10 ccFuel Capacity6.4 Gal.Drive Tires20 x 10 - 8Caster Tires11 x 4.0 - 5Speed Forward (mph)8.4Speed Reverse (mph)4.3Overall Length55"Overall Length55"Overall Width - Deflector Up (Down)49" (59")	Cutting Height Range1.75 - 4.5"1.75 - 4.5"Deck Lift SystemShims, fixed deckShims, fixed deckDeck Construction7 Gauge7 GaugeBlades (1/4" thick, high-lift wings)(3) 16.5"(3) 18"Blade Tip Speed (fpm at 3584 rpm)19,00019,000SpindlesCast Iron HousingsCast Iron HousingsBlade Clutch/BrakeWarner"Warner"Maintenance-Free; Rated Heavy DutyWarner"Warner"Discharge SystemsSide, Rear & MulchSide, Rear & MulchMakes AvailableKawasaki""Kawasaki""Horsepower17, 19, 2317, 19, 23, 25Cylinders22Starting17 Recoil & Electric 19, 23 Electric17 Recoil & Electric 19, 23, 25 ElectricHour MeterIncludedIncludedOperator ControlsQuad Lever"Quad Lever"Hydro Pumps10 cc10 cc10 ccFuel Capacity6.4 Gal.6.4 Gal.Drive Tires20 x 10 - 820 x 10 - 8Caster Tires11 x 4.0 - 511 x 4.0 - 5Speed Reverse (mph)4.34.3Overall Length55"56.5"Overall Width - Deflector Up (Down)49" (59")53" (63")	Cuting Height Range 1.75 - 4.5" 1.75 - 4.5" 1.75 - 4.5" Deck Lift System Shims, fixed deck Shims, fixed deck Shims, fixed deck Deck Lift System 7 Gauge 7 Gauge 7 Gauge Blades (1/4" thick, high-lift wings) (3) 16.5" (3) 18" (3) 21" Blades (1/4" thick, high-lift wings) (3) 16.5" (3) 18" (3) 21" Blade Tip Speed (fpm at 3584 rpm) 19,000 19,000 19,000 Spindles Cast fron Housings Cast fron Housings Cast fron Housings Blade Clitch/Brake Warner" Warner" Warner" Maintenance-Free; Rated Heavy Duty Varner" Warner" Warner" Discharge Systems Side, Rear & Mulch Side, Rear & Mulch Side, Rear & Mulch Makes Available Kawasaki" Kawasaki" Kawasaki", Kohler" Horsepower 17, 19, 23 17, 19, 23, 25 23, 25 Cylinders 2 2 2 2 Starting 17 Recoil & Electric 17 Recoil & Electric 19, 23 Lectric 17 Recoil & Electric 19, 23, 25 Electric 23, 25 E	Cuting Height Range1.75 - 4.5"1.

Warranty 2-year Limited Warranty: Covers parts and labor. For further details, see your local Wright dealer. To find the name of your nearest dealer, please visit www.wrightmfg.com.



COMING SOON TO A WRIGHT DEALER NEAR YOU!

For more information, call 1.301.360.9810 or find our dealer locator at www.wrightmfg.com.