



Nagra E

CCIR Order # 70 02006 000 # 70 02008 000 NAB

# Portable mono analogue recorder

3 pin XLR's

"T"power, Dynamic

From 0.2 mV to 4 mV / 0 dB

On microphone input, 2.5 mV / 0 dB

1/4" analogue tape recorder Designed for radio reporters Single speed 19cm/s NAB or CCIR Single microphone and balanced line input Reference generator

Confidence playback Monitoring speaker Modulometer Self-contained Lightweight and reliable

### General information

The Nagra E is particularly sturdy and simple to operate and service. It is designed to be adjustable and serviceable in the field, thanks to its simple circuit design, component markings and the enclosed circuit diagram indicating test points and voltages. Furthermore, the meter can be used as a voltmeter with the internally provided test probe. A number of electronic components are enclosed for easy servicing. The machine can be powered from either an external supply (ATN-4 Order # 70 14 378 000) or internal batteries (12 D cells).

#### **Specifications**

THD at 400 Hz Frequency response Signal to noise ratio Erase depth Wow and flutter Reference oscillator Built in reference oscillator Operating range Autonomy

#### Inputs / output

Mic input Mic powering Sensitivity Line input Line

#### Physical

Dimensions Weight

315 x 226 x 104 mm, (12.4 x 8.8 x 4 inch)

5.5 kg, 12.1 lbs (12 cells and tape included)

## **Optional accessories**

External accessories 20 99032 000 ETS 70 98254 000 PA-4 70 13908 000 CS

Soft carrying case, delivered with shoulder strap QHC-2 Set of 4 Ah rechargeable cells Line output cable 3 m (10 ft), 2x3 banana

**Nagra Office** 

#### **Nagravision SA** audio@nagra.com Route de Genève www.nagra.com 221033 Cheseaux Switzerland Tel

+ 41 21 732 01 01 + 41 21 732 02 12 Fax

> NAGRA E V 1 October 02 Copyright Nagravision SA

< 0.9 % at 0 dB, < 2 % at +3 dB 50-15000 Hz at +/- 2 dB 62 dB ASA A weighted 12000 Hz recorded signal > 79 dB +/- 0.1 % (DIN 45507) 1 kHz signal, 0 VU level – 8 dB For tape calibration -12 dB @ 1 kHz, 6.3 kHz and 10 kHz - 20 to 70 °C In continous operation 20 hours

Assymptical with output load >  $300 \Omega$ , 0.94 V for 320 nWb/m