

Technical Data



Binocular	
	8 x 20 BR
Order No. Product	
Rubber amored, black	40 256
Delivery scope	Woven carrying strap, eyepiece cover, Cordura case with belt loop
Magnification	8 x
Front lens diameter	20 mm
Exit pupil	2.5 mm
Twilight factor	12.7
Field of view at 1,000 m	113 m
Field of view at 1,000 yds	341 ft
Eye-relief	16 mm
Objective angle of view	6.5°
Close focusing distance	approx. 1.8 m/7.2 ft
Diopter compensation	± 3.5 diopters
Automatic diopter	
compensation ADC™	yes
Eyepieces for eyeglass	
wearers	yes
Adjustable interpupillary	
distance	34-74 mm
Focusing	Internal focusing via central focusing knob
No. of lens elements	
(each side)	6, all with HDC™ coating
Prism system	Roof prism with phase correcting coating P40 and HighLux-System HLS™
Watertightness	Watertight to a depth of 5 m/16.5 ft
Housing	Aluminum, nitrogen-filled
Dimensions (W x H x D)	111 x 93 x 39 mm
	4% x 3% x 1½ in
Weight	approx. 240 g / 8.5 oz

Page 1 of 1 / As at June 2006 / Specifications are subject to change without notice Leica Camera AG / Oskar-Barnack-Straße 11 / D-35606 Solms / Telephone +49 (0) 6442-208-0 / Telefax +49 (0) 6442-208-333 / info@leica-camera.com / www.leica-camera.com