



LEICA ULTRAVID BR 25 mm

Technical Data



Binocular	LEICA ULTRAVID 10 x 25 BR
Order No. Product	
Rubber armored, black	40 257
Delivery scope	Woven carrying strap, eyepiece cover, Cordura case with belt loop
Magnification	10 x
Front lens diameter	25 mm
Exit pupil	2.5 mm
Twilight factor	15.8
Field of view at 1,000 m	90 m
Field of view at 1,000 yds	273 ft
Eye-relief	15 mm
Objective angle of view	5.2°
Close focusing distance	approx. 3.2 m/ 10.5 ft
Diopter compensation	± 3.5 diopters
Automatic diopter compensation ADC™	yes
Eyepieces for eyeglass wearers	yes
Adjustable interpupillary distance	34–74 mm
Focusing	Internal focusing via central focusing knob
No. of lens elements (each side)	6, all with HDC™ coating
Prism system	Roof prism with phase correcting coating P40 and HighLux-System HLS™
Watertightness	Watertight to a depth of 5 m/ 16.5 ft
Housing	Aluminum, nitrogen-filled
Dimensions (W x H x D)	111 x 112 x 39 mm 4 3/8 x 4 3/8 x 1 1/2 in
Weight	approx. 265 g / 9.4 oz