

Conference- & Informationssystem 5 Schmalbandsender (36,64-37,98)

SKM 1030-7

Description

Cat. No. 03736

The SKM 1030 is a hand-held transmitter for mobile tour-guide systems. Besides its "classic" area of application – guided tours in museums or factories – it can also be used as a transmitter in a mini interpretation system or as a microphone in a talkback system. With the SZU 1032 lavalier clip the radio microphone can be worn around the neck.

Features

- Super-cardioid condenser microphone head, effectively rejects side-borne noise
- Lockable microphone on/off (mute) switch
- 6 switchable frequencies in the 8 m band
- Can be used with rechargeable BA 1032 accupack
- 100 mW RF output power for reliable transmission

Technical data

RF output power	< = 100 mW (-3 dB)
Transmission/receiving frequencies	6
RF frequency range	36,64; 36,72; 37,04; 37,16; 37,82; 37,98 MHz
Modulation	FM
Nominal deviation	+/- 8 kHz
Peak deviation	+/- 15 kHz
Frequency response (headphones)	80.....12000 Hz (+ 1 dB / - 3 dB)
THD, total harmonic distortion	< 0,3 %
Audio-XLR connector	-
Power supply	1 x 9-V-Battery or Accu BA 1032
Operating time (Battery)	6 h
Operating time (Accupack)	1,5 h
Dimensions	245 x 38 mm
Weight	250 g
Type approval number	A 111 309 D ME



Delivery includes

1 hand-held transmitter with antenna

Recommended Accessories

Plug-in mains unit (UK version)	NT 1032-UK	Cat. No.03749
Plug-in mains unit (120V version)	NT 1032-120	Cat. No.03748
Plug-in mains unit (EU version)	NT 1032	Cat. No.03747
Charging unit	L 1032	Cat. No.03729
Rechargeable accupack	BA 1032	Cat. No.03796
Lavalier clip	SZU 1032	Cat. No.03744
Velourised foam windshield	MZW 1032-PRO	Cat. No.03746
Foam windshield, black	MZW 1032	Cat. No.03745
Stand mount	STH 1051	Cat. No.03646

Product variants

SKM 1030-7	Cat. No.03735
SKM 1030-7-BU	Cat. No. 03737
SKM 1030-7-UK	Cat. No. 03738
SKM 1030-6-F	Cat. No. 03734