

SDC 8000 DV

Conference and Information Systems | SDC 8000

Cat. No. 009414

General Description

The digital SDC 8000 DV delegate unit is an ideal choice for both mobile and fixed conference systems. Its compact and elegant design harmoniously blends in with any conference room. The unit features a high-quality built-in loudspeaker, providing excellent sound at a pleasant volume. By pressing the Mic key, the conference participants can either switch on the microphone or signal their request to speak. At multi-lingual conferences, the translated languages can be listened to via headphones. SDC 8000 DV features two voting modes which are accessed via the participant's personal chip card. Results can be conveniently displayed on the unit's LCD display.



Technical Data

Frequency response	100 – 14,000 Hz
Pick-up pattern	cardioid
Headphone connector.....	3.5 mm mono (> 32 Ω)
Power supply.....	48 V DC
Power consumption.....	max. 3.9 W
Operating temperature	0 – 50 °C
Standards.....	IEC 849
Colour.....	Pantone Black 7C
Housing	ABS
Dimensions	150 x 80 x 185 mm
Gooseneck length	380 mm
Weight	650 g

Features

- Built-in high-quality loudspeaker (automatically muted when the microphone is switched on)
- Microphone on/off (request) key
- Gooseneck microphone with red LED ring
- Two RJ 45 sockets for connecting up to 15 units in one cable line
- Two 3.5 mm headphone jacks for headphones or induction couplers for the hearing impaired
- Headphone volume control
- Channel selection keys with numerical display of selected channel (floor language + up to 28 translations)
- Five voting keys with LED, two voting modes
- Back-lit graphic LCD display (122 x 32 dots)
- Built-in chip card reader for participant identification
- Delivery includes: 1 SDC 8000 DV Delegate Unit

Accessories

- RJ 45 conference bus cables, type 24 AWG, available lengths: 2 m, 3 m, 5 m, 10 m, 20 m, 50 m
- HD 410-D, HD 1029 headphones