

## HANDHELD DYNAMIC MICROPHONE

- Dynamic
- Uni-Directional
- 50Hz-16kHz
- 700-Ohm Impedance
- Sensitivity: -54dB±3dB
- XLR 3 Pin Male Connector
- On/Off Switch
- 20 ft. XLR MIC Cable Included
- Carrying Case



**MCHH-100**

## PERFORMANCE HANDHELD DYNAMIC MICROPHONE

- Dynamic
- Uni-Directional
- Zinc Die-Cast Housing
- Weather-Resistant Cartridge for Outdoor Use
- 40Hz-16kHz
- 600-Ohm Impedance
- Sensitivity: -52dB±3dB
- XLR 3 Pin Male Connector
- On/Off Switch
- 20 ft. XLR MIC Cable Included
- Carrying Case



**MCHH-200**

## PROFESSIONAL CONDENSER MICROPHONE


- Back Electret Condenser
- Uni-Directional
- Zinc Die-Cast Housing
- Ideal for Clear Reproduction of Natural Sound
- 50Hz-18kHz
- 600-Ohm Impedance
- Sensitivity: -45dB±3dB
- Max. Input SPL: 130dB (at 1kHz ≥1% T.H.D)
- S/N Ratio: ≥70dB
- Phantom Power Requirement: 9V-52V DC Phantom or 1.5V Battery



**MCHH-300**

## TABLETOP CONFERENCE MICROPHONE

- Back Electret Condenser
- Uni-Directional
- Flexible Gooseneck
- Easy Touch On/Off Button
- Blue LED On/Off Indicator
- 100Hz-16kHz
- 500-Ohm Impedance
- Sensitivity: -38dB±3dB
- XLR 3 Pin Male Connector
- Two AA Batteries Included
- 20 ft. XLR MIC Cable Included
- Windscreen Sponge over MIC



**MCDT-200**

## PROFESSIONAL TABLETOP CONFERENCE MICROPHONE

- Back Electret Condenser
- Uni-Directional
- Flexible Gooseneck
- Easy Touch On/Off Button
- Blue LED On/Off Indicator
- 50Hz-16kHz
- 500-Ohm Impedance
- Sensitivity: -37dB±3dB
- XLR 3 Pin Male Connector
- Two AA Batteries Included
- 20 ft. XLR MIC Cable Included
- 9V-52V DC Phantom or 1.5V Battery
- Windscreen Sponge over MIC



**MCDT-300**

## INDUSTRIAL GOOSENECK MICROPHONE

- Dynamic
- Uni-Directional
- On/Off Switch on MIC Head
- Flexible Gooseneck
- 80Hz-16kHz
- 500-Ohm Impedance
- Sensitivity: -54dB±3dB
- XLR 3 Pin Male Connector



**MCGN-100**

## PROFESSIONAL GOOSENECK MICROPHONE

- Back Electret Condenser
- Uni-Directional
- Blue LED On/Off Indicator
- Flexible Gooseneck
- Windscreen Sponge over MIC
- 50Hz-16kHz
- 1000-Ohm impedance
- Sensitivity: -45dB±3dB
- Three Wire Connection



**MCGN-300**

## PROFESSIONAL HANGING MICROPHONE

- Back Electret Condenser
- Uni-Directional
- Spring Neck Included
- 50Hz-16kHz
- 250-Ohm Impedance
- Sensitivity: -37dB±3dB
- 9V-52V DC Phantom Power Required
- XLR 3 Pin Male Connector
- 20 ft. Cable Included



**MCHM-300**

## PROFESSIONAL BOUNDARY MICROPHONE

- Back Electret Condenser
- Uni-Directional
- Stealth Design
- 20 ft. XLR Cable Included
- 60Hz-16kHz
- 250-Ohm Impedance
- Sensitivity: -36dB±3dB
- 9V-52V DC Phantom Power Required
- Mute Feature



**MCBM-300**



## PHANTOM POWER ADAPTER FOR CONDENSER MICROPHONE

48V DC phantom power supply is designed for condenser microphones.

- Male XLR MIC Output Connector
- Female XLR MIC Input Connector
- 110/230V 60/50Hz
- 5ft. AC Power Cord Included

**MCPP-100**

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: [www.specotech.com](http://www.specotech.com)  
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880