



Tripp Lite
 1111 West 35th Street
 Chicago, IL 60609 USA
 Telephone: +(773) 869 1234
 E-mail: saleshelp@tripplite.com

Model #: N422-03M

Mode Conditioning Fiber Optics - 3-meter (10-ft.) Mode Conditioning Patch Cable, LC/ST

Highlights



- 3 Meter LC/ST Mode Conditioning Cable
- Run 1000Base-LX Gigabit Ethernet over MMF by offsetting signal loss
- IEEE 802.3z Gigabit Ethernet Compliant

Description

Tripp Lites Mode Conditioning Cables are designed for use in Gigabit Ethernet 1000BASE-LX applications. They are fully compliant with IEEE 802.3z application standards. Mode Conditioning Cables are needed in applications where new high-speed Gigabit 1000BASE-LX routers and switches are being deployed into existing multimode plants. The need for this patch cord is due to the single-mode launch nature of the -LX or long-wave (1300 nm) transceiver modules used for Gigabit Ethernet. Launching a single-mode laser into the center of a multimode fiber can cause multiple signals to be generated that confuses the receiver at the other end of the fiber. These multiple signals, caused by Differential Mode Delay (DMD) effects, severely limit the cable distance lengths for operating Gigabit Ethernet. A mode conditioning patch cord eliminates these multiple signals by allowing the single-mode launch to be offset away from the center of a multimode fiber.

Applications

- Use when connecting a LX type fiber transceiver (Singlemode light) to a Multimode backbone

Package Includes

- 3 Meter LC/ST Mode Conditioning Cable

Features

- Use Singlemode Transceivers on Multimode Fiber Backbones
- Offsets the Singlemode Laser launch from the center of a Multimode fiber
- Available in a variety of connector combinations
- Lifetime Warranty

Specifications

OVERVIEW	
Intended Application	Computer Networking (Fiber)
PHYSICAL	
Color	Orange, Yellow
Style	Fiber Optic

Length	3 m
CONNECTIONS	
Connector A	 LC
Connector B	 ST
Number of Connectors	4

Related Items

Fiber Optic Cables & Adapters		
N422-01M	Mode Conditioning Fiber Optics - 1-meter (3-ft.) Mode Conditioning Patch Cable, LC/ST	Qty: [optional]
N422-02M	Mode Conditioning Fiber Optics - 2-meter (6-ft.) Mode Conditioning Patch Cable, LC/ST	Qty: [optional]
N422-10M	Mode Conditioning Fiber Optics - 10-meter (33-ft.) Mode Conditioning Patch Cable, LC/ST	Qty: [optional]
N424-01M	Mode Conditioning Fiber Optics - 1-meter (3-ft.) Mode Conditioning Patch Cable, LC/SC	Qty: [optional]
N424-04M	Mode Conditioning Fiber Optics - 4-meter (13-ft.) Mode Conditioning Patch Cable, LC/SC	Qty: [optional]
N424-05M	Mode Conditioning Fiber Optics - 5-meter (16-ft.) Mode Conditioning Patch Cable, LC/SC	Qty: [optional]
N426-02M	Mode Conditioning Fiber Optics - 2-meter (6-ft.) Mode Conditioning Patch Cable, SC/SC	Qty: [optional]
N426-03M	Mode Conditioning Fiber Optics - 3-meter (10-ft.) Mode Conditioning Patch Cable, SC/SC	Qty: [optional]
N426-05M	Mode Conditioning Fiber Optics - 5-meter (16-ft.) Mode Conditioning Patch Cable, SC/SC	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3514.