



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@triplite.com

Model #: N506-30M

Multimode Fiber Optics 30-meter (100-ft.) Duplex MMF 50/125 Patch Cable, SC/SC

Highlights

- Premium PVC 50/125 multimode patch cables
- Attenuation loss meets or exceeds the latest industry standards
- Higher bandwidth optimized for gigabit and 10Gbps networks
- Backward compatible with 62.5 micron fiber
- Built-in headroom for future applications



Description

Tripp Lite's 30-meter multimode duplex Fibre Channel SC/SC patch cable is manufactured from 50/125 zipcord fiber. The cable has SC connectors on each end, a PVC jacket and is FDDI and OFNR rated. 50/125 Duplex multimode fiber is most commonly used in Fibre Channel applications. It is backward compatible with 62.5 micron fiber and built-in headroom for future applications. The cable provides higher bandwidth optimized for Gigabit and 10Gbps networks as well. Also available in 2, 3, 5, 10, 15, and 50 meter lengths. Search "N506-" to bring up all lengths. Also search "N516-" for SC-LC cables, and "N520-" for LC-LC cables. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

System Requirements

- Any fiber optic hardware or NIC card requiring multimode duplex cable with SC/SC connectors

Package Includes



- 30M duplex MMF cable SC/SC 50/125 fiber

Features

- Constructed with 50/125 micron cable
- Length - 30M
- Use on fiber and fibre channel installations
- SC male to SC male connectors
- Higher bandwidth optimized for gigabit and 10Gbps networks
- Backward compatible with 62.5 micron fiber
- Built-in headroom for future applications
- Number of fibers: 2
- Fiber type: all glass graded index
- Core diameter: two 50+/-3 microns
- CLAD diameter: 125+/-2 microns
- Primary coating diameter: 245+/-15 microns
- Primary coating material: acrylate
- Secondary coating diameter: 900+/-50 microns
- Secondary coating material: PVC
- Attenuation @850NM: 3.5DB/KM maximum, @1300NM: 1.0DB/KM maximum

- Bandwidth @850NM: 220 MHz-KM minimum, @1300NM: 600 MHz-KM minimum
- Numeric aperture: .275 nominal
- Proof test level: 100,000 PSI
- Insertion loss testing performed on every connector (0.2db typical) and provided with cable
- Beveled edge on ends of glass makes insertion of plug a breeze
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

OVERVIEW	
Intended Application	Computer Networking (Fiber)
PHYSICAL	
Color	Orange
Style	Fiber Optic
Length	30 m
CONNECTIONS	
Connector A	 SC
Connector B	 SC
Number of Connectors	2

Related Items

Fiber Optic Cables & Adapters		
N506-03M	Multimode Fiber Optics 3-meter (10-ft.) Duplex MMF 50/125 Patch Cable, SC/SC	Qty: [optional]
N506-10M	Multimode Fiber Optics 10-meter (33-ft.) Duplex MMF 50/125 Patch Cable, SC/SC	Qty: [optional]
N516-10M	Multimode Fiber Optics 10-meter (33-ft.) Duplex MMF 50/125 Patch Cable, LC/SC	Qty: [optional]
N520-10M	Multimode Fiber Optics 10-meter (33-ft.) Duplex MMF 50/125 Patch Cable, LC/LC	Qty: [optional]
N520-30M	Multimode Fiber Optics 30-meter (100-ft.) Duplex MMF 50/125 Patch Cable, LC/LC	Qty: [optional]
N516-30M	Multimode Fiber Optics 30-meter (100-ft.) Duplex MMF 50/125 Patch Cable, LC/SC	Qty: [optional]
N506-50M	Multimode Fiber Optics 50-meter (165-ft.) Duplex MMF 50/125 Patch Cable, SC/SC	Qty: [optional]
N506-15M	Multimode Fiber Optics 15-meter (50-ft.) Duplex MMF 50/125 Patch Cable, SC/SC	Qty: [optional]
N506-05M	Multimode Fiber Optics 5-meter (16-ft.) Duplex MMF 50/125 Patch Cable, SC/SC	Qty: [optional]
N506-02M	Multimode Fiber Optics 2-meter (6-ft.) Duplex MMF 50/125 Patch Cable, SC/SC	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.triplite.com/en/products/model.cfm?txtModelID=2619.