




Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: S063-31I

SCSI/Fibre Channel - 31-in. Internal U320 SCSI Ribbon Cable 4Conn 68Pin 3 Drive with Terminator

Highlights

- Premium cabling



Description

Introducing Tripp Lite's internal SCSI Ultra320 3-drive LVD/SE cable with an active mode-conditioning T-type crimped on terminator. LVD/SE multi-mode termination enables backward compatibility to legacy single ended devices. The terminator will sense if the bus is running LVD or SE and terminate appropriately. This cable measures 31.5 inches in length from master to drive #3 and is UL rated with premium brand cabling. Meets the latest SCSI specification of ANSI (American National Standards Institute). For 5-Drive Connection, see S065-42I, or, for Round Version cables, see S073-31I and S075-42I. Tripp Lite warrants this product to be free from defects in materials and workmanship for life.

System Requirements

- U320/U160 SCSI HBA (Host bus adapter card)
- Any internal SCSI drive or device requiring HD68M interface



Package Includes

- 31-in. Int U320 SCSI ribbon cable 4Conn 68Pin 3Drive with terminator

Features

- Length (master to drive 3): 31.5 inches
- Supports transfer speeds up to 320Mbps
- Connect up to 3 drives or internal devices
- HD68 male connectors
- Cable includes active mode conditioning terminator T-type LVD/SE terminator with local chip (ART IDC type)
- SCSI U320 cables include active multi-mode terminators which compensate for fluctuations in the host adapter
- Constructed with premium brand twist and flat brand cable
- UL rated cable
- All Tripp Lite SCSI products, regardless of the SCSI generation, meet the latest specifications of ANSI
- Tripp Lite offers a complete line of internal and external solutions for SCSI/RAID and fibre channel ranging from the very latest Ultra 320 to legacy SCSI-1 and every combination in between
- Tripp Lite warrants this product to be free from defects in materials and workmanship for life

Specifications

OVERVIEW	
Drives Supported	3
Intended Application	Connecting Drives
PHYSICAL	
Color	Gray
Style	Ribbon & Internal Cables
Length	31" Overall (21" / 5" / 5" +Term)
CONNECTIONS	
Connector A	 INTERNAL HD68 (MALE)
Connector B	 INTERNAL HD68 (MALE)
Number of Connectors	4

Related Items

SCSI Cables		
S065-421	SCSI/Fibre Channel - 42-in. Internal U320 SCSI Ribbon Cable 6Conn 68Pin 5 Drive with Terminator	Qty: [optional]
S450-006	SCSI/Fibre Channel - 6-ft. SCSI U2/U160/U320 LVD/SE cable HD68M to HD68M w/thumbscrews	Qty: [optional]
S454-006	SCSI/Fibre Channel - 6-ft. SCSI U320/U160 LVD/SE cable, Offset VHDCI68M to HD68M	Qty: [optional]
S456-006	SCSI/Fibre Channel - 6-ft. SCSI U320/U160 LVD/SE cable, Offset VHDCI68M/M w/Thumbscrews	Qty: [optional]

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=2357.