



85 Mbps

MegaPlug

Ethernet Adapter

Model #: HPE100T

User Manual

Ver 1.0

Solutions for the Digital Life™

Table of Contents

1 Introduction	1
Package Contents	1
Features	2
System Requirements	2
Getting to Know the Ethernet Adapter	3
Technical Support	4
2 Connecting the MegaPlug Adapter	5
Connecting the Adapters	5
Installing the Configuration Utility	6
3 Using the Configuration Utility	9
Quick Setup	9
Advanced	10
About	12
4 Troubleshooting	13
Troubleshooting	13
Frequently Asked Questions	14
5 Setting Up Static IP Address	17
Windows 98 SE	17
Windows Me	20
Windows 2000	23
Windows XP	27
6 Setting Up File and Printer Sharing	31
File Sharing	31
Printer Sharing	39
A Specifications	41
General	41
LED Indicators	42
Environmental	42
B Glossary	43
Notices	47
Regulatory Compliance Notices	47
Modifications	47
Miscellaneous Legal Notices	48
Limited Warranty	49

This page left intentionally blank.

Introduction

Thank you for purchasing the Actiontec MegaPlug Ethernet Adapter. The MegaPlug Ethernet Adapter is one of the easiest ways to enjoy home or small business networking. It operates on the MegaPlug Powerline Specification Turbo standard, providing data transfer speeds up to 85 Mbps over home AC wiring. Since home power lines are the most pervasive medium in households, with multiple outlets in every room, the MegaPlug Ethernet Adapter allows multiple desktop and laptop computers to be networked easily, enabling them to share an Internet connection, printers, files, and games, without any additional wiring. If you want to take your computer networking to the next level, the Actiontec MegaPlug Ethernet Adapter is sure to be one of the keys to your success.



Package Contents

Make sure the following items came in this package:

- One Actiontec 85 Mbps MegaPlug Ethernet Adapter
- One Ethernet Cable
- Installation CD (includes this manual)
- Quick Start Guide

Features

- HomePlug Turbo compliant
- 85 Mbps data rate (maximum)
- 56-bit DES encryption
- Two-pronged US power plug (fits ungrounded power outlets)
- Power and Link indicators

System Requirements

- At least 1 available power outlet
- Standard home power wiring
- Computer with the following:
 - CD-ROM drive
 - IBM compatible running at 200 MHz or better
 - Windows 98SE, Me, 2000, or XP installed
 - 64 MB of RAM
 - Ethernet network adapter
 - TCP/IP installed

Getting to Know the Ethernet Adapter

This section contains a quick description of the Adapter's external features.

Front Panel

The Adapter's front panel features 2 lights (LEDs):



Power Light

The Power light glows green when synchronized with another device. If the Power light is off, it can still be powered up.

Link Light

The Link light glows green when an Ethernet connection is detected, and flickers when data is being transferred across the Adapter.

Bottom Panel

The Adapter's bottom panel contains one Ethernet port:

Ethernet Port

The Ethernet port is used to connect the Adapter to a computer or gateway/router via Ethernet cable.

Information Sticker

The information sticker (located beneath the electrical prongs) displays the MAC (Media Access Control) address, device ID, serial number, and other information about the Adapter.

Technical Support

Actiontec Electronics prides itself on making durable, high-quality, high-performance products. If you need assistance, the Actiontec Technical Support Department is available all day every day to provide professional support.

Actiontec Electronics, Inc.

760 N. Mary Avenue
Sunnyvale, CA 94085

Technical Support

Phone: (USA) 1-888-436-0657

E-mail: http://support.actiontec.com/email_support/support_form.php

Internet: www.actiontec.com/support

Connecting the MegaPlug Adapter

2


To connect the Adapter, it must be connected to a computer, plugged into a standard wall outlet, and the Configuration Utility loaded on the computer.

Connecting the Adapters

To use the Adapters properly, two Adapters should be plugged into electrical outlets, and devices (computers, printers, etc.) connected to them.

Connecting an Adapter to a Computer


1. Get an Adapter and one Ethernet cable.
2. Insert one end of the Ethernet cable into the Ethernet port of the Adapter.
3. Plug the Adapter into a wall outlet.

 **Note:** Do not plug the Adapter into a UPS or power strip with surge protection. The Adapter's network signal may not pass through these devices.

4. Insert the other end of the Ethernet cable into an Ethernet port on the back of a computer.

Connecting an Adapter to a Router/Gateway

1. Get an Adapter and one Ethernet cable.
2. Insert one end of the Ethernet cable into the Ethernet port of the Adapter.
3. Plug the Adapter into a wall outlet.

 **Note:** Do not plug the Adapter into a UPS or power strip with surge protection. The Adapter's network signal may not pass through these devices.

4. Insert the other end of the Ethernet cable into an Ethernet port on a router/gateway connected to a computer.


5. Insert the other end of the Ethernet cable into an Ethernet port on a router/gateway connected to a computer.

Follow the instructions in the next section, “Installing the Configuration Utility.”


Installing the Configuration Utility

After connecting the Adapters, install the Configuration Utility:


1. Insert the Installation CD in the CD-ROM drive of the computer connected to an Adapter.
2. When the “Welcome” screen appears, click **Next**.



3. When the “Choose Destination Screen” appears, click **Next**.



4. When this window appears, click **Finish**.



5. Repeat for other computers connected to an Adapter.

The MegaPlug Adapters are now connected and ready to use, and the Configuration Utility is loaded on the computers. Go to chapter 3, “Using the Configuration Utility” for information about changing the default configuration settings of the Adapter.

This page left intentionally blank.

Using the Configuration Utility

3


Once the Adapters have been properly connected and installed, the user can further configure the Adapters using the Actiontec MegaPlug Configuration Utility. The Utility also provides information about the network. To access the Utility:

1. Click **Start** on the desktop, then **Programs**.
2. From the Programs menu, find “Actiontec MegaPlug,” then select **MegaPlug Configuration Utility**.

The Utility appears on the desktop. See the following sections for more information about the Utility’s capabilities.

Quick Setup


Selecting **Quick Setup** from the row of tabs near the top of the Utility’s window generates the “Quick Setup” tab.



Use this tab to quickly set up security on all MegaPlug devices on the network.


Local Device(s) on Your Computer

The list displays all MegaPlug Adapters connected to the computer.

 **Note:** If no Adapter appears in the Device List, make sure the Adapter is connected properly (with the appropriate Ethernet cable) to the computer. Then, unplug the Adapter, and plug it back in again. If, after performing these actions, no Adapter appears in the Device List, the Adapter may be defective. Contact technical support.

MegaPlug Encryption Key

Enter an encryption key in this text box to provide security for your MegaPlug network. A key is similar to a password, and can be made up of any combination of letters or numbers, from 4 to 24 characters long. Once activated, this key must be entered into a device's network configuration to join the MegaPlug network.


 **Important:** All Adapters on the same network must have the same encryption key. If not, they will not be able to connect.

Set Local Device Only

Click this button to encrypt the device selected in the “Local Device(s) on your computer” list box.

Advanced

Selecting **Advanced** from the row of tabs near the top of the Utility's window generates the “Advanced” tab.



Local Device(s) on Your Computer

The list displays all MegaPlug Adapters connected to the computer.



Note: If no Adapter appears in the Device List, make sure the Adapter is connected properly (with the appropriate Ethernet cable) to the computer. Then, unplug the Adapter, and plug it back in again. If, after performing these actions, no Adapter appears in the Device List, the Adapter may be defective. Contact technical support.

Network List

The Network List (the list box at the center of the Network tab) lists all other Adapters connected to this MegaPlug network. Only Adapters with the same password as the Adapter connected to this computer are shown on this list. The available Adapters are listed by their MAC addresses, and include their device name, device ID, and the quality of the connection.

Add

Clicking this button allows the user to add a MegaPlug adapter to the network. In the window that appears, enter the device name and password in the appropriate text boxes, then click **OK**.

Rename

Clicking this button allows the user to rename a MegaPlug adapter listed in the Network List. Select the device from the Network list, click **Rename**, then enter the new name.

Enter Device ID

Clicking this button allows the user to enter a MegaPlug adapter device ID. The device ID is found on the sticker attached to the Adapter (see page 3).

MegaPlug Encryption Key


Enter an encryption key in this text box to provide security for your MegaPlug network. A key is similar to a password, and can be made up of any combination of letters or numbers, from 4 to 24 characters long. Once activated, this key must be entered into a devices network configuration to join the MegaPlug network.

Set All Devices

Click this button to encrypt all devices on the MegaPlug network.

About

Selecting **About** from the row of tabs near the top of the Utility's window generates the "About" tab.



The About tab displays the MegaPlug Configuration Utility version.

Troubleshooting

4

This chapter contains a list of problems that may be encountered while using the MegaPlug Ethernet Adapter, and techniques to solve them. Note that these techniques may not be successful in all cases. Also included is a list of frequently asked questions.

Troubleshooting

If the Adapter is showing signs of trouble, before attempting any other troubleshooting procedures, plug the Adapter into a working electrical wall socket.

The Power light doesn't light up after I plug the Adapter into a wall outlet.

First, make sure two Adapters are installed and connected. A single installed Adapter will not have any illuminated lights. Then, ensure the wall outlet is working by plugging other electric devices into it. If it is working, plug in the Adapter again, and if the Power light still doesn't illuminate, try plugging it into other wall outlets. If the Adapter is still experiencing this problem, contact technical support.

The Link light doesn't light up on the Adapter.

If the Adapter's Ethernet light is not illuminating, a LAN connection is not being detected.

- ♦ Make sure two Adapters are installed and connected. A single installed Adapter will not have any illuminated lights.
- ♦ Check the Ethernet adapter on the computer and make sure it is enabled and working properly. Also, make sure the right type of Ethernet cable is being used.

I can't connect to the Internet or any of the other computers on the network.

- ♦ Make sure the IP address and TCP/IP protocol are set up properly for all the computers on the network, then try to ping the gateway.

- ♦ Use the Adapter's Configuration Utility to detect all other Adapters on the network. Then, plug the Adapters into adjacent sockets. If the Ethernet lights still don't illuminate, contact technical support.

The Power and Link lights are on, but I can't access the router/gateway from the computer

- ♦ Try plugging the Adapters in different power outlets, preferably closer together.
- ♦ Make sure all Adapters on the network are using the same security parameters.

Frequently Asked Questions

What's the transfer speed over the Adapter's network?

The Adapter's network transfer speed is 85 Mbps (maximum) over a standard home power line network.

What's the estimated range of the Adapter's network?

Approximately 300 meters (~985 ft.) in wall power lines (one household).

Will the Adapter work in any home?

The Adapter will work in any home with built-in copper wiring. It may not operate in some older homes (pre-1950) with alternate wiring.

Will the Adapter's network signal pass through circuit breakers?

Yes, the Adapter's network signal will pass through circuit breakers. It will not, however, pass through power transformers.

Does the Adapter work with a 100 – 240V AC input ?

Yes.

Does using the Adapter cause any interference with other home networking devices?

No. The Adapter operates at a different frequency than other power line control devices and can co-exist with technologies such as X-10, CEBus, and LONworks.

Can my neighbor receive the Adapter's network signal?

It is possible for a neighbor to receive the network signal. To prevent this, change the default 56-bit DES security encryption password on the Adapter (see chapter 3).

How do I find out what the current speed and signal strength of the Adapter's network is?

Run the Adapter's Configuration Utility to show current speed and signal strength.

How many Adapters do I need to set up a network?

Two, at minimum.

To set up the Adapter's network correctly, do I have to install the Configuration Utility on each computer on the network?

No, the Configuration Utility is a diagnostic and security tool. Since the Adapter is fully plug-and-play compatible, it needs no software drivers to operate.

How many Adapters can be installed on the same LAN (local area network)?

Actiontec recommends using no more than 16 Adapters on one network.


This page left intentionally blank.

Setting Up Static IP Address

5


To communicate with a MegaPlug Ethernet Adapter from a computer on the network, the user may have to switch the IP address settings from DHCP-enabled to static IP, so that the computer and the Adapter are on the same subnet.

To set up static IP on a computer, select the operating system and follow the instructions.


 **Note:** The following procedures are based on the Adapter's factory default IP address. If the Adapter's IP address has been changed, enter the new IP address when instructed to enter an IP address.

Windows 98 SE


1. From the desktop, click on the **Start** button in the lower left corner.
2. From the menu that appears, select **Settings**.




3. Another menu appears. Select **Control Panel**.




4. When the “Control Panel” window appears, double-click **Network**.



5. The “Network” window appears. In the “The following network components are installed” list box, locate and double-click TCP/IP.



6. The “TCP/IP Properties” window appears. Select IP Address.



7. In the IP Address tab, make sure the circle next to “Specify an IP Address” is selected. When active, a black dot appears in the circle. If the circle already contains a black dot, leave it alone.

8. Enter the following numbers in the “IP Address” text box:

192.168.0.2


Press the space bar on the keyboard to add the periods between the numbers.

9. Enter the following numbers in the “Subnet mask” text box:

255 . 255 . 255 . 0

Press the space bar on the keyboard to add the periods between the numbers.


10. Click **OK**. The TCP/IP Properties window disappears.
11. In the Network window, click **OK**. The Network window disappears.
12. The “System Settings Change” window appears, asking whether the computer should be restarted. Click **Yes**.



The computer restarts. It is now set up with a static IP address.

Windows Me


1. From the desktop, click on the **Start** button in the lower left corner.
2. From the menu that appears, select **Settings**.




3. Another menu appears. Select **Control Panel**.




4. When the “Control Panel” window appears, double-click **Network**.



- The “Network” window appears. In the “The following network components are installed” list box, locate and double-click TCP/IP.



- The “TCP/IP Properties” window appears. Click **IP Address**.




- In the IP Address tab, make sure the circle next to “Specify an IP Address” is selected. When active, a black dot appears in the circle. If the circle already contains a black dot, leave it alone.
- Enter the following numbers in the “IP Address” text box:
192.168.0.2
Do not include the periods; they are automatically entered.

9. Enter the following numbers in the “Subnet mask” text box:

255 . 255 . 255 . 0

Do not include the periods; they are automatically entered.

10. Click **OK**. The TCP/IP Properties window disappears.
11. If there is a check in the box next to “Detect connection to network media,” click on it to uncheck the box.
12. In the Network window, click **OK**. The Network window disappears.
13. The “System Settings Change” window appears, asking whether the computer should be restarted. Click **Yes**.




The computer restarts. It is now set up with a static IP address.

Windows 2000


1. From the desktop, click on the **Start** button in the lower left corner.
2. From the menu that appears, select **Settings**.



3. Another menu appears. Select **Control Panel**.




4. When the “Control Panel” window appears, double-click **Network and Dial-up Connections**.




- In the “Network and Dial-up Connections” window, double-click **Local Area Connection**. A number may be displayed after the Local Area Connection. If there is more than one Local Area Connection listed, locate the one that corresponds to the network card installed in the computer by finding the name of the network card in the **Device Name** column.




- The “Local Area Connection Status” window appears. Select **General**, then click **Properties**.



- The “Local Area Connection Properties” window appears. Click **General**.
- In the “Components checked are used by this connection” list box, double-click **Internet Protocol (TCP/IP)**.



- The “Internet Protocol (TCP/IP) Properties” window appears.



- In the **General** tab, make sure the circle next to “Obtain an IP Address automatically” is selected. When active, a black dot appears in the circle. If the circle already contains a black dot, leave it alone.
- Enter the following numbers in the “IP Address” text box:
192.168.0.2
Press the space bar on the keyboard to add the periods between the numbers.

12. Enter the following numbers in the “Subnet mask” text box:

255 . 255 . 255 . 0


Press the space bar on the keyboard to add the periods between the numbers.

13. Click **OK**. The “Internet Protocol (TCP/IP) Properties” window disappears.
14. In the “Local Area Connection Properties” window, click **OK**. The Local Area Connection Properties window disappears.
15. Click **Close** in the Local Area Connection Status window. The window disappears.
16. Close the Network and Dial-up Connections window by clicking on the “x” button at the upper right corner of the window.


The computer is now set up with a static IP address.

Windows XP


1. From the desktop, click **Start** button in the lower left corner.
2. From the menu that appears, select **Control Panel**.




3. When the “Control Panel” window appears, double-click **Network Connections**.




4. In the “Network Connections” window, double-click **Local Area Connection**. A number may be displayed after the Local Area Connection. If more than one Local Area Connection is listed, locate the one that corresponds to the network card installed in your computer by finding the name of the network card in the “Device Name” column.



5. The “Local Area Connection Properties” window appears. Select **General**.
6. In the “This connection uses the following items” list box, double-click **Internet Protocol (TCP/IP)**.



7. The “Internet Protocol (TCP/IP) Properties” window appears.



8. In the **General** tab, make sure the circle next to “Use the following IP Address” is selected. When active, a black dot appears in the circle. If the circle already contains a black dot, leave it alone.
9. Enter the following address in the “IP Address” text box:
192.168.0.2
Enter the periods in the address by pressing the space bar on the keyboard.
10. Enter the following address in the “Subnet mask” text box:
255.255.255.0
Enter the periods in the address by pressing the space bar on the keyboard.
11. Click **OK**. The Internet Protocol (TCP/IP) Properties window disappears.
12. In the Local Area Connection Properties window, click **Close**. The Local Area Connection Properties window disappears.
13. Click **Close** in the Local Area Connection Status window. The window disappears.
14. Close the Network and Dial-up Connections window by clicking on the “x” button at the upper right corner of the window.

The computer is now set up with a static IP address.

6

Setting Up File and Printer Sharing

This chapter describes how to share files, hard drives, and printers over the MegaPlug network.


File Sharing

To share files, directories, or hard drives on the MegaPlug network, select the operating system running on the computer, then follow the instructions.


Windows XP

After installing and configuring the Adapter, Windows XP automatically enables file sharing. The only item that needs to be altered is workgroup settings. All the computers on the network must have the same workgroup name, but different computer names. To check or change this:

1. Right-click the **My Computer** icon and click **Properties**. The “System Properties” window appears.
2. Select the **Computer Name** tab.



3. Click **Change**.
4. When the “Computer Name Changes” window appears, enter a new computer name in the “Computer name” text box.




5. Enter a workgroup name in the “Workgroup” text box.
6. Click **OK**.
7. Restart the computer.

Windows 2000


After installing and configuring the Adapter, Windows 2000 automatically enables file sharing. The only item that needs to be altered is workgroup settings. All the computers on the network must have the same workgroup name, but different computer names. To check or change this:

1. Right-click the **My Computer** icon on your desktop, then select **Properties**.
2. When the “System Properties” window appears, select **Network Identification**.



3. If the **Workgroup** name is already the same as all the other computers on the network, click **OK**. If it is not the same, click **Properties**.


4. The “Identification Changes” window appears. In the “Computer Name” text box, type a name different than the other computers on the network.




5. In the “Workgroup” text box, enter the network workgroup name. This is the same on each computer on the network.
6. Click **OK**.
7. Click **OK** again.
8. Restart the computer.

Windows 98, 98SE, and Me


1. Click **Start**, select **Settings**, then **Control Panel**.
2. In the Control Panel window, double-click the **Network** icon. The Network window appears.



3. In the “Configuration” tab, click **Add**. The “Select Network Component Type” window appears.




4. Select **Service**, then click **Add**. The “Select Network Service” window appears.




5. Highlight **File and printer sharing for Microsoft Networks**, then click **OK**.
6. The “File and Print Sharing” window appears. Make sure both options have a check mark in their check boxes. If not, click in the box to activate.




- Click **OK**. The Network window reappears.
- In the Network window, select **Identification**. The “Identification” tab appears.



- In the “Computer Name” text box, type a name different than the other computers on the network.
- In the “Workgroup” text box, enter the network workgroup name. This is the same on each computer on the network.
- Enter any description in the “Computer Description” text box. Traditionally, the location name or main user’s name is entered.
- Select **Configuration** to display the Configuration window again.
- In the “Primary Network Logon” text box, make sure “Client for Microsoft Networks” is entered. If not, click the down arrow and select it from the list.
- Click **OK**. A “System Settings Change” window appears. Click **Yes**.



15. After your computer restarts, Windows prompts for a user name and password. Enter a user name and password, then write them on a sheet of paper, as they will be needed to access the network in the future.
16. Find a file or hard drive to share, right-click its icon, and select **Sharing**. The "Properties" window appears.
17. In the Properties window, select **Sharing**. The "Sharing" tab appears.



18. Click in the circle next to "Shared As" to share the file or hard drive.
19. Select an **Access Type**:

Read Only - Allows other users on the network to view and read the file or hard drive selected. They will not be able to modify it in any way. You can further restrict their privileges by entering a password in the appropriate text box.


Full - Allows other users on the network to read, modify, move, and delete any information in the shared file or hard drive. You can further restrict their privileges by entering a user name and password.

Depends on Password - Allows you to set both Read Only and Full access on the shared file or drive. The level of access will depend on the passwords entered in the appropriate field.


20. When finished, click **Apply**, then **OK**.

Printer Sharing


To share a printer connected to the computer, follow these instructions.

 **Note:** These instructions are basically identical for Windows XP, 2000, Me, and 98 SE, with some minor differences.


1. Click **Start, Settings, Control Panel**.
2. In the “Control Panel” window, double-click on the “Printers” icon.



3. In the “Printers” window, right-click on the icon of the printer to be shared and select **Sharing**.



4. A “Properties” window appears, with the “Sharing” tab displayed.



5. Select **Shared As or Share this Printer**. This automatically inserts a default name for the printer share name. You can set a password for the printer at this time if you want to restrict who on the network can use the printer. You can also set the default printer settings by modifying information on the other tabs of this window.
6. Click **OK**, and close all windows.

Specifications



General

Model Number

HPE100T (MegaPlug 85 Mbps Ethernet Adapter)

Standards

HomePlug Turbo
IEEE 802.3
10BaseT

Security

56-bit DES data encryption

Frequency Band

4.3 MHz - 20.9 MHz

Modulation

OFDM symbol modulation

Carrier Modulation

DQPSK, DBPSK, ROBO

Access Methods

CSMA/CA

Other Protocols

Automatic Channel Adaptation, Forward Error Correction

LED Indicators

Power, Link

Environmental

Power

External, 110 - 240v 0.2a, 50 - 60 Hz

Certifications

FCC part 15, CE

Operating Temperature

0° C to 40° C (32°F to 104°F)

Storage Temperature

-20°C to 70°C (-4°F to 158°F)

Operating Humidity

10% to 85% non-condensing

Storage Humidity

5% to 90% non-condensing



Note: Specifications are subject to change without notice.

Glossary

B

Access Point

A device that allows wireless clients to connect to one another. An access point can also act as a bridge between wireless clients and a “wired” network, such as an Ethernet network. Wireless clients can be moved anywhere within the coverage area of the access point and remain connected to the network. If connected to an Ethernet network, the access point monitors Ethernet traffic and forwards appropriate Ethernet messages to the wireless network, while also monitoring wireless traffic and forwarding wireless client messages to the Ethernet network.

ATM (Asynchronous Transfer Mode)

A networking technology based on transferring data in fixed-size packets

Client

A desktop or mobile computer connected to a network.

DHCP (Dynamic Host Configuration Protocol)

A protocol designed to automatically assign an IP address to every computer on your network.

DNS (Domain Name System) Server Address

Allows Internet host computers to have a domain name and one or more IP addresses. A DNS server keeps a database of host computers and their respective domain names and IP addresses so that when a user enters a domain name into a Web browser, the user is sent to the proper IP address. The DNS server address used by computers on the home network corresponds to the location of the DNS server the ISP has assigned.

DSL (Digital Subscriber Line) Modem

A modem that uses existing phone lines to transmit data at high speeds.

Encryption

A method to allow wireless data transmissions a level of security.

ESSID (Extended Service Set Identifier)

A unique identifier for a wireless network. Also known as “SSID.”

Ethernet Network

A standard wired networking configuration using cables and hubs.

Firewall

A method preventing users outside the network from accessing and/or damaging files or computers on the network.

Gateway

A central device that manages the data traffic of your network, as well as data traffic to and from the Internet.

IP (Internet Protocol) Address

A series of four numbers separated by periods identifying a unique Internet computer host.

ISP Gateway Address

An IP address for the Internet router. This address is only required when using a cable or DSL modem.

ISP (Internet Service Provider)

A business that allows individuals or businesses to connect to the Internet.

LAN (Local Area Network)

A group of computers and devices connected together in a relatively small area (such as a house or an office). A home network is considered a LAN.

MAC (Media Access Control) Address

The hardware address of a device connected to a network.

NAT (Network Address Translation)

A method allowing all of the computers on a home network to use one IP address, enabling access to the Internet from any computer on the home network without having to purchase more IP addresses from the ISP.

PC Card

An adapter that inserts in the PCMCIA slot of a computer, enabling the communication with a device.

**PPPoE (Point-To-Point Protocol over Ethernet)/
PPPoA (Point-To-Point Protocol over ATM)**

Methods of secure data transmission.

Router

A central device that manages the data traffic of your network.

Subnet Mask

A set of four numbers configured like an IP address used to create IP address numbers used only within a particular network.

SSID

See “ESSID.”

TCP/IP (Transmission Control Protocol/Internet Protocol)

The standard protocol for data transmission over the Internet.

WAN (Wide Area Network)

A network that connects computers located in separate areas, (i.e., different buildings, cities, countries). The Internet is a WAN.

WECA (Wireless Ethernet Compatibility Alliance)

An industry group that certifies cross-vender interoperability and compatibility of IEEE 802.11b wireless networking products and promotes the standard for enterprise, small business, and home environments.

WLAN (Wireless Local Area Network)

A group of computers and other devices connected wirelessly in a small area.

This page left intentionally blank.

Notices

Regulatory Compliance Notices

Class B Equipment

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by implementing one or more of the following measures:

- Reorient or relocate the receiving antenna;
- Increase the separation between the equipment and receiver;
- Connect the equipment to an outlet on a circuit different from that to which the receiver is connected;
- Consult the dealer or an experienced radio or television technician for help.


Modifications

The FCC requires the user to be notified that any changes or modifications made to this device that are not expressly approved by Actiontec Electronics, Inc., may void the user's authority to operate the equipment.

Declaration of conformity for products marked with the FCC logo – United States only.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

1. This device may not cause harmful interference
2. This device must accept any interference received, including interference that may cause unwanted operation

 **Note:** To comply with FCC RF exposure compliance requirements, the antenna used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter.

For questions regarding your product or the FCC declaration, contact:

Actiontec Electronics, Inc.
760 North Mary Ave.
Sunnyvale, CA 94086
United States
Tel: (408) 752-7700
Fax: (408) 541-9005

Miscellaneous Legal Notices

© 2005 Actiontec Electronics, Inc. Actiontec Installation Buddy, Connection 1-2-3, Solutions for the Digital Life, Actiontec Digital Gear, and the Actiontec logo are trademarks or registered trademarks of Actiontec Electronics, Inc.

All other names are the property of their respective owners.

Limited Warranty

Hardware: Actiontec Electronics, Inc., warrants to the end user (“Customer”) that this hardware product will be free from defects in workmanship and materials, under normal use and service, for twelve (12) months from the date of purchase from Actiontec Electronics or its authorized reseller.

Actiontec Electronics’ sole obligation under this express warranty shall be, at Actiontec’s option and expense, to repair the defective product or part, deliver to Customer an equivalent product or part to replace the defective item, or if neither of the two foregoing options is reasonably available, Actiontec Electronics may, in its sole discretion, refund to Customer the purchase price paid for the defective product. All products that are replaced will become the property of Actiontec Electronics, Inc. Replacement products may be new or reconditioned. Actiontec Electronics warrants any replaced or repaired product or part for ninety (90) days from shipment, or the remainder of the initial warranty period, whichever is longer.

Software: Actiontec Electronics warrants to Customer that each software program licensed from it will perform in substantial conformance to its program specifications, for a period of ninety (90) days from the date of purchase from Actiontec Electronics or its authorized reseller. Actiontec Electronics warrants the media containing software against failure during the warranty period. The only updates that will be provided are at the sole discretion of Actiontec Electronics and will only be available for download at the Actiontec Web site, www.actiontec.com. Actiontec Electronics’ sole obligation under this express warranty shall be, at Actiontec Electronics’ option and expense, to refund the purchase price paid by Customer for any defective software product, or to replace any defective media with software which substantially conforms to applicable Actiontec Electronics published specifications. Customer assumes responsibility for the selection of the appropriate applications program and associated reference materials. Actiontec Electronics makes no warranty or representation that its software products will meet Customer’s requirements or work in combination with any hardware or applications software products provided by third parties, that the operation of the software products will be uninterrupted or error free, or that all defects in the software products will be corrected. For any third-party products listed in the Actiontec Electronics software product documentation or specifications as being compatible, Actiontec Electronics will make reasonable efforts to provide compatibility, except where the non-compatibility is caused by a “bug” or defect in the third party’s product or from use of the software product not in accordance with Actiontec Electronics published specifications or user guide.

THIS ACTIONTEC ELECTRONICS PRODUCT MAY INCLUDE OR BE BUNDLED WITH THIRD-PARTY SOFTWARE, THE USE OF WHICH IS GOVERNED BY A SEPARATE END-USER LICENSE AGREEMENT.

THIS ACTIONTEC ELECTRONICS WARRANTY DOES NOT APPLY TO SUCH THIRD-PARTY SOFTWARE. FOR THE APPLICABLE WARRANTY, PLEASE REFER TO THE END-USER LICENSE AGREEMENT GOVERNING THE USE OF SUCH SOFTWARE.

Obtaining Warranty Service: Customer may contact Actiontec Electronics Technical Support Center within the applicable warranty period to obtain warranty service authorization. Dated proof of purchase from Actiontec Electronics or its authorized reseller may be required. Products returned to Actiontec Electronics must be pre-authorized by Actiontec Electronics with a Return Merchandise Authorization (RMA) number marked on the outside of the package, and sent prepaid and packaged appropriately for safe shipment, and it is recommended that they be insured or sent by a method that provides for tracking of the package. The repaired or replaced item will be shipped to Customer, at Actiontec Electronics' expense, not later than thirty (30) days after Actiontec Electronics receives the defective product.

Return the product to:
(In the United States)
Actiontec Electronics, Inc.
760 North Mary Avenue
Sunnyvale, CA 94085

Actiontec Electronics shall not be responsible for any software, firmware, information, memory data, or Customer data contained in, stored on, or integrated with any products returned to Actiontec Electronics for repair, whether under warranty or not.

WARRANTIES EXCLUSIVE: IF AN ACTIONTEC ELECTRONICS PRODUCT DOES NOT OPERATE AS WARRANTED ABOVE, CUSTOMER'S SOLE REMEDY FOR BREACH OF THAT WARRANTY SHALL BE REPAIR, REPLACEMENT, OR REFUND OF THE PURCHASE PRICE PAID, AT ACTIONTEC ELECTRONICS' OPTION. TO THE FULL EXTENT ALLOWED BY LAW, THE FOREGOING WARRANTIES AND REMEDIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, TERMS OR CONDITIONS, EXPRESS OR IMPLIED, EITHER IN FACT OR BY OPERATION OF LAW, STATUTORY OR OTHERWISE, INCLUDING WARRANTIES, TERMS OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, SATISFACTORY QUALITY, CORRESPONDENCE WITH DESCRIPTION, AND NON-INFRINGEMENT, ALL OF WHICH ARE EXPRESSLY DISCLAIMED. ACTIONTEC ELECTRONICS

Limited Warranty

NEITHER ASSUMES NOR AUTHORIZES ANY OTHER PERSON TO ASSUME FOR IT ANY OTHER LIABILITY IN CONNECTION WITH THE SALE, INSTALLATION, MAINTENANCE OR USE OF ITS PRODUCTS.

ACTIONTEC ELECTRONICS SHALL NOT BE LIABLE UNDER THIS WARRANTY IF ITS TESTING AND EXAMINATION DISCLOSE THAT THE ALLEGED DEFECT OR MALFUNCTION IN THE PRODUCT DOES NOT EXIST OR WAS CAUSED BY CUSTOMER'S OR ANY THIRD PERSON'S MISUSE, NEGLIGENCE, IMPROPER INSTALLATION OR TESTING, UNAUTHORIZED ATTEMPT TO OPEN, REPAIR OR MODIFY THE PRODUCT, OR ANY OTHER CAUSE BEYOND THE RANGE OF THE INTENDED USE, OR BY ACCIDENT, FIRE, LIGHTNING, OTHER HAZARDS, OR ACTS OF GOD.

LIMITATION OF LIABILITY: TO THE FULL EXTENT ALLOWED BY LAW, ACTIONTEC ELECTRONICS ALSO EXCLUDES FOR ITSELF AND ITS SUPPLIERS ANY LIABILITY, WHETHER BASED IN CONTRACT OR TORT (INCLUDING NEGLIGENCE), FOR INCIDENTAL, CONSEQUENTIAL, INDIRECT, SPECIAL, OR PUNITIVE DAMAGES OF ANY KIND, OR FOR LOSS OF REVENUE OR PROFITS, LOSS OF BUSINESS, LOSS OF INFORMATION OR DATA, OR OTHER FINANCIAL LOSS ARISING OUT OF OR IN CONNECTION WITH THE SALE, INSTALLATION, MAINTENANCE, USE, PERFORMANCE, FAILURE, OR INTERRUPTION OF ITS PRODUCT, EVEN IF ACTIONTEC ELECTRONICS OR ITS AUTHORIZED RESELLER HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, AND LIMITS ITS LIABILITY TO REPAIR, REPLACEMENT, OR REFUND OF THE PURCHASE PRICE PAID, AT ACTIONTEC ELECTRONICS' OPTION. THIS DISCLAIMER OF LIABILITY FOR DAMAGES WILL NOT BE AFFECTED IF ANY REMEDY PROVIDED HEREIN SHALL FAIL OF ITS ESSENTIAL PURPOSE.

Disclaimer: Some countries, states or provinces do not allow the exclusion or limitation of implied warranties or the limitation of incidental or consequential damages for certain products supplied to consumers, or the limitation of liability for personal injury, so the above limitations and exclusions may be limited in their application to you. When the implied warranties are not allowed to be excluded in their entirety, they will be limited to the duration of the applicable written warranty. This warranty gives you specific legal rights which may vary depending on local law.

Dispute Resolution: The customer may contact the Director of Technical Support in the event the Customer is not satisfied with Actiontec Electronics' response to the complaint. In the event that the Customer is still not satisfied with the response of the Director of Technical Support, the Customer is instructed to contact the Director of Marketing. In the event that the Customer is still not satisfied with the response of the Director of Marketing, the Customer is instructed to contact the Chief Financial Officer and/or President.

Governing Law: This Limited Warranty shall be governed by the laws of the State of California, U.S.A., excluding its conflicts of laws and principles, and excluding the United Nations Convention on Contracts for the International Sale of Goods.