

AMCORAIRE 2007 Single Zone 13 SEER Systems



Features

- Wireless Remote Control
- Dehumidification Mode
- Auto Swing Louver
- Auto Mode
- Temperature Display on Indoor Unit
- Sleep Mode

Amcoraire Ductless min-split Heat Pump systems are zoned in efficient at a price that you won't have to mortgage the house for. Now that's a Breath of Fresh Air.



Indoor Model #	UCHW-H09AF2	UCHW-H12AF2	UCHW-H18AF2	UCHW-H24AF2
Outdoor Model #	UCHW-H09CF2	UCHW-H12CF2	UCHW-H18CF2	UCHW-H24CF2
Capacity (BTU)				
Cooling	9,000	12,000	17,000	24,000
Heating	11,000	14,500	18,700	25,000
SEER	13.0	13.0	13.0	13.0
HSPF				
Op Range Cool	50 - 109	50 - 109	50 - 109	50 - 109
Op Range Heat	14 - 109	14 - 109	14 - 109	14 - 109
Voltage	115-60-1	115-60-1	230/208-60-1	230/208-60-1
Input Current (A)	7.2	9.6	6.5	8.5
Air Circulation CFM	295	400	648	735
Noise level dB(A)	35/42	36/45	43/49	43/49
Outdoor Noise Level dB(A)	54	60	59	59
Fan Speeds	3 + Auto	3 + Auto	3 + Auto	3 + Auto
Connection Method				
	Flare	Flare	Flare	Flare
Max Pipe Length (Ft.)	50	50	100	100
Max Elevation (Ft.)	25	25	50	50
Pipe Size (In.)	1/4—1/2	1/4—1/2	3/8—5/8	3/8—5/8
Service Port Connection (In.)	5/16	5/16	5/16	5/16
Indoor Dimensions				
W x H x D	34-1/4 x 13-3/4 x 9-5/8	39-3/4 x 13-3/4 x 10-1/4	46-1/4 x 15-1/2 x 12-5/8	52-1/2 x 16-1/8 x 12-1/8
Net Weight (lbs.)	22	35	40	44
Outdoor Dimensions				
	23-1/2 x 36-1/4 x 13-1/4	27-1/8 x 39-1/8 x 16-3/8	40-1/2 x 37-3/4 x 17-3/8	40-1/2 x 37-3/4 x 17-3/8
Net Weight (lbs.)	73	110	143	143
Refrigerant	R-410A	R-410A	R-410A	R-410A

Some specifications above are from preliminary data and may change with final product. Please contact Amcor for updates and review installation materials prior to installing.