

UP05C8GF

Silicon NPN epitaxial planar type (Tr)
Silicon epitaxial planar type (CCD load device)

For CCD output circuits

■ Features

- Two elements incorporated into one package (Tr + CCD load device)
- Downsizing of the equipment and costs can be reduced through reduction of the number of parts

■ Basic Part Number

- 2SC3932 + CCD load device

■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

Parameter		Symbol	Rating	Unit
Tr	Collector-base voltage (Emitter open)	V_{CBO}	30	V
	Collector-emitter voltage (Base open)	V_{CEO}	20	V
	Emitter-base voltage (Collector open)	V_{EBO}	3	V
	Collector current	I_C	50	mA
CCD load device	Limiting element voltage	V_{max}	40	V
	Limiting element current	I_{max}	10	mA
Overall	Total power dissipation *	P_T	125	mW
	Junction temperature	T_j	125	$^\circ\text{C}$
	Storage temperature	T_{stg}	-55 to +125	$^\circ\text{C}$

Note) *: Measuring on substrate at 17 mm × 10 mm × 1 mm


■ Package

- Code
SSMini6-F2
- Pin Name

1: Emitter	4: Source
2: Base	5: Drain
3: Gate	6: Collector

■ Marking Symbol: 4V

■ Internal Connection



■ Electrical Characteristics $T_a = 25^{\circ}\text{C} \pm 3^{\circ}\text{C}$

• Tr

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Collector-base voltage (Emitter open)	V_{CBO}	$I_{\text{C}} = 100 \mu\text{A}$, $I_{\text{E}} = 0$	30			V
Emitter-base voltage (Collector open)	V_{EBO}	$I_{\text{E}} = 10 \mu\text{A}$, $I_{\text{C}} = 0$	3			V
Base-emitter voltage	V_{BE}	$V_{\text{CE}} = 10 \text{ V}$, $I_{\text{C}} = 2 \text{ mA}$		720		mV
Forward current transfer ratio	h_{FE}	$V_{\text{CE}} = 10 \text{ V}$, $I_{\text{C}} = 2 \text{ mA}$	100		250	—
Transition frequency *	f_{T}	$V_{\text{CB}} = 10 \text{ V}$, $I_{\text{E}} = -15 \text{ mA}$, $f = 200 \text{ MHz}$		1 300		MHz
Power gain	PG	$V_{\text{CB}} = 10 \text{ V}$, $I_{\text{E}} = -1 \text{ mA}$, $f = 100 \text{ MHz}$		20		dB








Note) 1. Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7030 measuring methods for transistors.

2. *: Pulse measurement

• CCD Load Device


Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Pinch off current	I_{P}	$V_{\text{DS}} = 10 \text{ V}$, $V_{\text{G}} = 0$	3.8		5.2	mA
Output impedance	Z_{O}	$V_{\text{DS}} = 10 \text{ V}$, $V_{\text{G}} = 0$		0.05		$\text{M}\Omega$

Note) Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7030 measuring methods for transistors.



SSMini6-F2

Unit: mm



Request for your special attention and precautions in using the technical information and semiconductors described in this book

- (1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.
- (2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products, and no license is granted under any intellectual property right or other right owned by our company or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information described in this book.
- (3) The products described in this book are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
 - Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
 - Any applications other than the standard applications intended.
- (4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
 - ☐ Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.
- (7) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of Matsushita Electric Industrial Co., Ltd.