

**TOSHIBA**



**TOSHIBA AMERICA INFORMATION SYSTEMS  
STORAGE DEVICE DIVISION  
IRVINE, CALIFORNIA**

**MK2006GAL (HDD1488)  
1.8-INCH HARD DISK DRIVE  
USER MANUAL**

## CONTENTS

Introduction.....	1
Setup .....	2
Using the HDD .....	3
Specifications .....	4
Drive Connectors.....	6

## INTRODUCTION – MK2006GAL (HDD1488) HARD DISK DRIVE

### General Features

- 1.8" sized drive
- 1 Platter
- 20 Gigabytes\*
- 5mm High
- 15ms Average Seek Time
- ATA-6 Interface
- Ultra DMA 100
- 2Mbytes Buffer
- Rotational speed of 4,200rpm
- MTTF 300,000 Hours

*\*Toshiba defines a megabyte (MB) as 1,000,000 bytes and a gigabyte (GB) as 1,000,000,000 bytes.*

## SETUP – MK2006GAL (HDD1488) HARD DISK DRIVE



**Caution:** Your Hard Disk Drive is a precision device and even a small drop onto any surface can cause damage. Electrostatic discharge can also damage the drive. You should ground yourself prior to handling the drive.



*Figure 1. MK2006GAL Side View*

### Installation Notes

- Do not apply any force to the top cover, except the screw areas on top cover. Maximum force to the specified area is 2N.



**important Note:** *Disconnect power from your computer system before beginning installation*

## USING THE HARD DISK DRIVE – MK2006GAL (HDD1488) HARD DISK DRIVE

### **Backing up Data Files**

To avoid data loss, regularly back up the data files on the hard disk drive.

## SPECIFICATIONS – MK2006GAL (HDD1488) HARD DISK DRIVE

### General

Model	MK2006GAL (MK1488)
Interface	ATA-6

### Functionality

Formatted Capacity	20.0GB*
Rotational Speed	4200rpm
Avg. Rotational Latency	7.14/ms
Spin-up Time	3.5sec (typical)
Buffer	2Mbytes
Seek Time	
Average	15
Maximum	26
Internal Transfer Rate	132 ~ 230 Mbits/sec (max)
Host Transfer Rate	
Ultra DMA mode	100Mbytes/sec
PIO Mode	16.6Mbytes/sec
Interleave Factor	1:1

\*Toshiba defines a megabyte (MB) as 1,000,000 bytes and a gigabyte (GB) as 1,000,000,000 bytes.

### Internal Drive Characteristics

Number of Disks	1
Number of Data Heads	2
Track Density (TPI)	4,331 (110k)
Logical Cylinders	16,383
Logical Heads	16
Logical Sectors/track	63
Bytes per Sector	512
Logical Blocks (LBA)	39,063,024

### Reliability

Preventative maintenance	None
Non-recoverable read errors	1 error per 10 <sup>13</sup> bits read

### Electrical

Voltage	3.3V 5%
---------	---------

### Power Consumption

Start	1.8W typ
Seek	1.1W typ
Read/Write	1.1W typ
Sleep	0.07W typ
Energy Consumption Efficiency	0.015W/GB avg
Shock	
Operating	4,900m/s <sup>2</sup> (500G)(2msec)
Non-Operating	14,700m/s <sup>2</sup> (1500G)(1msec)

## Physical

Height	0.2" (5.0mm)
Width	2.13" (54.0mm)
Depth	3.09" (78.5mm)
Weight	1.8oz (51g) typ

## Regulatory

The drive satisfies the following standards:

Underwriters Laboratories (UL)	1950
Canadian Standard Association (CSA)	C22.2 No. 950
TUV Rheinland	EN 60 950
BSMI	D33003

## DRIVE CONNECTORS – MK2006GAL (HDD1488) HARD DISK DRIVE



*Figure 1. MK2006GAL HDD - INTERFACE CONNECTOR*

### **Interface Connector**

Drive Side Connector

MCD-D50 Series by DDK Connectors

Recommended Host Side Connector

MCD-D50 Series by DDK Connectors



## Interface Signals

DRIVE INTERFACE SIGNALS			
PIN	SIGNAL	PIN	SIGNAL
1	RESET	2	GROUND
3	DD 7	4	DD 8
5	DD 6	6	DD 9
7	DD 5	8	DD 10
9	DD 4	10	DD 11
11	DD 3	12	DD 12
13	DD 2	14	DD 13
15	DD 1	16	DD 14
17	DD 0	18	DD 15
19	GROUND	20	OPEN
21	DMARQ	22	GROUND
23	DIOW/STOP	24	GROUND
25	DIOR/ -DMARDY HSTROBE	26	GROUND
27	IORDY/ -DMARDY/ DSTROBE	28	CSEL
29	DMACK	30	GROUND
31	INTRQ	32	IOCS16
33	DA1	34	PDIAG
35	DA0	36	DA 2
37	CS0	38	CS1
39	DASP	40	GROUND
41	3.3V (LOGIC)	42	3.3V (MOTOR)
43	GROUND	44	RESERVED
<i>Note: Symbol () in front of signal indicates negative logic.</i>			