

100Base-FX PCI Network Cards

| PART NUMBER | DESCRIPTION |
|-------------|-----------------------------------------|
| FEP-4208-C | 100Base-FX (SC, MM) PCI Adapter Card |
| FEP-4208-T | 100Base-FX (ST, MM) PCI Adapter Card |
| FEP-4208-M | 100Base-FX (MT-RJ, MM) PCI Adapter Card |
| FEP-4208-V | 100Base-FX (VF-45, MM) PCI Adapter Card |

Specifications

Standards:

IEEE 802.3u 100Base-FX standards

Protocol:

32-bit PCI

Interface:

SC, ST, MT-RJ or VF-45 connector for Multi-Mode cable

Data Rate:

Up to 200Mbps in Full-Duplex mode

Cable Distance:

62.5/125 μ m Multi-Mode fiber optic cable, up to 2,000m.

LED Indicators:

LNK, TX, RX, FDX

Operation Temperature:

0°C - 50°C

Storage Temperature:

-20°C - 70°C

Operation Humidity:

10% - 90%

Storage Humidity:

10% - 90%

EMI:

FCC Class A, CE

Drivers Supported:

Novell ODI Client/Server
 Microsoft LAN Managers for DOS or OS/2
 Windows for Work group 3.X
 Windows NT 3.X
 Windows '95, '98, 2000
 Lantastic 4.X or 5.X
 SCO UNIX



908 Canada Court
 City of Industry, CA 91748 U.S.A.

Phone: 626.964.7873 or 800.346.6668 Fax: 626.964.7880
 www.unicomlink.com e-mail: info@unicomlink.com

©UNICOM 2007. UNICOM is a trademark of UNICOM Electric, Inc. All rights reserved.
 Specifications subject to change without notice.