

SATA / IDE TO USB 2.0 Adapter

SUPPORT 2.5", 3.5" & 5.25" IDE/SATA DRIVE

PRODUCT DESCRIPTION

of connecting almost any type of drive to your computer via USB. SATA, 3.5" IDE, 5.25" IDE, and 2.5"

IDE drives are all supported and can be easily hot-swapped to your system. The included exter-

nal power adapter will allow you to power your

quickly add or swap between drives without

opening your case. The SATA/IDE-USB adapter

incorporate 3 interfaces to one USB adapters.

drives outside your system giving you the ability to

The SATA/IDE-USB Adapter gives you the flexibility

SATA / IDE TO USB 2.0 Ade

SATA

[FEATURES]

Tweak

Your

- Transfer Rates Up to 12Mbps With USB 1.1
- Transfer Rates Up to 480Mbps With USB 2.0
- Easily add storage to any system with USB
- Currently supports up to 500GB
- Supports ATA/ATAPI-7
- Supports LBA-48 Addressing
- Hot-swappable: Plug and play without rebooting!

SPECIFICATION

Interface: SATA to USB 2.0

3.5" & 5.25" IDE to USB 2.0

2.5" IDE to USB 2.0

- Dimensions: 70 x 43 x 10 mm
- Cable Length: 92cm (36in)

SYSTEM REQUIREMENTS]

Intel Pentium II 350MHz-compatible or Apple G3 processor and greater Microsoft Windows 98SE/ME/2000/XP or Mac OS 8.6 and greater USB-equipped system

For USB 2.0 speeds, the system must support USB 2.0 specifications CD Rom drive (if drivers are needed)

MODEL: CB-ISATAU2

Tel: (510) 668-0368 Fax: (510) 668-0367 Address: 43951 Boscell Road Fremont, CA 94538

Copyright 2006 Vantec Thermal Technologies. All Rights Reserved All Registered Trademarks Belong To Their Respective Companies. www.vantecusa.com