



# IP Mini-DSLAM

## Total Access 1250 IP Mini-DSLAM

### Product Features

- Cost-effective DSLAM for CO, CEV, MDU, RT, and customer premises applications
- 24 ports of ADSL plus baseband POTS
- DMT, G.Lite, and T1.413 modulations
- Front panel access to all connections
- Two field replaceable GMT-type 3 amp fuses
- POTS service is not power dependent
- Provisioning and alarm monitoring via SNMP/ASCII text and TL1 through the local craft interface and in-band management channel
- Both short and long haul T1s (DSX-1 and DS1) can be used
- Industry-leading 10-year warranty

**Carriers are seeking cost-effective DSLAM solutions to meet demand for additional customer applications.** The ADTRAN™ Total Access® 1250 is a temperature-hardened Mini-DSLAM that enables delivery of 24 ports of POTS and ADSL via an Ethernet 10/100Base-T interface from smaller Central Offices (COs), Controlled Environmental Vaults (CEVs), Multiple Dwelling Units (MDUs), and Remote Terminals (RTs). The ADSL is derived from the network interface and is combined via onboard splitters with the existing POTS service for single-pair subscriber delivery.

The Total Access 1250 offers a scalable network interface today with the Ethernet interface module. The IP interface module supports 1483/2684 bridging via either LLC/SNAP or VC MUX encapsulation. Statistics are collected on both the subscriber and network parts.

The compact, 1U high unit provides space savings while offering multiple options for placement within compact environments. Its design leverages existing telco resources and can be rackmounted, wallmounted, or vertically positioned within the RT. It measures 1.75 in. H x 17.25 in. W x 11.125 in. D and offers redundant power using -42 to -56 VDC.

The Total Access 1250 is equipped with fan modules and filters. Each fan unit is independently field replaceable. The fans are controlled by heat-sensing circuits and will run only when necessary. Front panel access is available to all connections.

The ability to connect to the Total Access 1250 via an IP uplink at the customer premises immediately improves the economics of broadband for businesses such as hotels, service-based organizations, and small-to-mid-sized enterprises (SMEs). Carriers benefit by expanding IP in their existing networks without costly ATM server installations. This is especially true for network applications that don't require the expense associated with ATM-QoS. In these cases, IP is more ubiquitous and cost-efficient for both intra- and inter-network operations.

Management options include SNMP, ACSII, TL1, Telnet, or local VT100 interfaces. Menu-driven interfaces are simple and intuitive, ensuring a successful service implementation through local and remote access.

ADTRAN's Total Access 1250 Mini-DSLAM brings cost-effective and space-efficient ADSL with POTS solutions to carriers providing subscriber services at rural CO, MDU, CEV, and RT sites.





# IP Mini-DSLAM



## ADTRAN, Inc.

901 Explorer Boulevard  
Huntsville, AL 35806

P.O. Box 140000  
Huntsville, AL 35814-4000

256 963 8000 voice  
256 963 8030 fax  
877 457 5007 fax back

## General Information

800 9ADTRAN  
info@adtran.com  
www.adtran.com

## Pre-Sales

### Technical Support

888 5ADTRAN  
support@adtran.com  
www.adtran.com/support

## Where to Buy

800 827 0807  
www.adtran.com/where2buy

## Post-Sales

### Technical Support

800 726 8663  
support@adtran.com  
www.adtran.com/support

## Regional Offices

Dallas, TX  
972 830 9070  
Denver, CO  
303 471 9150  
Irvine, CA  
949 260 3500  
Kansas City, KS  
800 471 8649  
Newark, NJ  
800 471 8656  
Ontario, Canada  
416 290 0585  
Quebec, Canada  
877 923 8726  
San Antonio, TX  
888 223 7671

## International Inquiries

256 963 8000 voice  
256 963 6300 fax  
international@adtran.com  
www.adtran.com/international



I.S. EN ISO 9001  
ADTRAN is an  
ISO 9001:2000 registered company.



TL 9000  
ADTRAN is a  
TL 9000 registered company.

Printed in the USA  
64179611L3-8A July 2003

©2003 ADTRAN, Inc. All rights reserved.

## Total Access 1250 IP Mini-DSLAM

### Product Specifications

#### Front Panel Features

- **Five LEDs:** Power, ADSL, Network, Alarm, Ethernet
- **Two 50-pin Amphenol interfaces:** POTS, ADSL+POTS
- DB-9 craft interface
- DB-15 Alarm Interface, Input/Output
- RJ-45 uplink interface

#### Mechanical

- **Dimensions:** 1.75 in. H x 17.25 in. W x 11.125 in. D
  - **Weight:** 8 lbs.
  - **Mounting:** Rackmount or Wallmount
- Can be mounted in either a flush mount or mid-mount orientation in either a 19-inch or 23-inch rack.

#### Interfaces

##### Network Interfaces

- 10/100Base-T Ethernet
- POTS

##### Subscriber Interfaces

- ADSL+POTS

#### Electrical

- -42 VDC to -56 VDC

#### Regulatory Standards

- NEBS Level 3
- GR-1089-CORE, Issue 3
- GR-63-CORE, Issue 2
- NRTL Safety Listed

#### Management

- **Local management:** ASCII – menu
- **Remote management:** SNMP, TL1, 10Base-T Ethernet (future)

#### Environmental

- **Operating:** -40°C to +70°C
- **Storage:** -40°C to +85°C
- **Relative humidity:** 95 percent, noncondensing

### Ordering Information

Equipment	Part #
Total Access 1250 IP Mini-DSLAM	4179611L3
Total Access 1200 RDS Shelf, 19-inch, 24-port	1179601L1
Total Access 1250 IP Module	1179611L3



Specifications are subject to change without notice. ADTRAN is a trademark and Total Access is a registered trademark of ADTRAN, Inc. All other registered trademarks and trademarks mentioned in this publication are the property of their respective owners.