

Easy Configuration and Management

Support web based GUI, Telnet and Hyperterminal for configuration and management. Also supports remote management (Web and telnet) capability for remote user to configure and manage this product. It incorporates besides a client DynamicDNS

I-Fly Wireless Router ADSL

4 Fast Ethernet ports, Firewall, VPN with 3DES accelerator







WIRELESS









[echnical Features:

Interfaces

WAN(ADSL/ADSL2): RJ11

LAN: 4 RJ45 10/100 Base-T Ethernet

Wireless: 2 X 5Dbi Antennas Console: 1 cable PS2-RS232(DB9) 9 diagnostic LEDs, Reset and Power Switch

Standards ADSL/ADSL2/ATM/PAYLOAD

ADSL: ANSI T1.413 issue 2 / ITU-T G.992.1 (G.dmt) (8Mbps download, 1Mbps upload) G.992.2 (G.lite) (8Mbps download, 1Mbps upload) / G.992.4 (G.hs)

ADSL2: ITU G.992.3 (G.dmt.bis) (12Mbps download, 1Mbps upload)* ATM: ATM AAL2/AAL5 and ATM service class: CBR, UBR, VBR-rt, VBR, ATM Forum UNI 3.0, 3.1 and 4.0 Payload encapsulation: RFC 2364 (PPPoA), RFC 2516 (PPPoE), RFC 1483 Routed and Bridge and RFC

1577(IPoA)

Wireless

Standard IEEE802.11g and IEEE802.11b DSSS(Direct Sequence Spread Spectrum) Modulation: QPSK / BPSK / CCK and OFDM

RF Frequency/ Operating Channel:2.400 GHz ~2.4835GHz /13 (Europe)

Data Rate (with automatic adaptation): 802.11g: Up to 54Mbps (with Automatic Fall-Back) Intersil's Nitro Technology [higher overall performance in the real world environment]

Coverage Area: [Outdoor <100M / Indoor <30M] 2 X 5Dbi external detachable Antennas (reverse SMA) Wi-Fi Protected Access (WPA) and WEP 64/128

Firewall & Security

Rich packet filter, Content filter, Mac Filtering, URL blocking and Keywords Filtering DoS, Intrusion Detection, Stateful Packet Inspection, System security Log and real time attack alert NAT, PAP, CHAP

PPTP Client/Server embedded [Key Length:40 or 128 bit / Mode: Stateful, Stateless] IPSec embedded (AH, ESP, IKE) [Authentication: MD5, SH1 / Encryption: DES, 3DES, AES] With built-in DES/3DES accelerator [up to 3.5Mbps], the router enhances the IPSec VPN performance significantly. VPN Pass-Through

Management

Easy Web GUI (also remote), Telnet (also remote), Hyperterminal and SNMP [v1,v2 & v3] for configuration Firmware upgrade from local (Web, Telnet, PS2 port) or remote site (Web, Telnet) SysLog & Recovery disaster (PS2 port)

Network Protocols

RIP1, RIP2, STATIC ROUTING, IP, ICMP, TCP, UDP, IGMP Virtual Server, Universal Plug-and-Play(UPnP) & DMZ DHCP Server, Client & Relay / DNS Relay / POP3(check account e-mail)

Advanced Characteristics

Dynamic DNS (Dyndns, Zoneedit, Orgdns, Dhs, Dyns, Minidns, No-ip)
IP Throttling: [Using IP Throttling, bandwidth limits can be enforced on any system within your LAN, or even on a particular

Quality of Service:[The Prioritization functions allow you to specify which packets have priority and should not be delayed, and/or which packets have low priority and should be moved to the end of upload queues.]

Physical and Environmental

Power Consumation: (12V ± 5%, 1A)

Dimensions/ Weight: 210mm*145mm*32mm / 350g

Temperature Operating:[0°C to 40°C], Storage:[-20°C to 65°C], Humidity: 5-95% (without condensing)

Package contents

PPPC

I-Fly Wireless Router ADSL with CD-ROM containing the online manual (English, French and Italian), firmware and SNMP

Quick start guide (English, French, Italian, German and Spanish)

RJ-11 ADSL/telephone cable, CAT-5 LAN cable, RS232(DB9)-PS2 cable and AC-DC power adapter (12V, 1A)

I-Fly Wireless Router ADSL

4 Fast Ethernet ports, Firewall, VPN with 3DES accelerator

A02-WRA4-54G



WIRELESS

Application:





8 ports Fast Ethernet Desktop Switch I-Fly PCMCIA Card A02-WPCM-54G I-Fly Wireless Lan Router ADSL with Firewall & VPN A02-WRA4,54G I-Fly PCI Adapter A02-WP-54G Failed Attack I-Storm USB ADSL modem A01-AU1 I-Storm Lan Router ADSL with Firewall & VPN A02-RA3+ Failed Attack

HEADQUARTERS & EUROPE: Atlantis Land S.p.A. viale De Gasperi, 122 Mazzo di Rho - MI - Italy info@atlantis-land.com sales.@atlantis-land.com


Atlantis Land Technology L.t.d. 3rd. Floor, Jonsim Palace 228 Queen's Road East. Wanchai, Honk Kong info.hk@atlantis-land.com sales.hk@atlantis-land.com

INTERNATIONAL SALES FRANCE:

Atlantis Land France 57, Rue d'Amsterdam 75008 Paris - France info.fr@atlantis-land.com sales.fr@atlantis-land.com

FAR EAST & USA SALES: Atlantis Land International Sales Office N°. 249 Hsining South Rd. Taipei - Taiwan info.tw@atlantis-land.com sales.tw@atlantis-land.com

LEGENDA



WARRANTY 36 MONTHS "ON SITE"!

This ATLANTIS LAND® Networking product is warranted for 36 months with immediate substitution.

Due to the absolute relevance of this product ATLANTIS LAND® will send directly to the final customer the new substitutive product as soon as it will receive information about the defect and it will also retire the previous product . For defect we mean any kind of non functioning with the exclusion of natural phenomena and clear fraud.

The instructions for obtaining the substitution are wrote down in the hand book attached to the ATLANTIS LAND® product and on the web site www.atlantis-land.com.

ATLANTIS LAND S.p.A. via De Gasperi 122 - 20017 Mazzo di Rho (MI) Tel. 02 9390.6085 - Fax 02 9390.6161 - www.atlantis-land.com - info@atlantis-land.com

Company Certified ISO 9001:2000