


Overview

HP recommends Windows Vista™ Business



- | | |
|---|--|
| 1. Monitor (sold separately) | 7. 2 PCI, 3 PCI-X, 1 PCI Express slots |
| 2. 2004 Standard Keyboard | 8. 1 PCI Express x16 Graphics Bus |
| 3. 2-Button Scroll Mouse | 9. Dual 64-bit Intel® Xeon® processors |
| 4. Front IO: 2 USB 2.0, IEEE-1394 (standard), headphone and microphone | 10. 8 DIMM slots for DDR2 memory |
| 5. 5.25" external bay for optional diskette drive, optical drive or other 5.25"/3.5" device | 11. 6 USB 2.0, 1 standard serial port, 1 parallel port, 2 PS/2, 1 RJ-45, audio in/out, microphone, 1 IEEE-1394 |
| 6. 5 internal 3.5" bays, 3 external 5.25" bays | 12. 600 watt power supply |

At A Glance

- 64-bit Intel® Xeon® processors
- Choice of operating systems:
 - Microsoft Windows XP Professional
 - Microsoft Windows XP Professional x64 Edition (see <http://www.hp.com/workstations/pws/windowsxp64/> for details)
 - Red Hat Enterprise Linux Workstation 3.0 (32- or 64-bit version)
 - HP Linux Installer Kit (see <http://www.hp.com/workstations/software/linux/> for details)
- Up to 16 GB of DDR2 memory
- PCI-Express I/O and graphics
- Integrated Intel NetXtreme Gigabit ethernet
- 800 MHz processor front side bus support, depending on processor
- Intel Hyper-Threading technology support
- SATA and Ultra 320 SCSI drives
- Digital AC97 integrated audio with internal speaker
- Pre-loaded Manageability tools
- Energy Star compliance with energy-saving features
- Protected by HP Services, including a 3-3-3 standard warranty. Terms and conditions vary by country. Certain restrictions and exclusions apply.

Standard Features - Custom Components

Processor and Speed – Intel Xeon Processor with 800 MHz Front Side Bus

One of the following

- 2.80 GHz (2 MB L2 cache)
- 3.00 GHz (2 MB L2 cache)
- 3.20 GHz (2 MB L2 cache)
- 3.40 GHz (2 MB L2 cache)
- 3.60 GHz (2 MB L2 cache)
- 3.80 GHz (2 MB L2 cache)

2nd Intel Xeon Processor with 800 MHz Front Side Bus

- 2.80 GHz (2 MB L2 cache)
- 3.00 GHz (2 MB L2 cache)
- 3.20 GHz (2 MB L2 cache)
- 3.40 GHz (2 MB L2 cache)
- 3.60 GHz (2 MB L2 cache)
- 3.80 GHz (2 MB L2 cache)

Operating System –

One of the following

- Microsoft Windows XP Professional SP2
- Microsoft Windows XP Professional x64 Edition
- Red Hat Enterprise Linux Workstation 3 Update 5 (as an After Market Option only)
- HP Installer CD for Red Hat Linux 7.2, 7.3 and Workstation 3 Box Set (64 bit)

See <http://www.hp.com/workstations/software/linux/>.
Click on "Hardware support matrix" under "Related links" for details.

Transition Tool Kit HP 64-bit Xeon Transition Tool Kit

1st Hard Disk Drive

One of the following

Serial ATA 3Gb/s Hard Drives

(Currently supported only at 1.5Gb/s. To get 3Gb/s performance, a SATA 3Gb/s controller must be added - availability Fall '05)

- 80 GB SATA 3.0Gb/s 7200 rpm Hard Drive (8 MB cache)
- 160 GB SATA 3.0Gb/s 7200 rpm Hard Drive (8 MB cache)
- 250 GB SATA 3.0Gb/s 7200 rpm Hard Drive (8 MB cache)
- 500 GB SATA 3.0Gb/s 7200 rpm Hard Drive (8 MB cache)

Serial ATA 1.5Gb/s Hard Drives

- 74 GB SATA 1.5Gb/s 10K rpm Hard Drive (8 MB cache)

Ultra320 SCSI Hard Drives

- 73 GB Ultra320 SCSI 10K rpm Hard Drive
- 300 GB Ultra320 SCSI 10K rpm Hard Drive
- 36 GB Ultra320 SCSI 15K rpm Hard Drive
- 73 GB Ultra320 SCSI 15K rpm Hard Drive

Windows XP	Red Hat Linux
------------	---------------

32-Bit, 64-Bit	WS3, WS4
----------------	----------

32-Bit, 64-Bit	WS3, WS4
----------------	----------

32-Bit, 64-Bit	WS3, WS4
----------------	----------

32-Bit, 64-Bit	WS3, WS4
----------------	----------

32-Bit, 64-Bit	WS3, WS4
----------------	----------

32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
----------------	--------------------

32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
----------------	--------------------

32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
----------------	--------------------

32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
----------------	--------------------

Standard Features - Custom Components

2nd* Hard Disk Drive	Serial ATA 3Gb/s Hard Drives		
One of the following	2nd hard drive, 80 GB SATA 3.0Gb/s 7200 rpm Hard Drive (8 MB cache)	32-Bit, 64-Bit	WS3, WS4
	2nd hard drive, 160 GB SATA 3.0Gb/s 7200 rpm Hard Drive (8 MB cache)	32-Bit, 64-Bit	WS3, WS4
	2nd hard drive, 250 GB SATA 3.0Gb/s 7200 rpm Hard Drive (8 MB cache)	32-Bit, 64-Bit	WS3, WS4
	2nd hard drive, 500 GB SATA 3.0Gb/s 7200 rpm Hard Drive (8 MB cache)	32-Bit, 64-Bit	WS3, WS4
	Serial ATA 1.5Gb/s Hard Drives		
	2nd hard drive, 74 GB SATA 1.5Gb/s 10K rpm Hard Drive (8 MB cache)	32-Bit, 64-Bit	WS3, WS4
	Ultra320 SCSI Hard Drives		
	2nd hard drive, 73 GB Ultra320 SCSI 10K rpm Hard Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	2nd hard drive, 146 GB Ultra320 SCSI 10K rpm Hard Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	2nd hard drive, 300 GB Ultra320 SCSI 10K rpm Hard Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	2nd hard drive, 36 GB Ultra320 SCSI 15K rpm Hard Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	2nd hard drive, 73 GB Ultra320 SCSI 15K rpm Hard Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4

***NOTE:** Red Hat Linux WS3, 64-bit does not support mixing of drive types. When using a Serial ATA 2nd hard drive, the first must also be a Serial ATA hard drive.

3rd* Hard Disk Drive		Windows XP	Red Hat Linux
One of the following	Serial ATA 3Gb/s Hard Drives **		
	3rd hard drive, 80 GB SATA 3.0Gb/s 7200 rpm Hard Drive	32-Bit, 64-Bit	WS3, WS4
	3rd hard drive, 160 GB SATA 3.0Gb/s 7200 rpm Hard Drive	32-Bit, 64-Bit	WS3, WS4
	3rd hard drive, 250 GB SATA 7200 rpm Hard Drive (8 MB cache)	32-Bit, 64-Bit	WS3, WS4
	3rd hard drive, 500 GB SATA 7200 rpm Hard Drive (8 MB cache)	32-Bit, 64-Bit	WS3, WS4
	Serial ATA 1.5Gb/s Hard Drives**		
	3rd hard drive, 74 GB SATA 1.5Gb/s 10K rpm drive (8 MB cache)	32-Bit	WS3, WS4
	Ultra320 SCSI Hard Drives*		
	3rd hard drive, 73 GB Ultra320 SCSI 10K rpm Hard Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	3rd hard drive, 300 GB Ultra320 SCSI 10K rpm Hard Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	3rd hard drive, 36 GB Ultra320 SCSI 15K rpm Hard Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	3rd hard drive, 73 GB Ultra320 SCSI 15K rpm Hard Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4

NOTE: *Red Hat Linux WS3, 64-bit does not support mixing of drive types. When using a Serial ATA 2nd hard drive, the first must also be a Serial ATA hard drive.

**Second drive must be a Serial ATA; Serial ATA controller card required; Linux and Windows XP 64-Bit do not support more than two Serial ATA drives.

Standard Features - Custom Components

4th Hard Disk Drive One of the following		Windows XP	Red Hat Linux
Serial ATA 3Gb/s Hard Drives			
4th hard drive, 80 GB SATA 3.0Gb/s 7200 rpm Hard Drive		32-Bit, 64-Bit	WS3, WS4
4th hard drive, 160 GB SATA 3.0Gb/s 7200 rpm Hard Drive		32-Bit, 64-Bit	WS3, WS4
4th hard drive, 250 GB SATA 3.0Gb/s 7200 rpm Hard Drive (8 MB cache)		32-Bit, 64-Bit	WS3, WS4
4th hard drive, 500 GB SATA 3.0Gb/s 7200 rpm Hard Drive (8 MB cache)		32-Bit, 64-Bit	WS3, WS4
Serial ATA 1.5Gb/s Hard Drives			
4th hard drive, 74 GB SATA 1.0Gb/s 10K rpm Hard Drive (8 MB cache)		32-Bit	WS3, WS4
Ultra320 SCSI Hard Drives			
4th hard drive, 73 GB Ultra320 SCSI 10K rpm Hard Drive		32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
4th hard drive, 300 GB Ultra320 SCSI 10K rpm Hard Drive		32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
4th hard drive, 73 GB Ultra320 SCSI 15K rpm Hard Drive		32-Bit, 64-Bit	7.2, 7.3, WS3, WS4

5th*** Hard Disk Drive One of the following		Windows XP	Red Hat Linux
Ultra320 SCSI Hard Drives			
5th hard drive, 73 GB Ultra320 SCSI 10K rpm Hard Drive		32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
5th hard drive, 300 GB Ultra320 SCSI 10K rpm Hard Drive		32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
5th hard drive, 73 GB Ultra320 SCSI 15K rpm Hard Drive		32-Bit, 64-Bit	7.2, 7.3, WS3, WS4

***NOTE: Fourth hard drive must be SCSI.

Factory Integrated RAID		Windows XP	Red Hat Linux
RAID 0 Configuration – Striped Array		32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
RAID 0 Configuration - Data Array		32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
RAID 1 Configuration – Mirrored Array		32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
NOTE: Requires 2 identical hard drives (speeds, capacity, interface)			

Drive controllers		Windows XP	Red Hat Linux
LSI 3041E 4-port SAS/SATA RAID Card *		32-Bit, 64-Bit	WS3, WS4
Cable, 5 Part SCSI (required if 1st drive is SATA and any of the other drives are SCSI)			
Ultra320 back panel connect (uses HDCI connectors)			
NOTE: * No Support for SATA 1.5Gb/s non-NCQ hard drive RAID arrays. 48-Bit LBA is required.			

Standard Features - Custom Components

Memory –		Windows XP	Red Hat Linux
One of the following	512 MB PC2-3200 (DDR2 400 MHz) ECC Registered (2 x 256 MB)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	1 GB PC2-3200 (DDR2 400 MHz) ECC Registered (2 x 512 MB)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	2 GB PC2-3200 (DDR2 400 MHz) ECC Registered (2 x 1 GB)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	2 GB PC2-3200 (DDR2 400 MHz) ECC Registered (4 x 512 MB)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	3 GB PC2-3200 (DDR2 400 MHz) ECC Registered (6 x 512 MB)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	3 GB PC2-3200 (DDR2 400 MHz) ECC Registered (2 x 1GB + 2 x 512 MB)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	4 GB PC2-3200 (DDR2 400 MHz) ECC Registered (8 x 512 GB)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	4 GB PC2-3200 (DDR2 400 MHz) ECC Registered (4 x 1 GB)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	4 GB PC2-3200 (DDR2 400 MHz) ECC Registered (2 x 2 GB)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	6 GB PC2-3200 (DDR2 400 MHz) ECC Registered (6 x 1 GB)	32-Bit, 64-Bit	7.3, WS3, WS4
	8 GB PC2-3200 (DDR2 400 MHz) ECC Registered (8 x 1 GB)	64-Bit	7.3, WS3, WS4
	16 GB PC2-3200 (DDR2 400 MHz) ECC Registered (8 x 2 GB)	64-Bit	WS3, WS4

Removable Storage		Windows XP	Red Hat Linux
	HP No Optical Drive Option	all	all
	1.44 MB Diskette Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	48X CD-ROM Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	48X CD-RW Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	16X DVD-ROM drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	48X Combo CD-RW/DVD-ROM Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	16X DVD+/-RW, Dual-Layer, LightScribe* (LightScribe software works with Windows only)	32-Bit	WS3, WS4

2nd Removable Storage		Windows XP	Red Hat Linux
	48X CD-RW Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	16X DVD-ROM drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	48X Combo CD-RW/DVD-ROM Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	16X DVD+/-RW, Dual-Layer, LightScribe* (LightScribe software works with Windows only)	32-Bit	WS3, WS4

Standard Features - Custom Components

		Windows XP	Red Hat Linux
Keyboard – One of the following	PS/2 Standard Keyboard	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	USB Standard Keyboard	32-Bit, 64-Bit	WS3, WS4
Mouse – One of the following	PS/2 2-Button Scroll Mouse	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	USB 2-Button Optical Scroll Mouse	32-Bit, 64-Bit	WS3, WS4
	USB 3-Button Optical Mouse	32-Bit, 64-Bit	WS3, WS4
Audio	Integrated Digital AC97 audio with internal speaker	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
	Sound Blaster X-Fi XtremeMusic Audio Card	32-Bit, 64-Bit	Not Supported
	HP Optical Drive Internal Audio Cable (Only available with Windows XP-32 & XP 64-bit; Must order an optical drive; Can not order with the X-Fi audio card)	32-Bit, 64-Bit	
NIC	Intel Pro/1000 PT Gigabit PCIe NIC	32-Bit	WS3
	Intel Pro/1000 GT Gigabit PCI NIC	32-Bit	WS3, WS4
	Broadcom 5751 Netxtreme™ Gigabit PCIe NIC	32-Bit	WS3, WS4
Graphics	NVIDIA Quadro NVS 285 with TurboCache Technology PCIe (128 MB, VGA & DVI)	32-Bit	7.2, 7.3, WS3, WS4
	ATI FireGL V3100 PCIe (128 MB)	32-Bit	WS3, WS4
	NVIDIA Quadro FX 540 PCIe (128 MB)	32-Bit	7.2, 7.3, WS3, WS4
	NVIDIA Quadro FX 1400 PCIe (128 MB)	32-Bit	7.2, 7.3, WS3, WS4
	ATI FireGL V5100 PCIe (128 MB)	32-Bit, 64-Bit	
	NVIDIA Quadro FX 3450 PCIe (256 MB)	32-Bit	7.2, 7.3, WS3, WS4
	NVIDIA Quadro FX 4500 PCIe (512 MB)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4
Graphics Connectors	NVIDIA Quadro G-Sync Card* <i>Note: *Requires the installation of an NVIDIA Quadro FX 4500 PCIe Graphics Controller.</i>	32-Bit, 64-Bit	WS3, WS4
Miscellaneous	Hood intrusion sensor		
	Trusted Platform Module	32-Bit	
	HP Workstations Mouse Pad		

Standard Features - Custom Components

Software

	Windows XP	Red Hat Linux
Symantec Norton AntiVirus (optional)*	32-Bit	Not Supported
HP Performance Tuning Framework*	32-Bit	Not Supported
Altiris Recovery*	32-Bit	Not Supported
HP Client Manager Software v6.0*	32-Bit	Not Supported
CA® (Computer Associates) eTrust™ 64-bit Antivirus Software	64-Bit	Not Supported

*Not available with a Linux Operating System

Standard Features - Specs

Operating System (choice)	Microsoft Windows XP Professional SP2	
	Microsoft Windows XP Professional x64 Edition	
	OR HP Installer Kit for Linux (includes drivers for both 32-bit & 64-bit OS versions on HP xw9300, xw8200, xw6200 and xw4200 Workstations)	
Form factor	Minitower	
Color	Carbonite/Alloy metallic	
System Board Form Factor	E- ATX (12" x 13")	
Processor	Single or dual 64-bit Intel Xeon processors (Nocona) with Hyper-Threading Technology	
CPU Bus Speed Supported	800 MHz FSB	
Standard L2 Cache	1 MB L2 cache (non ECC) or 2 MB L2 cache	
Chipset	Intel Tumwater	
Memory Expansion Slots	8 DIMMs	
Memory Type Supported	DDR2 (ECC registered)	
Memory Speed Supported	DDR2 Synch DRAM PC2-3200 (400 MHz) Registered ECC	
Maximum Memory	16 GB (8 DIMMs slots with 2 GB DIMMS)	
Network controller	Integrated Intel Pro MT 10/100/1000 LAN	
Audio	Integrated AC'97 digital audio with S/PDIF 6-channel pass-through, stereo microphone, and Yamaha XG Lite Softsynth support	
PCI slots	2 full-length PCI slots (3 full-height PCI-X slots (one 133 MHz, two 100 MHz slots) 1 PCI Express (x8 mechanically, x4 electrically) 1 PCI Express x16 graphics	
AGP slot	None	
Bays	Total Bays = 8	
Internal Bays	<ul style="list-style-type: none"> Five 3.5 inch bays (4 with acoustic dampening rail assemblies) 	
External Bays	<ul style="list-style-type: none"> Three 5.25 inch full length 2003 mm maximum device depth (top bay is limited to 198 mm depth when optional smart cover solenoid lock is installed. Bottom bay can be converted to an internal 3.5" 3rd Hard Drive bay using optional bracket Floppy drive bay using optional bracket 	
Parallel Port	1	
Serial Port	1	
Front I/O	2 USB 2.0, Headphone, Microphone, IEEE 1394	
Rear I/O	1 IEEE-1394, 6 USB 2.0, 1 standard serial port, 1 parallel port, PS/2 keyboard and mouse, 1 RJ-45 to integrated Gigabit LAN, Audio In, Audio Out, Mic In	
USB Keyboard	Optional	
USB Mouse	Optional	
PS/2 Keyboard	1	
PS/2 Mouse	1	
Chassis Dimensions (H x W x D)	17.9 x 8.3 x 20.7 in (45.4 x 21.0 x 52.5 cm)	
System weight	Minimum config – 42 lb (19 kg) Standard config – 45 lb (20 kg) Maximum config – 54 lb (24 kg)	
Shipping weight	Standard config – 54 lb (24 kg)	
Temperature	Operating	40° to 95° F (5° to 35° C)
	Non-operating	-40° to 140° F (-40° to 60° C)
Humidity	Operating	8% to 85%
	Non-operating	8% to 90%
Maximum Altitude (nonpressurized)	Operating	10,000 ft (3,000 m)
	Non-operating	30,000 ft (9,100 m)

Standard Features - Specs

Power Supply	600W wide-ranging, active Power Factor Correction
Interfaces Supported	2 SATA interface (2 serial-ATA connectors), 2 Ultra320 SCSI interface, 2 EIDE interface (2 EIDE connectors) supported for optical drives, optional multi-bay interface
Hard Drive Controller (PCI) Supported	Ultra160 or Ultra320, or SATA RAID, or Ultra320 RAID
Preinstalled Software	
HP Performance Tuning Framework*	
HP Client Manager Software v6.0*	
Altiris Local Recovery*	
Alert Standard Format specification*	
CD/DVD software dependent on optical drive choices	
* Not available on Linux	

After-Market Options

Processors	2nd 64-bit Intel Xeon® processor with Hyper-Threading	Part Number
	64-bit Intel Xeon processor at 2.80 GHz with 800 MHz FSB & 2 MB of L2 cache	EC421AA
	64-bit Intel Xeon processor at 3.00 GHz with 800 MHz FSB & 2 MB of L2 cache	PQ903A
	64-bit Intel Xeon processor at 3.20 GHz with 800 MHz FSB & 2 MB of L2 cache	PQ904A
	64-bit Intel Xeon processor at 3.40 GHz with 800 MHz FSB & 2 MB of L2 cache	PQ905A
	64-bit Intel Xeon processor at 3.60 GHz with 800 MHz FSB & 2 MB of L2 cache	PQ906A
	64-bit Intel Xeon processor at 3.80 GHz with 800 MHz FSB & 2 MB of L2 cache	PH202A

Graphics	Multi display solutions	PCI	PCI-Express	Windows XP	Red Hat Linux	Part Number
	NVIDIA Quadro NVS 285 with TurboCache Technology PCI Express (128 MB)		X	32-Bit	7.2, 7.3, WS3, WS4	EE061AA
	DMS-59 to Dual DVI Cable for NVS cards	X	X	32-Bit		DL139A
	ATI FireGL V3100 (128 MB)		X	32-Bit		PE949A
	NVIDIA Quadro FX 540 (128 MB)		X	32-Bit	7.2, 7.3, WS3, WS4	PH791A
	NVIDIA Quadro FX 1400 (128 MB)		X	32-Bit	7.2, 7.3, WS3, WS4	PM979A
	ATI FireGL V5100 (128 MB)		X	32-Bit		PB330A
	NVIDIA Quadro FX 3450 (256 MB)		X	32-Bit	7.2, 7.3, WS3, WS4	PY640A
	NVIDIA Quadro FX 4500 (512 MB)		X	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	EA762AA

Graphics Connector	NVIDIA Quadro G-Sync*			32-Bit, 32-Bit	WS3, WS4	ED087AA
---------------------------	-----------------------	--	--	----------------	----------	---------

NOTE: * Requires the NVIDIA Quadro FX 4500 Graphics card to be installed.

Hard Drives	Serial ATA 3Gb/s Hard Drives	Windows XP	Red Hat Linux	Part Number
	NOTE: Serial ATA 3Gb/s Hard Drives (Currently supported only at 1.5Gb/s. To get 3Gb/s performance, a SATA 3Gb/s controller must be added)			
	74 GB SATA 1.5Gb/s Hard Drive (10,000 rpm)	32-Bit, 64-Bit	WS3, WS4	DX760A
	80 GB SATA 3.0Gb/s Hard Drive (7200 rpm)	32-Bit, 64-Bit	WS3, WS4	PY276AA
	160 GB SATA 3.0Gb/s Hard Drive (7200 rpm)	32-Bit, 64-Bit	WS3, WS4	PV944A
	250 GB SATA Hard Drive with NCQ (7200 rpm)	32-Bit, 64-Bit	WS3, WS4	EA788AA
	500 GB SATA 3.0Gb/s Hard Drive (7200 rpm)	32-Bit, 64-Bit	WS3, WS4	PV943A
	40 GB SATA 1.5Gb/s Hard Drive (7200 rpm)	32-Bit, 64-Bit	WS3, WS4	PB371A
	SCSI Hard Drives			
	73 GB Ultra320 SCSI Hard Drive (10K rpm)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	AA613A
	146 GB Ultra320 SCSI Hard Drive (10K rpm)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	AA614A
	300 GB Ultra320 SCSI Hard Drive (10K rpm)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	DY672A

After-Market Options

36 GB Ultra320 SCSI Hard Drive (15K rpm)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	AA616A
73 GB Ultra320 SCSI Hard Drive (15K rpm)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	AA617A
146 GB Ultra320 SCSI Hard Drive (15K rpm)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	DY671A

Hard Drive Accessories

Cable, 5-port SCSI 8200			AA818A
U320 SCSI Back Panel connector (Uses HDCI, HD68, or mini DB68 connectors)			AA658A

Removable Drive Enclosures

StorCase DX115 SATA Removable Enclosure	N/A	N/A	EA332AA
StorCase DX115 SATA/SAS Carrier Tray	N/A	N/A	RA697AA

Controllers	PCI	PCI-X	Windows XP	Red Hat Linux	Part Number
Serial ATA Controllers					
Adaptec Serial ATA 3Gb/s RAID 1420SA card		X	32-Bit, 64-Bit		ED090AA
SAS Controllers					
LSI SAS3041E Serial Attach SCSI (SAS) 4-Port Host Bus Adapter (HBA)*			X	32-Bit, 64-Bit	EH417AA
SCSI Controllers					
Optional U320 SCSI Controller - LSI 20320AR RAID 0,1 (required with SCSI HDDs)	X		32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	DZ554A
Ultra320 SCSI RAID Adaptec 2120S (Windows only)	X		32-Bit		AA850A

NOTE: * No Support for SATA 1.5Gb/s non-NCQ hard drive RAID arrays. 48-Bit LBA is required.

Input/Output Devices	Windows XP	Red Hat Linux	Part Number
Keyboards			
HP PS/2 Standard Keyboard (Carbonite/Silver)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	DT527A
HP USB Standard Keyboard (Carbonite/Silver)	32-Bit, 64-Bit	WS3, WS4	DT528A
HP USB Smart Card Keyboard	32-Bit, 64-Bit	WS3, WS4	ED707AA
Pointing Devices			
HP PS/2 2-Button Scroll Mouse (Carbonite)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	DD440B
HP USB 2-Button Optical Scroll Mouse (Carbonite/Silver)	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	DC172B
HP USB Optical 3-Button Mouse	32-Bit, 64-Bit	WS3, WS4	DY651A
HP USB Optical 3-Button 2.9M OEM Mouse	32-Bit, 64-Bit	WS3, WS4	ET424AA
USB SpaceBall 5000	32-Bit, 64-Bit	Not Supported	DV675A
USB SpaceMouse	32-Bit, 64-Bit	Not Supported	DZ203A

After-Market Options

HP SpacePilot 3D USB Intelligent Controller	32-Bit	Not Supported	EF390AA
---	--------	---------------	---------

Audio	Part Number
SoundBlaster X-Fi XtremeMusic Audio Card	EA326AA
HP Satellite Speakers	ZD929AA

Networking	NICs	PCI	PCI-Express	Windows XP	Red Hat Linux	Part Number
	Intel Pro/1000 PT Gigabit PCIe NIC		X	32-Bit	WS3	EH352AA
	Intel Pro/1000 GT Gigabit PCI NIC		X	32-Bit	WS3, WS4	AG393AA
	Broadcom 5751 Netxtreme™ Gigabit PCIe NIC		X	32-Bit	7.2, WS3 & WS4	EA833AA

Memory (DIMMs)	Windows XP	Red Hat Linux	Part Number
400 MHz DDR-2 PC2-3200 ECC Registered DIMMs			
256 MB PC2-3200 (DDR2 400 MHz) ECC Registered	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	DY656A
512 MB PC2-3200 (DDR2 400 MHz) ECC Registered	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	DY658A
1 GB PC2-3200 (DDR2 400 MHz) ECC Registered	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	DY655A
2 GB PC2-3200 (DDR2 400 MHz) ECC Registered - available winter 2005	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	PH201A

Monitors (Supported by all Operating Systems available from HP)	TFTs	Part Number
	HP TFT LP2465 (24-inch)	EF224A5#
	HP TFT L2335 (23-inch)	P9615W#
	HP TFT LP2065 (20.1-inch) TCO03 Two Tone (Carbonate/Silver)	EF227A5#
	HP TFT L2035 (20.1-inch)	P9614W#
	HP TFT L1955 (19.1-inch)	PD974A5#
	HP TFT L1755 (17-inch)	PL777AA#

After-Market Options

Optical Drives	Windows XP	Red Hat Linux	Part Number
DVD-ROM Drive 16X DVD-ROM w/ +R read	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	AA620B
CD-ROM Drive 48X Max CD-ROM Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	DC143B
CD-RW Drive 48X CD-RW Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	DE205B
Combo Drive 48X Combo DVD-ROM/CD-RW Drive	32-Bit, 64-Bit	7.2, 7.3, WS3, WS4	DE206B
DVD+/-RW Drive 16X DVD+/-RW, Dual-Layer, LightScribe (Windows 2K and XP only)	32-Bit	WS3, WS4*	DZ555B

NOTE: * LightScribe works with Windows 2K and XP only.

Removable Storage	Windows XP	Red Hat Linux	Part Number
HP 512 MB Drive Key II Flash Drive (USB 2.0)	32-Bit	WS3, WS4	ED516AA
HP 1 GB Drive Key II Flash Drive (USB 2.0)	32-Bit	WS3, WS4	AG382AA
1.44 MB Internal Floppy Drive	32-Bit	WS3, WS4	DY670A
HP StorageWorks DAT 24 USB external tape drive	32-Bit, 64-Bit	WS3, WS4	DW070A
HP StorageWorks DAT 24 USB internal tape drive	32-Bit, 64-Bit	WS3, WS4	DW069A
HP StorageWorks DAT 40 USB external tape drive	32-Bit, 64-Bit	WS3, WS4	DW023A
HP StorageWorks DAT 40 USB internal tape drive	32-Bit, 64-Bit	WS3, WS4	DW022A
HP StorageWorks DAT 72 USB external tape drive	32-Bit, 64-Bit	WS3, WS4	DW027A
HP StorageWorks DAT 72 USB internal tape drive	32-Bit, 64-Bit	WS3, WS4	DW026A
HP StorageWorks DAT 72 SCSI external tape drive	32-Bit, 64-Bit	WS3, WS4, 7.2, 7.3	Q1523B
HP StorageWorks DAT 72 SCSI internal tape drive	32-Bit, 64-Bit	WS3, WS4, 7.2, 7.3	Q1522B

The following Removable Drive Enclosure products are available from and supported by 3rd party:
 StorCase Rhino Jr. SCSI Removable Disk Enclosure
 (For NA, use: HP P/N A466719, for WW, use: vendor P/N S21A107)
 StorCase Rhino Jr. SATA 1.5Gb/s Removable Disk Enclosure (For NA, use: HP P/N A466720, for WW, use: vendor P/N S21J111)

Security	Chassis clamp lock, universal, no cable	DE817A
	Chassis clamp lock, universal, with cable	DE818A
Brackets/Stand	xw8200 slide rack kit IT/Broadcast	DY664A
	Fixed Rack Kit (IT/Broadcast)	AA640A

After-Market Options

Other Devices	Front Card Guide and Fan Kit	DY648A
----------------------	------------------------------	--------

Operating Systems	Red Hat Enterprise Linux Workstation 3 Update 7 (32-bit)	RA354AA
	Red Hat Enterprise Linux Workstation 3 Update 7 (64-bit)	RA355AA
	Red Hat Enterprise Linux Workstation 4 Update 3 (32/64-bit)	RA356AA

Software	Windows XP	Red Hat Linux	Part Number
HP Remote Graphics V3 LTU for HP WS	32-Bit	7.2, 7.3, WS3, WS4	PY682AA
HP Remote Graphics V4 LTU for HP WS	32-Bit, 64-Bit	WS3, WS4	RG088AA
HP Remote Graphics V3 Receiver LTU	32-Bit	7.2, 7.3, WS3, WS4	PY684AA
HP Remote Graphics V4 Receiver LTU	32-Bit, 64-Bit	WS3, WS4	RG090AA
HP Remote Graphics V3 software media	32-Bit	7.2, 7.3, WS3, WS4	PY685AA
HP Remote Graphics V4 software media (available 8/1/06)	32-Bit, 64-Bit	WS3, WS4	RG091AA
HP Remote SW for HP 1 year Update Subscription	32-Bit	7.2, 7.3, WS3, WS4	PN680A
HP Remote SW Receiver 1 year Update Subscription	32-Bit	7.2, 7.3, WS3, WS4	PN682A

Memory

E7525 chipset

DDR2 SDRAM ECC REGISTERED MEMORY

Memory must be added in pairs. This chart does not represent all possible memory configurations. The Intel E7525 chipset supports ECC Registered 400 MHz (PC2-3200) DDR2 memory only.

DIMM socket 1 is the furthest from the Memory Controller Hub at the top of the board. Additional DIMM slots should be populated consecutively; socket 2, 3, 4, etc. Speed mixing of memory DIMMs is not allowed. For efficient dual-channel performance, each pair of DIMMs must be same size and same DRAM technology. If mixing single sided and double sided memory, load the double sided DIMM pairs first. ECC Registered memory must be used.

If you have unused slots within a channel, chose the sockets closest to the memory controller (e.g. Sockets 7 & 8, then 5 and 6, and so on).

MAXIMUM MEMORY

Supports up to 16 GB of DDR2 SDRAM.


POSSIBLE MEMORY CONFIGURATIONS

Not all memory configurations possible are represented below.

DIMM Size	Slot							
	1	2	3	4	5	6	7	8
256 MB								
512 MB								
512 MB	256 MB	256 MB						
1 GB								
1 GB	512 MB	512 MB						
1 GB								
2 GB	1 GB	1 GB						
2 GB	512 MB	512 MB	512 MB	512 MB				
4 GB	1 GB	1 GB	1 GB	1 GB				
4 GB	512 MB							
6 GB	1 GB	1 GB	1 GB	1 GB	1 GB	1 GB		
8 GB	1 GB	1 GB	1 GB	1 GB	1 GB	1 GB	1 GB	1 GB
16 GB	2 GB	2 GB	2 GB	2 GB	2 GB	2 GB	2 GB	2 GB

Storage

Tower configuration



	Quantity Supported	Position Supported	Controller
Convertible Minitower			
Optional Diskette Drive	1	3	Diskette
5.25 inch Storage Drive Bays	3	1, 2, 3	IDE
3.5 inch Storage Drive Bays with acoustic dampening rail assemblies	5	4, 5, 6, 7, 8	SATA or SCSI

SCSI and SATA may be mixed in a Windows configuration, only the primary drive may be SATA.

SATA controller card required for 3rd and 4th SATA HDD; If SATA controller is ordered then no SCSI HDDs allowed; Linux does not support SATA controller or mixing SATA and SCSI drives.

Factory Integrated RAID*

* **NOTE:** Factory Integrated RAID 0 Configuration (Striped Array) and RAID 1 Configuration (Mirrored Array) requires 2 hard drives with identical speeds, capacity and interface.

Additional Technical Specifications

System Board	
Architecture	Xeon 64-bit/PCI-E
Chipset	Intel E7525/ICH5R Chipset
Super I/O Controller	SMSC LPC47B397
System Board Form Factor	E-ATX (12 x 13 in/30.5 x 33 cm)
Processor Socket	Dual 604 Pin ZIF
DIMM Connectors (DDR2, 1.8V)	4
AGP Connector (1.5V)	None
Integrated Graphics	None
PCI Connectors (5.0V)	2 full length 33 MHz 32-bit
PCI-X Connectors	2 full length 100 MHz 64-bit 1 full length 133 MHz 64-bit
PCI card guide	Optional, tool-free support for all full-length cards with PCI extender
Flash ROM	Yes
AC97 integrated audio	Yes
CD ROM IN (Audio)	Yes
AUX IN (Audio)	Yes
Clear CMOS Button	Yes
CPU Fan Header	Yes
Chassis Fan Header	Yes
Chassis Speaker Header	Yes
CMOS Battery Holder – Lithium	Yes
Hood Lock Header	None
Hood Sensor Header	None
Multibay Header	Yes
Hard drive acoustic dampening rails	Standard in 4 internal 3.5 inch bays, tool-free
Integrated SATA RAID	<ul style="list-style-type: none"> • RAID 0 and RAID 1 • Supports one RAID array on 2 ports • Creation of 2 drive HDD array • RAID 0 Configuration – Striped Array • RAID 1 Configuration – Mirrored Array
Integrated Intel Gigabit Ethernet	Yes
Wake-On-Lan®	Yes
ASF 1.0 (Alert Standard Format)	Will be provided in a BIOS upgrade
Power Supply Header	Yes
Power Switch, Power LED & Hard Drive LED Header	Yes
Password Clear Header	Yes
Riser Connector	None
HDD activity LED Header	Yes

Additional Technical Specifications

PCI extender that connects to System Board	None
--	------

Technical Specifications

Cooling	
Cooling Solutions Supported	Yes
Power Supply Fan	92 x 25 mm
Processor Fan-Heatsink	70 x 15 mm
Chassis Fan (front)	One 92 x 25 mm (optional)
Chassis Fan (rear)	One 120 mm x 28 mm (standard)
Internal Speaker	Standard

Power Supply																
Full Ranging Input	Yes															
Active Power Factor Correction (APFC) (Input Current is nearly ½ a non-APFC PS)	Yes															
Passive Power Factor Correction (PFC)	No															
Operating Voltage Range	90 – 264 VAC/118 VAC															
Rated Voltage Range	100 – 240 VAC															
Rated Line Frequency	50-60 Hz/400Hz															
Operating Line Frequency Range	47 – 66 Hz/393 – 407Hz															
Rated Input Current	10A/8.6A															
Maximum Rated Power	600 W															
Heat Dissipation	Typical 1206.2 btu/hr Maximum 2047.4 btu/hr															
PS Size (wide x high x deep)	92mm variable speed															
Energy Star Compliant	Yes															
Surge Tolerant Full Ranging Power Supply	Withstands power surges up to 2000V															
Typical configuration power consumption	2 processors (2x3.6GHz Xeon), 1 GB memory (2x512 MB) Two hard drives (2xSATA 40 GB), DVD-ROM drive PCI-Express Graphics Card (FX 1300) Floppy, Monitor															
	<table border="1"> <thead> <tr> <th>Input Power consumption</th> <th colspan="2">@ 120Vac/60Hz</th> </tr> </thead> <tbody> <tr> <td>Typical operating mode (system busy)</td> <td>353.5W</td> <td>= 1206.2 btu/hr</td> </tr> <tr> <td>Windows XP Idle</td> <td>210.3 W</td> <td>= 717.6 btu/hr</td> </tr> <tr> <td>Hibernate mode (S4)</td> <td>5.9 W</td> <td>= 20.1 btu/hr</td> </tr> <tr> <td>Power Off (S5)</td> <td>5.9 W</td> <td>= 20.1 btu/hr</td> </tr> </tbody> </table>	Input Power consumption	@ 120Vac/60Hz		Typical operating mode (system busy)	353.5W	= 1206.2 btu/hr	Windows XP Idle	210.3 W	= 717.6 btu/hr	Hibernate mode (S4)	5.9 W	= 20.1 btu/hr	Power Off (S5)	5.9 W	= 20.1 btu/hr
Input Power consumption	@ 120Vac/60Hz															
Typical operating mode (system busy)	353.5W	= 1206.2 btu/hr														
Windows XP Idle	210.3 W	= 717.6 btu/hr														
Hibernate mode (S4)	5.9 W	= 20.1 btu/hr														
Power Off (S5)	5.9 W	= 20.1 btu/hr														

ROM Features	Description
Instantly Available PC	Allows for very low power consumption with quick resume time
ROM Based F10 Setup and diagnostics	Review and customize BIOS settings
Remote System Installation via F12 (PXE) (Remote Boot from Server)	Allows a new or existing system to boot over the network and download software, including the operating system

Technical Specifications

System/Emergency ROM Flash Recovery with Video	Recovers corrupted system BIOS
ROM revision levels	<ul style="list-style-type: none"> Identifies system ROM revision levels and reports in ROM-based F10 setup Version is stored in an industry standard memory location (SMBIOS) so that management SW applications can use and report this information
System board revision level	<ul style="list-style-type: none"> Allows management SW to read the revision level of the system board Revision level is digitally encoded into the hardware and cannot be modified
Auto Setup when New Hardware Installed	System automatically detects addition of new hardware
Serial, Parallel, USB, Audio, Network, Enable/Disable Port Control	Enable or disables serial, parallel, USB, audio, and network ports
Removable Media Write/Boot Control	Prevents ability to boot from removable media on supported devices (and can disable writes to media)
Power-On Password	Prevents an unauthorized person from booting up the computer
Setup Password	Prevents an unauthorized person from changing the system configuration
Replicated Setup	Saves BIOS settings to diskette or USB disk-on-key in human readable file. Repset.exe utility can then replicate these settings on machines being deployed without entering ROM-based F10 setup
Memory Change Alert (Requires HP Client Manager Software)	Alerts management console if memory is removed or changed
Thermal Alert (Requires HP Client Manager Software)	<p>Monitors the temperature state within the chassis. Three modes:</p> <ul style="list-style-type: none"> NORMAL – normal temperature ranges ALERTED – excessive temperatures are detected. Raises a flag so action can be taken to avoid shutdown or provide for a smoother system shutdown SHUTDOWN – excessive temperatures are encountered. Automatically shuts down the computer without warning before hardware component damage occurs
Master Boot Record Security	Detects changes to MBR and optional restoration, useful in protecting from viruses
Remote ROM Flash	Provides secure, fail-safe ROM image management from a central network console
Remote Wakeup/shutdown	<ul style="list-style-type: none"> System administrators can power on, restart, and power off a client computer from a remote location. Enables cost-effective power consumption when the administrator needs to distribute software, perform security management, or update the ROM
ACPI (Advanced Configuration and Power Interface)	<ul style="list-style-type: none"> Allows the system to wake from a low power mode Controls system power consumption, making it possible to place individual cards and peripherals in a low-power or powered-off state without affecting other elements of the system <p>Supports ACPI 2.0 for full compatibility with 64-bit operating systems</p>
Keyboard-less Operation	The system can be operated without a keyboard
SMBIOS	System Management BIOS 2.3.5, previously known as DMI BIOS, for system management information
Localized ROM Setup	Common BIOS image supports configuration (Setup) in 11 languages, with local keyboard mappings
Asset tag	Allows user or MIS to set unique tag string in ROM
Ownership tag	Allows user or MIS to set unique tag string in ROM
Memory Scrubbing	Allows memory controller to transparently correct transient ECC errors in the background
Memory Remapping	Allows system memory lost to PCI devices to be reclaimed above 4 GB, for use with operating systems that support more than 4 GB (Windows XP 64-bit edition, Linux)
Per-slot control	Allows individual slot configuration (option ROM., latency)
Adaptive cooling	Fan control parameters are set according to detected hardware configuration for optimal acoustics
Pre-boot diagnostics	Early (pre-video) critical errors are reported via beeps and blinks on the power LED

Technical Specifications

Other deployment & management features	
HP Client Management Solutions	<p>HP Client Management Solutions help simplify management of Workstations and significantly reduce total ownership costs. These solutions share a common design and are highly integrated due to the extensive work between HP and its partner Altiris.</p> <p>HP Client Manager Software is included free with all HP business PCs and Workstations. It enables central tracking, monitoring, and management of the hardware aspects of HP client systems:</p> <ul style="list-style-type: none"> ● Get valuable hardware information such as CPU, memory, video, and security settings ● Monitor system health to fix problems before they occur ● Install drivers and BIOS updates without visiting each PC ● Remotely configure BIOS and security settings ● Automate processes to quickly resolve hardware problems <p>Additional Altiris solutions (fee-based) are available to address Workstation management challenges through the entire IT lifecycle including:</p> <ul style="list-style-type: none"> ● Inventory assessment ● Software license compliance ● Personality migration ● Software image deployment ● Software distribution ● Asset management ● Client backup and recovery ● Problem resolution <p>Visit http://www.hp.com/go/easydeploy for more information, to download HP Client Manager Software, and to evaluate the Altiris solutions.</p>
System Software Manager (free)	A free utility that detects and updates BIOS, device drivers, and management agent versions on your networked PCs and workstations
Altiris Local Recovery	Provides data and system file protection for HP business PCs to enable fast recovery of information that is accidentally deleted or if the system becomes corrupted. Designed for disconnected or seldom-connected users, Local Recovery protects your HP computer's data and system state by taking scheduled snapshots, which are then stored in a protected area on the local hard disk. System backup and disaster recovery is now simple and fast for all users, regardless of connectivity
Replicated Setup	Saves BIOS settings to diskette or USB disk-on-key in human readable file. Repset.exe utility can then replicate these settings on machines being deployed without entering ROM-based F10 setup
Software Restore CD	Restores computer to its original factory shipping image
Asset Tag	<ul style="list-style-type: none"> ● Repository for storing company-specific property asset numbers for easy tracking ● Initially set equal to the system serial number ● Stored in a protected section of non-volatile memory that can be accessed and modified with the F10 Setup program
DIMM Serial Presence Detect	Detects whether or not memory DIMMs are present and their type
Hard drive serial number, model, and manufacturer	Hard drive manufacturer, model, and serial number is stored in the hard drive firmware and reported in ROM-based F10 setup
Memory Change Alert (Requires HP Client Manager Software)	Alerts management console if memory is removed or changed
Ownership Tag	A user-defined string stored in non-volatile memory that is displayed in the BIOS splash screen
Ultra ATA Integrity Monitoring (CRC Checking)	A feature of SATA and SCSI, Cyclic Redundancy Checking provides data transfer verification and proactive notification of hard drive data transmission problems with recommendations for enhancing system performance. It detects all the following errors' types:

Technical Specifications

	<ul style="list-style-type: none"> • single bit errors • double bit errors • an odd number of errors • error bursts up to 32-bits long
Drive Self Tests (DPS)	<ul style="list-style-type: none"> • Drive Protection System (Adaptec and LSI SCSI controllers do not offer DPS) • A diagnostic hard drive self test. It scans critical physical components and every sector of the hard drive for physical faults and then reports any faults to the user. • Running independently of the operating system, it can be accessed through the computer's setup procedure. It produces an evaluation on whether the hard drive is the source of the problem and needs to be replaced. <p>The system expands on the Self-Monitoring, Analysis, and Reporting Technology (SMART), a continuously running systems diagnostic that alerts the user to certain types of failures. DPS Access through F10 Setup during Boot (F10 diagnostic access not available with SCSI drives)</p>
SMART Technology (Self-Monitoring, Analysis and Reporting Technology)	<p>Allows hard drives to monitor their own health and to raise flags if imminent failures were predicted before they occur. Tracks fault prediction and failure indication parameters such as re-allocated sector count, spin retry count, calibration retry count.</p> <p>By avoiding actual hard drive failures, SMART hard drives act as "insurance" against unplanned user downtime and potential data loss from hard drive failure.</p> <p>SMART I – Drive Failure Prediction SMART II – Off-Line Data Collection SMART III – Off-Line Read Scanning with Defect Reallocation</p>

Security Features	
Access panel key lock (standard)	Prevents removal of the access panel and all internal components including optical and floppy drives
Padlock (optional)	Prevents entire system theft and discourages access panel removal. 7mm diameter padlock loop at rear of system.
Kensington Cable Lock (optional)	Prevents entire system theft only. 3mm x 7mm slot at rear of system.
Universal chassis clamp lock (optional)	The version without a cable discourages access panel removal and prevents theft of IO devices. The version with a cable additionally prevents entire system theft and allows multiple systems to be secured with a single cable.

Serviceability Features of System	
Access panel	Tool-less, one-handed
Optical drives	Tool-less
Floppy drive	Tool-less
Hard drives	Tool-less
Expansion cards	Tool-less
Green user touch points	Yes, on tool-free internal chassis mechanisms
Color-coordinated cables and connectors	Yes
Memory	Tool-less, can be upgraded without removing any internal components
CPUs	Tool-less, can be upgraded without removing any internal components
Chassis fan removal	Tool-less
Power supply diagnostic LED	Yes, dual function: AC OK & power OK
Power Button	Yes, ACPI multi-function
Power LED	Yes, dual color LED indicates normal operation and faults.
Hard drive activity LED	Yes
Internal speaker	Yes, used for pre-boot diagnostic beep codes

Technical Specifications

Dual Color Power and HD LED on Front of Computer (Indicates Normal Operations and Fault Conditions)	green – normal red – fault
System/Emergency ROM Flash Recovery with Video	Recovers corrupted system BIOS.
Configuration Record SW	Yes
Over-Temp Warning on Screen (Requires IM Agents)	Yes
OS CD (Restore OS CD)	Restores computer to its original factory shipping image
Restore CD	Restores the computer to its original factory shipping image
Flash ROM	Yes
3.3V Aux Power LED on System PCA	Yes
Dual Function 5V Aux Power LED (ON)/PS_ON LED (OFF) on System PCA	Yes
Clear Password Jumper	Yes
Clear CMOS Button	Yes
CMOS Battery Holder for easy Replacement	Yes
Processor ZIF Socket for easy Upgrade	Yes
DIMM Connectors for easy Upgrade	Yes
NIC LEDs (integrated) (Green & Amber)	Used to determine NIC status
ASF 1.0 support (Alert Standard Format)	Industry-standard specification for network alerting in operating system-absent environments
Dual function front power switch	Causes a fail-safe power off when held for 4 seconds

Service and Support	On-site Warranty and Service (Note 1): This three-year, limited warranty and service offering delivers three years of on-site, next business-day (Note 2) service for parts and labor and includes free telephone support (Note 3) 24 x 7. Global coverage (Note 2) ensures that any product purchased in one country and transferred to another, non-restricted country will remain fully covered under the original warranty and service offering.
	NOTE 1: Terms and conditions may vary by country. Certain restrictions and exclusions apply.
	NOTE 2: On-site service may be provided pursuant to a service contract between HP and an authorized HP third-party provider, and is not available in certain countries. Global service response times are based on commercially reasonable best effort and may vary by country.
	NOTE 3: Technical telephone support applies only to HP-configured, HP and HP-qualified, third-party hardware and software. Toll-free calling and 24 x 7 support may not be available in some countries.

Technical Specifications - Audio

AC97 Integrated ADI 1981B Audio	Type	Integrated	
	AC '97 Stereo Codec	Yes	
	FM Synthesis Support	Yes – Yamaha XG Lite	
	OPL3 FM Synthesis Support	Yes	
	Sound Blaster Compatibility	Yes	
	Audio Jacks	Microphone-In (20-K ohm Input Impedance); rear stereo and front analog microphone ports Line-In (12-K ohm Input Impedance) Line-Out * (less than 800 ohms Output Impedance, expects at least a 10-K ohm load) Headphone-Out (2.5 Ohms Output Impedance, expects at least a 32 ohm load)	
	NOTE: *Internal Speaker Amplifier is for Internal Speaker only. External Speakers need to be powered externally.		
	Sampling	7 kHz – 48 kHz	
	Wavetable Syntheses (software)	Yes – GM and FM Midi Support, Direct Music and Down Loadable Soundset (4 Meg DLS Level 1 and 2 Support)	
	3D Positional Sound	No	
	Digital Audio	Yes	
	Analog Audio	Yes	
	Number of Channels on Line-Out (mono/stereo)	Stereo (Left & Right channels)	
	Internal Audio Speaker Power Rating	3W	
	Internal Speaker	Yes	
	Hardware Equalizer for Internal Speaker	Fixed 7 Band ParametricEQ	
	External Speaker Jack (Line-Out)	Yes	
	Sound Blaster X-Fi XtremeMusic Audio Card	Audio Quality	Total Harmonic Distortion + Noise at 1kHz (20kHz Low-pass filter) = 0.004%
		Signal to Noise Ratio (SNR)	Signal-to-Noise Ratio (20kHz Low-pass filter, A-Weighted) <ul style="list-style-type: none"> ● Stereo Output: 109dB ● Front and Rear Channels: 109dB ● Center, Subwoofer and Side Channels: 109dB
		Sound Conversion	24-bit Analog-to-Digital conversion of analog inputs at 96kHz sample rate
24-bit Digital-to-Analog conversion of digital sources at 96kHz to analog 7.1 speaker output			
24-bit Digital-to-Analog conversion of stereo digital sources at 192kHz to stereo output			
Recording/Sampling Rate	44.1, 48 and 96kHz		
ASIO 2.0 support	16-bit/44.1kHz, 16-bit/48kHz, 24-bit/44.1kHz 24-bit/48kHz and 24-bit/96kHz with direct monitoring		

Technical Specifications - Audio

Enhanced SoundFont support	up to 24-bit resolution 24-bit/96kHz
DACs	24-bit/192kHz
Voice Support	128 voices
Max. Channels in 3D Positional Audio	7.1
EAX® ADVANCED HD™ 5.0 support	Yes including EAX® MacroFX™, EAX® PurePath™ and Environment FlexiFX™
Connectors	FlexiJack (Performing a 3-in-1 function, Digital In / Line In / Microphone) via 3.50 mm minijack Line level out (Front / Rear / Center / Subwoofer / Rear Center) via 3.50 mm minijacks AUX_IN line-level analog input via 4-pin Molex connector on card One AD_Link (26 pin) connector for linking to the X-Fi I/O Console (upgrade option)
Dimensions	7.25" x5" x .9" (x x)
Additional product features	<p>Movies</p> <ul style="list-style-type: none"> THX Certification Dolby Digital EX 6.1 Playback DTS-ES 6.1 Playback <p>Music</p> <ul style="list-style-type: none"> X-Fi 24-bit Crystalizer CMSS-3D SuperRip <p>Audio Creation</p> <ul style="list-style-type: none"> Pristine audio playback quality with a near transparent SRC engine Up to eight 24 bit hardware effects ASIO recording with latency as low as one millisecond 24-bit SoundFont® sampling 3D MIDI <p>Gaming</p> <ul style="list-style-type: none"> EAX ADVANCED HD 5.0 <p>Software Bundle</p> <ul style="list-style-type: none"> Doom 3 Sound Blaster EAX patch Entertainment Mode Audio Creation Mode Game Mode Mode Switcher Audio Console Creative MediaSource Creative MediaSource DVD-Audio Player DTS Neo:6 Settings Karaoke Player Entertainment Center Smart Recorder SoundFont Bank Manager Speaker Connection Wizard THX Setup Console Vienna SoundFont Studio Volume Panel WaveStudio Console Launcher Creative Media Toolbox Creative Diagnostics
Minimum system	System RAM 256MB

Technical Specifications - Audio

requirements

Hard disk

600MB free space
Available PCI 2.1 slot for the audio card
CD-ROM/CD-RW or CD/DVD-ROM required
for software installation

Operating System

Microsoft® Windows® XP Service Pack 2
(SP2)

Technical Specifications - Communications

HP Gigabit by Broadcom (BCM5782) NIC	Connector	RJ-45
	Controller	Broadcom 5782 PCI LAN Controller
	Memory	Integrated 96Kb frame buffer memory
	Data rates supported	10/100/1000 Mbps
	Compliance	IEEE 802.1A, 802.1P, 802.1Q, 802.1Q, 802.2, 802.3, 802.3AB and 802.3u compliant, 802.3x flow control
	Bus architecture	PCI 2.2
	Data path width	32-bit, 33/66 MHz bus interface
	Data transfer mode	Bus-master DMA
	Hardware certifications	FCC, B, CE, TUV- cTUVus Mark Canada and United States, TUV- GS Mark for European Union
	Power requirement	1.48 watts @ +3.3V AUX supply with 5V tolerance
	Boot ROM support	Yes
	Network transfer rate	10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T, 1000 Mbps
	Environmental	Operating temperature 32° to 131° F (0° to 55° C) Operating humidity 85% at 131° F (55° C)
	Dimensions	4.7 x 2.0 x 0.08 in (12 x 5 x 1.9 cm)
	Operating system driver support	Microsoft Windows NT 4.0, Microsoft Windows 98, Microsoft Windows 2000, Microsoft Windows XP, Linux 2.2, Linux 2.4
	Management capabilities	ACPI, WOL and DMI 2.0, PXE 2.0, WfM 2.0, Broadcom mgmt utility
	Alerting	ASF 1.0
	Kit contents	Broadcom 5782, CD, Broadcom Gigabit Ethernet for HP, drivers, quick install guide, product warranty statement

Broadcom 5751 Netxtreme Gigabit PCIe NIC (model EA833AA)	Connector	RJ-45
	Controller	Broadcom 5751 PCI-E 1.0a LAN Controller
	Memory	Integrated 96Kb frame buffer memory
	Data rates supported	10/100/1000 Mbps
	Compliance	IEEE 802.1P, 802.1Q, 802.2, 802.3, 802.3AB and 802.3u compliant, 802.3x flow control
	Bus architecture	PCI-E
	Data path width	Single channel, PCI-E
	Data transfer mode	Bus-master DMA
	Hardware certifications	FCC, B, CE, TUV- cTUVus Mark Canada and United States, TUV- GS Mark for European Union
	Power requirement	3.1 watts @ +3.3V AUX supply with 5V tolerance
	Boot ROM support	Yes
	Network transfer rate	10BASE-T (half-duplex) 10 Mbps 10BASE-T (full-duplex) 20 Mbps 100BASE-TX (half-duplex) 100 Mbps 100BASE-TX (full-duplex) 200 Mbps 1000BASE-T (full-duplex) 2000 Mbps

Technical Specifications - Communications

Environmental	Operating temperature 32° to 131° F (0° to 55° C)
	Operating humidity 85% at 131° F (55° C)
Dimensions	4.4 x 2.2 x 0.08 in (11.2 x 5.5 x .2 cm)
Operating system driver support	Microsoft Windows XP, Linux 2.2, Linux 2.4, and Red Hat Linux 7.2
Management capabilities	ACPI, WOL and DMI 2.0, PXE 2.0, WfM 2.0, Broadcom mgmt utility
Alerting	N/A
Kit contents	Broadcom 5751, CD, Broadcom 5751 Netxtreme Gigabit PCIe NIC, drivers, quick install guide, product warranty statement

Technical Specifications - Controllers

U320 SCSI Controller - LSI 20320AR RAID 0,1 including external connector (required with SCSI HDDs)	Bus architecture	PCI-X (backward compatible with PCI)
	Number of supported devices	Up to 15 SCSI devices
	Interface protocol	64 bit, 133MHz PCI-X
	Host bus transfer rate	Up to 1MB/s
	SCSI data transfer rate	Up to 320 MB/s per channel
	SCSI Bus	Wide Ultra320, Low Voltage Differential, and Ultra Wide Single-Ended
	Internal connector	68-pin HD
	External connector	68 pin
	Total connectors	2
	Plug and Play Support	No
	Dimensions (H x L)	6.6 x 2.5 in (16.9 x 6.4 cm)
	Approvals	CE, VCCI, Canada, C-Tick, FCC class B, UL 94VO
	Operating system support	Microsoft Windows XP Professional Windows XP Professional x64 Edition
	Kit contents	Controller card, driver CD, LED cables, user documentation and warranty card.

Adaptec SCSI RAID 2120S Card	Dimensions (H x D)	2.5 x 6.6 in (6.4 x 16.8 cm) Low profile card
	RAID level	0, 1, 10, 5, 50, JBOD
	Data Transfer Rate	Up to 320 MB/s
	Cache Memory	64 MB (onboard)
	Device Support	Up to 15 SCSI devices
	Bus Type	64-bit/66 MHz PCI (Also support 32-bit/33 MHz PCI)
	Internal Connectors	One 68-pin high-density
	External Connectors	One 68-pin VHDCI
	System Requirements	Intel PC or equivalent with available PCI slot
	Operating Temperature	32° to 131° F (0° to 55° C)
	Power Requirements	4 amps @ +5V
	Operating System Support	Windows 2000 Professional, Windows XP Professional, Windows XP Professional x64 Edition
	Other	Optimized disk utilization Online RAID Level Migration Online capacity expansion Immediate RAID availability (background initialization) S.M.A.R.T. support
	Kit Contents	Controller card, driver CD, LED cables, user documentation and warranty card.

Technical Specifications - Hard Drives

Serial ATA 3.0-Gb/s Hard Drives	500 GB	Capacity	500,107,862,016 bytes	
		Height	1.0 in (2.54 cm)	
		Width	Media diameter: 3.5 in (8.89 cm) Physical size: 4 in (10.2 cm)	
		Interface	Serial ATA (3.0 Gb/s), Native Command Queuing enabled	
		Synchronous Transfer Rate (Maximum)	Up to 3 Gb/s	
		Buffer	16 MB	
		Seek Time (typical reads, includes controller overhead, including settling)	Single Track	1.3 ms
			Average	20.0 ms
			Full-Stroke	30 ms
		Rotational Speed	7,200 rpm	
		Logical Blocks	976,773,168	
		Operating Temperature	41° to 131° F (5° to 55° C)	
			250 GB	Capacity
	Height	1 in (2.54 cm)		
	Width	Media diameter: 3.5 in (8.89 cm) Physical size: 4 in (10.2 cm)		
	Interface	Serial ATA (3.0 Gb/s)		
	Synchronous Transfer Rate (Maximum)	Up to 3 Gb/s		
	Buffer	8 Mbytes		
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track		1.0 ms
		Average		8.5 ms
		Full-Stroke		18 ms
	Rotational Speed	7,200 rpm		
	Logical Blocks	488,397,168		
	Operating Temperature	41° to 131° F (5° to 55° C)		
	160 GB	Capacity		163,928,604,672 bytes
		Height	1.0 in (2.54 cm)	
		Width	Media diameter: 3.5 in (8.89 cm) Physical size: 4 in (10.2 cm)	
		Interface	Serial ATA (3.0 Gb/s)	
		Synchronous Transfer Rate (Maximum)	Up to 3 Gb/s	
		Buffer	8 Mbytes	
		Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.9 ms
			Average	9.3 ms
			Full-Stroke	18 ms
		Rotational Speed	7,200 rpm	
		Logical Blocks	320,173,056	
		Operating Temperature	41° to 131° F (5° to 55° C)	

Technical Specifications - Hard Drives

80 GB	Capacity	80,026,361,856 bytes		
	Height	1.0 in (2.54 cm)		
	Width	Media diameter: 3.5 in (8.89 cm) Physical size: 4 in (10.2 cm)		
	Interface	Serial ATA (3.0 Gb/s)		
	Synchronous Transfer Rate (Maximum)	Up to 3 Gb/s		
	Buffer	8 MB		
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	2 ms	
		Average	9.3 ms	
		Full-Stroke	21 ms	
	Rotational Speed	7,200 rpm		
	Logical Blocks	156,301,488		
Operating Temperature	41° to 131° F (5° to 55° C)			

Serial ATA 1.5-Gb/s Hard Drives (10,000 rpm)	74 GB	Capacity	74,355,769,344 bytes		
		Height	1.0 in (2.54 mm)		
		Width	Media diameter: 3.3 in (84mm) Physical size: 4 in (10.2 cm)		
		Interface	Serial ATA		
		Synchronous Transfer Rate (Maximum)	150 MB/s		
		Buffer	8 MB		
		Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.3 ms	
			Average	4.5 ms	
			Full-Stroke	10.2 ms	
		Rotational Speed	10,000 rpm		
		Logical Blocks	145,226,112		
Operating Temperature	41° to 140° F (5 to 60° C)				

Ultra320 SCSI Hard Drives (10,000 rpm)	73 GB	Capacity	73,407,865,856 bytes		
		Height	1.0 in (2.54 cm)		
		Width	3.5 in (8.9 cm)		
		Interface	68 pin LVD SCSI		
		Synchronous Transfer Rate (Maximum)	320 MB/s		
		Buffer	8 Mbytes		
		Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.3 msec	
			Average	<4.5 msec	
			Full-Stroke	<11.0 msec	
		Rotational Speed	10,000 rpm		
		Logical Blocks	143,374,738		
Operating Temperature	40° to 130° F (5° to 55° C)				

Technical Specifications - Hard Drives

146 GB	Capacity	146,815,737,856 bytes		
	Height	1.0 in (2.54 cm)		
	Width	3.5 in (8.9 cm)		
	Interface	68 pin LVD SCSI		
	Synchronous Transfer Rate (Maximum)	320 MB/s		
	Buffer	8 Mbytes		
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.3 msec	
		Average	<4.5 msec	
		Full-Stroke	<11.0 msec	
	Rotational Speed	10,000 rpm		
	Logical Blocks	286,749,488		
Operating Temperature	40° to 130° F (5° to 55° C)			

300 GB	Capacity	300,000,000,000 bytes		
	Height	1.0 in (2.54 cm)		
	Width	3.5 in (8.9 cm)		
	Interface	68 pin LVD SCSI		
	Synchronous Transfer Rate (Maximum)	320 MB/s		
	Buffer	8 Mbytes		
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.3 msec	
		Average	<4.5 msec	
		Full-Stroke	<11.0 msec	
	Rotational Speed	10,000 rpm		
	Logical Blocks	585,937,500		
Operating Temperature	40° to 130° F (5° to 55° C)			

Ultra320 SCSI Hard Drives (15,000 rpm)	36 GB	Capacity	36,420,075,520 bytes		
		Height	1.0 in (2.54 cm)		
		Width	3.5 in (8.9 cm)		
		Interface	68 pin LVD SCSI		
		Synchronous Transfer Rate (Maximum)	320 MB/s		
		Buffer	8 Mbytes		
		Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.3 msec	
			Average	<4.5 msec	
			Full-Stroke	<11.0 msec	
		Rotational Speed	15,000 rpm		
		Logical Blocks	71,132,960		
Operating Temperature	40° to 130°F (5° to 55°C)				

73 GB	Capacity	73,407,865,856 bytes	
	Height	1.0 in (2.54 cm)	
	Width	3.5 in (8.9 cm)	

Technical Specifications - Hard Drives

	Interface	68 pin LVD SCSI	
	Synchronous Transfer Rate (Maximum)	320 MB/s	
	Buffer	8 Mbytes	
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.3 msec
		Average	<4.5 msec
		Full-Stroke	<11.0 msec
	Rotational Speed	15,000 rpm	
	Logical Blocks	143,374,738	
	Operating Temperature	40° to 130°F (5° to 55° C)	
146 GB	Capacity	146,815,737,856 bytes	
	Height	1.0 in (2.5 cm)	
	Width	3.5 in (8.9 cm)	
	Interface	68 pin LVD SCSI	
	Synchronous Transfer Rate (Maximum)	320 MB/s	
	Buffer	8 Mbytes	
	Seek Time (typical reads, includes controller overhead, including settling)	Single Track	0.3 msec
		Average	<4.5 msec
		Full-Stroke	<11.0 msec
	Rotational Speed	15,000 rpm	
	Logical Blocks	143,374,738	
	Operating Temperature	40° to 130°F (5° to 55° C)	

Technical Specifications - Removable Storage

USB Disk on Key	Dimensions (HxWxD)	0.9 x 0.7 x 3.9 in (2.3 x 1.8 x 9.8 cm)
	Weight	0.05 lb (0.02 kg)
	USB Specification	2.0
	Transfer Rate	Read-1023 KB/Sec; Write-850 KB/Sec
	Storage Media	Solid state flash memory, no moving parts
	Power Supply	USB Bus-powered, no external power required
	Capacity	256 MB

Technical Specifications - Input/Output Devices

PS/2 OR USB Standard Keyboard	Physical characteristics	Keys	104, 105, 106, 107, 109 layout (depending upon country)
		Dimensions (L x W x H)	18.0 x 6.4 x 0.98 in (45.8 x 16.3 x 2.5 cm)
		Weight	2 lb (0.9 kg) minimum
	Electrical	Operating voltage	+ 5VDC ± 5%
		Power consumption	50-mA maximum (with three LEDs ON)
		ESD	CE level 4, 15-kV air discharge
		EMI - RFI	Conforms to FCC rules for a Class B computing device
	Mechanical	Microsoft PC 99 - 2001	Functionally compliant
		Languages	38 available
		Keycaps	Low-profile design
		Switch actuation	55-g nominal peak force with tactile feedback
		Switch life	20 million keystrokes (using Hasco modified tester)
		Switch type	Contamination-resistant switch membrane
		Key-leveling mechanisms	For all double-wide and greater-length keys
		Cable length	6 ft (1.8 m)
		Microsoft PC 99 - 2001	Mechanically compliant
	Environmental	Acoustics	43-dBA maximum sound pressure level
		Operating temperature	50° to 122° F (10° to 50° C)
		Non-operating temperature	-22° to 140° F (-30° to 60° C)
		Operating humidity	10% to 90% (non-condensing at ambient)
		Non-operating humidity	20% to 80% (non-condensing at ambient)
		Operating shock	40 g, six surfaces
		Non-operating shock	80 g, six surfaces
		Operating vibration	2-g peak acceleration
		Non-operating vibration	4-g peak acceleration
		Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence
		Drop (in box)	42 in (107 cm) on concrete, 16-drop sequence
	Operating system support		Microsoft Windows XP Professional, Microsoft Windows XP Professional x64 Edition, Red Hat Enterprise Linux Workstation 3 and 4
	Approvals		UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, MIC
	Ergonomic compliance		ANSI HFS 100, ISO 9241-4, and TUVGS
	Kit contents		Keyboard, keyboard software media, installation guide, warranty card, safety and comfort
HP USB Smart Card Keyboard (ED707AA)	Physical characteristics	Keys	104, 105, 106, 107, 109 layout (depending upon country)
		Form factor	USB basic Smart Card keyboard
		Colors	Carbonite/Silver
		Dimensions (L x W x H)	18.2 x 6.3 x 1.3 in (46.3 x 16.1 x 3.3 cm)
		Weight	2 lb (0.9 kg) minimum

Technical Specifications - Input/Output Devices

Electrical	Operating voltage	+ 5VDC ± 5%	
	Power consumption	100-mA maximum (with four LEDs ON)	
	System interface	USB Type A plug connector	
	ESD	CE level 4, 15-kV air discharge	
	EMI - RFI	Conforms to FCC rules for a Class B computing device	
Mechanical	Microsoft PC 99 - 2001	Functionally compliant	
	Languages	30+ available	
	Keycaps	Low-profile design	
	Switch actuation	55-g nominal peak force with tactile feedback	
	Switch life	20 million keystrokes (using Hasco modified tester)	
	Switch type	Contamination-resistant switch membrane	
	Key-leveling mechanisms	For all double-wide and greater-length keys	
	Cable length	6 ft (1.8 m)	
	Microsoft PC 99 - 2001	Mechanically compliant	
	Acoustics	43-dBA maximum sound pressure level	
Environmental	Operating temperature	50° to 122° F (10° to 50° C)	
	Non-operating temperature	-22° to 140° F (-30° to 60° C)	
	Operating humidity	10% to 90% (non-condensing at ambient)	
	Non-operating humidity	20% to 80% (non-condensing at ambient)	
	Operating shock	40 g, six surfaces	
	Non-operating shock	80 g, six surfaces	
	Operating vibration	2-g peak acceleration	
	Non-operating vibration	4-g peak acceleration	
	Drop (out of box)	26 in (66 cm) on carpet, six-drop sequence	
	Drop (in box)	42 in (107 cm) on concrete, 16-drop sequence	
	SMARTCARD function	Support	All ISO 7816 smart cards
		Interface	Reads from and writes to all ISO7816-1, 2, 3, 4 memory and microprocessor smart cards (T=0, T=1)
		Chipset	SCM STCII
Standard APIs supported		PC/SC, EMV2000, SET	
Power		Power	USB Port
			Short circuit detection (protects smart card and reader)
			Power supply compliant with ISO7816 and EMV (5V, 60 mA)
			Supports 3-V and 5-V cards
Power consumption		250-mA maximum draw (50 mA for the keyboard with three LEDs ON and 200-mA maximum startup current using a high-current, 60-mA smart card)	

Technical Specifications - Input/Output Devices

	Communication	From card	Programmable from 9,600 baud to 115,200 baud
		From computer	Up to 38,400 baud
	Landing mechanism	Contact device	Friction contact
		Card insertions rating	Up to 100,000 insertion cycles
	Interface modes	USB communications through USB port SCM protocol Automatic card insertion/removal detection	
	Reader performance interface	USB connection	
	Electro-magnetic standards	Europe	89/336/CEE guideline
		USA	USAFCC part 15
Operating system support	Microsoft® Windows® 2000, Windows XP Home, Windows XP Professional, xpe, ce.net, Linux, XP-64		
Approvals	CE-Mark, UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, MIC, JITC, EMV2000, USB-IF		
Ergonomic compliance	ANSI HFS 100, ISO 9241-4, TUVGS		
Kit contents	Keyboard, I/O Security and Documentation CD, , warranty card		
Smart card compatibility	HP	HP ProtectTools Smart Card	
	American Express	Amex Blue	
	Axalto (Schlumberger)	Cryptoflex 8K Cryptoflex 16K Cryptoflex 32K Cryptoflex 32K e-gate Cyberflex Access 64K Cyberflex Access 32K Cyberflex 32K e-gate Cyberflex 64K Cyberflex Palmera Payflex-S Payflex 1K Payflex 2K Payflex 4K Payflex 8K Prismera US DoD CAC	
	Cardlogix	CLXSU004KK4 CLXSU008KK5	
	Datakey	Model 300 Model 330	
	De La Rue	VisaCash	
	Gemplus	Gem Espresso GKK32K Gemclub Memo GemClub Micro GemXplore GemSafe	
	Infineon	SLE66C322P	
	SafLink (Litronic)	Forte	

Technical Specifications - Input/Output Devices

Sharp	Java Card
Oberthur	CosmopolIIC v4 CosmopolIIC v4.1 Cosmo ID-One GalatlIIC v2.1 US DoD CAC
Memory Cards	
Atmel	AT24C01ASC AT24C02SC AT24C04SC AT24C08SC AT24C16SC AT24C32SC AT24C64SC AT24C128SC AT24C256SC AT24C512SC AT88SC153 AT88SC1608
Axalto (Schlumberger)	PrimeFlex Store 8K PrimeFlex Store 2K
nfineon	SLE4406 SLE4406E SLE4406E SE SLE4418 SLE4428 SLE4432 SLE4436E SLE4442 SLE5536
ISSI	IS23SC4418 IS23SC4428
ST	14C02
Telefonkarte	SLE4406 SLE4436 SLE5536
XICOR	X24026

Technical Specifications - Input/Output Devices

HP PS/2 Scroll Mouse	Dimensions	3.8 x 6.3 x 11.6 cm (1.5 x 2.5 x 4.6 in)	
	Weight	4.44 oz (126 g)	
	Environmental	Operating temperature	50° to 122° F (10° to 50° C)
		Non-operating temperature	-22° to 140° F (-30° to 60° C)
		Operating humidity	10% to 90% (non-condensing at ambient)
		Non-operating humidity	20% to 80% (non-condensing at ambient)
		Operating shock	40 g, 6 surfaces
		Non-operating shock	80 g, 6 surfaces
		Operating vibration	2 g peak acceleration
		Non-operating vibration	4 g peak acceleration
		Drop (out-of-box)	26 in (66 cm) on carpet, 6-drop sequence
		Drop (out-of-box)	1 m on asphalt tile over concrete, 6-drop sequence
	Electrical	Operating voltage	5 VDC ± 10%
		Power consumption	15 mA
System consumption		PS/2 mini-din connector	
ESD		CE level 4, 15 kV air discharge	
EMI-RFI		Conforms to FCC rules for a Class B computing device	
Microsoft PC99 - 2001		Functionally compliant	
Mechanical	Resolution	400 ± 20% DPI	
	Tracking speed	10 in/s maximum	
	Acceleration	100 in/s	
	Switch actuation	65 g nominal peak force	
	Switch life	1,000,000 operations (using Hasco modified tester)	
	Switch type	Low force micro-switches	
	Tracking mechanism life	155 mi (250 km) at average speed of 10 in/s	
	Cable length	6 ft (1.8 m)	
	Microsoft PC99 - 2001	Mechanically compliant	
	Scroll wheel	Width	8 mm
Diameter		0.99 in (25.2 mm)	
Maximum rotation speed		30 mm/s	
Switch type		Light force micro-switch	
Switch life		1 million operations	
Mechanical life		Minimum 200,000 revolutions	
Regulatory approvals		Compliant UL, CSA, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, MIC	
Compatibility	Operating system support Microsoft Windows XP Professional, Microsoft Windows XP Professional x64 Edition, Red Hat Enterprise Linux Workstation 3 and 4		

Technical Specifications - Input/Output Devices

HP 2-button Optical Scroll Mouse (USB)	Dimensions (H x L x W)	1.5 x 4.5 x 2.5 in (3.8 x 11.6 x 6.3 cm)
	Weight	0.27 lb (0.12 kg)
	Cable length	72.8 in (185 cm)
	System requirements	Microsoft Windows XP Professional, Microsoft Windows XP Professional x64 Edition, Red Hat Enterprise Linux Workstation 3 and 4

Spaceball 5000 USB (Windows XP only)	Physical characteristics	Dimensions (H x W x D)	3.0 x 6.0 x 8.4 in (7.6 x 15.2 x 21.3 cm)
		Ball Diameter	2.2 in (5.6 cm)
		Weight	2.1 lb (9.94 kg)
		Features	Six degrees of freedom motion control through the X, Y, Z axis (pitch, roll, yaw) Certified for leading CAD and DCC applications
	Environmental	Operating temperature	50° to 104° F (10° to 40° C)
		Non-operating temperature	43° to 140° F (6° to 60° C)
		Operating humidity	8% to 80% (non-condensing at ambient)
		Non-operating humidity	5% to 80% (non-condensing at ambient)
	Mechanical	Buttons	12 programmable (unshifted)
		Ball Force Range	0.5 - 8.2N/1.8 - 29.5 oz
		Ball Torque Range	0.085 – 0.33 oz-in. (6.91 Nmm)
		Resolution	10 bits
	Serial Specifications	Connector	USB 1.1 or greater
		Cable Length	12.8 ft. (3.9 m)
		Data Rate	USB model – 16 msec
		Flow Control	Xon/Xoff (on PS/2 model only)
	Software Drivers Available	USB model	Microsoft Windows XP Professional
	System Requirements	Disk Space	10 MB free disk space
	Regulatory Approvals	UL, cUL, EN 950, EN 60950, CSA, FCC, CE Mark, TUV, CISPR 22, EN 50082, IEC 1000 4-2, IEC 1000-4-3, AS/NZS, VCCI, BSMI, C-Tick	

Technical Specifications - Input/Output Devices

HP SpacePilot 3D USB Intelligent Controller (model EF390AA)	Physical Characteristics	Dimensions (L x W x H)	9.3 x 5.6 x 2.0 in (236 x 143 x 53 mm)
	Mechanical	Weight	1.875 lb (0.85 kg)
		Palmrest	Sculpted
	System Requirements	Buttons	21+ programmable speed keys 15 reprogrammable
		LCD Viewing Area	(W x H) 4.1 x 1.2 in (102 x 30 mm)
		Active Area	(W x H) 3.9 x 1.0 in (98 x 26 mm)
		Display Format	240 x 64
		Motion Controller	Six degrees of freedom motion control through the X, Y, Z axis (pitch, roll, yaw)
	Operating System Supported	Device Sensitivity	Adjustable to preference
		System Requirements	Intel Pentium 4 or AMD Athlon processor based system 20 megabytes free disk space for driver and plug-in installation (CD-ROM device required) USB 1.1 or 2.0
Regulatory Approvals		Microsoft Windows 2000 and XP	
		FCC, CE	
<hr/>			
HP SpaceMouse Plus USB (Windows XP only)	Physical characteristics	Dimensions (H x W x D)	7.4 x 4.72 x 1.73 in (18.8 x 12.0 x 4.4 cm)
	Environmental	Cap Diameter	2 x 6.5 x 6.6 mm
		Weight	1.5 lb (0.68 kg)
		Features	Six degrees of freedom motion control through the X, Y, Z axis (pitch, roll, yaw) Certified for leading CAD and DCC applications
	Mechanical	Operating temperature	41° to 140° F (5° to 60° C)
		Non-operating temperature	-13° to 158° F (-25° to 70° C)
		Operating humidity	10 to 98 % RH (non-condensing)
	USB Specifications	Non-operating humidity	10 to 98 % RH (non-condensing)
		Buttons	11 programmable (unshifted)
		Cap Force Range	0.2 N – 4.5 N
Cap Torque Range		4 Nmm to 100 Nmm	
Software Drivers Available	Resolution	8 bit	
	Connector	USB 1.1 or greater	
	Cable Length	6.56 ft (2 m)	
System Requirements	Data Rate	16 msec	
	System Requirements	Microsoft Windows XP Professional	
Regulatory Approvals	Disk Space	10 MB free disk space	
		UL, cUL, EN 950, EN 60950, CSA, FCC, CE Mark, TUV, CISPR 22, EN 50082, IEC 1000 4-2, IEC 1000-4-3, AS/NZS, VCCI, BSMI, C-Tick	

Technical Specifications - Optical Devices

48X CD-ROM Drive	Form Factor	5.25-in, half-height, tray load	
	Mounting Orientation	Horizontal or vertical	
	Interface	ATAPI/EIDE	
	Dimensions (HxWxD)	1.63 x 5.83 x 7.27 in (4.13 x 14.6 x 18.5 cm)	
	Weight	1.76 lb (0.8 kg)	
	Data Transfer Rates - Read	Digital audio extraction (minimum) – 1,200 KB/s (8X) CD read – up to 7,200 KB/s (48X)	
	Media and Formats - Read	CD Media	stamped, CD-R, CD-RW (LS, HS, US)
		CD Capacities	180 MB (mode 2, 8 cm); 540 MB (mode 1, 12 cm); 650 MB (mode 2, 12 cm); 700 MB (Mode 2, 12 cm, 80-minute)
		CD Formats	CD-DA, CD-ROM (Mode 1 and 2), CD-XA (Mode 2, Form 1 and 2), Photo CD (Single and Multi-session), Mixed Mode (Audio and Data combined), CD-I (Mode 2, Form 1 and 2, and CD-I Ready), CD-Extra, CD-Bridge, Video CD
	Access Times (typical reads, including settling)	CD-ROM Mode 1	< 125 ms
		Full Stroke CD	< 210 ms
		Start-up Time (typical)	< 7 s (single session), < 30 s (multi-session)
		Stop Time (typical)	< 4 s
		Write Buffer Size	128 KB (minimum)
		Data Transfer Modes	PIO Mode 4 (16.6 MB/s); Multi-word DMA mode 2 (16.6 MB/s); UltraDMA Mode 0 (16.7 MB/s); UltraDMA Mode 2 (33.3 MB/s)
		Power	Source
	DC Power Requirement		5 VDC ± 5% - 100 mV ripple p-p
			12 VDC ± 5% - 200 mV ripple p-p
	DC Current		5 VDC - <1000 mA typical, < 1600 mA maximum
			12 VDC - < 600 mA typical, <1400 mA maximum
	Audio Output	Total Drive Power (standby mode)	< 2.5 Watt
		Line-Out	0.7 VRMS
Signal-to-Noise Ratio		74 dB	
Configuration Jumper Block	Channel Separation	65 dB	
		Master, slave, and cable select modes	
Operating Conditions (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)	
	Humidity	10% to 80%	
Certifications, Approvals	MMC-3 support, multi-read compliant, Microsoft WHQL certification, ACA AS/NZS 3548 class B, BSMI CNS 13438, CE Mark, C.I.S.P.R. Put 22, TUV or VDE EN60950, EN 55022, EN55024, EMKO EN60950, EN 60825-1, UL 60950, CSA C22.2 60950-2000, CFR 21 part 1040 class 1, CFR 47 C.I.S.P.R. Pub 22 Class B, DHHS/FDA, ANSI C63.4-1992 (FCC Class B)		
Operating Systems Supported	Microsoft Windows XP Professional, Microsoft Windows XP Professional x64 Edition, Red Hat Enterprise Linux Workstation 3		

Technical Specifications - Optical Devices

Supplied Software None

16X/48X DVD-ROM Drive with +R Read Support	Height	5.25-in, half-height, tray load	
	Interface Type	ATAPI/EIDE	
	Dimensions (W x H x D)	5.88 x 1.71 x 7.87 [max] in (149.5 x 43.25 x 200.0 [max] mm) (external, excluding bezel)	
	Disc Formats	DVD-ROM (single and dual layer); DVD-video; DVD-R version 1.0 and 2.0; DVD-RW version 1.0 and 1.1; DVD-R multi-border; DVD+RW; DVD+R ; CD-ROM Mode 1 and 2; CD-DA; CD-ROM XA Mode 2, Form 1 and 2; CD-extra; CD-text; CD-I Mode 2, Form 1 and 2; CD-I ready; video CD, CD-bridge; PhotoCD (single and multi-session); CD-R; CD-RW	
	Disc Capacity	DVD-ROM	4.7 GB (DVD-5), 8.54 GB (DVD-9), 9.4 GB (DVD-10), 3.95 GB (DVD-R version 1.0), 4.7 GB (DVD-R version 2.0), 4.7 GB (DVD-RW version 1.0 and 1.1), 4.7 GB (DVD+RW), 4.7G (DVD+R)
		CD-ROM	540 MB (Mode 1, 12 cm), 640 MB (Mode 2, 12 cm), 700 MB (80 minimum CD-R and CD-RW), 180 MB (8 cm)
	Access Times (typical reads, including settling)	DVD-ROM Single Layer	120 ms
		CD-ROM Mode 1	90 ms
		Full Stroke DVD	240 ms (seek)
		Full Stroke CD	160 ms (seek)
Startup Time		< 10 seconds (typical)	
Stop Time		< 4 seconds	
Data Transfer Modes		PIO Mode 4 (16.6 MB/s); Multi-word DMA mode 2 (16.6 MB/s); UltraDMA Mode 3 (44.4 MB/s)	
Maximum Data Transfer Rates	CD-ROM Read	6000 KB/s (40X) Max	
	DVD-ROM Read	21,600 KB/s (16X) Max	
	Digital Audio Extraction	6000 KB/s (40X) Max	
Power	Source	Four-pin, DC power receptacle	
	DC Power Requirement	5 VDC \pm 5% – 100 mV ripple p-p 12 VDC \pm 5% – 200 mV ripple p-p	
	DC Current	5 VDC – <800 mA typical, < 1000 mA maximum 12 VDC – < 870 mA typical, <1800 mA maximum	
Audio Output	Line-Out	0.7 VRMS	
	Signal-to-Noise Ratio	85 dB	
	Channel Separation	65 dB	
Configuration Jumper Block	Master, slave, and cable select modes		
Data Interface Connector	40-pin, shrouded and keyed, flat ribbon		

Technical Specifications - Optical Devices

Operating Environmental (all conditions non-condensing)	Temperature (operating) 41° to 122° F (5° to 50° C)
	Relative Humidity 10% to 85% (operating)
	Maximum Wet Bulb Temperature 86° F (30° C) (operating)
Certifications, Approvals	MMC II support, multi-read certification, Microsoft WHQL certification, ACA AS/NZS 3548 class B, CNS 13438, C.I.S.P.R. Pub 22, TUV or VDE EN60950, EN 55022, EN55024, EMKO EN60950, EN 60825-1, UL 60950, CSA C22.2 60950-2000, CFR 21 part 1040 class 1, CFR 47 C.I.S.P.R. Pub 22 Class B, DHHS/FDA, ANSI C63.4-1992
Operating Systems Supported	Windows 2000, XP Professional, and XP Professional x64 Edition Red Hat Linux 7.2, 7.3 WS3 and WS4 Versions
Kit Contents	16X/40X DVD-ROM Drive, InterVideo WinDVD MPEG Movie Playback software, audio cable, and installation guide.

HP 48X CD-RW

Form Factor	5.25-inch, half-height, tray-load
Mounting Orientation	Horizontal or vertical
Interface	ATAPI/EIDE
Dimensions (HxWxD)	1.63 x 5.75 x 7.27 [max] in (4.13 x 14.6 x 18.5 [max] cm) (external, excluding bezel)
Weight (max)	2.0 lb (0.9 kg)
Read Only Disc Parameters	<p>Data Transfer Rates - Read</p> <p>Digital audio extraction (minimum) - 1,800 KB/s (12X)</p> <p>CD read - up to 7,200 KB/s (48X)</p> <p>Media and Formats - Read</p> <p>CD Media: stamped; CD-R; CD-RW (LS, HS, US)</p> <p>CD Capacities: 180 MB (mode 2, 8 cm); 540 MB (mode 1, 12 cm); 650 MB (mode 2, 12 cm); 700 MB (Mode 2, 12 cm, 80-minute)</p> <p>CD Formats: CD-DA, CD-ROM (Mode 1 and 2), CD-XA (Mode 2, Form 1 and 2), Photo CD (Single and Multi-session), Mixed Mode (Audio and Data combined), CD-I (Mode 2, Form 1 and 2, and CD-I Ready), CD-Extra, CD-Bridge, Video CD</p>
Writeable Disc Parameters	<p>Data Transfer Rates - Write</p> <p>CD-R write - 2100 KB/s (14X) to 7200 KB/s (48X)</p> <p>CD-RW write - 600 KB/s (4X)</p> <p>CD-RW write (high speed) - 1500 KB/s (10X) to 1800 KB/s (12X)</p> <p>CD-RW write (ultra high speed) - 2400 KB/s (16X) to 4800 KB/s (32X)</p> <p>Media and Formats - Write</p> <p>CD Media: CD-R; CD-RW (LS, HS, US)</p> <p>CD Capacities: 180 MB (mode 2, 8 cm); 540 MB (mode 1, 12 cm); 650 MB (mode 2, 12 cm); 700 MB (Mode 2, 12 cm, 80-minute)</p> <p>CD Formats: CD-DA, CD-ROM (Mode 1 and 2), CD-XA (Mode 2, Form 1 and 2), Photo CD (Single and Multi-session), Mixed Mode (Audio and Data combined), CD-I (Mode 2, Form 1 and 2, and CD-I Ready), CD-Extra, CD-Bridge, Video CD</p>

Technical Specifications - Optical Devices

	Write Methods	Disc-at-once, session-at-once, track-at-once, incremental fixed and variable packet, multi-session
Access Times (typical reads, including settling)	CD-ROM Mode 1	< 125 ms
	Full Stroke CD	< 210 ms
	Start-up Time (typical)	< 7 s (single session), < 30 s (multi-session)
	Stop Time (typical)	< 4 s
	Write Buffer Size	2 MB
	Data Transfer Modes	PIO Mode 4 (16.6 MB/s); Multi-word DMA mode 2 (16.6 MB/s); UltraDMA Mode 2 (33.3 MB/s)
	Power	Source
DC Power Requirement		5 VDC \pm 5%-100 mV ripple p-p 12 VDC \pm 5%-200 mV ripple p-p
DC Current		5 VDC (< 1000 mA typical, < 1600 mA maximum) 12 VDC (< 600 mA typical, < 1400 mA maximum)
Total Drive Power (standby mode)		< 2.5 Watt
Audio Output		Line-Out
	Signal-to-Noise Ratio	74 dB
	Channel Separation	65 dB
Configuration Jumper Block	Master, slave, and cable select modes	
Operating Conditions	Temperature	41° to 122° F (5° to 50° C)
	Humidity	10% to 90% 10% to 90%
Certifications, Approvals	MMC-3 support, multi-read compliant, Microsoft WHQL certification, ACA AS/NZS 3548 class B, BSMI CNS 13438, CE Mark, C.I.S.P.R. Put 22, TUV or VDE EN60950, EN 55022, EN55024, EMKO EN60950, EN 60825-1, UL 60950, CSA C22.2 60950-2000, CFR 21 part 1040 class 1, CFR 47 C.I.S.P.R. Pub 22 Class B, DHHS/FDA, ANSI C63.4-1992 (FCC Class B)	
Operating Systems Supported	Microsoft Windows XP Professional, Microsoft Windows XP Professional x64 Edition, Red Hat Enterprise Linux Workstation 3	
Supplied Software (for Windows XP)	Roxio Digital Media Plus: Create or copy CDs and DVDs, including music and data CDs, and data DVDs	

HP 48X CD-RW/DVD-ROM Combo Drive

Form Factor	5.25-inch, half-height, tray-load	
Mounting Orientation	Horizontal or vertical	
Interface	ATAPI/EIDE	
Dimensions (HxWxD)	5.77 x 1.71 x 7.87 [max] in (14.66 x 4.34 x 20.0 [max] cm) (external, excluding bezel)	
Weight (max)	2.6 lb (1.2 kg)	
Read Only Disc Parameters	Data Transfer Rates - Read	CD read - 7200 KB/s (48X) Max Digital audio extraction (minimum) - 1,800 KB/s (12X) DVD ROM read - 21,632 KB/s (16X) Max
	Media and Formats - Read	CD Media: stamped; CD-R; CD-RW (LS, HS, US)

Technical Specifications - Optical Devices

		<p>CD Capacities: 180 MB (mode 2, 8 cm); 540 MB (mode 1, 12 cm); 650 MB (mode 2, 12 cm); 700 MB (Mode 2, 12 cm, 80-minute)</p> <p>CD Formats: CD-DA, CD-ROM (Mode 1 and 2), CD-XA (Mode 2, Form 1 and 2), Photo CD (Single and Multi-session), Mixed Mode (Audio and Data combined), CD-I (Mode 2, Form 1 and 2, and CD-I Ready), CD-Extra, CD-Bridge, Video CD</p> <p>DVD Media: stamped (single and double layer); DVD+R; DVD+RW; DVD+R DL; DVD-R; DVD-RW</p> <p>DVD Capacities: 4.7 GB (DVD-5), 8.54 GB (DVD-9), 9.4 GB (DVD-10), 3.95 GB (DVD-R version 1.0), 4.7 GB (DVD-R version 2.0), 4.7 GB (DVD-RW version 1.0 and 1.1), 4.7 GB (DVD+RW), 4.7G (DVD+R)</p> <p>DVD Formats: DVD-ROM (single and dual layer); DVD-video; DVD-R version 1.0 and 2.0; DVD-RW version 1.0 and 1.1; DVD-R multi-border ; DVD+R version 1.2 (including multi-session); DVD+R DL version 1.0; DVD+RW version 1.2</p>
Writeable Disc Parameters	Data Transfer Rates - Write	<p>CD-R write - 2100 KB/s (14X) to 7200 KB/s (48X)</p> <p>CD-RW write - 600 KB/s (4X)</p> <p>CD-RW write (high speed) - 1500 KB/s (10X) to 1800 KB/s (12X)</p> <p>CD-RW write (ultra high speed) - 2400 KB/s (16X) to 4800 KB/s (32X)</p>
	Media and Formats - Write	<p>CD Media: CD-R; CD-RW (LS, HS, US)</p> <p>CD Capacities: 180 MB (mode 2, 8 cm); 540 MB (mode 1, 12 cm); 650 MB (mode 2, 12 cm); 700 MB (Mode 2, 12 cm, 80-minute)</p> <p>CD Formats: CD-DA, CD-ROM (Mode 1 and 2), CD-XA (Mode 2, Form 1 and 2), Photo CD (Single and Multi-session), Mixed Mode (Audio and Data combined), CD-I (Mode 2, Form 1 and 2, and CD-I Ready), CD-Extra, CD-Bridge, Video CD</p>
	Write Methods	<p>Disc-at-once, session-at-once, track-at-once, incremental fixed and variable packet, multi-session</p>
Access Times (typical reads, including settling)	Random DVD	< 140 ms
	Random CD	< 125 ms, (typical)
	Full Stroke DVD	< 250 ms
	Full Stroke CD	< 210 ms
	Startup Time (single)	< 7 seconds (typical)
	Startup Time (multi-session)	< 30 seconds (typical)
	Stop Time (typical)	< 4 s
	Cache Buffer	2 MB (minimum)

Technical Specifications - Optical Devices

	Data Transfer Modes	ATA PIO mode 4 (16.7 MB/s); ATA Multi-word DMA mode 2 (16.7 MB/s); ATA UltraDMA Mode 3 (44 Mbytes/s)
Power	Source	Four-pin, DC power receptacle
	DC Power Requirement	5 VDC \pm 5%-100 mV ripple p-p 12 VDC \pm 5%-200 mV ripple p-p
	DC Current	5 VDC (< 1000 mA typical, < 1600 mA maximum) 12 VDC (< 600 mA typical, < 1400 mA maximum)
	Total Drive Power (standby mode)	< 2.5 Watt
Audio Output	Line-Out	0.7 VRMS
	Signal-to-Noise Ratio	74 dB
	Channel Separation	65 dB
Configuration Jumper Block	Master, slave, and cable select modes	
Data Interface Connector	40-pin, shrouded and keyed, flat ribbon	
Operating Conditions (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)
	Relative humidity	10% to 90%
	Maximum wet bulb temperature	86° F (30° C)
Certifications, Approvals	MMC-3 support, multi-read compliant, Microsoft WHQL certification, ACA AS/NZS 3548 class B, BSMI CNS 13438, CE Mark, C.I.S.P.R. Put 22, TUV or VDE EN60950, EN 55022, EN55024, EMKO EN60950, EN 60825-1, UL 60950, CSA C22.2 60950-2000, CFR 21 part 1040 class 1, CFR 47 C.I.S.P.R. Pub 22 Class B, DHHS/FDA, ANSI C63.4-1992 (FCC Class B)	
Operating Systems Supported	Microsoft Windows XP Professional, Microsoft Windows XP Professional x64 Edition, Red Hat WS3 and WS4 Versions	
Supplied Software (for Windows XP)	Roxio Cineplayer Movie Playback Roxio Digital Media Plus: Create or copy CDs and DVDs, including music and data CDs, and data DVDs	

16X DVD+/-RW, Dual-Layer, with LightScribe Direct Disc Labeling	Form Factor	5.25-inch, half-height, tray-load	
	Orientation	Horizontal or vertical	
	Interface	ATAPI/EIDE	
	Dimensions (HxWxD)	5.9 x 1.7 x 7.9 in (15.0 x 4.4 x 20.0 cm)	
	Weight (maximum)	2.6 lb (1.2 kg)	
	Read Only Disc Parameters	Data Transfer Rates - Read	DVD-ROM, DVD-video read - 5-16X (6750 - 21,600 KB/s CAV) DVD-video playback, DVD+R, DVD+RW, DVD-R, DVD-RW - 4-8X (5400 - 10,800 KB/s CAV) CD-audio playback - 8x (1200 KB/s CLV) Digital audio extraction (minimum) - 12X (1,800 KB/s CAV) CD-ROM, CD-R, CD-RW, CD-Audio read - 16-40X (2400 to 6000 KB/s CAV)

Technical Specifications - Optical Devices

	<p>Media and Formats - Read</p>	<p>CD Media: stamped; CD-R; CD-RW (supports AM2) (LS, HS, US)</p> <p>CD Capacities: 180 MB (mode 2, 8 cm); 540 MB (mode 1, 12 cm); 650 MB (mode 2, 12 cm); 700 MB (Mode 2, 12 cm, 80-minute)</p> <p>CD Formats: CD-DA, CD-ROM (Mode 1 and 2), CD-XA (Mode 2, Form 1 and 2), Photo CD (Single and Multi-session), Mixed Mode (Audio and Data combined), CD-I (Mode 2, Form 1 and 2, and CD-I Ready), CD-Extra, CD-Bridge, Video CD, UDF (1.02 and 1.50)</p> <p>DVD Media: stamped (single and double layer); DVD+R; DVD+RW; DVD+R DL; DVD-R; DVD-RW</p> <p>DVD Capacities: 4.7 GB (DVD-5), 8.54 GB (DVD-9), 9.4 GB (DVD-10), 14.1 GB (DVD-14), 17.0 GB (DVD-18), 3.95 GB (DVD-R version 1.0), 4.7 GB (DVD-R version 2.0), 4.7 GB (DVD-RW version 1.0 and 1.1), 4.7 GB (DVD+RW), 4.7G (DVD+R), 1.46 GB (DVD+R, 8cm), 1.46 GB (DVD+RW, 8cm)</p> <p>DVD Formats: DVD-ROM (single and dual layer); DVD-video; DVD-R version 1.0 and 2.0 (including multi-border); DVD-RW version 1.0 and 1.1; DVD+R version 1.3 (including multi-session); DVD+R DL version 1.0; DVD+RW version 1.2</p>
<p>Writeable Disc Parameters</p>	<p>Data Transfer Rates - Write</p>	<p>CD-R write - 16-40X (2400-6000 KB/s CAV)</p> <p>CD-RW write - 4X (600 KB/s CLV)</p> <p>CD-RW write (high speed) - 10X (1500 KB/s CLV)</p> <p>CD-RW write (ultra high speed) - 16-24X (2400-3600 KB/s ZCLV)</p> <p>DVD+R - 6-16X (8100-21,600 KB/s CAV), 8x (10,800 KB/s ZCLV), 2.4-4x (3250-5400 KB/s CLV)</p> <p>DVD+R DL - 2.4 (3250 KB/s CLV)</p> <p>DVD+RW - 2.4-4X (3250-5400 KB/s CLV)</p> <p>DVD-R - 2-4X (2700-5400 KB/s CLV), 8X (10,800 KB/s ZCLV)</p> <p>DVD-RW - 2-4X (2700-5400 KB/s CLV)</p>
	<p>Media and Formats - Write</p>	<p>CD Media: CD-R (OBII Vol2.0 Rev 1.2), CD-RW (LS, HS, US)</p> <p>CD Capacities: 180 MB (mode 1, 8 cm); 540 MB (mode 1, 12 cm); 650 MB (mode 2, 12 cm); 700 MB (Mode 2, 12 cm, 80-minute)</p> <p>CD Formats: CD-DA, CD-ROM (Mode 1 and 2), CD-XA (Mode 2, Form 1 and 2), Photo CD (Single and Multi-session), Mixed Mode (Audio and Data combined), CD-I (Mode 2, Form 1 and 2, and CD-I Ready), CD-Extra, CD-Bridge, Video CD, UDF (1.02 and 1.50)</p> <p>DVD Media: DVD+R, DVD+R DL, DVD+RW, DVD-R, DVD-RW</p>

Technical Specifications - Optical Devices

		DVD Capacities: 4.7 GB (DVD-5), 8.54 GB (DVD-9), 4.7 GB (DVD-R version 2.0), 4.7 GB (DVD-RW version 1.1), 4.7 GB (DVD+RW version 1.3), 4.7G (DVD+R version 1.2)), 1.46 GB (DVD+R, 8cm), 1.46 GB (DVD+RW, 8cm)
		DVD Formats: DVD-R version 1.0 and 2.0 (including multi-border); DVD-RW version 1.0 and 1.1; DVD+R version 1.3 (including multi-session); DVD+R DL version 1.0; DVD+RW version 1.2
	Write Methods	Disc-at-once, session-at-once, track-at-once, incremental fixed and variable packet, multi-session
LightScribe Direct Disc Labeling Parameters	Media Supported	CD-R: LightScribe Version 1.0 DVD+R: LightScribe Version 1.0
	Resolution	Dots per inch: 600 Tracks per inch: 500-1600 (mode dependent)
	Labeling Times	Draft quality: < 20 min Normal quality: < 28 min Best quality: < 36 min
Access Times (typical reads, including settling)	Random DVD	< 130 ms (typical)
	Random CD	< 120 ms (typical)
	Full Stroke DVD	< 240 ms
	Full Stroke CD	< 200 ms
	Startup Time (single)	< 7 seconds (typical)
	Startup Time (multi-session)	< 30 seconds (typical)
	Stop Time (typical)	< 4 s
	Cache Buffer	2 MB
	Data Transfer Modes	ATA PIO mode 4 (16.7 MB/s); ATA Multi-word DMA mode 2 (16.7 MB/s); ATA UltraDMA Mode 3 (44.4 MB/s) (default on most HP xw series workstations)
Power	Source	Four-pin, DC power receptacle
	DC Power Requirement	5 VDC \pm 5%-100 mV ripple p-p 12 VDC \pm 5%-200 mV ripple p-p
	DC Current	5 VDC (< 1000 mA typical, < 1600 mA maximum) 12 VDC (< 600 mA typical, < 1400 mA maximum)
	Total Drive Power (standby mode)	< 2.5 Watt
Audio Output	Line-Out	0.7 VRMS
	Signal-to-Noise Ratio	74 dB
	Channel Separation	65 dB
Operating Conditions (all conditions non-condensing)	Temperature	41° to 122° F (5° to 50° C)
	Relative humidity	10% to 90%
	Maximum wet bulb temperature	86° F (30° C)

Technical Specifications - Optical Devices

Certifications, Approvals	MMC-4 compliant, multi-read compliant, Microsoft WHQL certification, ACA AS/NZS 3548 class B, BSMI CNS 13438, CE Mark, C.I.S.P.R. Part 22, TUV or VDE EN60950, EN 55022, EN55024, EMKO EN60950, EN 60825-1, UL 60950, CSA C22.2 60950-2000, CFR 21 part 1040 class 1, CFR 47 C.I.S.P.R. Part 22 Class B, DHHS/FDA, ANSI C63.4-1992 (FCC Class B), relevant parts of IEC 61000-4.
Operating Systems Supported	Microsoft Windows XP Professional, Microsoft Windows XP Professional x64 Edition Red Hat Linux 7.3 WS3 and WS4 Versions (LightScribe labeling functionality not supported on Linux)
Supplied Software (for Windows XP)	Roxio Cineplayer Movie Playback Roxio Digital Media Plus: Create or copy CDs and DVDs, including music and data CDs, and data DVDs Roxio MyDVD for DVD authoring NOTE: LightScribe Direct Disc Labeling is supported only on 32-bit Windows XP in the launch timeframe for the xw4300. Support for Windows XP Professional x64 Edition is anticipated to be available some time after the launch, and will require software updates. There is no support for LightScribe labeling under Linux. The drive will operate as a DVD writer under these other operating systems, but will not be available in software applications as a LightScribe "printer".

NOTE: This DVD writer kit does not include any software for burning DVDs on Linux. DVD burning is supported with the 'growisofs' command. CD burning is supported with the 'cdrecord' command. Red Hat Enterprise Linux WS 3 distribution includes both 'cdrecord' and 'growisofs'. Red Hat Linux 8, 9.0 distributions only include 'cdrecord'. Therefore DVD burning is only supported on WS 3.

Technical Specifications - Graphics

NVIDIA Quadro NVS 285 with TurboCache Technology PCIe Graphics	Form Factor	NVIDIA Quadro NVS 285 with TurboCache Technology 128MB PCIe Dual Head Low profile, both ATX and low profile brackets included
	Graphics Controller	Integrated Quadro 285 2D graphics processor unit (GPU)
	Bus Type	PCI-Express
	Memory	128 MB DDR (64 MB local frame buffer plus 64 MB of shared system memory via TurboCache technology) NOTE: The graphics card uses part of the total system memory (RAM) for graphics performance. System memory dedicated to graphics performance is not available for other use by other programs.
	Connectors	DMS-59 to dual-DVI Y-cable or dual-VGA Y-cable
	Dimensions	Low-profile, 2.586 x 6.6 in (6.57 x 16.76 cm)
	Overlay planes	One 16-bit Video overlay plane
	Multi-monitor support	Dual analog or digital monitors
	Maximum pixel clock	350 MHz
	RAMDAC	Dual 350 MHz (integrated)
	High-definition Video Processor (HDVP)	Full screen, full frame video playback of HDTV and DVD content DVD-ready motion compensation for MPEG-2 Independent hardware color controls for video overlay Hardware color-space conversion (YUV 4:2:2 and 4:2:0) IDCT motion compensation 5-tap horizontal by 3-tap vertical filtering 8:1 up/down scaling
	Available graphics drivers	Microsoft Windows 2000 and Microsoft Windows XP (Provides full native Dual View mode, Span or Big Desktop mode, and Clone mode) HP qualified drivers may be preloaded or available from the HP support Web site: http://www.hp.com/country/us/en/support.html?pageDisplay=drivers

ATI FireGL V3100 Graphics Card (PCI Express)	Form factor	ATX
	Graphics controller	RV370
	Bus type	PCI-Express x16
	Memory	128 MB 200MHz DDR unified frame buffer, Z-buffer and Texture storage
	Connectors	1 DVI-I analog/digital and 1 VGA analog monitor output
	Multi-monitor support	Dual integrated display controllers supporting up to 2048x1536 @ 85Hz on both displays
	RAMDAC	Dual 400 MHz integrated
	Architecture features	128-bit memory interface 128-bit IEEE floating-point precision 24-bits per RGBA color precision 4-bit sub-pixel precision 2 parallel geometry engines 4 parallel pixel pipelines 2x/4x/6x FSAA Hardware accelerated antialiased points and lines Hardware OpenGL overlay planes Hardware accelerated two-sided lighting Hardware accelerated clipping planes Hardware accelerated occlusion culling Hardware accelerated clip planes
	Shading architecture	Smartshader™ technology

Technical Specifications - Graphics

	<p>Programmable pixel and vertex shaders 16 textures per pass Pixel shaders up to 160 instructions with 32-bit floating point precision for each RGBA component Multiple render target support Shadow volume rendering acceleration High precision 10-bit per channel frame buffer support</p>
Supported graphics APIs	<p>OpenGL 1.5 DirectX 9.0</p>
Available graphics drivers	<p>Windows XP Professional, Windows XP Professional x64 Edition, Linux Xfree86HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/eng/software_drivers.html.</p>
Maximum resolution	<p>DVI-I output – drives digital display at resolutions up to 1600x1200 Internal 400MHz RAMDACs – drives dual analog displays up to 2048x1536 @ 85Hz each</p>

NVIDIA Quadro FX 540 PCI-Express Graphics Card	Form Factor	<p>ATX, 4.376" x 7.0" Single slot</p>
	Graphics Controller	NVIDIA NV43GL
	Bus Type	PCI-Express x16, <75W power consumption
	RAMDAC	Dual 400 MHz integrated
	Memory	<p>128 MB 275 MHz DDR SDRAM unified frame buffer, Z-buffer and Texture storage 8.8 GB/sec graphics memory bandwidth</p>
	Connectors	DVI-I + VGA + 10-pin HDTV Out (HD cable purchased separately)
	Multi-monitor support	Integrated analog display controller supporting a single analog display at 2048x1536 @ 75Hz, one digital display at 1600x1200 @ 60Hz.
	Additional product features	<p>128 KB BIOS 3.3V Flash ROM reprogrammable by SW Hardware accelerated Overlay Planes Hardware accelerated two-sided lighting Hardware accelerated antialiased points and lines 3D Volumetric Texture support Hardware accelerated Occlusion Culling Compliant with Microsoft/Intel PC2001 Workstation requirements Video Timings compliant with VESA DMT 1.0 and VESA GTF 1.0 specifications DDC2B+ Monitor support on all OS platforms ACPI Version 1.0b Power Management support (all modes)</p>
	Shading architecture	<p>Fully programmable GPU (OpenGL 1.5/DirectX 9.0c class) Long fragment programs (up to 65,536 instructions) Long vertex programs (up to 65,536 instructions) Looping and subroutines (up to 256 loops per vertex program) Dynamic flow control Conditional execution Optimized compilers for Cg, OpenGL shading language, and Microsoft HLSL</p>
	Supported graphics APIs	<p>OpenGL 1.5 ICD with immediate mode support for all OGL primitive types DirectX 9.0c</p>
	Available graphics drivers	<p>HP-tested: Microsoft Windows XP, Windows 2000, and Linux HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/eng/software_drivers.html.</p>

Technical Specifications - Graphics

Maximum Resolution	DVI-I output - drives digital display at resolutions up to 1600x1200 @ 60Hz Internal 400MHz RAMDACs – drives dual analog display up to 2048x1536 @ 75Hz each
---------------------------	---

NVIDIA Quadro FX 1400 PCI-Express Graphics Controller	Form Factor	ATX, 4.376" x 8.5" Single slot
	Graphics Controller	NVIDIA NV41GL
	Bus Type	PCI-Express x16, <75W power consumption
	RAMDAC	Dual 400 MHz integrated
	Memory	128 MB 300 MHz DDR SDRAM unified frame buffer, Z-buffer and Texture storage 19.2 GB/s graphics memory bandwidth
	Connectors	2 DVI-I analog/digital monitor outputs, 1 3-pin Mini DIN stereo output
	Multi-monitor support	Dual integrated analog display controllers supporting up to two analog displays at 2048x1536 @ 85Hz on both displays.
	Additional product features	128 KB BIOS 3.3V Flash ROM reprogrammable by SW Hardware accelerated Overlay Planes Hardware accelerated two-sided lighting Hardware accelerated antialiased points and lines Quad-buffered Stereo 3D Volumetric Texture support Hardware accelerated Occlusion Culling Scalable Link Interface (SLI) technology Compliant with Microsoft/Intel PC2001 Workstation requirements Video Timings compliant with VESA DMT 1.0 and VESA GTF 1.0 specifications DDC2B+ Monitor support on all OS platforms ACPI Version 1.0b Power Management support (all modes)
	Shading architecture	Fully programmable GPU (OpenGL 1.5/DirectX 9.0c class) Long fragment programs (up to 65,536 instructions) Long vertex programs (up to 65,536 instructions) Looping and subroutines (up to 256 loops per vertex program) Dynamic flow control Conditional execution Optimized compilers for Cg, OpenGL shading language, and Microsoft HLSL
	Supported graphics APIs	OpenGL 1.5 ICD with immediate mode support for all OGL primitive types DirectX 9.0c
	Available graphics drivers	HP-tested: Microsoft Windows XP, Windows 2000 and Linux HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/eng/software_drivers.html .
	Maximum Resolution	Dual DVI-I output – drives dual digital displays at resolutions up to 1900x1200 @ 60Hz Internal 400MHz RAMDACs – drives dual analog displays up to 2048x1536 @ 85Hz each

Technical Specifications - Graphics

ATI FireGL V5100 PCI-Express Graphics Controller	Form Factor	ATX	
	Graphics Controller	RV423	
	Bus Type	PCI-Express x16	
	Memory	128 MB 350MHz DDR unified frame buffer, Z-buffer and Texture storage	
	Connectors	2 DVI-I analog/digital monitor outputs, 1 3-pin Mini DIN stereo output	
	Multi-monitor support	Dual integrated display controllers supporting up to two analog displays at 2048x1536 @ 85Hz on both displays.	
	RAMDAC	Dual 400 MHz integrated	
	Architecture features	256-bit memory interface 128-bit IEEE floating-point precision 24-bits per RGBA color precision 8-bit sub-pixel precision 6 parallel geometry engines 12 parallel pixel pipelines 2x/4x/6x FSAA Hardware accelerated antialiased points and lines Hardware OpenGL overlay planes Hardware accelerated two-sided lighting Hardware accelerated clipping planes Hardware accelerated occlusion culling Hardware accelerated clip planes Quad-buffered stereo	
	Shading architecture	Smartshader™ technology Programmable pixel and vertex shaders 16 textures per pass Pixel shaders up to 160 instructions with 32-bit floating point precision for each RGBA component Multiple render target support Shadow volume rendering acceleration High precision 10-bit per channel frame buffer support	
	Supported graphics APIs	OpenGL 1.5 DirectX 9.0	
	Available graphics drivers	HP-tested: Microsoft Windows XP, Windows 2000, and Linux HP qualified drivers may be preloaded or available from the HP support Web site: http://welcome.hp.com/country/us/eng/software_drivers.html .	
	Maximum Resolution	DVI-I output – drives digital displays at resolutions up to 1600x1200 Internal 400MHz RAMDAC – drives dual analog displays up to 2048x1536 @ 85Hz each	
	NVIDIA Quadro FX 3450 Graphics Controller	Form Factor	ATX
		Graphics Controller	NVIDIA Quadro FX 3450 Workstation GPU
Bus Type		PCI-Express x16	
Memory		256 MB 450 MHz GDDR3 SDRAM unified graphics memory	
Connectors		2 DVI-I (one dual-link/one single-link) analog/digital monitor outputs, 1 3-pin Mini DIN stereo output, DVI-I to VGA adapters included	
Multi-Monitor Support		Dual integrated display controllers supporting up to two analog displays at 2048 x 1536 @ 75 Hz on both displays or dual digital displays at 1920 x 1200 (single-link) and 3840 x 2400 (dual-link). NVIEW advanced multi-display desktop and application management seamlessly integrated into Microsoft Windows	
Architecture Features		256-bit memory interface 128-bit IEEE floating-point color precision 12-bit sub-pixel precision 65,536 fragment instruction	

Technical Specifications - Graphics

	65,536 vertex instruction
	3D volumetric textures
	Single-system powerwall
	12 pixels per clock rendering engine
	Hardware accelerated antialiased points and lines
	Hardware OpenGL overlay planes
	Hardware accelerated two-sided lighting
	Hardware accelerated clipping planes
	3rd generation occlusion culling
	16 textures per pixel in fragment programs
	Window ID clipping functionality
	Hardware accelerated line stippling
	OpenGL Quad-buffered stereo
Shading Architecture	Fully programmable GPU (OpenGL 2.0/DirectX 9.0c class) Long fragment programs (up to 65,536 instructions) Long vertex programs (up to 65,536 instructions) Looping and subroutines (up to 256 loops per vertex program) Dynamic flow control Conditional execution
High Level Shader Languages	Optimized compiler for Cg and Microsoft® HLSL OpenGL 2.0 and DirectX 9.0c support Open source compiler
High-Resolution Antialiasing	12-bit subpixel sampling precision enhances AA quality Rotated-grid full-scene antialiasing (RG FSAA) 8x FSAA dramatically reduces visual aliasing artifacts or "jaggies" at resolution up to 1920x1200
Display Resolution Support	Dual Link DVI- I output-drives digital displays at resolutions up to 3840 x 2400 @ 24 Hz Single Link DVI-I output drives digital displays at resolutions up to 1920 x 1200 @ 75 Hz Internal 400 MHz DACs - Two analog displays up to 2048 x 1536 @ 75 Hz each
nView Architecture	Advanced multi-display desktop & application management seamlessly integrated into Microsoft Windows.
Supported Graphics APIs	OpenGL 2.0 ICD with immediate mode support for all OGL primitive types DirectX 9.0c
Available Graphics Drivers	Microsoft Windows XP, Linux - Full Open GL implementation, complete with NVIDIA and ARB extensions. HP qualified drivers may be preloaded or available from the HP support web site: http://welcome.hp.com/country/us/eng/software_drivers.html .

NVIDIA Quadro FX 4500 Graphics Controller	Graphics Controller	NVIDIA Quadro FX 4500 Workstation GPU
	Bus Type	PCI Express x16
	RAMDAC	Dual 400 MHz integrated
	Memory	512 MB GDDR3 SDRAM unified graphics memory
	Form Factor	ATX
	Connectors	2 DVI-I analog/digital monitor outputs, 1 3-pin Mini DIN stereo output, DVI-I to VGA adapters included
	Multi-Monitor Support	Dual integrated display controllers supporting up to 2048 x 1536 @ 75 Hz (analog) or 3840 x 2400 @ 41 Hz (digital) on both displays
	NVIDIA Quadro FX	256-bit memory interface

Technical Specifications - Graphics

4500 Architecture	35.2GB/sec. memory bandwidth Full 128-bit floating point color precision 12-bit subpixel precision 65,536 fragment instruction 65,536 vertex instruction 3D volumetric textures Single-system powerwall 12 pixels per clock rendering engine Hardware accelerated antialiased points & lines Hardware OpenGL® overlay planes Hardware accelerated two-sided lighting Hardware accelerated clipping planes Hardware two-sided lighting 3rd-generation occlusion culling OpenGL quad-buffered stereo Hardware-Accelerated Pixel Read-Back
Shading Architecture	16 textures per pixel in fragment programs Window ID clipping functionality Hardware accelerated line stippling Fully programmable GPU (OpenGL2.0/DirectX 9.0c class) Long fragment programs (up to 65,536 instructions) Long vertex programs (up to 65,536 instructions) Looping and subroutines (up to 256 loops per vertex program) Dynamic flow control Conditional execution
High Level Shader Languages	Optimized compiler for Cg and Microsoft HLSL OpenGL 2.0 and DirectX 9.0c support Open source compiler
High-Resolution Antialiasing	12-bit subpixel sampling precision enhances AA quality Rotated-grid full-scene antialiasing (RG FSAA) 16x FSAA dramatically reduces visual aliasing artifacts or "jaggies" at resolution up to 1920 x 1200
Display Resolution Support	Dual Dual Link DVI- I output-drives digital displays at resolutions up to 3840 x 2400 @ 41 Hz Internal 400 MHz DACs - Two analog displays up to 2048 x 1536 @ 75 Hz each
nView Architecture	Advanced multi-display desktop & application management seamlessly integrated into Microsoft Windows.
Supported Graphics APIs	OpenGL 2.0 ICD with immediate mode support for all OGL primitive types DirectX 9.0c
Available Graphics drivers	Microsoft Windows XP, Linux - Full Open GL implementation, complete with NVIDIA and ARB extensions. HP qualified drivers may be preloaded or available from the HP support web site: http://welcome.hp.com/country/us/eng/software_drivers.html

Technical Specifications - Monitors

HP L1755 Flat Panel Monitor	Panel	Type	Active matrix, thin film transistor (TFT)	
		Viewable Image Area	17 in (43.2 cm) maximum viewable (diagonal)	
		Screen Opening (WxH)	13.4 x 10.7 in (33.9 x 27.2 cm)	
		Viewing Angle (typical)	176 degrees horizontal/176 degrees vertical (10:1 minimum contrast ratio)	
		Brightness (typical)	Up to 250 nits (cd/m ²)	
		Contrast Ratio (typical)	Up to 1000:1 (typical)	
		Response Rate (typical)	25 ms (typical rise + fall)	
		Pixel Pitch	0.264 mm	
		Video/Other Inputs	Plug and Play	Yes (supports VESA DDC2B; PC2001 compliant)
			Self Powered USB 2.0 Hub	One upstream, four downstream ports (cable included)
Input Signal	Two connectors: one 15-pin mini D-sub analog VGA; and one DVI-I (VGA analog or digital)			
Input Impedance	75 ohms ± 2%			
Sync Input	Separate sync (HSYNC/VSYNC); composite sync, Sync on Green (activated through on-screen display)			
Video Cable	VGA to VGA, DVI-D to DVI-D, and DVI-I to VGA			
Video Cable Length	78 in (2.0 m)			
Signal Interface/ Performance	Horizontal Frequency		30 to 82 kHz	
	Vertical Frequency		56 to 75 Hz	
	Native Resolution		1280 x 1024 @ 60 Hz analog 1280 x 1024 @ 60 Hz digital	
	Maximum Resolution (Analog)	1280 x 1024 @ 75 Hz analog		
	Maximum Resolution (Digital)	1280 x 1024 @ 75 Hz digital		
	Preset VESA Graphic Modes (non-interlaced)	640 x 480 @ 60 Hz, 72 Hz, 75 Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz, 72 Hz, 75 Hz 1024 x 768 @ 60 Hz, 70 Hz, 75 Hz 1280 x 1024 @ 60 Hz, 75 Hz		
	Preset MAC Mode	832 x 624 @ 75 Hz 1152 x 870 @ 75 Hz		
	Preset VGA Mode	640 x 480 @ 60 Hz, 72 Hz		
	Preset SUN Mode	1152 x 900 @ 76 Hz		
	Fail Safe Mode	Yes (limits out of range signal messages)		
Maximum Pixel Clock Speed	140 MHz			
User Programmable Modes	Yes, 15			
Anti-Glare	Yes			
Anti-Static	Yes			

Technical Specifications - Monitors

	AssetControl	Yes (accessible on HP Compaq Business Desktops featuring Intelligent Manageability)
	Default Color Temperature	Yes (6500k, 9300k, SRGB, Custom User)
On Screen Display (OSD) Controls	Buttons or Switches	Power on/off; 3-button OSD; second level OSD buttons include dual-input switch, dedicated auto adjust switch
	Languages	English, Spanish, French, German, Italian, Japanese, Simplified Chinese
	User Controls	Size and positioning, contrast, brightness, clock, clock phase, selectable color temperature, serial number, mode displayed, sleep timer, input selection, factory reset, individual color contrast, full-screen resolution
Power	Power Supply	Auto-ranging, 90 to 265 VAC; internal power supply
	Input Power	100 ~ 240 VAC
	Nominal Current	1.5 A maximum
	Frequency	50 ~ 60 Hz
	Average	33 watts when displaying standard office software
	Typical Power Consumption	< 40 watts
	Maximum	< 60 watts
	Power Saving	< 2 W
	Off Mode	0 watts (when master power switch is in the off position)
	Power Cable Length	70 in (1.8 m); non-captive
Mechanical	Dimensions (H x W x D)	Unpacked with stand 16.1 (minimum) to 21.2 (maximum) x 14.4 x 8.3 in (40.9 (minimum) to 42.2 (maximum) x 36.5 x 21.1 cm)
		Base Area (Footprint D x W) 8.3 x 12.2 in (21.1 x 30.9 cm)
		Panel only (without stand) (H x W x D) 11.8 x 14.4 x 2.9 in (30.1 x 40.9 x 7.3 cm)
	Weight	Unpacked with stand 14.7 lb (6.7 kg)
		Unpacked without stand 8.1 lb (3.7 kg)
		Packaged 20.2 lb (9.2 kg)
	Bezel Width	13 mm left and right, 14 mm top, and 15 mm bottom
	Tilt Range	-5° to +35°
	Swivel Range	± 50° horizontal swivel
	Height Adjustable	Yes (5.1 in/13 cm adjustment range)
	Pivot Rotation	Yes, 90 °
	Base	Ships detached and is removable after installation
Environmental	Temperature –	41° to 95° F (5° to 35° C)

Technical Specifications - Monitors

	Operating Temperature – Non-operating	-4° to 140° F (-20° to 60° C)
	Humidity – Operating	20% to 80%
	Humidity – Non-operating	5% to 95%
	Altitude – Operating	0 to 13,000 ft (0 to 4,000 m)
	Altitude – Non-operating	0 to 40,000 ft (0 to 12,192 m)
Options	HP Desktop Access Center – Part number: DK985A	Features integrated microphone/headset jacks, dual function headset for phone/PC support, a MultiBay slot for adding an optical drive (sold separately), and four USB ports for easy integration of third-party digital solutions. Sold separately. For more information, refer to the HP Desktop Access Center QuickSpec document.
	HP Flat Panel Speaker Bar – Part number: PF804AA	Powered directly by the monitor, seamlessly attaches to the monitor's bezel to bring full multimedia support to select HP flat panel monitors. Features dual speakers with full sound range and external jack for headphones. Sold separately. For more information, refer to the HP Flat Panel Speaker Bar QuickSpec document.
	HP Compaq 7000 Series Ultra-slim Desktop Integrated Work Center Stand – Part number: DL641B	Allows mounting of a 15-, 17- or 19-inch HP flat panel monitor and an HP Compaq dc7100 Ultra-slim Desktop PC on a single stand for the convenience of an "all-in-one" form factor. Sold separately. For more information, refer to this product's QuickSpec document
Other	Accessories Included	VGA to VGA cable, DVI-D to DVI-D cable, DVI-I to VGA cable, USB cable, user CD-ROM with Pivot Pro software
	Software	Pivot Pro software from Portrait Displays, Inc. interacts with your PC's native graphics driver to enable seamless portrait screen redraws with a simple mouse-click or keyboard command. Pivot Pro supports 90-degree portrait and landscape views. Language support is available in English, Japanese, French, German, Spanish, Italian, and Traditional and Simplified Chinese.
	Software	HP Display LiteSaver feature lets you schedule Sleep mode at preset times to help protect the display against image retention, drastically lower power consumption and energy costs, and extend the lifespan of the monitor.
	User Guide Languages	English, Latin America Spanish, Brazilian Portuguese, Danish, Dutch, Finnish, French, German, Italian, Norwegian, Swedish, Greek, Polish, Russian, Slovenian, Turkish, Simplified Chinese, Traditional Chinese, Korean, and Japanese

Technical Specifications - Monitors

	Warranty Languages	English, Canadian French, Latin America Spanish, Brazilian Portuguese, Danish, Dutch, Finnish, French, German, Italian, Norwegian, Spanish, Swedish, Bahasa Indonesian, Simplified Chinese, Traditional Chinese, and Korean
	Color	Carbonite, two-tone carbonite and silver (EMEA only)
	VESA Mounting	Yes (swing arm/wall mount not included); base must be removed for mounting options)
	VESA External Mounting	Yes (standard 4 hole pattern, 100 mm)
	Kensington Lock-ready	Yes
Certification and Compliance		Australian ACA Approval, Canadian Requirements/CSA, CE Marking, China CCC Approval, CISPR Requirements, Eastern European Approvals, Energy Star Compliant, FCC Approval, German Ergonomic (TUV and GS Mark), ISO 13406-2 Compliant (Pixel Defect Guidelines), Mexican NOM Approval, MPR-II Compliant, PC2001 Compliant, PC99 Certified, S. Korean MIC Approval, Taiwan BSMI Approval, TCO 99 or 03 depending on region (emissions, ergonomics, environment), TUV-Ergo, UL Listed, VCCI Approvals, Microsoft Windows Certification
Compatibility		VESA Video Signal Standard (VSIS) Compliant video cards have been tested and proven compatible for use with the HP L1755 Flat Panel Monitor. Recommended for use with HP products.
Service and Warranty		Limited three-year parts and repair labor, service provider labor, and on-site service. Next business day advanced exchange direct replacement service available during warranty period. Certain restrictions and exclusions apply. For details, contact HP Customer Support.

HP L1955 Flat Panel Monitor

Panel	Type	Active matrix, thin film transistor (TFT)
	Viewable Image Area	19 in (48.25 cm) maximum viewable (diagonal)
	Screen Opening (WxH)	14.9 x 12.0 in (38.0 x 30.5 cm)
	Viewing Angle (typical)	176 degrees horizontal/176 degrees vertical (10:1 minimum contrast ratio)
	Brightness (typical)	Up to 250 nits (cd/m ²)
	Contrast Ratio (typical)	Up to 1000:1 (typical)
	Response Rate (typical)	<16 ms (typical rise + fall)
	Pixel Pitch	0.294 mm
Video/Other Inputs	Plug and Play	Yes (supports VESA DDC2B; PC2001 compliant)
	Self Powered USB 2.0 Hub	One upstream, four downstream ports (cable included)
	Input Signal	Two connectors: one 15-pin mini D-sub analog VGA; and one DVI-I (VGA analog or digital)
	Input Impedance	75 ohms ± 2%
	Sync Input	Separate sync (HSYNC/VSING); composite sync, Sync on Green (activated through on-screen display)
	Video Cable	VGA to VGA, DVI-D to DVI-D, and DVI-I to VGA

Technical Specifications - Monitors

Signal Interface/ Performance	Video Cable Length	78 in (2.0 m)	
	Horizontal Frequency	30 to 82 kHz	
	Vertical Frequency	56 to 75 Hz	
	Native Resolution	1280 x 1024 @ 75 Hz analog 1280 x 1024 @ 60 Hz digital	
	Maximum Resolution (Analog)	1280 x 1024 @ 75 Hz analog	
	Maximum Resolution (Digital)	1280 x 1024 @ 75 Hz digital	
	Preset VESA Graphic Modes (non-interlaced)	640 x 480 @ 60 Hz, 72 Hz, 75 Hz 720 x 400 @ 70 Hz 800 x 600 @ 60 Hz, 72 Hz, 75 Hz 1024 x 768 @ 60 Hz, 70 Hz, 75 Hz 1280 x 1024 @ 60 Hz, 75 Hz	
	Preset MAC Mode	832 x 624 @ 75 Hz 1152 x 870 @ 75 Hz	
	Preset VGA Mode	640 x 480 @ 60 Hz, 72 Hz	
	Preset SUN Mode	1152 x 900 @ 76 Hz	
	Fail Safe Mode	Yes (limits out of range signal messages)	
	Maximum Pixel Clock Speed	140 MHz	
	User Programmable Modes	Yes, 15	
	Anti-Glare	Yes	
	Anti-Static	Yes	
	AssetControl	Yes (accessible on HP Compaq Business Desktops featuring Intelligent Manageability)	
	Default Color Temperature	Yes (6500k, 9300k, SRGB, Custom User)	
	On Screen Display (OSD) Controls	Buttons or Switches	Power on/off; 3-button OSD; second level OSD buttons include dual-input switch, dedicated auto adjust switch
		Languages	English, Spanish, French, German, Italian, Japanese, Simplified Chinese
		User Controls	Size and Positioning
Contrast			
Brightness			
Power	Power Supply	Clock, Clock Phase	
		Selectable Color Temperature	
	Serial Number		
	Mode Displayed		
	Sleep Timer		
	Input Selection		
	Factory Reset		
	Individual Color Contrast		
	Full-screen Resolution		
	Input Power	Auto-ranging, 90 to 265 VAC; internal power supply 100 ~ 240 VAC	

Technical Specifications - Monitors

	Nominal Current	1.5 A maximum
	Frequency	50 ~ 60 Hz
	Average	33 watts when displaying standard office software
	Typical Power Consumption	< 40 watts
	Maximum	< 60 watts
	Power Saving Off Mode	< 2 watts
		0 watts (when master power switch is in the off position)
	Power Cable Length	70 in (1.8 m); non-captive
Mechanical	Dimensions (H x W x D)	Unpacked with stand 16.8 (minimum) to 22.3 (maximum) x 15.9 x 8.3 in (42.7 (minimum) to 56.6 (maximum) x 40.4 x 21.1 cm)
		Base Area (Footprint D x W) 8.3 x 12.2 in (21.1 x 30.9 cm)
		Panel only (without stand) (H x W x D) 13.2 x 15.9 x 3.1 in (33.5 x 40.4 x 7.9 cm)
		Weight Unpacked with stand 16.5 lb (7.5 kg)
		Unpacked without stand 10.5 lb (4.75 kg)
		Packaged 23.5 lb (10.7 kg)
		Bezel Width 13 mm left and right, 14 mm top, and 15 mm bottom
		Tilt Range -5° to +35°
		Swivel Range ± 50° horizontal swivel
		Height Adjustable Yes (5.1 in/13 cm adjustment range)
	Pivot Rotation Yes, 90 °	
	Base Ships detached and is removable after installation	
Environmental	Temperature – Operating	41° to 95° F (5° to 35° C)
	Temperature – Non-operating	-4° to 140° F (-20° to 60° C)
	Humidity – Operating	20% to 80%
	Humidity – Non-operating	5% to 95%
	Altitude – Operating	0 to 13,000 ft (0 to 4,000 m)
	Altitude – Non-operating	0 to 40,000 ft (0 to 12,192 m)
	Options	Desktop Access Center Features integrated microphone/headset jacks, dual function headset for phone/PC support, a MultiBay slot for adding an optical drive (sold separately), and four USB ports for easy integration of third-party digital solutions. Sold separately; part number DK985A. For more information, refer to the HP Desktop Access Center QuickSpecs.

Technical Specifications - Monitors

	HP Flat Panel Speaker Bar	Powered directly by the monitor, seamlessly attaches to the monitor's bezel to bring full multimedia support to select HP flat panel monitors. Features dual speakers with full sound range and external jack for headphones. Sold separately, part number PF804AA. For more information, refer to the HP Flat Panel Speaker Bar QuickSpecs.
Other	Accessories Included	VGA to VGA cable, DVI-D to DVI-D cable, DVI-I to VGA cable, USB cable, user CD-ROM with Pivot Pro software
	Software	Pivot Pro software from Portrait Displays, Inc. interacts with your PC's native graphics driver to enable seamless portrait screen redraws with a simple mouse-click or keyboard command. Pivot Pro supports 90-degree portrait and landscape views. Language support is available in English, Japanese, French, German, Spanish, Italian, and Traditional and Simplified Chinese.
	Software	HP Display LiteSaver feature lets you schedule Sleep mode at preset times to help protect the display against image retention, drastically lower power consumption and energy costs, and extend the lifespan of the monitor.
	User Guide Languages	English
	Warranty Languages	English
	Color	Carbonite, two-tone carbonite and silver (EMEA only)
	VESA Mounting	Yes (swing arm/wall mount not included); base must be removed for mounting options)
	VESA External Mounting	Yes (standard 4 hole pattern, 100 mm)
	Kensington Lock-ready	Yes
	Certification and Compliance	Australian ACA Approval, Canadian Requirements/CSA, CE Marking, China CCIB/CCEE Approval, CISPR Requirements, Eastern European Approvals, Energy Star Compliant, FCC Approval, German Ergonomic (TUV and GS Mark), ISO 13406-2 Compliant (Pixel Defect Guidelines), Mexican NOM Approval, MPR-II Compliant, PC2001 Compliant, PC99 Certified, S. Korean MIC Approval, Taiwan BSMI Approval, TCO 99 or 03 depending on region (emissions, ergonomics, environment), TUV-Ergo, UL Listed, VCCI Approvals, Microsoft® Windows® Certification
Compatibility	VESA Video Signal Standard (VSIS) Compliant video cards have been tested and proven compatible for use with the HP L1955 Flat Panel Monitor. Recommended for use with HP products.	
Service and Warranty	Limited three-year parts and repair labor, service provider labor, and on-site service. Next Business Day advanced exchange direct replacement service available during warranty period. Certain restrictions and exclusions apply. For details, contact HP Customer Support.	

HP Flat Panel Monitor Panel L2035

Type 20-inch Active Matrix TFT (thin film transistor)
Viewable Image Area 20.1 in (51 cm) (diagonal)



Technical Specifications - Monitors

	Screen Opening (W x H)	16.2 x 12.17 in (41.1 x 30.9 cm)
	Viewing Angle (typical)*	Up to 170° H/170° V (10:1 minimum contrast ratio)
	Brightness (typical)*	Up to 250 nits (cd/m ²)
	Contrast Ratio (typical)*	Up to 400:1
	Response Rate (typical)*	16 ms (typical, rise + fall)
	Pixel Pitch	0.255 mm
	*All specifications are provided by the component manufacturers. Performance specifications represent the highest specification of all HP's component manufacturers' typical level specifications for performance. Actual performance may vary either higher or lower.	
On Screen Display (OSD) Controls	Buttons or Switches	PiP (Picture in Picture), Input select, auto adjust, OSD up, OSD down, OSD menu select, power
	Languages	English, French, German, Spanish, Italian
	User Controls	Brightness, contrast, positioning, color temperature, individual color control, serial number display, full screen resolutions, clock, clock phase, video picture-in-picture (size and position), input selection (includes separate direct access key for dedicated swap between inputs 1 and 2), factory reset
Signal Interface/ Performance	Horizontal Frequency	30 to 94 kHz (VGA input); 30 to 92 KHz (DVI input) (for modes with pixel clock less than 157 MHz)
	Vertical Frequency	48 to 85 Hz (VGA input); 30 to 92 KHz (DVI input) (for modes with pixel clock less than 157 MHz)
	Graphics Controller	Pixelworks PW171
	Native Resolution	1600 x 1200 @ 60 Hz (recommended)
	Preset VESA Graphic Modes (non-interlaced)	1600 x 1200 @ 60 Hz, 75 Hz (VGA input) 1280 x 1024 @ 60 Hz, 75 Hz, 85 Hz 1280 x 960 @ 60 Hz 1152 x 900 @ 66 Hz 1024 x 768 @ 60 Hz, 75 Hz, 85 Hz 800 x 600 @ 60 Hz, 85 Hz 640 x 480 @ 60 Hz, 75 Hz, 85 Hz
	Text Mode	720 x 400 @ 70 Hz
	Mac Mode	1152 x 870 @ 75 Hz and 832 x 624 @ 75 Hz
	Sun Mode	1152 x 900 @ 66 Hz
	Maximum Pixel Clock Speed	202 MHz (VGA input); 162 MHz (DVI input)
	User Programmable Modes	Yes, 10
	Anti-Glare	Yes
	Anti-Static	Yes
	Default Color Temperature	6500 K
Video Input	Plug and Play	Yes

Technical Specifications - Monitors

	Input Signal	Four connectors, including one 15-pin mini D-sub VGA, one DVI-I (VGA analog and digital input), one composite video, and one s-video
	Input Impedance	75 ohms ± 10%
	Sync Input	Separate sync (HSYNC/VSYNC); composite sync, Sync on Green
	Video Cable	VGA to VGA; VGA to DVI-I; DVI-D to DVI-I
	Video Cable Length	5.9 ft (1.8 m)
Power	Input Power	Auto-Ranging, 90 to 132 VAC and 195 to 265 VAC; internal power supply, 50 Hz/60 Hz
	Frequency	47.5 to 63 Hz
	Maximum	< 75 W
	Power Saving	< 5 W
	Power Cable Length	5.9 ft (1.8 m)
Mechanical	Dimensions (H x W x D)	Unpacked with stand 17.36 to 20.9 x 17.8 x 8.27 in (44.1 to 53.1 x 45.2 x 21.0 cm)
		Unpacked without stand (head only) 14.29 x 17.8 x 3.19 in (36.3 x 45.2 x 8.1 cm)
		Packaged 11.5 x 21.9 x 23.9 in (29.2 x 55.6 x 60.6 cm)
	Weight	Unpacked With stand: 20.28 lb (9.2 kg); Without stand: 12.35 lb (5.6 kg)
		Packaged 26.9 lb (12.2 kg)
	Tilt Range	-5° to + 25° vertical
	Swivel Range	-35° to + 35°
	Height Adjustable	Yes, range 3.54 in (9.0 cm)
	Pivot Rotation	Yes
	Base	Attached
Environmental	Temperature – Operating	46° to 95° F (10° to 35° C)
	Temperature – Non-operating	6° to 140° F (-10° to 60° C)
	Humidity – Operating	20% to 80% non-condensing
	Humidity – Non-operating	5% to 85%
	Altitude – Operating	+12,000 ft (+3,657.6 m)
	Altitude – Non-operating	+40,000 ft (+12,192 m)

Technical Specifications - Monitors

Options	HP Desktop Access Center	Sold separately, the HP Desktop Access Center features integrated microphone/headset jacks, dual function headset for phone/PC support, a MultiBay slot for adding an optical drive (sold separately), and four USB ports for easy integration of third-party digital solutions; part number DK985A. For more information, refer to the HP Desktop Access Center QuickSpecs.
Other	Accessories Included	<p>VGA to VGA cable – connects the graphic card's VGA analog connector to the monitor's input #1 (VGA analog) connector</p> <p>VGA to DVI-I cable – connects the graphic card's VGA connector to the monitor's input #2 (DVI-I analog) connector</p> <p>DVI-D to DVI-I cable – connects the graphic card's DVI-D digital connector to the monitor's input #2 (DVI-I digital) connector</p>
	User Guide Languages	English, B. Portuguese, French, LA Spanish, Korean, S. Chinese, T. Chinese, Bahasa, Japanese, Danish, Finnish, German, Norwegian, Spanish, Swedish, Greek, Polish, Russian, Slovenian, Turkish
	Warranty Languages	English, Canadian French, LA Spanish, Brazilian Portuguese, Danish, German, Castilian Spanish, French, Italian, Dutch, Norwegian, Finnish, Swedish, Bahasa Indonesian, Korean, T. Chinese, S. Chinese
	Color	Carbonite/Silver
	VESA External Mounting	Yes (Standard 4 hole pattern, 100 mm)
	Kensington Lock-Ready	Yes
Certification and Compliance		<p>Australian ACA Approval, Canadian Requirements/CSA, CE Marking, China CCIB/CCEE Approval, CISPR Requirements, Eastern European Approvals, *Energy Star Compliant, FCC Approval, German Ergonomic (TUV and GS Mark), ISO 9241-3,7,8 VDT Guidelines, ISO 13406-2 Pixel Defect Guidelines, Mexican NOM Approval, MIC Requirements (New Zealand), MPR-II Compliant, Nordic Approvals (Nemko, Fimko, Demko, Semko), PC2001 Compliant, PC99 Certified, S. Korean MIC Approval, Taiwan BSMI Approval, TCO 03 (emissions, ergonomics, environment), TUV-Ergo, UL Listed, VCCI Approvals, Windows Certification (Microsoft® Windows® 98, Microsoft Windows 2000, and Microsoft Windows XP)</p> <p>* Energy Star Compliant available summer 2004.</p>
Compatibility		Compatible with platforms using the VESA standard video modes and HP Compaq Business Desktops d500, d300, and d200 Series, Compaq Evo Desktops, and HP Workstations
Service and Warranty		Limited three years parts, labor, and on-site service, including backlight. Availability varies by region. Certain restrictions and exclusions apply. Consult HP Customer Service for details.

HP Flat Panel Monitor Panel

Type

20-inch Active Matrix TFT (thin film transistor)



Technical Specifications - Monitors

LP2065	<p>Viewable Image Area 20.1 in (51 cm) (diagonal)</p> <p>Screen Opening 16.2 x 12.17 in (41.1 x 30.9 cm) (W x H)</p> <p>Viewing Angle (typical)* Up to 178° horizontal/178° vertical (10:1 minimum contrast ratio)</p> <p>Brightness (typical)* Up to 300 nits (cd/m²)</p> <p>Contrast Ratio (typical)* Up to 800:1</p> <p>Response Rate (typical)* 8 ms (gray to gray), 16 ms (rise + fall)</p> <p>Pixel Pitch 0.255 mm</p> <p>Backlight Lamp Life (to half brightness) 45K hours</p>
On Screen Display (OSD) Controls	<p>Buttons or Switches Input select, auto adjust/OSD up, OSD down, OSD menu select, power</p> <p>Languages English, French, German, Spanish, Italian, Dutch, and Japanese</p> <p>User Controls Brightness, contrast, positioning, color temperature, individual color control, serial number display, full screen resolutions, clock, clock phase, input selection, image control (including scaling), and factory reset</p>
Signal Interface/ Performance	<p>Horizontal Frequency 30 to 94 kHz (VGA input); 30 to 92 KHz (DVI input for modes with pixel clock less than 157 MHz)</p> <p>Vertical Frequency 48 to 85 Hz (VGA input); 30 to 92 KHz (DVI input for modes with pixel clock less than 157 MHz)</p> <p>Native Resolution 1600 x 1200 @ 60 Hz (recommended)</p> <p>Preset VESA Graphic Modes (non-interlaced) 1600 x 1200 @ 60 Hz, 75 Hz (VGA input) 1280 x 1024 @ 60 Hz, 75 Hz, 85 Hz 1280 x 960 @ 60 Hz 1152 x 900 @ 66 Hz 1024 x 768 @ 60 Hz, 75 Hz, 85 Hz 800 x 600 @ 60 Hz, 85 Hz 640 x 480 @ 60 Hz, 75 Hz, 85 Hz</p> <p>Text Mode 720 x 400 @ 70 Hz</p> <p>Mac Mode 1152 x 870 @ 75 Hz and 832 x 624 @ 75 Hz</p> <p>Sun Mode 1152 x 900 @ 66 Hz</p> <p>Maximum Pixel Clock Speed 202 MHz (VGA input); 162 MHz (DVI input)</p> <p>User Programmable Modes Yes, 10</p> <p>Anti-Glare Yes</p> <p>Anti-Static Yes</p> <p>Default Color Temperature 6500 K</p>
Video Input	<p>Plug and Play Input Signal Yes</p> <p>Four connectors, including one 15-pin mini D-sub VGA, one DVI-I (VGA analog and digital input), one composite video, and one s-video</p>

Technical Specifications - Monitors

	Self Powered USB 2.0 Hub	One upstream, four downstream ports (cable included)
	Input Signal	Two DVI-I connectors (dual VGA analog or dual digital input possible)
	Input Impedance	75 ohms \pm 10%
	Sync Input	Separate sync (HSYNC/VSYNC); composite sync, Sync on Green
	Video Cable	Two VGA to DVI-I; two DVI-D to DVI-I
	Video Cable Length	5.9 ft (1.8 m)
Power	Input Power	Auto-Ranging, 90 to 132 VAC and 195 to 265 VAC; internal power supply, 50 Hz/60 Hz
	Frequency	47.5 to 63 Hz
	Typical Power Consumption	55 watts (without USB ports); 70 watts (USB ports fully loaded)
	Maximum	< 75 W
	Power Saving	< 2 watts
	Power Cable Length	5.9 ft (1.8 m)
Mechanical	Dimensions (H x W x D)	Unpacked with stand 16.7 to 21.8 x 17.4 x 8.67 in (42.5 to 55.5 x 44.3 x 22.0 cm)
		Unpacked w/o stand 13.58 x 17.4 x 3.42 in (34.5 x 44.3 x 8.7 cm)
		Packaged 11.77 x 22.2 x 16.77 in (29.9 x 56.4 x 42.6 cm)
	Weight	Unpacked With stand: 20.28 lb (9.2 kg); Without stand: 12.35 lb (5.6 kg)
		Packaged 26.3 lb (11.95 kg)
	Tilt Range	-5° to + 25° vertical tilt
	Swivel Range	-45° to + 45°
	Height Adjustable	Yes, range 5.1 in (13.0 cm)
	Pivot Rotation	Yes
	Base	Detachable, ships attached
Environmental	Temperature – Operating	46° to 95° F (10° to 35° C)
	Temperature – Non-operating	6° to 140° F (-10° to 60° C)
	Humidity – Operating	20% to 80% non-condensing
	Humidity – Non-operating	5% to 85%
	Altitude – Operating	+12,000 ft (+3,657.6 m)
	Altitude – Non-operating	+40,000 ft (+12,192 m)
Options	HP Silver Flat Panel Speaker Bar - Part number: EE418AA	Powered directly by the monitor or the PC, the Speaker Bar seamlessly attaches to the monitor's lower bezel to bring full audio support to select HP flat panel monitors.

Technical Specifications - Monitors

Other	Accessories Included	<p>Features include dual speakers with full sound range and external jack for headphones. Sold separately. For more information, refer to the HP Silver Flat Panel Speaker Bar QuickSpec.</p> <p>VGA to DVI-I cable – connects the graphic card's VGA connector to the monitor's input #1 or 2 (DVI-I analog) connector.</p> <p>DVI-D to DVI-I cable – connects the graphic card's DVI-D digital connector to the monitor's input #1 or #2 (DVI-I digital) connector.</p>
	User Guide Languages	English, B. Portuguese, French, LA Spanish, Korean, S. Chinese, T. Chinese, Bahasa, Japanese, Danish, Finnish, German, Norwegian, Spanish, Swedish, Greek, Polish, Russian, Slovenian, Turkish
	Software	<p>HP Display Assistant Utility makes it possible to adjust displays settings through the PC using two-way communication via DDCI.</p> <p>HP Display Lite Saver allows ability to power up and down display at predetermined hours of the day to save power and backlight life.</p> <p>Pivot Pro software from Portrait Displays, Inc. interacts with your PC's native graphics driver to enable seamless portrait screen redraws with a simple mouse-click or keyboard command. Pivot Pro supports 90-degree portrait and landscape views. Language support is available in English, Japanese, French, German, Spanish, Italian, and Traditional and Simplified Chinese.</p>
	User Guide Languages	English
	Warranty Languages	English
	Color	Carbonite/Silver
	VESA External Mounting	Yes (Standard 4 hole pattern, 100 mm)
	Kensington Lock-Ready	Yes
Certification and Compliance		Canadian Requirements/CSA, CE Marking, CISPR Requirements, Energy Star Compliant, FCC Approval, ISO 13406-2 Pixel Defect Guidelines, Mexican NOM Approval,, MPR-II Compliant, PC2001 Compliant, PC99 Certified, TCO 03 (emissions, ergonomics, environment), TUV-Ergo, UL Listed, VCCI Approvals, Microsoft Windows Certification (Microsoft Windows 98, Microsoft Windows 2000, and Microsoft Windows XP)
Compatibility		Compatible with platforms using the VESA standard video modes. Recommended for use with HP products.
Service and Warranty		Three years parts, labor, and on-site service. 24-hour 365-day 1-800 technical support. Replacement options include 2nd business day on-site service or next business day direct replacement. With direct replacement, HP will ship a replacement display product directly to you. Using the shipping labels provided, return your failed display to HP. Certain restrictions and exclusions apply. For details, contact HP Customer Support.

Technical Specifications - Monitors

HP Flat Panel Monitor Panel L2335

Type	23-inch Active Matrix TFT (thin film transistor)
Viewable Image Area (diagonal)	23 in (58.4 cm)
Screen Opening (W x H)	19.53 x 12.24 in (49.6 x 31.1 cm)
Viewing Angle (typical)*	Up to 170° H/170° V (10:1 minimum contrast ratio)
Brightness (typical)*	Up to 250 nits (cd/m ²)
Contrast Ratio (typical)*	Up to 500:1
Response Rate (typical)*	16 ms (typical, rise + fall)
Pixel Pitch	0.258 mm

* All specifications are provided by the component manufacturers. Performance specifications represent the highest specification of all HP's component manufacturers' typical level specifications for performance. Actual performance may vary either higher or lower.

On Screen Display (OSD) Controls

Buttons or Switches PiP (Picture in Picture), Input Select, Auto Adjust, OSD Up, OSD Down, OSD Menu Select, Power

Languages English, French, German, Spanish, Italian

User Controls Brightness, contrast, positioning, color temperature, individual color control, serial number display, full screen resolutions, clock, clock phase, video picture-in-picture (size and position), input selection (includes separate direct access key for dedicated swap between inputs 1 and 2), factory reset

Signal Interface/ Performance

Horizontal Frequency 30 to 94 kHz (VGA input); 30 to 92 KHz (DVI input) (for modes with pixel clock less than 157 MHz)

Vertical Frequency 48 to 85 Hz (VGA and DVI input)

Graphics Controller Pixelworks PW172

Native Resolution 1920 x 1200 @ 60 Hz (recommended)

Preset VESA Graphic Modes (non-interlaced)
1920 x 1200 @ 60Hz
1600 x 1200 @ 60 Hz, 75 Hz
1280 x 1024 @ 60 Hz, 75Hz, 85 Hz
1280 x 960 @ 60 Hz
1152 x 900 @ 66 Hz
1024 x 768 @ 60 Hz, 75 Hz, 85 Hz
800 x 600 @ 60 Hz, 75Hz
640 x 480 @ 60 Hz, 75 Hz

Text Mode 720 x 400 @ 70 Hz

Mac Mode 1152 x 870 @ 75 Hz and 832 x 624 @ 75 Hz

Sun Mode 1152 x 900 @ 66 Hz

Maximum Pixel Clock Speed 202 MHz (VGA input); 162 MHz (DVI input)

User Programmable Modes Yes, 10

Anti-Glare Yes

Technical Specifications - Monitors

	Anti-Static	Yes
	Default Color Temperature	6500 K
Video Input	Plug and Play	Yes
	Input Signal	Five connectors, including one 15-pin mini D-sub VGA, one DVI-I (VGA analog and digital input), one composite video, one s-video, component video
	Input Impedance	75 ohms \pm 10%
	Sync Input	Separate sync (HSYNC/VSYNC); composite sync, Sync on Green
	Video Cable	VGA to VGA; VGA to DVI-I; DVI-D to DVI-I
	Video Cable Length	5.9 ft (1.8 m)
Power	Input Power	Auto-Ranging, 90 to 132 VAC and 195 to 265 VAC; internal power supply, 50 Hz/60 Hz
	Frequency	47.5 to 63 Hz
	Maximum	< 100 W
	Power Saving	< 5 W
	Power Cable Length	5.9 ft (1.8 m)
Mechanical	Dimensions (H x W x D) Unpacked	17.36 (min) to 20.9 (max) x 21.46 x 8.27 in (44.1 (min) to 53.1 (max) x 54.5 x 21.0 cm)
	Unpacked without stand (head only)	14.57 x 21.46 x 3.35 in (37.0 x 54.5 x 8.5 cm)
	Packaged	11.5 x 25.75 x 23.86 in (29.2 x 65.4 x 60.6 cm)
	Weight Unpacked	22.27 lb (10.1 kg)
	Packaged	30.87 lb (14.0 kg)
	Tilt Range	-5° to + 25° vertical
	Swivel Range	-35° to + 35°
	Height Adjustable	Yes, range 3.54 in (9.0 cm)
	Pivot Rotation	Yes
	Base	Attached
Environmental	Temperature – Operating	46° to 95° F (10° to 35° C)
	Temperature – Non-operating	6° to 140° F (-10° to 60° C)
	Humidity – Operating	20% to 80% non-condensing
	Humidity – Non-operating	5% to 85%
	Altitude – Operating	+12,000 ft (+3,657.6 m)
	Altitude – Non-operating	+40,000 ft (+12,192 m)
Options	HP Desktop Access Center	Sold separately, the HP Desktop Access Center Features integrated microphone/headset jacks, dual function headset for phone/PC support, a MultiBay slot

Technical Specifications - Monitors

Other	Accessories Included	<p>for adding an optical drive (sold separately), and four USB ports for easy integration of third-party digital solutions; part number DK985A. For more information, refer to the HP Desktop Access Center QuickSpecs.</p> <p>VGA to VGA cable – connects the graphic card's VGA analog connector to the monitor's input #1 (VGA analog) connector</p> <p>VGA to DVI-I cable – connects the graphic card's VGA connector to the monitor's input #2 (DVI-I analog) connector</p> <p>DVI-D to DVI-I cable – connects the graphic card's DVI-D digital connector to the monitor's input #2 (DVI-I digital) connector</p>
	User Guide Languages	English, B. Portuguese, French, LA Spanish, Korean, S. Chinese, T. Chinese, Bahasa, Japanese, Danish, Finnish, German, Norwegian, Spanish, Swedish, Greek, Polish, Russian, Slovenian, Turkish
	Warranty Languages	English, Canadian French, LA Spanish, Brazilian Portuguese, Danish, German, Castilian Spanish, French, Italian, Dutch, Norwegian, Finnish, Swedish, Bahasa Indonesian, Korean, T. Chinese, S. Chinese
	Color	Carbonite/silver
	VESA External Mounting	Yes (Standard 4 hole pattern, 100 mm)
	Kensington Lock-Ready	Yes
Certification and Compliance		<p>Australian ACA Approval, Canadian Requirements/CSA, CE Marking, China CCIB/CCEE Approval, CISPR Requirements, Eastern European Approvals, *Energy Star Compliant, FCC Approval, German Ergonomic (TUV and GS Mark), ISO 9241-3,7,8 VDT Guidelines, ISO 13406-2 Pixel Defect Guidelines, Mexican NOM Approval, MIC Requirements (New Zealand), MPR-II Compliant, Nordic Approvals (Nemko, Fimko, Demko, Semko), PC2001 Compliant, PC99 Certified, S. Korean MIC Approval, Taiwan BSMI Approval, TCO 03 (emissions, ergonomics, environment), TUV-Ergo, UL Listed, VCCI Approvals, Windows Certification (Microsoft® Windows® 98, Microsoft Windows 2000, and Microsoft Windows XP).</p> <p>* Energy Star Compliant available summer 2004.</p>
Compatibility		Compatible with platforms using the VESA standard video modes and HP Compaq Business Desktops d500, d300, and d200 Series, Compaq Evo Desktops, and HP Business Desktops d300 series.
Service and Warranty		Limited three years parts, labor, and on-site service, including backlight. Availability varies by region. Certain restrictions and exclusions apply. Consult HP Customer Service for details.

Technical Specifications - Monitors

**HP Flat Panel Monitor Panel
LP2465**

	Type	24-inch Active Matrix TFT (thin film transistor)
	Viewable Image Area (diagonal)	24 in (60.96 cm)
	Screen Opening (W x H)	20.47 x 12.83 in (52.0 x 32.6 cm)
	Viewing Angle (typical)*	178° H/ 178° V (10:1 minimum contrast ratio)
	Brightness (typical)*	500 nits (cd/m ²)
	Contrast Ratio (typical)*	1000:1
	Response Rate (typical)*	8 ms (typical gray to gray)
	Pixel Pitch	0.270 mm
	Backlight Lamp Life (to half brightness)	50K hours
	<i>*Response time 13 ms rise and fall, 6 ms gray to gray.</i>	
On Screen Display (OSD) Controls	Buttons or Switches	Input Select, Auto Adjust, OSD Up, OSD Down, OSD Menu Select, Power
	Languages	English, French, German, Spanish, Italian, Japanese, Dutch
	User Controls	Brightness, contrast, positioning, color temperature, individual color control, serial number display, full screen resolutions, clock, clock phase, input selection (includes separate direct access key for dedicated swap between inputs 1 and 2), factory reset
Signal Interface/ Performance	Horizontal Frequency	30 to 94 kHz (VGA input); 30 to 92 KHz (DVI input) (for modes with pixel clock less than 157 MHz)
	Vertical Frequency	48 to 85 Hz (VGA and DVI input)
	Native Resolution	1920 x 1200 @ 60 Hz (recommended) (native aspect ratio of 16:10)
	Preset VESA Graphic Modes (non-interlaced)	1920 x 1200 @ 60 Hz 1600 x 1200 @ 60 Hz, 75 Hz 1280 x 1024 @ 60 Hz, 75 Hz, 85 Hz 1280 x 960 @ 60 Hz 1152 x 900 @ 66 Hz 1024 x 768 @ 60 Hz, 75 Hz, 85 Hz 800 x 600 @ 60 Hz, 75 Hz 640 x 480 @ 60 Hz, 75 Hz
	Text Mode	720 x 400 @ 70 Hz
	Mac Mode	1152 x 870 @ 75 Hz and 832 x 624 @ 75 Hz
	Sun Mode	1152 x 900 @ 66 Hz
	Maximum Pixel Clock Speed	202 MHz (VGA input); 162 MHz (DVI input)
	User Programmable Modes	Yes, 20
	Anti-Glare	Yes
	Anti-Static	Yes
	Default Color Temperature	6500 K

Technical Specifications - Monitors

Video/Other Inputs	Plug and Play	Yes	
	Self Powered USB 2.0 Hub	One upstream, four downstream ports (located on side of monitor, cable included)	
	Input Signal	Two DVI-I (VGA analog and digital) inputs	
	Input Impedance	75 ohms ± 10%	
	Sync Input	Separate sync (HSYNC/VSYNC); composite sync, Sync on Green	
	Video Cable	VGA to DVI-I; DVI-D to DVI-D	
	Video Cable Length	5.9 ft (1.8 m)	
	Power	Input Power	Auto-Ranging, 90 to 132 VAC and 195 to 265 VAC; internal power supply, 50 Hz/60 Hz
		Frequency	47.5 to 63 Hz
		Typical Power Consumption	75 watts
Maximum		< 110 watts	
Power Saving		< 2 watts	
Power Cable Length		6.2 ft (1.9 m)	
Mechanical	Dimensions (H x W x D)	Unpacked w/ stand 14.6 (min) to 19.7 (max) x 22 x 9.1 in (37.1 (min) to 50.1 (max) x 55.4 x 23.2 cm)	
		Unpacked w/o stand (head only) 14.4 x 22 x 3.7 in (36.6 x 55.84 x 9.2 cm)	
		Packaged 11.7 x 22.1 x 25.6 in (29.8 x 56.0 x 65.1 cm)	
	Weight	Unpacked 23.6 lbs (10.7 kg)	
		Packaged 23.6 lbs (10.7 kg)	
	Tilt Range	-5° to + 25° vertical	
	Swivel Range	-45° to + 45°	
	Height Adjustable	Yes, range 5.1 in (130 mm)	
	Pivot Rotation	Yes	
	Base	Detachable, ships detached	
Environmental	Temperature – Operating	46° to 95° F (10° to 35° C)	
	Temperature – Non-operating	6° to 140° F (-10° to 60° C)	
	Humidity – Operating	20% to 80% non-condensing	
	Humidity – Non-operating	5% to 85%	
	Altitude – Operating	+12,000 ft (+3,657.6 m)	
	Altitude – Non-operating	+40,000 ft (+12,192 m)	
	Accessories Included	VGA to DVI-I cable – connects the graphic card's VGA connector to the monitor's input #2 (DVI-I analog) connector DVI-D to DVI-D cable – connects the graphic card's DVI-D digital connector to the monitor's input #2 (DVI-I digital) connector	
Other			

Technical Specifications - Monitors

	Software	<p>Pivot Pro software from Portrait Displays, Inc. interacts with your PC's native graphics driver to enable seamless portrait screen redraws with a simple mouse-click or keyboard command. Pivot Pro supports 90-degree portrait and landscape views. Language support is available in English, Japanese, French, German, Spanish, Italian, and Traditional and Simplified Chinese.</p> <p>HP Display Assistant is a software utility that allows monitor adjustment, color calibration, and security/asset management using the Display Data Channel Command Interface (DDC/CI) protocol of the connected desktop PC.</p> <p>HP Display LiteSaver feature allows you to schedule Sleep mode at preset times to help protect the monitor against image retention, drastically lower power consumption and energy costs, and extend the lifespan of the monitor.</p>
	User Guide Languages	English, B. Portuguese, French, LA Spanish, Korean, S. Chinese, T. Chinese, Bahasa, Japanese, Danish, Finnish, German, Norwegian, Spanish, Swedish, Greek, Polish, Russian, Slovenian, Turkish
	Warranty Languages	English, Canadian French, LA Spanish, Brazilian Portuguese, Danish, German, Castilian Spanish, French, Italian, Dutch, Norwegian, Finnish, Swedish, Bahasa Indonesian, Korean, T. Chinese, S. Chinese
	Color	Carbonite/silver
	VESA External Mounting	Yes (Standard 4 hole pattern, 100 mm)
	Kensington Lock-Ready	Yes
Options	HP Silver Flat Panel Speaker Bar - Part number: EE418AA	Powered directly by the monitor or PC, the Speaker Bar seamlessly attaches to the monitor's lower bezel to bring full audio support to select HP flat panel monitors. Features include dual speakers with full sound range and an external jack for headphones. Sold separately. For more information, refer to the HP Flat Panel Speaker Bar QuickSpec.
Certification and Compliance		Australian ACA Approval, Canadian Requirements/CSA, CE Marking, China CCIB/CCEE Approval, CISPR Requirements, Eastern European Approvals, Energy Star Compliant, FCC Approval, German Ergonomic (TUV and GS Mark), ISO 9241-3,7,8 VDT Guidelines, ISO 13406-2 Pixel Defect Guidelines, Mexican NOM Approval, MIC Requirements (New Zealand), MPR-II Compliant, Nordic Approvals (Nemko, Fimko, Demko, Semko), PC2001 Compliant, PC99 Certified, S. Korean MIC Approval, Taiwan BSMI Approval, TCO 03 (emissions, ergonomics, environment), TUV-Ergo, UL Listed, VCCI Approvals, Microsoft Windows Certification (Microsoft Windows 98, Microsoft Windows 2000, and Microsoft Windows XP)

Technical Specifications - Monitors

Compatibility	Compatible with platforms using the VESA standard video modes. Recommended for use with HP products.
Service and Warranty	Three years parts, labor, and on-site service. 24-hour, 90-day, toll-free technical support. Replacement options may include second business day on-site service, or next business day direct replacement, at HP's sole discretion. With direct replacement, HP will ship a replacement display product directly to you. Using the prepaid shipping labels provided, return your failed display to HP in the same packaging as the replacement. Certain restrictions and exclusions apply. For details see your product warranty or contact HP Customer Support.

© Copyright 2007 Hewlett-Packard Development Company, L.P.

All rights reserved. HP and the HP logo are trademarks of the Hewlett Packard Company in the U.S. and/or other countries.

Microsoft, Windows, Windows Vista, and Windows XP are registered trademarks or trademarks of Microsoft Corporation in the U.S. and/or other countries. NVIDIA and Quadro are trademarks of NVIDIA Corporation. All other product names mentioned herein may be trademarks of their respective companies.

HP shall not be liable for technical or editorial errors or omissions contained herein. The information is provided as is without warranty of any kind and is subject to change without notice. The warranties for HP products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty.