

SoMo® 650Rx Handheld Computer

With Antimicrobial Protection

Specification Sheet

Size	5.00 x 2.94 x 0.98 inches (127 x 74.60 x 25 mm)		
Weight	7.20 oz (204 g) with extended battery and stylus		
Antimicrobial Rating (JIS Z2801:2000 Test)	2.49 on Methicillin-resistant Staphylococcus aureus (MRSA) 6.07 when cleaned with Sani-Cloth® Plus disposable cloth wipes		
Display	EasyView® 65K colors TFT LCD, 3.5" 16 bit per pixel, 240 (w) x 320 (l) resolution		
Touch Panel	Glass analog resistive touch		
Backlight	White LED backlight		
Extended Battery	3.7V 2600 mAh Lithium Ion rechargable		
Backup Battery	Super Capacitor to support Realtime Clock		
Expansion Slots	CompactFlash and SDIO Slots: Reinforced to prevent damage from drop events		
LED Indicators	Red/Green LED for alarm, battery charging Blue/Green LED for <i>Bluetooth</i> and Wireless LAN		
Buttons	4 front panel programmable soft buttons 2 side programmable action buttons Control hold switch 5 navigation buttons Device reset button Power on/off button		
Input Devices	Stylus (Note: touch sensitive display for stylus or fingertip)		
Connectors	Barrel connector power jack 26 pin docking connector for ActiveSync USB 1.1 host & USB 2.0 Client 2.5mm headset jack with support for both voice and stereo music		
Audio	Built-in Microphone and Speaker, voice recording capability with Notes application		
	SocketScan™ keyboard wedge Connect!Agent™ <i>Bluetooth®</i> software Modem Utilities		

ш
~
_
۹.
>
>
_
ш.
$\overline{}$
O
S

Pre-loaded Socket Software	SocketScan™ keyboard wedge	Connect!Agent™ <i>Bluetooth</i> ® software		Modem Utilities
	Serial I/O Card drivers	Enhanced Wi-Fi® Companion™ software*		Ethernet Utilities
	SoMo 650 Back Pack software	USB Ethernet Gigabit Adapter drivers		USB to Serial drivers
Pre-loaded 3rd Party Software	Programmable Home Screen Outlook Mobile PowerPoint Mobile .NET Compact Framework v2.0	IE Mobile Word Mobile Calculator ActiveSync Client	Excel Mobile Windows Medi MSN Messenge	a Player 10.2 Mobile r Client

PERFORMANCE

Processor	Intel PXA270 @ 624 MHz
Operating System Windows Mobile® 6 Classic - Worldwide English Other languages available with ROM upgrade DVD (sold separately)	
Memory 128MB SDRAM, 256MB NAND FLASH	
SoMo File Store	Non-volatile memory for device applications/configurations can survive hard reset of device Features Auto-Run support, ideal for provisioning deployments

ENVIRONMENT

Operating Temperature	0° to 50° C (32° to 120° F)	
Storage Temperature	-25° to 75° C (-13° to 167° F)	
Humidity	95% non-condensing	
Drop Specification	p Specification Multiple 1 meter drops to concrete covered with vinyl	
ESD Specification	+/- 8kV air discharge, +/- 8kV direct discharge	

PTIONAL ACCESSORIES

SO		
Cales Of	fices	

Sales Offices Corporate Headquarters: 39700 Eureka Drive Newark, CA 94560 USA

Web: socketmobile.com Phone: +1-510-933-3000

USA & Canada Toll Free: 800-552-3300

SKU

Fax: +1-510-933-3030

Online: socketmobile.com/contact

Wireless Local Area Network	IEEE® 802.11 b/g Data Rate: 1/2/5.5/6/9/11/12/18/24/36/48/54 Mbps Frequency Range: Country dependent (chan 1- 14); 2.412 to 2.484 GHz Output Power: 14.5 dBm (OFDM); 16 dBm (CCK) Antenna: Internal		
Bluetooth	v2.0 + EDR Class 2 Supported Profiles: - GAP: Generic Access Profile - SDP: Service Discovery Profile - A2DP - Advanced Audio Profile - AVCTP - Audio/Video Control Transport Protocol - AVRCP - Audio/Video Remote Control Profile - GAVDP - Generic Audio/Video Distribution Profile	- DUN - Dial-up Networking Profile - AVDTP - Audio/Video Distribution Transport Protocol - HP: Headset Profile - HID - Human Interface Device (Host role) - OPP - Object Push Profile (Client and Server) - SPP - Serial Port Profile	

Warranty	Handheld Computer: One year standard warranty Accessories (battery, cable, etc.): 90 day warranty SocketCare enhanced service program available separately		
Certification/ Compliance	FCC: Part 15, Class B Industry Canada ROHS and WEEE compliant EMI / RFI Bluetooth Certification (BQB test) Microsoft Windows Mobile 5.0 Logo Test Certification EU/International: EN301 489-1, -17 EN61000-4-2: 1995, ESD ± 8kV air/±4kV contact Cisco CCX 4.0 (requires Enhanced Wi-Fi Companion, opti	EN61000-4-3: 1997, radiated Immunity 3V/m EN61000-4-4: 1995, EFT ± 0.55kV EN61000-4-5: 1995, Surge ± 0.5kV EN61000-4-6: 1 CE: EN Electrical Safety EN60950, UL, CSA Wi-Fi Alliance Certification USB IF Test ional to install)	

SoMo 650Rx-E	SoMo 650Rx handheld computer Wall charger: AC/DC adapter, Input 100~240 V AC Full Size Stylus Quick Start Guide	Extended battery USB ActiveSync cable Companion CD with software and User's Guide
SoMo 650Rx-M	Same as above plus: - Desktop cradle: can charge both the SoMo and a spare battery, includes USB 1.1 Host and USB 2.0 Cl ports, and is powered from wall charger - Leather Carrying Case - Audio Headset - 2.5mm to 3.5mm barrel converter	

Socket Data Collection Peripherals	Secure Digital Scan Card Series 3 CompactFlash Scan Card Series 5 / 5 Rx Socket <i>Bluetooth</i> Cordless Hand Scanner Series 7 / 7 Rx	CF Mag Stripe Reader Card Series 4 CF RFID Reader Card Series 6 Socket <i>Bluetooth</i> Cordless Ring Scanner Series 9	
Socket Data Communication Peripherals	CF Serial I/O Card Rugged CF 10/100 Ethernet Card SoMo 650Rx Back Pack wireless broadband ExpressCard ac		
Charging Accessories	Cradle Kit Multi-bay charger (charges 4 devices & 4 batteries)	Car Charger ger (charges 4 devices & 4 batteries) Portable Power battery back	
Protective Accessories	FlexGuard protective silicone cover Belt carrying case	Screen protector kit	

SoMo 650Rx-E	North America	Single: HC0684-1085	10 pack: HC0685-1086
JOINIO OJONA-L	Europe, Middle East, Africa	Single: HC0690-1091	10 pack: HC0691-1092
SoMo 650Rx-M	North America	Single: HC0676-1066	10 pack: HC0677-1067
SOIVIO OSORX-IVI	Europe, Middle East, Africa	Single: HC0678-1068	10 pack: HC0679-1069

© 2008-2009 Socket Mobile, Inc. Socket, the Socket logo, SoMo, Enhanced Wi-Fi Companion, SocketScan, Connect!Agent, SD Scan Card, CF Mag Stripe Reader Card, CF Scan Card, CF RFID Reader Card, Socket Bluetooth Cordless Hand Scanner, Socket Bluetooth Cordless Ring Scanner, CF 56K Modem Card, SDIO 56K Modem Card, Serial I/O Card, and Business Mobility Now! are registered trademarks of trademarks of Socket Mobile, Inc. Microsoft is a registered trademark of the Microsoft group of companies. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Socket Mobile, Inc. is under license. Wi-Fi is a registered trademark of the Wi-Fi Alliance. EasyView is a trademark of Weintek Labs, Inc. All other brand and product names are trademarks of their respective holders. 6450-00188 E 7/2009