

Black and White Color Camera Module

Technical Manual



FCB-EX45MC/EX45MCC

Table of Contents

Features	3
Precautions	4
Locations of Controls	5
Basic Functions	6
Overview of Functions	6
Spectral Sensitivity Characteristics	28
Eclipse	28
Vibration Specifications	28
Initial Settings, Custom Preset and Backup	29
Mode Condition	31
Command List	34
VISCA/RS-232C Commands	34
FCB Camera Commands	
Specifications	53

Features

- The Ex-View HAD™ CCD features 380,000 (NTSC) or 440,000 (PAL) effective picture elements and high-sensitivity shooting. The minimum illumination required is 0.01 lx.
- 18× optical zoom.
- Supports external synchronization (V-lock).
- Adopts a newly developed DSP for improved picture quality when using the digital zoom.
- VISCA is a communications protocol, which enables the camera to be controlled remotely by commands from a host computer/controller.
- Six memory locations are provided to temporarily save and recall up to six sets of camera settings.
- Enhanced privacy zone masking (max. 24 blocks)
- Alarm function

With consideration given to environmental protection, this module is designed to operate with low power consumption and also incorporates lead-free and halogen-free circuit boards.

Precautions

Software

Use of the demonstration software developed by Sony Corporation or use of the software with customer developed application software may damage hardware, the application program or the camera. Sony Corporation is not liable for any damages under these conditions.

Operation

Start the camera control software on your computer after you turn on the camera and the image is displayed.

Operation and Storage Locations

Do not shoot images that are extremely bright (e.g., light sources, the sun, etc.) for long periods of time. Do not use or store the camera in the following extreme conditions:

- Extremely hot or cold places (operating temperature 0 °C to +40 °C (32 °F to 104 °F))
- Close to generators of powerful electromagnetic radiation such as radio or TV transmitters
- Where it is subject to fluorescent light reflections
- Where it is subject to unstable (flickering, etc.) lighting conditions
- Where it is subject to strong vibration

Care of the Unit


Remove dust or dirt on the surface of the lens with a blower (commercially available).

Other

Do not apply excessive voltage. (Use only the specified voltage.) Otherwise, you may get an electric shock or a fire may occur.

In case of abnormal operation, contact your authorized Sony dealer or the store where you purchased the product.

Locations of Controls



- 1 Lens
- 2 CN992 connector
- 3 TELE button
- 4 WIDE button

5 Tripod screw holes

When a tripod is used, please use 10 mm (13/32 in.) screws to attach it to the camera. Also, please be sure to attach the tripod securely.

Basic Functions

Overview of Functions

VISCA commands are the basis of camera control.

Timing Chart

As VISCA Command processing can only be carried out one time in a Vertical cycle, it takes the maximum 1V cycle time for an ACK/Completion to be returned. If the Command ACK/Completion communication time can be cut shorter than the 1V cycle time, then every 1V cycle can receive a Command.

General Commands Command ACK Completion TxD Within 16.7msec(20msec*PAL) Query Command Command RxD Command Completion TxD Command Completion TxD Completion

Commands

Power On/Off

Powers the camera on and off. When the power is off, the camera is able to accept only the lowest level of VISCA Commands; the display and other features are turned off.

• I/F clear

Clears the Command buffer of the FCB camera. Clearing the buffer can also be carried out from the control application software when the power is on.

Address set

VISCA is a protocol, which normally can support a daisy chain of up to seven attached devices. However, the FCB camera does not support camera connections in a daisy chain. Therefore, whenever a camera is connected for the first time, be sure to use the address set to confirm the address.

• ID Write

Sets the camera ID.

• Mute

Blanks the screen and sends out a synchronizing signal.

• Lens Initialization

Initializes the zoom and focus of the lens. Even when power is already on, it initializes the zoom and the focus.

• Comp Scan

A pixel blemish-masking feature is used to reevaluate overall CCD pixel blemishes and mask severely flawed pixels automatically upon receiving the COMP SCAN command. This feature helps to mask the flaws found in CCD imagers, even after the camera has been powered on for some time.

Zoom

The FCB camera employs an 18× optical zoom lens combined with a digital zoom function allowing you to zoom up to 216×.

Lens specifications: Optical $18 \times$, f = 4.1 to 73.8 mm (F1.4 to F3.0)

The horizontal angle of view is approximately 48 degrees (wide end) to 2.8 degrees (tele end). Digital Zoom enlarges the center of the subject by expanding each image in both the vertical and horizontal directions. When 216× zoom is used, the number of effective picture elements in each direction reduces to $\frac{1}{12}$ and the overall resolution deteriorates.

You can activate the zoom in the following two ways:

- By pressing the TELE or WIDE buttons on the camera itself.
- Using a VISCA Command

Using Standard Mode Using Variable Mode

There are eight levels of zoom speed.

Direct Mode

Setting the zoom position enables quick movement to the designated position.

Digital Zoom ON/OFF

In these standard and variable Speed Modes, it is necessary to send a "Stop Command" to stop the zoom operation.

• The Zoom Mode supports a Combined Mode and a Separate Mode.

Combined Mode

This is the previously existing zoom method. After the optical zoom has reached its maximum level, the camera switches to Digital Zoom Mode.

Separate Mode

In this mode, Optical Zoom and Digital Zoom can be operated separately. You can use digital zoom magnification at any time from within any level of optical magnification.

Focus

Focus has the following modes, all of which can be set using VISCA Commands.

Auto Focus Mode

The minimum focus distance is 290 mm at the optical wide end and 800 mm at the optical tele end (distance from the front end of the lens), and is independent of the digital zoom.

The AutoFocus (AF) function automatically adjusts the focus position to maximize the high frequency content of the picture in a center measurement area, taking into consideration the high luminance and strong contrast components.

- Normal AF Mode

This is the normal mode for AF operations.

- Interval AF Mode

The mode used for AF movements carried out at defined intervals. The time intervals for AF movements and for the timing of the stops can be set in one-second increments using the Set Time Command. The initial value for both is set to five seconds.

- Zoom Trigger Mode

When the zoom is changed with the TELE or the WIDE buttons, the pre-set value (initially set at 5 seconds) becomes that for AF Mode. Then, it returns to Manual Focus mode.

AF sensitivity can be set to either Normal or LOW.

- Normal

Reaches the highest focus speed quickly. Use this when shooting a subject that moves frequently. Usually, this is the most appropriate mode.

- LOW

Improves the stability of the focus. When the lighting level is low, the AF function does not take effect, even though the brightness varies, contributing to a stable image.

When used for 24 hours continuously, initialization of lens system once a day is recommended because this will make the life of lens longer.

The Initialize Lens Command takes a little less than 3 seconds to initialize the focus and zoom.

Manual Focus Mode

Manual Focus has both a Standard Speed Mode and a Variable Speed Mode. Standard Speed Mode focuses at a fixed rate of speed. Variable Speed Mode has eight speed levels that can be set using a VISCA Command.

In these standard and variable Speed Modes, it is necessary to send a "Stop Command" to stop the zoom operation.

• One Push Trigger Mode

When a Trigger Command is received, the lens moves to adjust the focus for the subject. The focus lens then holds the same position until the next Trigger Command is input.

• Infinity Mode

The lens is forcibly moved to a position suitable for an unlimited distance.

• Near Limit Mode

Can be set in a range from $1000 (\infty)$ to C000 (10 mm). The focus range is narrowed by excluding the unnecessary range.

Automatic Exposure Mode

The variety of AE functions, which allow video signal to output the optimum image for subjects from low light conditions to bright light conditions, are available.

• Full Auto

Auto Iris and Gain, Fixed Shutter Speed (NTSC: 1/60 s, PAL: 1/50 s)

ullet Shutter Priority $^{1)}$

Variable Shutter Speed, Auto Iris and Gain (1/60 to 1/10,000 s, 16 steps, std. shutter: 16 steps)

• Iris Priority

Variable Iris (F1.4 to Close, 18 steps), Auto Gain and Shutter speed.

• Manual

Variable Shutter, Iris and Gain.

• Bright

Variable Iris and Gain (Close to F1.4, 17 steps at 0 dB: F1.4, 15 steps from 0 to 28 dB)

AE – Shutter Priority

The shutter speed can be set freely by the user to 16 high speeds. In high speed mode, the shutter speed can be set up to \(^{1}\)/10,000 s. The iris and gain are set automatically, according to the brightness of the subject.

Data	NTSC	PAL
15	10000	10000
14	6000	6000
13	4000	3500
12	3000	2500
11	2000	1750
10	1500	1250
0F	1000	1000
0E	725	600
0D	500	425
0C	350	300
0B	250	215
0A	180	150
09	125	120
08	100	100
07	90	75
06	60	50

Note

When the shutter speed 1/1 s or 1/2 s is used, Auto Focus and White Balance may not function fully.

AE – Iris Priority

The iris can be set freely by the user to 18 steps between F1.4 and Close.

The gain and shutter speed are set automatically according to the brightness of the subject.

Data	Setting value	Data	Setting value
11	F1.4	08	F6.8
10	F1.6	07	F8.0
0F	F2.0	06	F9.6
0E	F2.4	05	F11
0D	F2.8	04	F14
0C	F3.4	03	F16
0B	F4.0	02	F19
0A	F4.8	01	F22
09	F5.6	00	CLOSE

AE - Manual

The shutter speed (16 steps), iris (18 steps) and gain (16 steps) can be set freely by the user.

¹⁾ Flicker can be eliminated by setting shutter to:


[→] ¹/100 s for NTSC models used in areas with a 50 Hz power supply frequency.

[→] ¹/120 s for PAL models used in countries with a 60 Hz power supply frequency.

AE - Bright

The bright control function adjusts both the gain and iris using an internal algorithm according to a brightness level freely set by the user. Exposure is controlled by gain when dark and by iris when bright. As both gain and iris are fixed, this mode is used when exposing at a fixed camera sensitivity. When switching from Full Auto or Shutter Priority Mode to Bright Mode, the current status will be retained for a short period of time.

Only when the AE mode is set to "Full Auto" or "Shutter Priority," the user can switch it to "Bright."




Data	Iris	Gain	Data	Iris	Gain
1F	F1.4	28 dB	0F	F2.0	0 dB
1E	F1.4	26 dB	0E	F2.4	0 dB
1D	F1.4	24 dB	0D	F2.8	0 dB
1C	F1.4	22 dB	0C	F3.4	0 dB
1B	F1.4	20 dB	0B	F4.0	0 dB
1A	F1.4	18 dB	0A	F4.8	0 dB
19	F1.4	16 dB	09	F5.6	0 dB
18	F1.4	14 dB	08	F6.8	0 dB
17	F1.4	12 dB	07	F8.0	0 dB
16	F1.4	10 dB	06	F9.6	0 dB
15	F1.4	8 dB	05	F11	0 dB
14	F1.4	6 dB	04	F14	0 dB
13	F1.4	4 dB	03	F16	0 dB
12	F1.4	2 dB	02	F19	0 dB
11	F1.4	0 dB	01	F22	0 dB
10	F1.6	0 dB	00	CLOSE	0 dB

When switching from the Shutter Priority mode to the Bright mode, the shutter speed set in the Shutter Priority mode is maintained.

Spot Exposure Mode

In Full Auto AE, the level for the entire screen is computed and the optimum Auto Iris and Gain levels are determined. In Spot AE, a particular section of the subject can be designated, and then that portion of the image can be weighted and a value computed so that Iris and Gain can be optimized to obtain an image. For example, in an image with a lot of movement and with varying levels of brightness, portions without much change can be designated as such a "spot," and changes to the screen can be minimized in that area. As shown in the diagram below, a range of 16 blocks vertically and 16 blocks horizontally can be designated.

In the case where the center is designated (shown in black), the level is computed along with a weighted value for the surrounding block (shaded), including the specified portions; and then the Gain and Iris are set. The value of the designated portions and the surrounding areas should be calculated as 90% and the rest should be set to 10%. The range of the Spot AE frame is fixed to five blocks vertically and four blocks horizontally.



Exposure Compensation

Exposure compensation is a function which offsets the internal reference brightness level used in the AE mode by steps of 1.5 dB.

Data	Step	Setting value
0E	7	10.5 dB
0D	6	9 dB
0C	5	7.5 dB
0B	4	6 dB
0A	3	4.5 dB
09	2	3 dB
08	1	1.5 dB
07	0	0 dB
06	-1	−1.5 dB
05	-2	-3 dB
04	-3	-4.5 dB
03	-4	-6 dB
02	-5	-7.5 dB
01	-6	–9 dB
00	-7	-10.5 dB

Aperture Control

Aperture control is a function which adjusts the enhancement of the edges of objects in the picture. There are 16 levels of adjustment, starting from "no enhancement." When shooting text, this control may help by making the text sharper.

Back Light Compensation

When the background of the subject is too bright, or when the subject is too dark due to shooting in the AE mode, back light compensation will make the subject appear clearer.

Camera ID

The ID can be set up to 65,536 (0000 to FFFF). As this will be memorized in the nonvolatile memory inside the camera, data will be saved regardless of whether it has been backed up.

Effect

Negative/Positive Reversal (Neg. Art) function is provided.

Others

Mirror Image

This function reverses the video output from the camera horizontally.

Memory (Position Preset)

Using the position preset function, 6 sets of camera shooting conditions can be stored and recalled. This function allows you to achieve the desired status instantly even without adjusting the following items each time:

- Zoom Position
- Digital Zoom On/Off
- Focus Auto/Manual
- Focus Position
- AE Mode
- Shutter control parameters
- Bright Control
- Iris control parameters
- Gain control parameters
- Exposure Compensation On/Off
- Exposure Level
- Backlight Compensation On/Off
- Aperture

Custom Preset

As with the position preset function, the camera shooting conditions can be stored and recalled. The settings are recalled when the power is turned on.

For setting items, see the "Initial Settings, Custom Preset and Backup" section on page 29.

User Memory Area

A user area of 16 bytes allows you to write data, such as an ID for each customer, data for each system, and so on, freely.

Note

Rewriting of memory is not unlimited. Be careful to avoid using the memory area for such as unnecessary tasks as rewriting the contents of the memory for every operation.

Privacy Zone Settings

For details, see page 12.

Alarm

For details, see page 16.

Title Display

The FCB camera can be given a title containing up to 20 characters such as "ENTRANCE" or "LOBBY". The position of the first character (horizontal, vertical) of the title, blinking state, and color can also be changed.

Vposition	00 to 0A
Hposition	00 to 17
Blink	00: Does not blink
DIIIK	01: Blinks

00	01	02	03	04	05	06	07
Α	В	С	D	Е	F	G	Н
08	09	0a	0b	0c	0d	0e	0f
I	J	K	L	M	N	O	P
10	11	12	13	14	15	16	17
Q	R	S	T	U	V	W	X
18	19	1a	1b	1c	1d	1e	1f
Y	Z	&		?	!	1	2
20	21	22	23	24	25	26	27
3	4	5	6	7	8	9	0
28	29	2a	2b	2c	2d	2e	2f
À	È	Ì	Ò	Ù	Á	É	Í
30	31	32	33	34	35	36	37
Ó	Ú	Â	Ê	Ô	Æ	Œ	Ã
38	39	3a	3b	3c	3d	3e	3f
Õ	Ñ	Ç	В	Ä	Ϊ	Ö	Ü
40	41	42	43	44	45	46	47
Å	\$	F	¥	DM	£	i	i
48	49	4a	4b	4c	4d	4e	4f
ø	"	:	6		,	/	-

Synchronization Methods

Internal and external synchronization are available; VISCA Commands allow you to switch between them.

• Internal Synchronization

An internal vibrator inside the camera generates a synchronizing signal as a basic oscillator. EIA=28.636363MHz CCIR=28.375MHz

• External Synchronization (V-Lock Synchronization)

When a TTL level V-Lock pulse is input, the camera synchronizes to the input signal (V-lock synchronization). The frequency of the input signal synchronizes to within ± 1 Hz of the external synchronization.

Also, V-Phase phase adjustment can be carried out to within ±90 degrees due to the V-Lock phase adjustment. In addition, 360 degree phase adjustment is possible because you can switch between 0 degree and 180 degree phases.

Because V-Lock synchronization is a simple synchronization method, color signals like a VBS "GenLock" cannot be synchronized.


Privacy Zone Function

Privacy Zone masking protects private objects and areas such as house windows, entrances, and exits which are within the camera's range of vision but not subject to surveillance.

Privacy zone masking can be masked on the monitor to protect privacy.

Features

- Mask can be set on up to 24 places according to Pan/ Tilt positions.
- Mask can be displayed on 8 places per screen simultaneously.
- Privacy Zones are displayed according to priority in alphabetical order.
- Individual on/off zone masking settings.
- Two colors from among 28 colors can be individually set for each of 24 privacy zones.
- Interlocking control with zooming.
- Interlocking control with Pan/Tilt.
- Non-interlocking control with Pan/Tilt.



Privacy Zone Setting Command List

Command Set	Command	Command Packet	Comments
CAM_PrivacyZone	SetMask	8x 01 04 76 mm nn 0r 0r 0s 0s FF	Setting Mask(Size) See "mm: mask setting list", "nn: setting", and "rr: w, ss: h" in "Parameters" on page 14.
	Display	8x 01 04 77 pp pp pp pp FF	Setting Mask Display On/Off See "pp pp pp pp: Mask bit" in "Parameters" on page 14. pp pp pp pp: Mask setting (0: OFF, 1: ON)
	SetMaskColor	8x 01 04 78 pp pp pp pp qq rr FF	Setting Color of Mask See "pp pp pp pp: Mask bit" and "qq, rr: Color code" in "Parameters" on page 14. qq: Color setting when setting the Mask bit to 0 rr: Color setting when setting the Mask bit to 1
	SetPanTiltAngle	8x 01 04 79 0p 0p 0p 0q 0q 0q FF	Setting Pan/Tilt Angle See "Setting pan/tilt angle" in "Parameters" on page 14. ppp: Pan angle, qqq: Tilt angle
	SetPTZMask	8x 01 04 7B mm 0p 0p 0p 0q 0q 0q 0r 0r 0r 0r FF	Setting the direct position of PTZ mm: See "mm: mask setting list" and "Setting pan/tilt angle" in "Parameters" on page 14. ppp: Pan, qqq: Tilt, rrrr: Zoom
	Non_InterlockMask	8x 01 04 6F mm 0p 0p 0q 0q 0r 0r 0s 0s FF	Setting non-interlocking the mask to pan/tilt See "mm: mask setting list" and "pp: x, qq: y, rr: w, ss: h" in "Parameters" on page 14.
	Grid On	8x 01 04 7C 02 FF	Setting Grid Display On/Off
	Grid Off	8x 01 04 7C 03 FF	
	CenterLineOn	8x 01 04 7C 04 FF	Setting the center line On

Privacy Zone Inquiry Command List

Inquiry Command	Command Packet	Inquiry Packet	Comments
CAM_Privacy DisplayInq	8x 09 04 77 FF	y0 50 pp pp pp pp FF	Inquiry about the status of Setting Mask Display On/Off See "pp pp pp pp: Mask bit" in "Parameters" on page 14. 1:On, 0:Off
CAM_PrivacyPan TiltInq	8x 09 04 79 FF	y0 50 0p 0p 0p 0q 0q 0q FF	Inquiry about the pan/tilt position currently set See "Setting pan/tilt angle" in "Parameters" on page 14. ppp: Pan, qqq: Tilt
CAM_Privacy PTZInq	8x 09 04 7B mm FF	y0 50 0p 0p 0p 0q 0q 0q 0r 0r 0r 0r FF	Inquiry about pan/tilt/zoom position at the mm Mask setting See "mm: Mask setting list" and "Setting pan/tilt angle" in "Parameters" on page 14. ppp: Pan Position, qqq: Tilt Position rrrr: Zoom Position
CAM_Privacy MonitorInq	8x 09 04 6F FF	y0 50 pp pp pp pF	Inquiry about the mask currently displayed See "pp pp pp pp: Mask bit" in "Parameters" on page 14.

Parameters

mm: Mask setting list

	•
Mask Name	mm (Hex)
Mask_A	00h
Mask_B	01h
Mask_C	02h
Mask_D	03h
Mask_E	04h
Mask_F	05h
Mask_G	06h
Mask_H	07h
Mask_I	08h
Mask_J	09h
Mask_K	0Ah
Mask_L	0Bh

Mask Name	mm (Hex)
Mask_M	0Ch
Mask_N	0Dh
Mask_O	0Eh
Mask_P	0Fh
Mask_Q	10h
Mask_R	11h
Mask_S	12h
Mask_T	13h
Mask_U	14h
Mask_V	15h
Mask_W	16h
Mask_X	17h

Note


The priority order of the mask display is in the sequence from A (highest) to X (lowest).

When you set the parameters of masks non-sequentially, it is recommended that you set the mask whose priority order is higher, first.

nn: Setting

nn	Setting
00	Resetting the zone size (the value of w, h)
	for the existing mask.
01	Setting newly the zone size (the value of
	w, h).

pp: x, qq: y, rr: w, ss: h




pp pp pp: Mask bit


	pp)							pp)							pp)							pp)						
bit	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0
Mask	-	-	X	W	V	U	Т	S	-	-	R	Q	Р	О	N	M	-	-	L	K	J	Ι	Н	G	-	-	F	Е	D	С	В	Α

qq, rr: Color code

-1-17					
Mask (Color)	Code (qq, rr)	Semi-transparency (qq, rr)			
Black	00h	10h			
Gray1	01h	11h			
Gray2	02h	12h			
Gray3	03h	13h			
Gray4	04h	14h			
Gray5	05h	15h			
Gray6	06h	16h			
White	07h	17h			
Red	08h	18h			
Green	09h	19h			
Blue	0Ah	1Ah			
Cyan	0Bh	1Bh			
Yellow	0Ch	1Ch			
Magenta	0Dh	1Dh			

Setting pan/tilt angle





Details of Setting Commands

Set Mask

Command: 8x 01 04 76 mm nn 0r 0r 0s 0s FF **Parameters:**

mm	Setting Mask
	See "mm: mask setting list" in "Parameters" on page 14.
nn	Selects new setting or resetting for the zone. See nn:
	Setting" in "Parameters" on page 14.
rr	Sets the half value "w" of the Mask Width.
ss	Sets the half value "h" of the Mask Height.
	See "rr: w, ss: h" in "Parameters" on page 14.

Comments: To set the mask, first display the object at the center of the screen. When "nn" is set to 1, the current Pan/Tilt/Zoom position is recorded in internal memory.

When "nn" is set to 0, the Pan/Tilt/Zoom position in memory is not changed.

Notes

- The tilt angle at which you can set the mask is between -70 to +70 degrees.
- It is recommended that you set the size to at least twice the size of the object (height and width).

Set Display

Command: 8x 01 04 77 pp pp pp pF FF

Parameter:

pp pp pp pp	Each 24 Privacy Zones corresponds to 1 bit.
	See "pp pp pp pp: Mask bit" in "Parameters" on
	page 14.

Comments: Each of 24 Privacy zones can be switched on and off individually by a single VISCA command. If you want to display a Privacy zone, you must set its bit to 1. If you do not want to display a Privacy zone, you must set its bit to 0.

Set Mask Color

Command: 8x 01 04 78 pp pp pp pp qq rr FF **Parameter:**

pp pp pp pp	Each 24 Privacy Zones correspond with the BIT.
	See "pp pp pp: Mask bit" in "Parameters" on
	page 14.
qq	Set the color code include the semi-transparency
	code.
rr	Set the color code include the semi-transparency
	code. See "qq, rr: Color code" in "Parameters" on
	page 14.

Comments: Two different color masks can be chosen.

The colors can be chosen from among 14 colors including the possibility for semi-transparency of each color. Therefore two colors from among the total of 28 colors can be individually set for each of 24 privacy zones.

If the bit of parameter (pp pp pp pp) is set to "0", mask color will be "qq" color (Color code). If the bit of parameter (pp pp pp pp) is set to "1", the mask color will be "rr" color (Color code).

Example: 8x 01 04 78 00 00 00 03 10 07 FF

The mask color of Mask_A and Mask_B is White (color code 07h), and the mask color of the other Mask (C to X) is semi-transparent Black (color code 10h).

Set Pan Tilt Angle

Command: 8x 01 04 79 0p 0p 0p 0q 0q 0q FF **Parameter:**

ppp	Pan Angle
qqq	Tilt Angle See "Setting pan/tilt angle" in "Parameters" on page 14.

Comments: Pan/Tilt angle settings are hexadecimal data.

The resolution of Pan/Tilt angle is 0.088 degrees.

Note

When you set the pan/tilt angle, locate the pan/tilt position at the center point of the FCB camera's position.

Non Interlock Mask

Command: 8x 01 04 6F mm 0p 0p 0q 0q 0r 0r 0s 0s

Parameters:

mm	Setting Mask
	See "mm: mask setting list" in "Parameters" on page 14.
pp	Sets the center position "x" of the Mask on screen.
qq	Sets the center position "y" of the Mask on screen.
rr	Sets the half value "w" of the Mask Width.
ss	Sets the half value "h" of the Mask Height.
	See "pp: x, qq: y, rr: w, ss: h" in "Parameters" on page 14.

Commands: Mask does not interlock with pan/tilt.

The limitations of parameters are as follows. (hexadecimal representation)

x: ±50h w: ±50h


y: ±3ch h: ±3ch

Note

When the Set Mask command and the Non Interlock Mask command are set to the same mask, the command set later becomes effective.

Grid

Use the grid displayed on the screen to set mask positions (see the figure below).



Alarm Function

This function instructs the camera to detect movement within the monitoring area and then send an alarm signal automatically.

A High level signal is output when camera detects movement inside the monitoring area. A Low level signal is output when object stops moving.

However, when the mode is set to "DAY/NIGHT", the High level signal is output for dark and the Low level signal is output for bright.

The Detect signal goes out through the serial command (VISCA) communication line.

Example

- 1. A door is motionless, so the Detect Level is Low.
- 2. At the moment when the door is opened by someone, the Detect Level goes to High.
- 3. The Detect Level is High while the shooting object is moving.
- 4. When the door is closed, Detect Level goes to Low again, or signals are output only once at the time of switching between High Level and Low Level.

ALARM Setting Command List

Command Set	Command	Command Packet	Comments
CAM _ Alarm	On	8x 01 04 6B 02 FF	Alarm start
	Off	8x 01 04 6B 03 FF	Alarm stop
	Set Mode	8x 01 04 6C pp FF	Mode Setting
			*Select one from 13 modes
	Set Day Night Level		ppp: Day distinction AE level qqq: Night distinction AE level.

90 07 04 6B 01 FF	High signal output
	$(Low \rightarrow High edge)$
90 07 04 6B 00 FF	Low signal output
	$(High \longrightarrow Low edge)$


VISCA Mode Code (pp)	Details of Mode
00	Set the internal focus position. When focus movement is detected, the detect signal is High. When focus goes back to the previous position, the detect signal is Low.
01	Set a fixed period of time. When focus does not move during the time, the focus position is memorized as a rest position and the detect signal is Low. When focus moves, the detect signal is High. Afterwards when focus does not move for the fixed period of time, the focus position is memorized and the detect signal becomes Low.
02	Set the internal AE Level. When AE movement is detected, the detect signal is High. When AE Level goes back to the previous level, the detect signal is Low.
03	Set a fixed period of time. When AE Level does not change during this time, the AE value is memorized as a rest value and the detect signal is Low. When AE value changes, the detect signal is High. Afterwards when AE value does not change for the fixed period of time, the AE value is memorized and the detect signal becomes Low.
04	mode "00" and mode "02"
05	mode "00" and mode "03"
06	mode "01" and mode "02"
07	mode "01" and mode "03"
08	mode "00" or mode "02"
09	mode "00" or mode "03"
0A	mode "01" or mode "02"
0B	mode "01" or mode "03"
0C	Day-Night Mode

ALARM Inquiry Command List


Inquiry Command	Command Packet	Inquiry Packet	Comments
CAM _ Alarm Inq	8x 09 04 6B FF	y0 50 02 FF	On
		y0 50 03 FF	Off
CAM _ Alarm Mode Inq	8x 09 04 6C FF	y0 50 pp FF	pp: Alarm Mode
CAM_AlarmDayNightLevel Inq	8x 09 04 6D FF	y0 50 0p 0p 0p 0q 0q 0q 0r 0r 0r FF	ppp: Day setting AE Level qqq; Night setting AE Level rrr: Now AE Level
CAM_AlarmDetLevelInq	8x 09 04 6E FF	y0 50 01 FF y0 50 00 FF	Detect Level is High. Detect Level is Low.

Flowchart of 12 Modes Function


Mode "00"




Mode "01"




Mode "02"




Mode "03"




Details of Mode "01"/"03"




Mode "04"




Mode "05"




Mode "06"




Mode "07"




Mode "08"




Mode "09"




Mode "0A"




Mode "0B"




Day-Night Mode (Mode "0C")





Spectral Sensitivity Characteristics



Vibration Specifications


Test Method (Random vibration)

- Fix the camera at the four fixation points of the base using M2 screws.
- Perform the random vibration test under the following conditions in the X, Y and Z directions for 20 minutes in each direction.
- The camera vibration specification is to have no malfunction after this test.

Power spectrum density	5 to 50 Hz 4.14 m ² /s ³ {0.043 G ² /Hz} 50 to 100 Hz -36 dB/oct
Effective overall value	14.3 m/s ² {1.46 G}
Test time	20 minutes

Eclipse

When designing the housing, refer to the dimensional allowance as shown in the figure below.



Initial Settings, Custom Preset and Backup

Initial settings for the various functions are indicated in the "Initial settings" column.

The "Custom preset" column indicates whether the custom preset function can be used to store the settings. The function enables the stored settings to be recalled automatically when the camera is turned on. The "Standby backup" column indicates whether the data is preserved even when the camera is powered OFF. A circle "O" in this column signifies that the data is preserved. A cross "x" signifies that the data IS NOT preserved.

Mode/Position	Initial settings	Custom preset	Standby backup
Zoom Position	Wide end	0	0
D-Zoom On/Off	On	0	0
D-Zoom Separate/Combine	Combine	0	0
D-Zoom Position	00h	0	0
Focus Position	_	0	0
Focus Auto/Manual	Auto	0	0
Near Limit Setting	8000h (29cm)	0	0
AF Sensitivity	Normal	0	0
AF Mode	Normal	0	0
AF Run Time	5 sec	0	0
AF Interval	5 sec	0	0
AE Mode	Full Auto	0	0
Shutter Position	1/60sec (NTSC), 1/50sec (PAL)	0	0
Iris Position	_	0	0
Gain Position	_	0	0
Bright Position	_	0	0
Exposure Compensation On/Off	Off	0	0
Exposure Compensation Amount	±0	0	0
Backlight On/Off	Off	0	0
Spot AE On/Off	Off	0	0
Spot AE Position Setting	X=8, Y=8	0	0
Aperture Level	5	0	0
LR Reverse On/Off	Off	0	0
Picture Effect	Off	0	0
Camera Memory	Same as the initial value setting	0	0
Display On/Off	Off	0	0
Mute On/Off	Off	×	×

Mode/Position	Initial settings	Custom preset	Standby backup
Title Display On/Off	Off	0	0
Title Setting	_	0	0
Mask Setting	_	0	0
Mask Display On/Off	Off	0	0
Mask Color Setting	_	0	0
Alarm On/Off	Off	0	0
Alarm Mode	_	0	0
Alarm Detect Level	_	0	0
Privacy Zone On/Off	Off	0	0
Privacy Zone Setting	_	0	0
Key Lock On/Off	Off	0	0
Camera ID	0000h	0	0
External Lock Mode	Internal	0	0
V-Phase	Vsync edge position	0	0
V-Phase Phase Inversion	No inversion	0	0

Note

The number of times data can be written to EEPROM (by executing Custom Preset) is limited.

Mode Condition

Condition

Mode	Power Off	Initializing	Power On Freeze On	Freeze On	MemBecall
Address Set	0		0	0	0
IF_Clear	0	0	0	0	0
Command Cancel	0	0	0	0	0
Power On/Off	0	0	0	0	0

Lens

Mode	Power Off	Initializing	Power On	Freeze On	MemRecall	Zoom Direct	Focus Direct	ZmFo Direct	Focus Auto
Zoom Tele/Wide/Stop	×	×	0	×	×	×	0	×	0
Zoom Direct	×	×	0	×	×	0	0	×	0
Zoom Focus Direct	×	×	0	×	×	×	×	0	×
D-Zoom On/Off	×	×	0	×	×	×	0	×	0
D-Zoom Separate/Combine	×	×	0	×	×	×	0	×	0
D-Zoom Tele/Wide/Stop	×	×	0	×	×	0	0	0	0
D-Zoom ×1/Max	×	×	0	×	×	0	0	0	0
D-Zoom Direct	×	×	0	×	×	0	0	0	0
Focus Far/Near/Stop	×	×	0	×	×	0	×	×	×
Focus Direct	×	×	0	×	×	0	0	×	×
Focus Auto/Manual	×	×	0	×	×	0	×	×	0
One Push AF	×	×	0	×	×	0	×	×	×
Focus Infinity	×	×	0	×	×	0	×	×	0
Focus Near Limit	×	×	0	×	×	0	×	×	0
AF Sensitivity Normal/Low	×	×	0	×	×	0	0	0	0
AF Mode Norm/Interval/Zoom	×	×	0	×	×	0	0	0	0
AF Activation Time/Interval Setting	×	×	0	×	×	0	0	0	0
Camera Memory Set/Reset	×	×	0	0	×	×	×	×	0
Camera Memory Recall	×	×	0	0	O a)	×	×	×	0
Lens Initialization	×	×	0	0	×	×	×	×	0
Comp Scan	×	×	0	0	×	×	×	×	0
11:									

S C C C C C C C C C C C C C C C C C C C	Dower Off	Duitieliu	Dower On	Eroozo On	MemBecall	AF EIII AIIto	AE Manual	ShutterDriority	Irie Driority	Bricht
	500	HIII GII S	5000	10020011	Mellinedali	מוחר ווה ו שר	אבווממו	Ollutter From y	113 1 1101113	il Bill
AE Full Auto	×	×	0	×	×	0	0	0	0	0
AE Manual	×	×	0	×	×	0	0	0	0	0
Shutter Priority	×	×	0	×	×	0	0	0	0	0
Iris Priority	×	×	0	×	×	0	0	0	0	0
Bright	×	×	0	×	×	0	×	0	×	0
Shutter Setting	×	×	0	×	×	×	0	0	×	×
Iris Setting	×	×	0	×	×	×	0	×	0	×
Gain Setting	×	×	0	×	×	×	0	×	×	×
Bright Setting	×	×	0	×	×	×	×	×	×	0
Exposure Compensation On/Off	×	×	0	×	×	0	0	0	0	0
Exposure Compensation Setting	×	×	0	×	×	0	0	0	0	0
Backlight On/Off	×	×	0	×	×	0	×	×	×	×
SpotAE On/Off	×	×	0	×	×	0	0	0	0	0
SpotAE Setting	×	×	0	×	×	0	0	0	0	0

Others

Mode	Power Off	Initializing	Power On	Freeze On	MemRecal
Aperture Setting	×	×	0	×	×
LR_Reverse On/Off	×	×	0	×	×
Picture Effect Setting	×	×	0	×	×
Display On/Off	×	×	0	0	0
Mute On/Off	×	×	0	0	0
Title Setting	×	×	0	0	0
Privacy Zone On/Off/Clear	×	×	0	0	0
Privacy Zone Setting	×	×	0	0	0
Key Lock On/Off	×	×	0	0	0
ID Write	×	×	0	0	0

External Synchronization

Mode	Power Off	Initializing	Power Off Initializing Power On Freeze On MemRecall	Freeze On	MemRecall
External Lock Mode	×	×	0	0	0
V-Phase Up/Down/Stop/Reset	×	×	0	0	0
V-Phase Direct	×	×	0	0	0
V-Phase Phase Turnover Setting	×	×	0	0	0

Command List

VISCA¹/RS-232C Commands

This Manual outlines an RS-232C control protocol and command list for certain Sony cameras from which control software can be developed.

THIS CONTROL PROTOCOL AND COMMAND LIST IS PROVIDED BY SONY ON AN "AS-IS BASIS" WITHOUT WARRANTY OF ANY KIND. SONY DOES NOT WARRANT ANY PARTICULAR RESULT FROM THE USE OF THIS CONTROL PROTOCOL AND COMMAND LIST AND DISCLAIMS AND EXCLUDES ALL WARRANTIES, EXPRESS OR IMPLIED, WITH RESPECT TO THAT CONTROL PROTOCOL AND COMMAND LIST, INCLUDING, BUT NOT LIMITED TO, ANY OR ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. IN FACT, SONY SPECIFICALLY ACKNOWLEDGES THAT SOFTWARE DEVELOPED BASED ON THIS CONTROL PROTOCOL AND COMMAND LIST MAY CAUSE MALFUNCTION OR DAMAGE TO HARDWARE AND SOFTWARE USED WITH IT (INCLUDING SONY HARDWARE AND SOFTWARE) AND SPECIFICALLY DISCLAIMS ANY LIABILITY FOR ANY SUCH MALFUNCTION OR DAMAGE. THIS CONTROL PROTOCOL AND COMMAND LIST SHOULD BE USED WITH CAUTION.

Overview of VISCA

In VISCA the device outputting commands, for example, a computer, is called the controller. The device receiving the commands, an FCB camera is called the peripheral device. In VISCA, up to seven peripheral devices like the FCB camera can be connected to one controller using communication conforming to the RS-232C standard. The parameters of RS-232C are as follows:

Communication speed: 9.6 kbps/19.2 kbps/ 38.4 kbps

Data bits: 8Start bit: 1Stop bit: 1/2Non parity

Flow control using XON/XOFF, RTS/CTS, etc., is not supported.


VISCA Communication Specifications

VISCA Packet Structure

The basic unit of VISCA communication is called a packet. The first byte of the packet is called the header and comprises the sender's and receiver's addresses. For example, the header of the packet sent to the FCB camera assigned address 1 from the controller (address 0) is hexadecimal 81H. The packet sent to the camera

assigned address 2 is 82H. In the command list, as the header is 8X, input the address of the camera at X. The header of the reply packet from the camera assigned address 1 is 90H. The packet from the camera assigned address 2 is A0H.

Some of the commands for setting cameras can be sent to all devices at one time (broadcast). In the case of broadcast, the header should be hexadecimal 88H. When the terminator is FFH, it signifies the end of the packet.



Command and Inquiry

Command

Sends operational commands to the FCB camera.

Inquiry

Used for inquiring about the current state of the FCB camera.

Command Packet Note

Inquiry 8X QQ RR ... FF QQ¹¹

QQ¹⁾ = Command/Inquiry, RR²⁾ = category code

1) QQ = 01 (Command), 09 (Inquiry)

2) RR = 00 (Interface), 04 (camera 1), 06 (Pan/Tilter), 07 (camera 2)

X = 1 to 7: FCB camera address

Responses for Commands and Inquiries

ACK message

Returned by the FCB camera when it receives a command. No ACK message is returned for inquiries.

Completion message

Returned by the FCB camera when execution of commands or inquiries is completed. In the case of inquiry commands, it will contain reply data for the inquiry after the 3rd byte of the packet. If the ACK message is omitted, the socket number will contain 0.

	Reply Packet	Note
Ack	X0 4Y FF	Y = socket number
Completion (commands)	X0 5Y FF	Y = socket number
Completion (Inquiries)	X0 5Y FF	Y = socket number
X = 9 to F: FCB camera as	ddress + 8	

Error message

When a command or inquiry command could not be executed or failed, an error message is returned instead of the completion message.

Error Packet	Description
X0 6Y 01 FF	Message length error (>14 bytes)
X0 6Y 02 FF	Syntax Error
X0 6Y 03 FF	Command buffer full
X0 6Y 04 FF	Command cancelled
X0 6Y 05 FF	No socket (to be cancelled)
X0 6Y 41 FF	Command not executable
X = 9 to F: FCB ca	amera address + 8, Y = socket number

Socket Number

When command messages are sent to the FCB camera, it is normal to send the next command message after waiting for the completion message or error message to return. However to deal with advanced uses, the camera has two buffers (memories) for commands, so that up to two commands including the commands currently being executed can be received. When the camera receives commands, it notifies the sender which command buffer was used using the socket number of the ACK message. As the completion message or error message also has a socket number, it indicates which command has ended. Even when two command buffers are being used at any one time, a camera management command and some inquiry messages can be executed.

The ACK message is not returned for these commands and inquiries, and only the completion message of socket number 0 is returned.

Command Execution Cancel

To cancel a command which has already been sent, send the Cancel command as the next command. To cancel one of any two commands which have been sent, use the cancel message.

	Cancel Packet	Note
Cancel	8X 2Y FF	Y = socket number
X = 1 to 7: FC	B camera address, \	Y = socket number

An error message will be returned for this command, but this is not a mistake. This message indicates that the command has been canceled.

VISCA Device Setting Command

Before starting control of the FCB camera, be sure to send the Address command and the IF_Clear command using the broadcast function.

For VISCA Network Administration

Address

Sets an address of a peripheral device. Use when initializing the network and when receiving the network change message indicated below.

Network Change

Sent from the peripheral device to the controller when a device is removed from or added to the network. The address must be re-set when this message is received.

Packet Note

Address 88 30 01 FF Always broadcasted.

Network Change X0 38 FF X = 9 to F: FCB camera address + 8

VISCA Interface Command

• IF_Clear

Clears the command buffers in the FCB camera and cancels the command currently being executed.

Command Packet Reply Packet Note

IF_Clear 8X 01 00 01FF X0 50 FF
IF_Clear (broadcast) 88 01 00 01 FF 88 01 00 01 FF
X = 1 to 7: FCB camera address (For inquiry packet)
X = 9 to F: FCB camera address +8 (For reply packet)

VISCA Interface and Inquiry

● CAM_VersionInq

Returns information on the VISCA interface.

X = 1 to 7: FCB camera address (For inquiry packet) X = 9 to F: FCB camera address +8 (For reply packet)

VISCA Command/ACK Protocol

Command	Command Message	Reply Message	Comments
General Command	81 01 04 38 02 FF (Example)	90 41 FF (ACK)+90 51 FF (Completion) 90 42 FF 90 52 FF	Returns ACK when a command has been accepted, and Completion when a command has been executed.
	81 01 04 38 FF (Example)	90 60 02 FF (Syntax Error)	Accepted a command which is not supported or a command lacking parameters.
	81 01 04 38 02 FF (Example)	90 60 03 FF (Command Buffer Full)	There are two commands currently being executed, and the command could not be accepted.
	81 01 04 08 02 FF (Example)	90 61 41 FF (Command Not Executable) 90 6 <u>2</u> 41FF	Could not execute the command in the current mode.
Inquiry Command	81 09 04 38 FF (Example)	90 50 <u>02</u> FF (Completion)	ACK is not returned for the inquiry command.
	81 09 05 38 FF (Example)	90 60 02 FF (Syntax Error)	Accepted an incompatible command.
Address Set	88 30 <u>01</u> FF	88 30 <u>02</u> FF	Returned the device address to +1.
IF_Clear (Broadcast)	88 01 00 01 FF	88 01 00 01 FF	Returned the same command.
IF_Clear (For x)	8x 01 00 01 FF	z0 50 FF (Completion)	ACK is not returned for this command.
Command Cancel	8x 2y FF	z0 6y 04 FF (Command Canceled)	Returned when the command of the socket specified is canceled. Completion for the command canceled is not returned.
		z0 6y 05 FF (No Socket)	Returned when the command of the specified socket has already been completed or when the socket number specified is wrong.

VISCA Camera-Issued Messages

ACK/Completion Messages

	Command Messages	Comments
ACK	z0 4y FF	Returned when the command is accepted.
	(y:Socket No.)	
Completion	z0 5y FF	Returned when the command has been executed.
	(y:Socket No.)	

z = Device address + 8

Error Messages

	Command Messages	Comments
Syntax Error	z0 60 02 FF	Returned when the command format is different or when a command with illegal command parameters is accepted.
Command Buffer Full	z0 60 03 FF	Indicates that two sockets are already being used (executing two commands) and the command could not be accepted when received.
Command Canceled	z0 6y 04 FF (y:Socket No.)	Returned when a command which is being executed in a socket specified by the cancel command is canceled. The completion message for the command is not returned.
No Socket	z0 6y 05 FF (y:Socket No.)	Returned when no command is executed in a socket specified by the cancel command, or when an invalid socket number is specified.
Command Not Executable	z0 6y 41 FF (y:Socket No.)	Returned when a command cannot be executed due to current conditions. For example, when commands controlling the focus manually are received during auto focus.

Network Change Message

	Command Message	Comments
Network Change	z0 38 FF	Issued when power is being routed.

FCB Camera Commands

Command List (1/4)

Command Set	Command	Command Packet	Comments
AddressSet	Broadcast	88 30 01 FF	
IF_Clear	Broadcast	88 01 00 01 FF	
CommandCancel		8x 2p FF	p: Socket No.(=1or2)
CAM_Power	On	8x 01 04 00 02 FF	Power ON/OFF
	Off	8x 01 04 00 03 FF	
CAM_Zoom	Stop	8x 01 04 07 00 FF	
	Tele(Standard)	8x 01 04 07 02 FF	
	Wide(Standard)	8x 01 04 07 03 FF	
	Tele(Variable)	8x 01 04 07 2p FF	p=0 (Low) to 7 (High)
	Wide(Variable)	8x 01 04 07 3p FF	
	Direct	8x 01 04 47 0p 0q 0r 0s FF	pqrs: Zoom Position
CAM_DZoom	On	8x 01 04 06 02 FF	Digital zoom ON/OFF
	Off	8x 01 04 06 03 FF	
	Combine Mode	8x 01 04 36 00 FF	Optical/Digital Zoom Combined
	Separate Mode	8x 01 04 36 01 FF	Optical/Digital Zoom Separate
	Stop	8x 01 04 06 00 FF	
	Tele(Variable)	8x 01 04 06 2p FF	p=0 (Low) to 7 (High)
	Wide(Variable)	8x 01 04 06 3p FF	
	x1/Max	8x 01 04 06 10 FF	x1/MAX Magnification Switchover
	Direct	8x 01 04 46 00 00 0p 0q FF	pq: D-Zoom Position
CAM_Focus	Stop	8x 01 04 08 00 FF	
	Far(Standard)	8x 01 04 08 02 FF	
	Near(Standard)	8x 01 04 08 03 FF	
	Far(Variable)	8x 01 04 08 2p FF	p=0 (Low) to 7 (High)
	Near(Variable)	8x 01 04 08 3p FF	
	Direct	8x 01 04 48 0p 0q 0r 0s FF	pqrs: Focus Position
	Auto Focus	8x 01 04 38 02 FF	AF ON/OFF
	Manual Focus	8x 01 04 38 03 FF	
	Auto/Manual	8x 01 04 38 10 FF	
	One Push Trigger	8x 01 04 18 01 FF	One Push AF Trigger
	Infinity	8x 01 04 18 02 FF	Forced infinity
	Near Limit	8x 01 04 28 0p 0q 0r 0s FF	pqrs: Focus Near Limit Position
AF Sensitivity	Normal	8x 01 04 58 02 FF	AF Sensitivity High/Low
	Low	8x 01 04 58 03 FF	
CAM_AFMode	Normal AF	8x 01 04 57 00 FF	AF Movement Mode
	Interval AF	8x 01 04 57 01 FF	
	Zoom Trigger AF	8x 01 04 57 02 FF	
	Active/Interval Time	8x 01 04 27 0p 0q 0r 0s FF	pq: Movement Time, rs: Interval
CAM_ZoomFocus	Direct	8x 01 04 47 0p 0q 0r 0s	pqrs: Zoom Position
		Ot Ou Ov Ow FF	tuvw: Focus Position
CAM_Initialize	Lens	8x 01 04 19 01 FF	Lens Initialization Start
	Comp Scan	8x 01 04 19 02 FF	Correction of CCD pixel blemishes

Command List (2/4)

Command Set	Command	Command Packet	Comments
CAM_AE	Full Auto	8x 01 04 39 00 FF	Automatic Exposure mode
	Manual	8x 01 04 39 03 FF	Manual Control mode
	Shutter Priority	8x 01 04 39 0A FF	Shutter Priority Automatic Exposure mode
	Iris Priority	8x 01 04 39 0B FF	Iris Priority Automatic Exposure mode
	Bright	8x 01 04 39 0D FF	Bright Mode (Manual control)
CAM_Shutter	Reset	8x 01 04 0A 00 FF	Shutter Setting
	Up	8x 01 04 0A 02 FF	
	Down	8x 01 04 0A 03 FF	
	Direct	8x 01 04 4A 00 00 0p 0q FF	pq: Shutter Position
CAM_Iris	Reset	8x 01 04 0B 00 FF	Iris Setting
	Up	8x 01 04 0B 02 FF	
	Down	8x 01 04 0B 03 FF	
	Direct	8x 01 04 4B 00 00 0p 0q FF	pq: Iris Position
CAM_Gain	Reset	8x 01 04 0C 00 FF	Gain Setting
	Up	8x 01 04 0C 02 FF	
	Down	8x 01 04 0C 03 FF	
	Direct	8x 01 04 4C 00 00 0p 0q FF	pq: Gain Position
CAM_Bright	Reset	8x 01 04 0D 00 FF	Bright Setting
	Up	8x 01 04 0D 02 FF	
	Down	8x 01 04 0D 03 FF	
	Direct	8x 01 04 4D 00 00 0p 0q FF	pq: Bright Position
CAM_ExpComp	On	8x 01 04 3E 02 FF	Exposure Compensation ON/OFF
	Off	8x 01 04 3E 03 FF	
	Reset	8x 01 04 0E 00 FF	Exposure Compensation Amount Setting
-	Up	8x 01 04 0E 02 FF	
	Down	8x 01 04 0E 03 FF	
	Direct	8x 01 04 4E 00 00 0p 0q FF	pq: ExpComp Position
CAM_Backlight	On	8x 01 04 33 02 FF	Back Light Compensation ON/OFF
	Off	8x 01 04 33 03 FF	
CAM_SpotAE	On	8x 01 04 59 02 FF	Spot Automatic Exposure Setting
	Off	8x 01 04 59 03 FF	
	Position	8x 01 04 29 0p 0q 0r 0s FF	pq: X (0 to F), rs: Y (0 to F)

Command List (3/4)

Command Set	Command	Command Packet	Comments
CAM_Aperture	Reset	8x 01 04 02 00 FF	Aperture Control
	Up	8x 01 04 02 02 FF	
	Down	8x 01 04 02 03 FF	
	Direct	8x 01 04 42 00 00 0p 0q FF	pq: Aperture Gain
CAM_LR_Reverse	On	8x 01 04 61 02 FF	Mirror Image ON/OFF
	Off	8x 01 04 61 03 FF	
CAM_PictureEffect	Off	8x 01 04 63 00 FF	Picture Effect Setting
	Neg.Art	8x 01 04 63 02 FF	
CAM_Memory	Reset	8x 01 04 3F 00 0p FF	p: Memory Number (=0 to 5)
	Set	8x 01 04 3F 01 0p FF	
	Recall	8x 01 04 3F 02 0p FF	
CAM_CUSTOM	Reset	8x 01 04 3F 00 7F FF	Starts in this mode at Power ON.
	Set	8x 01 04 3F 01 7F FF	
	Recall	8x 01 04 3F 02 7F FF	
CAM_MemSave	Write	8x 01 04 23 0X 0p 0p	X: 00 to 07 (Address) Total 16 Byte
		0q 0q FF	ppqq: 0x0000 to 0xFFFF (Data)
CAM_Display	On	8x 01 04 15 02 FF	Display ON/OFF
		(8x 01 06 06 02 FF)	
	Off	8x 01 04 15 03 FF	
		(8x 01 06 06 03 FF)	
	On/Off	8x 01 04 15 10 FF	
		(8x 01 06 06 10 FF)	
CAM_Title	Title Set1	8x 01 04 73 00 mm nn pp	mm: Vposition, nn: Hposition
		qq 00 00 00 00 00 00 FF	pp: Color, qq: Blink
	Title Set2	8x 01 04 73 01 mm nn pp	mnpqrstuvw: Setting of Display Characters
		qq rr ss tt uu vv ww FF	(1st to 10st Character)
	Title Set3	8x 01 04 73 02 mm nn pp	mnpqrstuvw: Setting of Display Characters
		qq rr ss tt uu vv ww FF	(11th to 20th Character)
	Title Clear	8x 01 04 74 00 FF	Title Setting Clear
	On	8x 01 04 74 02 FF	Title Display ON/OFF
	Off	8x 01 04 74 03 FF	
CAM_Mute	On	8x 01 04 75 02 FF	Mute ON/OFF
	Off	8x 01 04 75 03 FF	
	On/Off	8x 01 04 75 10 FF	

Command List (4/4)

Command	Command Packet	Comments
SetMask	8x 01 04 76 mm nn	mm: Mask Settings
	Or Or Os Os FF	nn 00: Modify, 01: New
		rr: W, ss:H
Display	8x 01 04 77 pp pp pp FF	Mask Display ON/OFF
		pp pp pp pp: Mask Settings (0: OFF, 1: ON)
SetMask Color	8x 01 04 78 pp pp pp pp	pp pp pp pp: Mask Color Settings
	qq rr FF	qq: "0" Color Settings
G .D . Till A . 1	0.01.04.70.0.0	rr: "1" Color Settings
SetPan HitAngle		Pan/Tilt Angle Settings
	0q 0q 0q FF	ppp: Pan qqq: Tilt
SetPTZMask	8x 01 04 7B mm 0p 0p 0p	Pan/Tilt/Zoom Settings for Mask
	0q 0q 0q 0r 0r 0r 0r FF	mm: Mask Setings
		ppp: Pan, qqq: Tilt, rrrr: Zoom
Non_InterlockMask	8x 01 04 6F mm	mm: Non-Interlock Mask Settings
	0p 0p 0q 0q 0r 0r 0s 0s FF	pp: X, qq: Y, rr: W, ss: H
GridOn	8x 01 04 7C 02 FF	Grid Display On
GridOff	8x 01 04 7C 03 FF	Grid/Center Line Display Off
CenterLineOn	8x 01 04 7C 04 FF	Center Line Display On
Off	8x 01 04 17 00 FF	Camera Control Enable/Disable
On	8x 01 04 17 02 FF	
	8x 01 04 22 0p 0q 0r 0s FF	pqrs: Camera ID (=0000 to FFFF)
INT	8x 01 04 55 00 FF	Internal mode
Line Lock	8x 01 04 55 01 FF	Line Lock mode
Stop	8x 01 04 05 00 FF	
Up	8x 01 04 05 02 FF	
Down	8x 01 04 05 03 FF	
Up (Step)	8x 01 04 05 2p FF	p=step (1-7)
Down (Step)	8x 01 04 05 3p FF	
Reset	8x 01 04 05 40 FF	Restore Factory Settings
Direct	8x 01 04 45 00 00 0p 0q FF	pq: V-Phase (00-FF)
0 degree	8x 01 04 25 00 FF	No Phase Turnover
180 degree	8x 01 04 25 01 FF	Phase Turnover
On	8x 01 04 6B 02 FF	Alarm ON/OFF
Off	8x 01 04 6B 03 FF	
SetMode	8x 01 04 6C pp FF	PP: Mode Settings
		00 Focus Move Detection (The rest position is fixed.)
		01 Focus Move Detection (The rest position is reset.)
		02 AE Move Detection (The rest value is fixed.)
	8x 01 04 6D 0p 0p 0p 0q 0q 0q FF	01 AE Move Detection (The rest value is reset.)
	L XX OT O4 BO OB OB OB OB OB FF	ppp: Day Detect Level Setting
SetDayNightLevel	ox or or ob op op oq oq oq ri	
SetDayNightLevel Alarm (Reply)	y0 07 04 6B 01 FF	qqq: Night Detect Level Setting Detect Level "Low" → "High"
	SetMask Display SetMask Color SetPan TiltAngle SetPTZMask Non_InterlockMask GridOn GridOff CenterLineOn Off On INT Line Lock Stop Up Down Up (Step) Down (Step) Reset Direct O degree 180 degree On Off	SetMask 8x 01 04 76 mm nn or 0r 0r 0s 0s FF Display 8x 01 04 77 pp pp pp pp FF SetMask Color 8x 01 04 78 pp pp pp pp pp qq rr FF SetPan TiltAngle 8x 01 04 79 0p 0p 0p 0p 0q 0q 0q 0r FF SetPan TiltAngle 8x 01 04 7B mm 0p 0p 0p 0q 0q 0q 0r 0r 0r 0r 0r FF Non_InterlockMask 8x 01 04 6F mm 0p 0p 0q 0q 0r 0r 0r 0s 0s FF GridOn 8x 01 04 7C 02 FF GridOff 8x 01 04 7C 03 FF CenterLineOn 8x 01 04 17 00 FF On 8x 01 04 17 02 FF INT 8x 01 04 22 0p 0q 0r 0s FF Line Lock 8x 01 04 55 00 FF Line Lock 8x 01 04 05 02 FF Down 8x 01 04 05 03 FF Up 8x 01 04 05 03 FF Up (Step) 8x 01 04 05 07 FF Down (Step) 8x 01 04 05 07 FF Reset 8x 01 04 05 07 FF Direct 8x 01 04 25 00 FF Odegree 8x 01 04 25 01 FF On 8x 01 04 25 01 FF Off 8x 01 04 25 01 FF Off 8x 01 04 25 01 FF

Inquiry Command List (1/2)

Inquiry Command	Command Packet	Inquiry Packet	Comments
CAM_PowerInq	8x 09 04 00 FF	y0 50 02 FF	On
		y0 50 03 FF	Off
CAM_ZoomPosInq	8x 09 04 47 FF	y0 50 0p 0q 0r 0s FF	pqrs: Zoom Position
CAM_DZoomModeInq	8x 09 04 06 FF	y0 50 02 FF	D-Zoom On
		y0 50 03 FF	D-Zoom Off
CAM_DZoomC/SModeInq	8x 09 04 36 FF	y0 50 00 FF	Combine Mode
		y0 50 01 FF	Separate Mode
CAM_DZoomPosInq	8x 09 04 46 FF	y0 50 00 00 0p 0q FF	pq: D-Zoom Position
CAM_FocusModeInq	8x 09 04 38 FF	y0 50 02 FF	Auto Focus
		y0 50 03 FF	Manual Focus
CAM_FocusPosInq	8x 09 04 48 FF	y0 50 0p 0q 0r 0s FF	pqrs: Focus Position
CAM_FocusNearLimitInq	8x 09 04 28 FF	y0 50 0p 0q 0r 0s FF	pqrs: Focus Near Limit Position
CAM_AFSensitivityInq	8x 09 04 58 FF	y0 50 02 FF	AF Sensitivity Normal
		y0 50 03 FF	AF Sensitivity Low
CAM_AFModeInq	8x 09 04 57 FF	y0 50 00 FF	Normal AF
		y0 50 01 FF	Interval AF
		y0 50 02 FF	Zoom Trigger AF
CAM_AFTimeSettingInq	8x 09 04 27 FF	y0 50 0p 0q 0r 0s FF	pq: Movement Time, rs: Interval
CAM_AEModeInq	8x 09 04 39 FF	y0 50 00 FF	Full Auto
		y0 50 03 FF	Manual
		y0 50 0A FF	Shutter Priority
		y0 50 0B FF	Iris Priority
		y0 50 0D FF	Bright
CAM_ShutterPosInq	8x 09 04 4A FF	y0 50 00 00 0p 0q FF	pq: Shutter Position
CAM_IrisPosInq	8x 09 04 4B FF	y0 50 00 00 0p 0q FF	pq: Iris Position
CAM_GainPosInq	8x 09 04 4C FF	y0 50 00 00 0p 0q FF	pq: Gain Position
CAM_BrightPosInq	8x 09 04 4D FF	y0 50 00 00 0p 0q FF	pq: Bright Position
CAM_ExpCompModeInq	8x 09 04 3E FF	y0 50 02 FF	On
		y0 50 03 FF	Off
CAM_ExpCompPosInq	8x 09 04 4E FF	y0 50 00 00 0p 0q FF	pq: ExpComp Position
CAM_BacklightModeInq	8x 09 04 33 FF	y0 50 02 FF	On
		y0 50 03 FF	Off
CAM_SpotAEModeInq	8x 09 04 59 FF	y0 50 02 FF	On
		y0 50 03 FF	Off
CAM_SpotAEPosInq	8x 09 04 29 FF	y0 50 0p 0q 0r 0s FF	pq: X position, rs: Y position
CAM_ApertureInq	8x 09 04 42 FF	y0 50 00 00 0p 0q FF	pq: Aperture Gain
			· · · · · · · · · · · · · · · · · · ·

Inquiry Command List (2/2)

Inquiry Command	Command Packet	Inquiry Packet	Comments
CAM_LR_ReverseModeInq	8x 09 04 61 FF	y0 50 02 FF	On
		y0 50 03 FF	Off
CAM_PictureEffectModeInq	8x 09 04 63 FF	y0 50 00 FF	Off
		y0 50 02 FF	Neg.Art
CAM_MemoryInq	8x 09 04 3F FF	y0 50 pp FF	pp: Last Recall Memory No.
CAM_MemSaveInq	8x 09 04 23 0X FF	y0 50 0p 0p 0q 0q FF	X: 00 to 07 (Address)
			ppqq: 0x0000 to 0xFFFF (Data)
CAM_DisplayModeInq	8x 09 04 15 FF	y0 50 02 FF	On
	(8x 09 06 06 FF)	y0 50 03 FF	Off
CAM_TitleDisplayModeInq	8x 09 04 74 FF	y0 50 02 FF	On
		y0 50 03 FF	Off
CAM_MuteModeInq	8x 09 04 75 FF	y0 50 02 FF	On
		y0 50 03 FF	Off
CAM_PrivacyDisplayInq	8x 09 04 77 FF	y0 50 pp pp pp FF	pp pp pp pp: Mask Display (0: OFF, 1: ON)
CAM_PrivacyPanTiltInq	8x 09 04 79 FF	y0 50 0p 0p 0p 0q 0q 0q FF	ppp: Pan qqq: Tilt
CAM_PrivacyPTZInq	8x 09 04 7B mm FF	y0 50 0p 0p 0p 0q 0q 0q 0r 0r 0r 0r FF	mm: Mask Settings ppp: Pan qqq: Tilt rrrr: Zoom
CAM_PrivacyMonitorInq	8x 09 04 6F FF	y0 50 pp pp pp FF	pp pp pp: Mask is displayed now
CAM_KeyLockInq	8x 09 04 17 FF	y0 50 00 FF	Off
		y0 50 02 FF	On
CAM_IDInq	8x 09 04 22 FF	y0 50 0p 0q 0r 0s FF	pqrs: Camera ID
CAM_ExternalLockModeInq	8x 09 04 55 FF	y0 50 00 FF	Internal Mode
		y0 50 01 FF	Line Lock Mode
CAM_VPhaseSetInq	8x 09 04 25 FF	y0 50 00 FF	0 degree
		y0 50 01 FF	180 degree
CAM_VPhasePosInq	8x 09 04 45 FF	y0 50 00 00 0p 0q FF	pq: V-Phase Position
CAM_VersionInq	8x 09 00 02 FF	y0 50 00 20	mnpq: Model Code (04xx)
(See page 37 for details.)		mn pq rs tu vw FF	rstu: ROM version
			vw: Socket Number (=02)
CAM_AlarmInq	8x 09 04 6B FF	y0 50 02 FF	On
		y0 50 03 FF	Off
CAM_AlarmModeInq	8x 09 04 6C FF	y0 50 pp FF	pp: Alarm Mode
CAM_AlarmDayNightLevelInq	8x 09 04 6D FF	y0 50 0p 0p 0p 0p 0q 0q 0q 0r 0r 0r FF	ppp: Day Detect Level qqq: Night Detect Level rrr: Current AE Level
CAM_AlarmDetectLevelInq	8x 09 04 6E FF	y0 50 01 FF	Detect Level "High"
		y0 50 00 FF	Detect Level "Low"

Block Inquiry Command List

Lens Control System Inquiry Commands...... Command Packet 8x 09 7E 7E 00 FF

Byte	Bit	Comments
	7	
	6	D 2 2 A11
	5	Destination Address
	4	
0	3	
	2	0 411
	1	Source Address
	0	
	7	0 Completion Message (50h)
	6	1
	5	0
1	4	1
1	3	0
	2	0
	1	0
	0	0
	7	0
	6	0
	5	0
2	4	0
2	3	
	2	Zoom Position (IIII)
	1	Zoom Position (HH)
	0	
	7	0
	6	0
	5	0
2	4	0
3	3	
	2	7 P '4' (III.)
	1	Zoom Position (HL)
	0	
	7	0
	6	0
	5	0
4	4	0
4	3	
	2	Zoom Position (LII)
	1	Zoom Position (LH)
	0	
	7	0
	6	0
	5	0
5	4	0
J	3	
	2	Zoom Position (LL)
	1	Zoom Position (LL)
	0	
	0	

Byte	Bit	Comments
	7	0
	6	0
	5	0
6	4	0
	3	
	2	Focus Near Limit (H)
	1	rocus rear Ellilit (11)
	0	
	7	0
	6	0
	5	0
_	4	0
7	3	
	2	
	1	Focus Near Limit (L)
	0	
	7	0
	6	0
	5	0
	4	0
8	3	
	2	
	1	Focus Position (HH)
	0	
	7	0
	6	0
	5	0
	4	0
9		U
	3	
	2	Focus Position (HL)
	1	
	0	
	7	0
	6	0
	5	0
10	4	0
	3	
	2	Focus Position (LH)
	1	
	0	
	7	0
	6	0
	5	0
11	4	0
11	3	
	2	E D 22 (7.1)
	1	Focus Position (LL)

Byte	Bit	Comments		
	7	0		
	6	0		
	5	0		
	4	0		
12	3	0		
	2	0		
	1	0		
	0	0		
	7	0		
	6	0		
	5	DZoomMode 0: Combine		
		1: Separate		
	4	0: Normal 1: Interval		
13	3	2: Zoom Trigger		
	2	AF Sensitivity 0: Slow		
		1: Normal		
	1	Digital Zoom 1:On 0:Off		
	0	Focus Mode 0:Manual 1:Auto		
	7	0		
	6	0		
	5	0		
	4	0		
14	3	Low Contrast Detection 1: Yes		
		0: No		
	2	Camera Memory Recall 1:		
		Executing 0: Stopped		
	1	Focus Command 1: Executing		
		0: Stopped		
	0	Zoom Command 1: Executing		
		0: Stopped		
	7	1 Terminator (FFh)		
	6	1		
	5	1		
15	4	1		
	3	1		
	2	1		
	1	1		
	0	1		

Camera Control System Inquiry Commands Command Packet 8x 09 7E 7E 01 FF

Byte	Bit	Comments	Byte	Bit	Comments
	7			7	0
	6			6	0
	5	Destination Address		5	0
	4				0
0	3		6	3	0
	2			2	
	1	Source Address		1	WB Mode
	0			0	
	7	0 Completion Message (50h)		7	0
		The state of the s		6	0
	6	1		5	0
	5	0		4	0
	4	1	7	3	
1	3	0		2	
	2	0		1	Aperture Gain
	1	0		0	
	0	0		7	0
	7	0		6	0
	6	0		5	0
	5	0	8	4	
	4	0		3	
2	3			2	Exposure Mode
	2			1	
	1	R Gain (H)		0	
	0			7	0
	7	0		6	0
	6	Stabilizer (1: On, 0: Off)	9	5	0
	5	0		4	0
	4	0		3	Spot AE 1: On 0: Off
3	3			2	Back Light 1:On 0:Off
	2			1	Exposure Comp. 1:On 0:Off
	1	R Gain (L)		0	Slow Shutter 1:Auto 0:Manual
	0			7	0
	7	0		6	0
	6	0		5	0
	5	0	10	4	
	4	0	10	3	
4	3			2	Shutter Position
	2	D.G. 1. 470		1	
	1	B Gain (H)		0	
	0			7	0
	7	0		6	0
	6	0		5	0
	5	0	4.4	4	
_	4	0	11	3	
5	3			2	Iris Position
	2			1	
	1	B Gain (L)		0	

12	7 6 5 4 3 2 1 0	0 0 0 0 Gain Position
12	5 4 3 2 1 0	0
12	4 3 2 1 0	0
12	3 2 1 0	
12	2 1 0	Gain Position
	1 0	Gain Position
	0	Gain Fosition
	7	1
		0
	6	0
	5	0
10	4	
13	3	
	2	Bright Position
	1	
	0	
	7	0
	6	0
	5	0
1.4	4	0
14	3	
	2	
	1	Exposure Comp. Position
	0	
	7	1 Terminator (FFh)
	6	1
	5	1
1.5	4	1
15	3	1
	2	1
	1	1
	0	1
	13	13

Other Inquiry Commands Command Packet 8x 09 7E 7E 02 FF

Byte	Bit	Comments		
	7			
	6			
	5	Destination Address		
	4			
0	3			
	2			
	1	Source Address		
	0			
	7	0 Completion Message (50h)		
	6	1		
	5	0		
	4	1		
1	3	0		
	2	0		
	1	0		
	0	0		
	7	0		
	6	0		
	5	0		
2	4	0		
	3	0		
	2	Auto ICR 1: On 0: Off		
	1	Key Lock 1: On 0: Off		
	0	Power 1:On 0:Off		
	7	0		
	6	0		
	5	0		
3	4	ICR 1: On 0: Off		
	3	Freeze 1:On 0:Off		
	2	LR Reverse 1:On 0:Off		
	1	0		
	0	0		
	7	0		
	6	0		
	5	Privacy Zone 1: On 0: Off		
4	4	Mute 1: On 0: Off		
'	3	Title Display 1: On 0: Off		
	2	Display 1: On 0: Off		
	1	0		
	0	0		
	7	0		
	6	0		
	5	0		
5	4	0		
)	3			
	2	Diotumo Effe - 4 M - 1 -		
	1	Picture Effect Mode		
	0			
		1		

Byte	Bit	Comments	
	7	0	
	6	0	
	5	0	
	4	0	
6	3	0	
	2	0	
	1	0	
	0	0	
	7	0	
	6	0	
	5	0	
	4	0	
7	3	0	
	2	0	
	1	0	
	0	0	
	7	0	
	6	0	
	5	0	
	4	0	
8	3		
	2		
	1	Camera ID (HH)	
	0		
	7	0	
	6	0	
	5	0	
	4	0	
9	3		
	2		
	1	Camera ID (HL)	
	0		
	7	0	
	6	0	
	5	0	
	4	0	
10	3		
	2		
	1	Camera ID (LH)	
	0		
	7	0	
	6	0	
	5	0	
	4	0	
11	3	U	
	2		
	1	Camera ID (LL)	
	0		

Byte	Bit	Comments			
	7	0			
	6	0			
	5	External Lock 1: Provided 0:			
		Not provided			
12	4	Memory 1: Provided 0: Not			
12		provided			
	3	Clock 1: Provided 0: Not			
		provided			
	2	ICR 1: Provided 0: Not			
		provided			
	1	Stabilizer 1: Provided 0: Not			
	0	provided			
	0	System 1:PAL 0:NTSC			
	7	0			
	6	0			
	5	V-Phase 1: 180 degree 0: 0			
	4	degree			
13	4	External Lock Mode 1: Line Lock 0: Internal			
	3	Lock of internal			
	2				
	1	V-Phase (H)			
	0				
	7	0			
		0			
	5	0			
	4	0			
14	3	0			
	2				
	1	V-Phase (L)			
	0				
	7	1 Terminator (FFh)			
		,			
	6	1			
	5	1			
15	4	1			
	3	1			
	2	1			
	1	1			
	0	1			

Enlargement Function Query Command Command Packet 8x 09 7E 7E 03 FF

Byte	Bit	Comments
	7	
	6	B 2 2 A11
	5	Destination Address
	4	
0	3	
	2	C A 11
	1	Source Address
	0	
	7	0 Completion Message (50h)
	6	1
	5	0
1	4	1
1	3	0
	2	0
	1	0
	0	0
	7	0
	6	0
	5	0
2	4	0
	3	
	2	Digital Zoom Position (H)
	1	Digital Zoolii Positioli (H)
	0	
	7	0
	6	0
	5	0
3	4	0
	3	
	2	Digital Zoom Position (L)
	1	Digital Zooni i osition (L)
	0	
	7	0
	6	0
	5	0
4	4	0
	3	
	2	AF Activation Time (H)
	1	211 1 201 (11)
	0	
	7	0
	6	0
	5	0
5	4	0
	3	
	2	AF Activation Time (L)
	1	THE TRUTTURE (L)
		t and the second

Byte	Bit	Comments
	7	0
	6	0
	5	0
6	4	0
J	3	
	2	AF Interval Time (H)
	1	Ar micival time (H)
	0	
	7	0
	6	0
	5	0
7	4	0
7	3	
	2	API (177) (7)
	1	AF Interval Time (L)
	0	
	7	0
	6	0
	5	0
0	4	0
8	3	
	2	
	1	SpotAE Position (X)
	0	
	7	0
	6	0
	5	0
	4	0
9	3	
	2	
	1	SpotAE Position (Y)
	0	
	7	0
	6	0
	5	0
	4	0
10	3	0
	2	0
	1	Alarm (1: On, 0: Off)
	0	Picture flip (1: On, 0: Off)
	J 0	1 icture inp (1. Oii, 0. Oii)

Byte	Bit	Comments	
	7	0	
	6	0	
	5	0	
	4	0	
11	3	0	
	2	Advanced Privacy (1:	
		Provided, 0: Not provided)	
	1	Alarm (1: Provided, 0: Not	
		provided)	
	0	Picture flip (1: Provided, 0: Not provided)	
	7	0	
	6	0	
	5	0	
10	4	0	
12	3	0	
	2	0	
	1	0	
	0	0	
	7	0	
	6	0	
	5	0	
	4	0	
13	3	0	
	2	0	
	1	0	
	0	0	
	7	0	
	6	0	
	5	0	
	4	0	
14	3	0	
	2	0	
	1	0	
	0	0	
	7	1 Terminator (FFh)	
	6	1	
	5	1	
1.7	4	1	
15	3	1	
	2	1	
	1	1	
	0	1	

VISCA Command Setting Values

Exposure Control (1/2)

		NTSC	PAL
Shutter Speed	15	10000	10000
	14	6000	6000
	13	4000	3500
	12	3000	2500
	11	2000	1750
	10	1500	1250
	0F	1000	1000
	0E	725	600
	0D	500	425
	0C	350	300
	0B	250	215
	0A	180	150
	09	125	120
	08	100	100
	07	90	75
	06	60	50
Iris	11	F1.4	•
	10	F1.6	
	0F	F2.0	
	0E	F2.4	
	0D	F2.8	
	0C	F3.4	
	0B	F4.0	
	0A	F4.8	
	09	F5.6	
	08	F6.8	
	07	F8.0	
	06	F9.6	
	05	F11	
	04	F14	
	03	F16	
	02	F19	
	01	F22	
	00	CLOSE	

Gain	0F	28 dB
	0E	26 dB
	0D	24 dB
	0C	22 dB
	0B	20 dB
	0A	18 dB
	09	16 dB
	08	14 dB
	07	12 dB
	06	10 dB
	05	8 dB
	04	6 dB
	03	4 dB
	02	2 dB
	01	0
	00	−3 dB

Exposure Control (2/2)

		IRIS	GAIN
Bright	1F	F1.4	28 dB
	1E	F1.4	26 dB
	1D	F1.4	24 dB
	1C	F1.4	22 dB
	1B	F1.4	20 dB
	1A	F1.4	18 dB
	19	F1.4	16 dB
	18	F1.4	14 dB
	17	F1.4	12 dB
	16	F1.4	10 dB
	15	F1.4	8 dB
	14	F1.4	6 dB
	13	F1.4	4 dB
	12	F1.4	2 dB
	11	F1.4	0
	10	F1.6	0
	0F	F2.0	0
	0E	F2.4	0
	0D	F2.8	0
	0C	F3.4	0
	0B	F4.0	0
-	0A	F4.8	0
	09	F5.6	0
	08	F6.8	0
	07	F8.0	0
	06	F9.6	0
	05	F11	0
	04	F14	0
-	03	F16	0
	02	F19	0
	01	F22	0
	00	CLOSE	0
Exposure Comp.	0E	7	10.5 dB
	0D	6	9 dB
	0C	5	7.5 dB
	0B	4	6 dB
	0A	3	4.5 dB
	09	2	3 dB
	08	1	1.5 dB
	07	0	0 dB
	06	-1	-1.5 dB
	05	-2	-3 dB
-	04	-3	-4.5 dB
-	03	-4	-6 dB
-	02	-5	-7.5 dB
-	01	-6	-9 dB
	00	-7	-10.5 dB
		,	10.5 dD

Zoom Ratio and Zoom Position (for reference)

Zoom Ratio	Optical Zoom		
×18 Lens	Position Data		
×1	0000		
×2	1606		
×3	2151		
×4	2860		
×5	2CB5		
×6	3060		
×7	32D3		
×8	3545		
×9	3727		
×10	38A9		
×11	3A42		
×12	3B4B		
×13	3C85		
×14	3D75		
×15	3E4E		
×16	3EF7		
×17	3FA0		
×18	4000		

Digital Zoom Combine mode

Digital Zoom Ratio	Digital Zoom Position Data
×1	4000
×2	6000
×3	6A80
×4	7000
×5	7340
×6	7540
×7	76C0
×8	7800
×9	7900
×10	7980
×11	7A40
×12	7AC0

Digital Zoom Separete mode

Digital Zoom Ratio	Digital Zoom Position Data
×1	00
×2	80
×4	C0
×8	E0
×12	EB

Lens Control

	0000	to	4000 to 7AC0			
Zoom Position Wide end Opt		cal Tele end Digital Tele end				
	Focus Position 1000 to C000 Far end Near en		to C000			
Focus Position			Near end			
	1000: Over Inf					
	2000: 8.0 m					
	3000: 3.5 m					
	4000: 2.0 m		As the distance on the left			
	5000: 1.4 m		will differ due to			
Focus Near	6000: 1 m		temperature characteristics,			
Limit	7000: 80 cm		etc., use as approximate			
	8000: 29 cm		values.			
	9000: 10 cm		* The lower 1 byte is fixed			
	A000: 4.7 cm		at 00.			
	B000: 2.3 cm					
	C000: 1.0 cm					

Others

R,B gain	00~FF
Aperture	00~0F

Title Setting

Vposition	00 to 0A			
Hposition	00 to 17			
	00: Does not blink			
Blink	01: Blinks			
	00	White		
	01	Yellow		
	02	Violet		
Color	03	Red		
	04	Cyan		
	05	Green		
	06	Blue		

00	01	02	03	04	05	06	07
A	В	C	D	Е	F	G	Н
08	09	0a	0b	0c	0d	0e	0f
I	J	K	L	M	N	О	P
10	11	12	13	14	15	16	17
Q	R	S	T	U	V	W	X
18	19	1a	1b	1c	1d	1e	1f
Y	Z	&		?	!	1	2
20	21	22	23	24	25	26	27
3	4	5	6	7	8	9	0
28	29	2a	2b	2c	2d	2e	2f
À	È	Ì	Ò	Ù	Á	É	Í
30	31	32	33	34	35	36	37
Ó	Ú	Â	Ê	Ô	Æ	Œ	Ã
38	39	3a	3b	3c	3d	3e	3f
Õ	Ñ	Ç	В	Ä	Ϊ	Ö	Ü
40	41	42	43	44	45	46	47
Å	\$	₽	¥	DM	£	i	i
48	49	4a	4b	4c	4d	4e	4f
ø	"	:	•		,	/	-

Specifications

Image sensor 1/4 type IT CCD (Ex-View HAD)
Picture elements FCB-EX45MC: Approx. 380K

pixels (768 (H) × 494 (V)) FCB-EX45MCC: Approx. 440K pixels (752 (H) × 582 (V))

Horizontal resolution

EIA: 520 TV lines (WIDE end) CCIR: 520 TV lines (WIDE end)

Lens 18× zoom

F= 4.1 mm (WIDE) to 73.8 mm (TELE), F1.4 to F3.0

Zoom movement speed
Optical WIDE/Optical TELE 2.1 s
Optical WIDE/Digital TELE 3.7 s
Digital WIDE/Digital TELE 1.7 s

 ∞ to Near 0.5 s

Digital zoom $12 \times (216 \times \text{ with optical zoom})$

Angle of view (H)

48 degree (WIDE end) to 2.8 degree (TELE end)

Min. working distance

290 mm (WIDE end), 800 mm

(TELE end)

Sync system Internal/External (V-Lock)

Min. illumination

0.01 lx (F1.4, $^{1}/_{60}$ s (EIA) or $^{1}/_{50}$ s

(CCIR))

Recommended illumination

100 to 100,000 lx

S/N ratio 50 dB or more

Back light compensation

ON/OFF

Electronic shutter speed

FCB-EX45MC: 1/60 to 1/10,000 s

(16 steps)

FCB-EX45MCC: 1/50 to 1/10,000 s

(16 steps)

Gain Auto/Manual (-3 to 28 dB, 2 dB

steps)

Aperture control 16 steps

Preset 6-POSITIONS

Serial interface VISCA protocol (TTL/CMOS)

9.6 Kbps, 19.2 Kbps, 38.4 Kbps,

Stop bit, 1/2 bit

Video Output VBS: 1.0 Vp-p (Sync negative)

Storage temperature/Humidity

-20 to 60 °C (-4 to 140 °F)/20 to 95 %

Operating temperature/Humidity

0 to 50 °C (32 to 122 °F)/20 to 80 %

Power requirements/Power consumption

6 to 12 V DC/1.5 W (2.5 W)

Weight 230 g (8.1 oz.)


Dimensions $50.0 \times 57.5 \times 88.5 \text{ mm}$

 $(2 \times 2^{3}/8 \times 3^{1}/2 \text{ in.}) \text{ (w/h/d)}$


Design and specifications are subject to change without notice.

Dimensions


Front




Right side



Top




Left side



Within a depth of 3 mm (1/8 in.) or less form the side

Unit: mm (inches)


Pin assignment



CN992

KYOCERA ELCO 00 6200 097 032 800

Pin No.	Name	Level
1	RxD	CMOS 5V (low: max 0.8V,
		high: min 2.0V) Read Data
2	TxD	CMOS 5V (low: max 0.1V,
		high: min 4.4V) Send Data
3	GND (for RxD&TxD)	
4	DC IN	9.0V±3V
5	GND (for DC IN)	
6	VBS OUT	1.0V±0.2V
7	GND (for VBS OUT)	
8	V LOCK PULSE	External VD-Lock Pulse
		(EX.FV: Negative, 3Vp-p
		50% duty)
9	GND (VL PULSE)	



RxD, TxD: Positive TTL level