

## Outdoor Speed Dome Internet Camera



The PLANET ICA-651, outdoor speed dome internet camera, offers pan / tilt / zoom to control over TCP/IP networks. The ICA-651 features a 220X zooming (22x optical zoom, 10x digital zoom), auto focus, auto iris, fast, accurate and continuous 360 panning operations. Plus the 32 presets, 4 camera tour configurations, and combining the motion detection, these unparalleled surveillance functions of the ICA-651 are able to satisfy the demanding surveillance and remote monitoring applications.

The ICA-651 can send video and audio via the internet to a web browser anywhere in the world. The ICA-651 can be setup into most of the wicked outdoor environments and keep working properly with the IP-66 protecting cover.

The ICA-651 also offers complete secure features, such as IP address filtering and camera movement control. The ICA-651 is perfect for every surveillance environment with these benefits whenever working at traffic centers, shopping malls, railway stations, warehouses, airports, and production facilities.

Multi-profile stands for video stream simultaneously. The ICA-651 can generate MPEG-4 and M-JPEG streaming to different users in the meantime. Moreover, the resolution can differ from one user to another. This state-of-art design is considerable to fit in various network environments. Up to 10 users can have access to the ICA-651 simultaneously at any point in time.

### KEY FEATURES


- Supports 360 degree continuous PAN, Tilt (0°~90°) and 220X zooming (22X optical, 10X digital) adjustment
- Clear and high resolution quality pictures for day and night
- 3GPP for 3G mobile remote applications
- Multi-profile encoder supports MPEG-4 and M-JPEG video compression simultaneously and 30fps for all resolution
- Plug-N-Watch is able to simplify system integration in existing network environment
- Because of supporting TCP/IP networking, SMTP e-mail and HTTP public network standards, ICA651 can be applied and utilized to a mixed IP network environment
- Easy configuration: Network administrators can configure and manage ICA651 via Windows-based utility or web interface
- DDNS, PPPoE and FTP uploading supports more alternatives in surveillance network
- Motion Detection: the motion detection feature can monitor any suspicious movement in specific area

**SPECIFICATION**

<b>Product</b>	<b>Outdoor Speed Dome Internet Camera</b>
<b>Model</b>	<b>ICA-651</b>
<b>Camera Specification</b>	
<b>Horizontal Resolution</b>	480 TV Lines
<b>Sensor</b>	1/4" Color SONY CCD image sensor
<b>NTSC</b>	Frequency: 15,734 Hz (H), 60 Hz (V), Pixels: 811 (H) x 508 (V)
<b>PAL</b>	Frequency: 15,625 Hz (H), 60Hz (V), Pixels: 795 (H) x 596 (V)
<b>Illumination</b>	0.001 Low Lux (DSS)
<b>Signal to Noise</b>	More than 50 dB
<b>Image (Video Setting)</b>	
<b>Video Encoder</b>	MPEG-4 and M-JPEG simultaneously
<b>Video Resolution</b>	640 x 480, 320 x 240, 160 x 120, 30fps for all resolution
<b>Audio</b>	
<b>Audio Codec</b>	G.726 / AMR
<b>Audio Triggered</b>	Send snapshot to Email / FTP, Audio out alert, DO output
<b>Network and Configuration</b>	
<b>Network Interface</b>	Ethernet 10Base-T/100Base-TX
<b>Networking Protocol</b>	TCP/IP, HTTP, SMTP, FTP, NTP, DNS, DDNS, DHCP, UPnP, RTSP, PPPoE, 3GPP
<b>Browser</b>	Microsoft ® Internet Explorer 6.0 or later
<b>Hardware</b>	
<b>Pan Degree</b>	360 Degree continuous panning
<b>Tilt Degree</b>	90 Degree with instant flip
<b>Manual Pan Degree</b>	1.0 to 240 Degree/second
<b>Manual Tilt Degree</b>	1.0 to 120 Degree/second
<b>Preset Pan Degree</b>	360 Degree/second
<b>Preset Point</b>	32 present points
<b>Camera Tour</b>	4 tours
<b>Audio in / Audio out</b>	1 x Line in / 1 x Line out
<b>Protection Class</b>	IP-66 outdoor classification Built-in Fan and Heater
<b>Dimension (W x D x H)</b>	220 x 390 x 336 (mm)
<b>Weight</b>	6.89kg
<b>Power Supply</b>	12V DC, 4.0A external power adapter
<b>Power Consumption</b>	Min: 7.2W Max: 23W (Fan & Heater on)
<b>Operating Temperature</b>	-40 to 60 Degree C
<b>Emission</b>	CE, FCC

**APPLICATIONS**

*Remote monitoring application*



**ORDERING INFORMATION**

ICA-651-NT	Outdoor Speed Dome Internet Camera (NTSC)
ICA-651-PA	Outdoor Speed Dome Internet Camera (PAL)

**ACCESSORIES PRODUCTS**

ICA-6CM	Ceiling Mount Kit for ICA-651
ICA-CT50	50 cm Ceiling Tube

**RELATED PRODUCT**

ICA-601-NT	Indoor Speed Dome Internet Camera (NTSC)
ICA-601-PA	Indoor Speed Dome Internet Camera (PAL)
CAM-KB300	3-Axis Control Keyboard