

OLYMPUS®

Stylus® 1000 Designed to Do More.™



Premium quality images. Unparalleled performance.

Digital Image Stabilization



Digital Image Stabilization Mode lets you capture sharp images free from the blur sometimes caused by camera shake or moving subjects. Digital Image Stabilization Edit lets you retouch unanticipated blurry pictures in your camera.

Bright Capture Technology



See what you're shooting even in the dark. When you're ready, just frame it and take the picture.

Perfect Fix


Activate three different editing features to make your pictures perfect.



Digital Image Stabilization Edit corrects the blurs.



Lighting Fix adjusts the underexposed area.



Red-Eye Fix gives you beautiful portraits.

- ▶ **10 Megapixel CCD** Get sharp, high-resolution and high-quality photos regardless of the print size.
- ▶ **Digital Image Stabilization** Shoot with Digital Image Stabilization Mode to capture crisp, clear images. Sharpen with Digital Image Stabilization Edit right in the camera to correct any blurry images.
- ▶ **All-Weather** Shoot in rain or shine, at the beach or on the slopes. Sealed and coated in all the right places, the Stylus® 1000 resists water, snow and dust.
- ▶ **Bright Capture Technology** Low light is no problem. Even when it's too dark for your eyes to see, you can preview your subject clearly on the LCD, then capture an image that's clear and bright without having to use a flash. Plus, Bright Capture Movie lets you record the moments in the dark even after the candles are blown out!
- ▶ **15x Total Seamless Zoom** 3x optical zoom plus 5x digital zoom moves you closer to your subject without taking a step.
- ▶ **2.5" LCD** Previewing, composing, shooting and sharing are so much easier and more enjoyable with this bright, premium-sized LCD.
- ▶ **TruePic TURBO™ Image Processor** With this exclusive technology, you not only get truer colors – you also get quicker start-up and shutter release times so you can shoot faster.
- ▶ **24 Shooting Modes including QuickTime® Movie with Sound** Take the best shots in any situation with advanced shooting options such as Landscape, Portrait, Indoor, Night Scene and more.
- ▶ **Perfect Fix** With this Olympus Stylus 1000 feature, a less-than-perfect shot can still turn out perfectly! Lighten up shadows, remove red-eyes and eliminate blurs quickly and easily.
- ▶ **Built-In Help Guide** A brief in-camera description helps you quickly choose the ideal setting for each situation and purpose. An improved Shooting Guide even sets the camera for you automatically.

| | | | | | | | |
|-------------------------------------|------------------------------|---|-----------------------------|--------------------------------|-----------------------------|-------------------------------|---------------------|
| Megapixel 10 Effective | Optical 3x Zoom | Total Zoom 15x Optical & Digital | All-Weather Construction | Digital Image Stabilization | Color 2.5" LCD | Auto USB Connect | Movie With Audio |
|-------------------------------------|------------------------------|---|-----------------------------|--------------------------------|-----------------------------|-------------------------------|---------------------|

Olympus® Stylus 1000 Specifications

Stock No. 225855

| | |
|-----------------------------------|--|
| Imager: | 10.0 Megapixel (effective), 10.0 Megapixel gross, 1/1.8" (1.41cm) CCD |
| Lens: | 7.4 – 22.2mm (35 – 105mm equivalent in 35mm photography), 6 lenses in 4 groups, 4 aspherical lenses |
| Zoom: | 3x Optical Zoom + 5x Digital Zoom (seamless to 15x) 5x Fine Zoom (3 Megapixel) |
| Aperture Range: | f2.8 – f4.7 |
| LCD: | 2.5" (6.4cm) Color LCD, approx. 230,000 pixels |
| Focus System: | CCD Contrast Detection |
| Focus Range: | Normal Mode: 23.6" – infinity (0.6m – infinity) Macro Mode (Wide): 11.8" – infinity (0.3m – infinity) Macro Mode (Tele): 19.7" – infinity (0.5m – infinity) Super Macro Mode: 3.9" – 23.6" (10 – 60cm) |
| Focus Mode: | iESP Auto, Spot AF |
| Shutter Speed: | 1/1000 sec. – 1/2 sec. (up to 4 sec. in Night Scene Mode) |
| ISO: | Auto, 64, 100, 200, 400, 800, 1600*, 3200*, 6400* (equivalent) |
| Metering Mode: | Digital ESP Multi-Pattern, Spot Metering |
| White Balance: | iESP2 Multi-Pattern Auto TTL, Pre-Set (Daylight, Overcast, Tungsten, Fluorescent1, Fluorescent2, Fluorescent3) |
| Exposure Compensation: | ±2 EV steps in 1/3 EV steps |
| Recording Modes: | Still Image: JPEG Movie: QuickTime® motion JPEG |
| Adjustment Resolutions: | 3,648 x 2,736, SHQ / HQ 2,560 x 1,920, SQ1 2,304 x 1,728, SQ1 2,048 x 1,536, SQ1 1,600 x 1,200, SQ2 1,280 x 960, SQ2 1,024 x 768, SQ2 640 x 480, SQ2 1,920 x 1,080, 16:9 |
| Shooting Modes: | 24 Shooting Modes: Auto, Program Auto, Scene Preset (Portrait, Landscape, Landscape & Portrait, Night Scene, Night & Portrait, Sport, Indoor*, Candle*, Self-Portrait, Available Light Portrait*, Sunset, Fireworks, Museum, Cuisine, Behind Glass, Documents, Auction*, Shoot & Select1, Shoot & Select2, Beach & Snow), Digital Image Stabilization Mode*, Movie |
| Panorama: | Up to 10 frames automatically stitchable with OLYMPUS Master Software when using Olympus brand xD-Picture Card™ |
| Sequential Shooting: | High speed: 3.6 frames per second up to 12 frames in SQ1 mode |
| Shooting Assist Functions: | Histogram, Frame Assist |
| Shooting Edit Effects: | Frame |
| Movie Mode: | QuickTime® Movie with Sound: 640x480/30fps, SHQ; 320x240/30 fps, HQ; 160x120/15fps, SQ |
| Image Processing: | TruePic TURBO™ Image Processor |
| Pixel Mapping: | Automatic Pixel Mapping (APM) available via menu setting |
| Noise Reduction: | Set automatically at shutter speeds of 0.5 seconds or longer |
| Image Playback: | Still Image: Single, Index Display (4/9/16/25), Up to 10x Enlargement, Slideshow, Rotation, Calendar, Album, Histogram Movie: Normal, Reverse, Frame-By-Frame |
| Playback Edit Effects: | Still Image: Digital Image Stabilization Edit, Lighting Fix, Red-Eye Fix, Resize, Trimming, Rotation, Black & White, Sepia, Frame, Title, Calendar, Layout, Brightness, Saturation Movie: Movie Edit, Frame Index |
| Direct Printing Options: | PictBridge™ and DPOF |
| Flash: | Built-in |
| Flash Modes: | Auto (for low-light and backlit conditions), Red-Eye Reduction, Fill-In, Off |
| Flash Working Range: | Wide: 17.1 ft. (5.2m), Tele: 10.5 ft. (3.2m) |
| Self-Timer: | 12 Seconds/Auto |
| Settings Memorization: | On/Off (Hold changes/Reset to default settings) |
| Date/Time Calendar: | Simultaneous recording into image data, Automatic up to 2099 |
| Memory: | 28.5MB internal memory |
| Removable Media Card: | xD-Picture Card™ (16, 32, 64, 128, 256, 512MB, 1GB or 2GB) |
| Outer Connectors: | Multi-terminal (USB connector, Audio/Video output, DC input*) *Optional DC coupler (CB-MA1) is required. |
| Auto-Connect USB: | 2.0 Full Speed (USB mass storage) |
| System Requirements: | Auto-Connect USB: Windows® 98SE/ME/2000PRO/XP with USB Port, Mac OS® 9.0-9.2x/OS X 10.1-10.4 with USB port Software: Windows 98SE/ME/2000PRO/XP, Mac® 10.2 and higher |
| Operating Environment: | Operation: 32° – 104°F (0° – 40°C), 30% – 90% humidity Storage: -4° – 140°F (-20° – 60°C), 10% – 90% humidity |
| Power Supply: | Li-Ion Rechargeable Battery (LI-12B), AC Adapter (D-7AC) with the Optional DC Coupler (CB-MA1) |
| Size: | 3.8" W x 2.2" H x 0.89" D (97.0mm x 56.2mm x 22.7mm) |
| Weight: | 4.9 oz. (140g) without battery and media card |

*1 Works with Bright Capture. *2 Works with Bright Capture. Image size is automatically changed to 2,048 x 1,536. *3 Image quality is limited to 640 x 480.



getolympus.com

Available Accessories

| | | |
|--|--|--|
| | Olympus xD-Picture Card™ 256MB 512MB 1GB 2GB | 202066 Neoprene Compact Camera Case 200496 Metal Neck Strap 200830 MAUSB-10 xD-Picture Card™/SmartMedia™ USB Reader/Writer |
| | Leather Case (Vertical, Top-Loading) 200398 | 200846 LI-10C Replacement Charger 200850 D-7AC AC Adapter 202053 CB-MA1 DC Coupler (For Use With D-7AC) |
| | LI-12B Lithium Ion Battery 200838 | 200372 CB-USB6 Digital Camera USB Cable (Replacement) 200347 CB-AVC3 Digital Camera A/V Cable (Replacement) |
| | MAUSB-200 xD-Picture Card USB Reader/Writer 202049 | 202044 2-Year Extended Digital Warranty |

Package Contents

| | |
|--|---|
| Stylus 1000 Digital Camera | Basic Manual |
| LI-12B Li-Ion Rechargeable Battery and Charger | 2 CD-ROMs (OLYMPUS Master Software and Advanced Manual) |
| USB Cable, Audio/Video Cable | Warranty Card |
| Wrist Strap | |
| Quick Start Guide | |



Olympus Digital Still Cameras can be used with confidence wherever you go. They are backed by a one-year repair warranty service that is available worldwide. Please contact our service center or check the Authorized Distributors list for service and applicable areas of service. May not be available in all areas.

Specifications subject to change without notice or obligation on the part of the manufacturer.

© 2006 Olympus Imaging America Inc. All rights reserved. Printed in the United States of America. Olympus and Stylus are trademarks or registered trademarks of Olympus Corporation, Olympus Imaging America Inc. or their affiliated entities. All trademarks and registered trademarks listed herein are the property of their respective holders.

D1350-0806