

CLS SERIES

H O M E A U D I O S E R I E S



System Features:

- Revised waveguide with taller midrange protective grille
- Improved high frequency tweeter response with copper shorting ring.
- Improved midrange power handling
- Dual pairs of gold plated all metal binding posts with jumper straps for bi-wire or bi-amp applications



High Power Cast-Frame Woofers

Custom designed woofers made with cast aluminum frames, exotic fiber impregnated cellulose cones and huge high temp voice coils submerged in a massive motor structure result in legendary CV bass output and dynamics!



Proprietary Integrated Midrange and Tweeter Waveguide

Computer optimized waveguide provides high sensitivity and dynamics with extremely low distortion. The geometry of the waveguides results in near perfect integration of the midrange and tweeter for seamless midrange and highs.

TECHNICAL SPECIFICATIONS :

	CLS-6	CLS-6C	CLS-10	CLS-12	CLS-15	CLS-215	CLS-12S	CLS-15S
Frequency Response	50Hz - 20kHz	50Hz - 20kHz	38Hz - 20kHz	32Hz - 20kHz	28Hz - 20kHz	24Hz - 20kHz	28Hz - 150Hz	25Hz - 150Hz
Power handling	125W Peak	125W Peak	200W Peak	300W Peak	400W Peak	500W Peak	250W	200W RMS
Dimensions (h x w x d)	15.4x8x10.45	8x22.7x9.5	33x12.2x11	37x14x11.7	40x16.5x16.6	48x16.5x19	19x17x17	23.5"x18.8"x18.8"
Weight	20lbs	27lbs	48lbs	57lbs	80lbs	110lbs	46lbs	64lbs



9340 De Soto Ave. • Chatsworth, California 91311

Phone: 1-818-534-1500 • Fax: 1-818-534-1590 • www.cerwin-vega.com