

DATACARD™
CS-100
DIGITAL CAMERA



COST-EFFECTIVE DIGITAL IMAGE CAPTURE WITH INTEGRATED FLASH

The Datacard CS-100 digital camera, available exclusively from Datacard, is a smart choice for convenient, high-quality image capture



The Datacard CS-100 Digital Camera is ideal for image capture when speed is not a concern and volumes are low, but image quality is a must.

- **Plug-and-play performance.** The CS-100 digital camera is easy to set up and use, right out of the box. Just install the batteries, load the driver, and you are ready to start capturing high-quality digital images for any photo ID program.
- **Integrated flash.** Unlike other cameras in this class, the CS-100 digital camera features an integrated flash, even when it is connected to a computer. This helps optimize lighting under virtually any operating conditions.
- **Single-source reliability.** When you combine the CS-100 digital camera with a card printer and identification software from Datacard, you can acquire a complete photo ID solution from a single, reliable source. Depend on Datacard to meet all your program-specific needs, including systems, supplies and service.
- **Versatile language support.** User's Guide, Quick Start Guide and camera driver are available in Dutch, English, French, German, Italian, Japanese, Polish, Portuguese, Spanish, Traditional Chinese and Simplified Chinese.

DatacardGroup

SECURE ID AND CARD PERSONALIZATION SOLUTIONS

Choose the Datacard CS-100 digital camera for a complete image capture solution -- including tripod, backdrop, stand and software -- from a single reliable source.



DATACARD™
CS-100 DIGITAL CAMERA

Standard Features

Digital still camera

- 3.0 megapixel
- 4x digital zoom
- Flash (tethered and untethered)
- TWAIN driver
- Resolution: 2048 × 1536, 1024 × 768, and 640 × 480 pixels
- Lens focal length: 10 mm (up to 40 mm equivalent with 4x digital zoom)
- Flash range: 3 to 4 feet (0.9 to 1.2 meters) under normal lighting conditions
- 12-month warranty

Accessories

- 2 AAA alkaline batteries
- Camera strap
- USB cable
- User's manual
- Quick start guide
- Camera case

Options

- Tripod
- Backdrop and stand

Specifications

Dimensions (wxhxd)

- 3.70 × 2.13 × 0.7 inches /
- 96.2 × 54.2 × 18 mm

Weight

- 92g (without battery and external memory card)

Operating environment

- Humidity: 45 to 80%
- Temperature: 0 to 40° C

Agency Approvals

- CE Mark
- FCC Class B
- UL

USB Connection

- Requires USB connection directly to computer (connection through USB hub is not recommended)

DatacardGroup

11111 Bren Road West
Minnetonka, MN 55343-9015
+1 952 933 1223
+1 952 931 0418 FAX
www.datacard.com

Datacard is a registered trademark, trademark or service mark of DataCard Corporation in the United States and/or other countries.

© 2004 DataCard Corporation.
All rights reserved.

DC4-7002