



AT-245 IFTX

PCI 32-bit Fast Ethernet Fiber Network Interface Card

AT-245 IFTX

10Mbps Ethernet dual fiber and copper 100TX interface card

Choice and Flexibility

Allied Telesis' AT-245 IFTX is the answer for those fiber interface cards that support Wake-on-LAN (WoL) for either PCI 2.1 or PCI 2.2 systems but not both. Allied Telesis' NICs support WoL through the PCI 2.2 bus and support PCI 2.1 WoL via external cables. Resistant to signal degradation, snooping, and interference, the AT-245 IFTX is the ideal solution for networks requiring protection from electrical interference and hackers. The small footprint—together with the low-profile option of the AT-245 IFTX—make these products a perfect choice for PCs equipped with small desktop solutions.

Advanced Manageability

Allied Telesis' AT-245 IFTX features a full-line of card assistant software:

- AT-Setup reduces Windows Driver installation to a mouse click. This Windows program guides users through driver installation, updates, and problem corrections.
- AT-Stat is an advanced Windows application that reports network conditions and performance such as hardware resources, network statistics, and configuration.
- The VLAN protocol driver allows network administrators to configure their VLAN network fabric at the PC instead of the switch, enabling transparent movement of systems between switches.
- TCP/IP checksum off-loading improves CPU use by verifying TCP/IP traffic checksums at the interface card rather than at the host processor, improving overall system performance for slower PCs.
- Packet prioritization enables Windows applications with Class of Service capabilities to prioritize out-bound packet streams to these NICs, a useful feature for video streaming and VoIP where interruptions are unacceptable.
- The AT-245 IFTX's onboard Managed Boot Agent (MBA) provides a wide set of industry-standard boot protocols, including PXE, NetWare NCP/IPX, IBM's RPL, traditional DHCP, and BOOTP, supporting both BBS (BIOS Boot Specification) and non-BBS compliant PCs. It also includes an extensive set of utilities for boot ROM configuration, as well as access to pre-OS and network boot image files.
- Offering a wide range of connector choices—ST or SC—these cards meet the requirements of most fiber installations.

Key Features

Management Software

- VLAN support

- Link aggregation

- Failover

Advance Properties

- PCI 2.2 compliant

- Wake-on-LAN (WoL)

- Secured transmissions

- Advanced installation utility

- Advanced diagnostics

- Remote boot (PXE 2.1)

- TCP/IP checksum off-loading

- Priority queuing

- Driver support for popular operating systems including Sun Solaris

- Available with SC or ST fiber connections

- Compliant with the Trade Agreement Act

- Microsoft certified drivers

- RoHS compliant

- Low-profile and standard height brackets included

- IPv6

- Also can be used in PCI-x bus

AT-245 IFTX | 32-bit PCI Fast Ethernet Fiber Network Interface Card

Specifications

Management Features

WMI
ACPI 2.0/w01
PXE 2.1 Boot ROM

Bus Type

PCI 2.2

Ethernet Standards

IEEE 802.1p	Quality of Service
IEEE 802.1Q	VLANs
IEEE 802.2	LLC
IEEE 802.3ac	MAC
IEEE 802.3	10 Ethernet
IEEE 802.3u	Fast Ethernet

Drivers

Supported

Vista
Vista 64-bit
Windows XP
Windows XP 64-bit
Windows 2003
Windows 2003 64-bit
Windows 2000
NDIS2
NetWare 6.x
Linux 2.4
Linux 2.6

Available

Windows NT 4
Solaris x86
Solaris Sparc 32-bit
Solaris Sparc 64-bit
NetWare 5.x

Compliance

RoHS
UL
FCC/EN55022 Class B
TUV
EN55024
CE
C-TICK
VCCI

Connectors

SC
ST
Optical receive sensitivity (max) -34.4dBm
Transmit optical power (min/max) -18.8/-13.8dBm

Environmental Specifications

Operating temperature 0°C to 50°C
Storage temperature -25°C to 70°C
Relative humidity 5% to 90% non-condensing

Power

Power consumption 4.86 Watts (max)
Signaling voltage 3.3/5V

Status Indicators

10	ON	10Mbps link up
	Green	Full-duplex mode
	Yellow	Half-duplex mode
	Blink	Activity
OFF		10Mbps link down
100	ON	100Mbps link up
	Green	Full-duplex mode
	Yellow	Half-duplex mode
	Blink	Activity
OFF		100Mbps link down

Physical Characteristics

Dimensions 16.8cm x 6.5cm
(W x H) (6.7") x (2.6")

Ships with standard bracket attached to interface card.
Low-profile bracket is included in packaging.

Network Type

10/100TX, 10FL

Network Controller

AMD AM79C976

Ordering Information

AT-245 IFTX/AA-xxx

10Mbps Fast Ethernet dual fiber and copper interface card

Where AA = ST or SC

Where xxx = 001 for single pack
020 for 20-pack

901 for single pack,
compliant with Trade Agreements Act

920 for 20-pack,
compliant with Trade Agreements Act

Ships with standard bracket attached to interface card.
Low-profile bracket is included in packaging.

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesis.com

© 2007 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners.

617-00540 Rev.G