

24V DRIVE, ULTRA HIGH SPEED LINE THERMAL PRINTER 2" MECHANISM, WITH AVAILABLE CUTTER

FTP-621MCL351/352

■ OVERVIEW

This thermal printer (driven by 24 VDC) and cutter provide high speed printing for 2-inch wide paper (60 mm). This printer is small in size, light weight, and has low power consumption. The print head is designed with open construction for easy maintenance.

This printer is suitable for a variety of applications, such as POS terminals, ticket machines, label printers, measuring devices and medical equipment.


In addition to the interface board, a driving LSI (MCU + Gate Array) is also available.

■ HIGHLIGHTS

- **Ultra high speed printing**
It can print at 100 mm/s (800 dotlines/s) by using Fujitsu Components' unique head drive control system.
- **Auto cutter**
Full or partial cutting are available by normal or reverse rotation of the motor (command set).
- **Low power consumption**
The peak current for head driving is approximately 2.2 A (at 50 mm/s printing speed, 50% printing ratio).
- **Easy head access**
Open head construction makes head maintenance easy, especially for head cleaning.
- **Paper auto loading function**
The thermal paper can be loaded without head-up lever operation.
- **High resolution**
8 dots/mm head provide clear print output.
- **Selectable paper paths**
Front or rear insertion types are available.



FTP-621MCL351/352 shown after assembly with FTP-621CT001cutter



FTP-621CU102, FTP-633GA101



FTP-621DCL013

■ DESIGNATION

| Item | | Part number |
|-------------------|----------------------------|---------------|
| Printer mechanism | Front paper insertion type | FTP-621MCL351 |
| | Rear paper insertion type | FTP-621MCL352 |
| Cutter | | FTP-621CT001 |
| Interface board | | FTP-621DCL013 |
| LSI | Micro Controller Unit | FTP-621CU102 |
| | Gate Array | FTP-633GA101 |

■ GENERAL SPECIFICATIONS

| Item | Specifications | |
|--|--|---------------------------------------|
| Printing method | Thermal-sensitive line dot method | |
| Dot structure | 432 dots/line | |
| Dot pitch (Horizontal) | 0.125 mm (8 dots/mm)—Dot density | |
| Dot pitch (Vertical) | 0.125 mm (8 dots/mm)—Line feed pitch | |
| Effective printing area | 54 mm | |
| Number of columns | 36 columns/line (maximum)—Alphanumeric KANA | |
| Maximum printing speed | 800 dotlines/s (100 mm/s) maximum | |
| Character types | JIS ANK : 128 International characters : 130 Semi-graphic : 63 ASCII small characters : 31 Download : 384 | |
| Character composition, dimensions (H×W), Number of columns (standard) | 24 × 12 dots, (3.0 × 1.5 mm), 36 columns 32 × 16 dots, (4.0 × 2.0 mm), 27 columns 24 × 24 dots, (3.0 × 3.0 mm), 18 columns 32 × 32 dots, (4.0 × 4.0 mm), 13 columns | |
| Interface | 1) Centronics standard 2) Bus interface*1 | |
| Cutter | Cutting method | Guillotine method |
| | Cutting type | Full-cut or partial cut (command set) |
| | Minimum cut length | 20 mm |
| | Paper thickness | 65 to 150 μm |

(Continued)

(Continued)

| Item | | Specifications |
|---|-----------------------|---|
| Power supply | For head | 24 V DC \pm 5%, average:* ² 0.41 (0.56) A (at 25 mm/s printing speed, 25% printing ratio) 0.63 (1.11) A (at 50 mm/s printing speed, 25% printing ratio) 1.23 (1.65) A (at 100 mm/s printing speed, 25% printing ratio) (): Peak |
| | For motor | 24 VDC \pm 5%, 1.0 A maximum |
| | For logic | 5 VDC \pm 5%, 0.5 A maximum |
| Weight | | Mechanism with cutter: approx. 450 g. Interface board: approx. 100 g |
| Dimensions | Mechanism + cutter | 107 (W) \times 60 (D) \times 71.0 (H) mm (excluding connector) |
| | Interface board | 140 (W) \times 89 (D) \times 24.0 (H) mm |
| Life | Thermal head | Pulse durability : 5×10^7 pulse/dot (using Fujitsu Takamisawa's standard driving method) Wear resistance : 50 km (at 12.5% printing ratio) |
| | Cutter | Cutting life: 3×10^5 times |
| Environmental conditions | Operating temperature | +5 to +40°C* ³ |
| | Operating humidity | 20 to 85% RH (no condensation) |
| | Storage temperature | -20 to +60°C (excluding paper) |
| | Storage humidity | 5 to 95% RH (no condensation) |
| Detection | Head temperature | By thermistor (applied energy control, abnormal temperature detection) |
| | Paper out/Mark detect | By photointerrupter (command set) |
| | Head-up | By microswitch |
| Paper width | | 60 $^{+0}_{-1}$ mm |
| Recommended thermal sensitive paper* ⁴ | | 1 ply paper in roll: FTP-020P0020 |

*1: The data to be printed is automatically read out by the printer driver equipment memory (host system frame memory). The communication is parameter transfer.


*2: At 25°C, maximum applied voltage, minimum head resistance, specified paper, stable printing ratio.

*3: Temperature range for guaranteed printing density. It can operate at 0 to +40°C.



*4: Please contact us for other thermal papers.

■ DIMENSIONS

Printer mechanism with cutter



Interface board



Unit: mm

■ INTERFACE, COMMAND, OPTIONS

Please refer to the FTP-621DCL003/013 DATA SHEET for Interface, Command, and Options.

Fujitsu Components International Headquarter Offices

Japan

Fujitsu Component Limited
Gotanda-Chuo Building
3-5, Higashigotanda 2-chome, Shinagawa-ku
Tokyo 141, Japan
Tel: (81-3) 5449-7010
Fax: (81-3) 5449-2626
Email: promothq@ft.ed.fujitsu.com
Web: www.fcl.fujitsu.com

North and South America

Fujitsu Components America, Inc.
250 E. Caribbean Drive
Sunnyvale, CA 94089 U.S.A.
Tel: (1-408) 745-4900
Fax: (1-408) 745-4970
Email: marcom@fcai.fujitsu.com
Web: www.fcai.fujitsu.com

Europe

Fujitsu Components Europe B.V.
Diamantlaan 25
2132 WV Hoofddorp
Netherlands
Tel: (31-23) 5560910
Fax: (31-23) 5560950
Email: info.marketing@fceu.fujitsu.com
Web: www.fceu.fujitsu.com

Asia Pacific

Fujitsu Components Asia Ltd.
102E Pasir Panjang Road
#04-01 Citilink Warehouse Complex
Singapore 118529
Tel: (65) 375-8560
Fax: (65) 273-3021
Email: fcac@fcal.fujitsu.com
www.fcal.fujitsu.com

© 2001 Fujitsu Components America, Inc. All company and product names are trademarks or registered trademarks of their respective owners. Rev. 09/2001