



LCD MONITOR

Display size	19" (48,26 cm) WIDE				
Panel Type	Active Matrix TFT				
Brightness	300 cd/m ² (typ.)				
Contrast (typ.)	700:1				
X-Contrast (dyn.)	-				
Pixel pitch	0,283(H) x 0,283(V) mm				
Resolution (H x V)	WXGA+ 1440 x 900				
Response time	5 ms (typ.)				
View angles (CR>10)	H/V 150°/140°				
View angles (CR>5)					
Display colors	16,2 Mio colors				
Display Surface	Anti-Glare				
Input 1	VGA, Audio				
Input 2					
Input 3					
Headphone					
Speakers	1 W x 2				
Supply	AC 100~240V, 50~60Hz				
Consumption	On:	36 W	Stand-by:	<2 W	Off: <1 W
Operation Temp/Hum	5 ~ 35°C			10 ~ 80%	
Dimension (W*D*H)	450 x 190 x 390 mm				
Net weight	4,8 kg				
Tilt	-5°~ 20°				
Kensington Lock	✓				
VESA mounting	VESA Standard, 100mm				
On screen display	EN, SC, TC, IT, DE, FR, JP, KO, NL, PT, ES				
Safety	UL/CUL, TUV, CB, BSMI, FCC, CE				
Emission	TCO03				
Power saving	EPA Energy Star				
Extras 1					
Extras 2					
Extras 3					
EAN	4710859554451				
incl Accessory	powercord, VGA cable, audio cable, users manual (CD), quickstart guide (paper), warranty card				



© HANNspree Europe GmbH. Information in this document is subject to change without notice. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Screenshots are simulated.