

# Leica DISTO™ E7400x

The original laser distance meter



- when it has to be **right**

**Leica**  
Geosystems

<b>Instrument Set-up</b>	<b>2</b>
Introduction	2
Overview	2
Display	3
Insert batteries	3
<b>Operations</b>	<b>4</b>
Switching ON/OFF	4
Clear	4
Message Codes	4
Adjusting measuring reference / tripod	4
Multifunctional endpiece	5
Distance unit setting	5
Tilt unit setting	5
Timer (automatic release)	5
Beep ON/OFF	6
Illumination ON/OFF	6
Keypad lock ON	6
Keypad lock OFF	6
<b>Measuring Functions</b>	<b>7</b>
Measuring single distance	7
Permanent / Minimum-Maximum measuring	7
Add / Subtract	7
Area	8
Volume	9
Triangular area	10
Pythagoras (3-point)	11
Pythagoras (partial height)	12
Stake out	13
Smart Horizontal Mode	14
Height tracking	14
Memory (20 last displays)	15

Delete Memory	15
---------------	----

<b>Calibration</b>	<b>16</b>
--------------------	-----------

Calibration of tilt sensor (Tilt Calibration)	16
---	----

<b>Technical Data</b>	<b>17</b>
-----------------------	-----------

<b>Message Codes</b>	<b>18</b>
----------------------	-----------

<b>Care</b>	<b>18</b>
-------------	-----------

<b>Warranty</b>	<b>18</b>
-----------------	-----------

<b>Safety Instructions</b>	<b>18</b>
----------------------------	-----------

Areas of responsibility	18
Permitted use	19
Prohibited use	19
Hazards in use	19
Limits of use	19
Disposal	19
Electromagnetic Compatibility (EMC)	19
FCC statement (applicable in U.S.)	20
Laser classification	20
Labelling	20

## Introduction



The safety instructions and the user manual should be read through carefully before the product is used for the first time.



The person responsible for the product must ensure that all users understand these directions and adhere to them.

The symbols used have the following meanings:

**WARNING**

Indicates a potentially hazardous situation or an unintended use which, if not avoided, will result in death or serious injury.


**CAUTION**

Indicates a potentially hazardous situation or an unintended use which, if not avoided, may result in minor injury and/or appreciable material, financial and environmental damage.




Important paragraphs which must be adhered to in practice as they enable the product to be used in a technically correct and efficient manner.


## Overview



## Display




## Insert batteries




i

To ensure a reliable use, do not use zinc-carbon batteries. Change batteries when battery symbol is flashing.



## Switching ON/OFF



Press ON button 2 sec to start continuous laser mode.

## Clear



Undo last action.



Leave actual function, go to default operation mode.


## Message Codes

If the message "InFo" appears with a number, observe the instructions in section "Message Codes".

Example:




## Adjusting measuring reference / tripod




Distance is measured from the front of the device.



Press button 2 sec and reference from front is set permanently.





Distance is measured from the tripod thread permanently.



Distance is measured from the rear of the device (standard setting).


## Multifunctional endpiece



i

The orientation of the endpiece is automatically detected and the zero point is accordingly adjusted.


## Distance unit setting



Switch between the following units:

0.000 m	0'00" 1/4
0.0000 m	0.00 in
0.00 m	0 in 1/32
0.00 ft	0 in 1/16
0'00" 1/32	0 in 1/8
0'00" 1/16	0 in 1/4
0'00" 1/8	



## Tilt unit setting



Switch between the following units:

0.0 °
0.0 %

## Timer (automatic release)



Adjust delay of automatic release (max. 60 sec, standard setting 5 sec)

i

Once the key is released with the laser activated, the remaining seconds until the measurement are displayed in a countdown. The delayed release is recommended for precise aiming e.g. at long distances. It avoids shaking of the device when pressing the measurement key.


## Beep ON/OFF




2 sec  
simultane-  
ously



## Illumination ON/OFF



2 sec  
simultane-  
ously




## Keypad lock ON



2 sec  
simultane-  
ously




## Keypad lock OFF



within  
2 sec




## Measuring single distance



i

Target surfaces: Measuring errors can occur when measuring to colourless liquids, glass, styrofoam or semi-permeable surfaces or when aiming at high gloss surfaces. Against dark surfaces the measuring time increases.


## Permanent / Minimum-Maximum measuring



3

Stops permanent / minimum-maximum measuring.

## Add / Subtract




i

The result is shown in the main line and the measured value above. This process can be repeated as required. The same process can be used for adding or subtracting areas or volumes.




## Area



i

The result is shown in the main line and the measured value above.  
Partial Measurements:  
Press + or - after starting the first measurement. Measure and add or subtract distances. Finish with DIST. Measure 2nd length.



## Volume

1

**2x**  
**FUNC**

2

Aim laser at first target point.

3

**ON**  
**DIST**

4

Aim laser at second target point.

5

**ON**  
**DIST**

6

Aim laser at third target point.

7

**ON**  
**DIST**

**78.694 m³**

**i**


The result is shown in the main line and the measured value above.

8


**FUNC**  
**2 sec**

	80.208 m	— Circumference
	208.703 m²	— Wall areas
	24.224 m²	— Ceiling/floor area
	78.694 m³	— Volume

## Triangular area



## Pythagoras (3-point)



## Pythagoras (partial height)

1

5x  
FUNC

2

Aim laser at upper point.

3

ON  
DIST

4

Aim laser at 2nd point.

5

ON  
DIST

6

Aim laser at rectangular point.

7

ON  
DIST

2.602 m

i




The result is shown in the main line and the measured distance above.

Pressing the measuring key for 2 sec in the function activates automatically Minimum or Maximum measurement.


## Stake out

1

Two different distances (a and b) can be entered to mark off defined measured lengths.



2



Adjust value "a".




3



Approve value "a".

4



Adjust value "b".




5




Approve value "b" and start measurement.

6



Move device slowly along the stake-out line. The distance to the next stake out point is displayed.




0.240 m is missing up to next 0.625 m distance.

1





When approaching a stake out point to less than 0.1 m the instrument starts to beep. The function can be stopped by pressing the CLEAR/OFF button.

## Smart Horizontal Mode






Press key again to switch off horizontal measurement.


## Height tracking



## Memory (20 last displays)




## Delete Memory





## Calibration of tilt sensor (Tilt Calibration)



Distance measurement	
<b>Typical Measuring Tolerance*</b>	± 1.0 mm / ~1/16" ***
<b>Maximum Measuring Tolerance**</b>	± 2.0 mm / 0.08 in ***
<b>Range at Leica target plate GZM26</b>	100 m / 330 ft
<b>Typical Range*</b>	0.05-80 m / 2-265 ft
<b>Range at unfavourable condition ****</b>	60 m / 197 ft
<b>Smallest unit displayed</b>	0.1 mm / 1/32 in
<b>Power Range Technology™</b>	yes
<b>Ø laser point at distances</b>	6 / 30 / 60 mm (10 / 50 / 100 m)
Tilt measurement	
<b>Measuring tolerance to laser beam*****</b>	± 0.2°
<b>Measuring tolerance to housing*****</b>	± 0.2°
<b>Range</b>	360°
General	
<b>Laser class</b>	2
<b>Laser type</b>	635 nm, < 1 mW
<b>Protection class</b>	IP65 (dust tight and jet water protected)
<b>Autom. laser switch off</b>	after 90 s
<b>Autom. power switch-off</b>	after 180 s
<b>Battery durability (2 x AAA)</b>	up to 5000 measurements
<b>Dimension (H x D x W)</b>	122 x 55 x 31 mm 4.80 x 2.17 x 1.22 in
<b>Weight (with batteries)</b>	155 g / 4.98 oz
<b>Temperature range:</b>	
- Storage	-25 to 70 °C -13 to 158 °F
- Operation	-10 to 50 °C 14 to 122 °F


\* applies for 100 % target reflectivity (white painted wall), low background illumination, 25 °C

\*\* applies for 10 to 500 % target reflectivity, high background illumination, - 10 °C to + 50 °C

\*\*\* Tolerances apply from 0.05 m to 10 m with a confidence level of 95%. The maximum tolerance may deteriorate to 0.1 mm/m between 10 m to 30 m and to 0.20 mm/m for distances above 30 m

\*\*\*\* applies for 100 % target reflectivity, background illumination of approximately 30'000 lux

\*\*\*\*\* after user calibration. Additional angle related deviation of +/- 0.01° per degree up to +/-45° in each quadrant. Applies at room temperature. For the whole operating temperature range the maximum deviation increases by +/- 0.1°.

 For accurate indirect results, the use of a tripod is recommended. For accurate tilt measurements a transverse tilt should be avoided.

Functions	
<b>Distance measuring</b>	yes
<b>Min/Max measuring</b>	yes
<b>Permanent measuring</b>	yes
<b>Stake-out</b>	yes
<b>Addition/Subtraction</b>	yes
<b>Area</b>	yes
<b>Triangle area</b>	yes
<b>Volume</b>	yes
<b>Painter function (area with partial measurem.)</b>	yes
<b>Pythagoras</b>	3-point, partial height
<b>Smart Horizontal Mode / Indirect height</b>	yes
<b>Height tracking</b>	yes
<b>Memory</b>	20 displays
<b>Beep</b>	yes
<b>Illuminated display</b>	yes
<b>Multifunctional endpiece</b>	yes

If the message **Error** does not disappear after switching on the device repeatedly, contact the dealer.

If the message **InFo** appears with a number, press the Clear button and observe the following instructions:

No.	Cause	Correction
156	Transverse tilt greater than 10°	Hold the instrument without any transverse tilt.
162	Calibration mistake	Make sure, the device is placed on a absolutely horizontal and flat surface. Repeat the calibration procedure. If the mistake still occurs, contact your dealer.
204	Calculation error	Perform measurement again.
252	Temperature too high	Let device cool down.
253	Temperature too low	Warm device up.
255	Received signal too weak, measuring time too long	Change target surface (e.g. white paper).
256	Received signal too high	Change target surface (e.g. white paper).
257	Too much back-ground light	Shadow target area.
258	Measurement outside of measuring range	Correct range.
260	Laser beam interrupted	Repeat measurement.

- Clean the device with a damp, soft cloth.
- Never immerse the device in water.
- Never use aggressive cleaning agents or solvents.

## Warranty

The device comes with a 3-year warranty. To receive the 3-year warranty, the product must be registered on [www.disto.com](http://www.disto.com) within 8 weeks of the purchase date. If the product is not registered, a 2-year warranty applies.

The person responsible for the instrument must ensure that all users understand these directions and adhere to them.

## Areas of responsibility

### Responsibilities of the manufacturer of the original equipment:

Leica Geosystems AG  
Heinrich-Wild-Strasse  
CH-9435 Heerbrugg  
Internet: [www.disto.com](http://www.disto.com)

The company above is responsible for supplying the product, including the User Manual in a completely safe condition.

The company above is not responsible for third party accessories.

### Responsibilities of the person in charge of the instrument:

- To understand the safety instructions on the product and the instructions in the User Manual.
- To be familiar with local safety regulations relating to accident prevention.
- Always prevent access to the product by unauthorised personnel.

## Permitted use

- Measuring distances
- Tilt measurement

## Prohibited use

- Using the product without instruction
- Using outside the stated limits
- Deactivation of safety systems and removal of explanatory and hazard labels
- Opening of the equipment by using tools (screwdrivers, etc.)
- Carrying out modification or conversion of the product
- Use of accessories from other manufacturers without express approval
- Deliberate dazzling of third parties; also in the dark
- Inadequate safeguards at the surveying site (e.g. when measuring on roads, construction sites, etc.)
- Deliberate or irresponsible behaviour on scaffolding, when using ladders, when measuring near machines which are running or near parts of machines or installations which are unprotected
- Aiming directly in the sun

## Hazards in use



### WARNING

Watch out for erroneous measurements if the instrument is defective or if it has been dropped or has been misused or modified. Carry out periodic test measurements. Particularly after the instrument has been subject to abnormal use, and before, during and after important measurements.



### CAUTION

Never attempt to repair the product yourself. In case of damage, contact a local dealer.



### WARNING

Changes or modifications not expressly approved could void the user's authority to operate the equipment.

## Limits of use



Refer to section "Technical data".

The device is designed for use in areas permanently habitable by humans. Do not use the product in explosion hazardous areas or in aggressive environments.

## Disposal



### CAUTION

Flat batteries must not be disposed of with household waste. Care for the environment and take them to the collection points provided in accordance with national or local regulations.

The product must not be disposed with household waste.

Dispose of the product appropriately in accordance with the national regulations in force in your country.



Adhere to the national and country specific regulations.

Product specific treatment and waste management can be downloaded from our homepage.

## Electromagnetic Compatibility (EMC)



### WARNING

The device conforms to the most stringent requirements of the relevant standards and regulations.

Yet, the possibility of causing interference in other devices cannot be totally excluded.


## FCC statement (applicable in U.S.)

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications.

However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

## Laser classification



The device produces visible laser beams, which are emitted from the instrument: It is a Class 2 laser product in accordance with:

- IEC60825-1 : 2007 „Radiation safety of laser products“

### Laser Class 2 products:

Do not stare into the laser beam or direct it towards other people unnecessarily. Eye protection is normally afforded by aversion responses including the blink reflex.




Looking directly into the beam with optical aids (e.g. binoculars, telescopes) can be hazardous.



Looking into the laser beam may be hazardous to the eyes.

## Labelling



Subject to change (drawings, descriptions and technical data) without prior notice.



Leica Geosystems AG, Heerbrugg, Switzerland has been certified as being equipped with a quality system which meets the International Standards of Quality Management and Quality Systems (ISO standard 9001) and Environmental Management Systems (ISO standard 14001).

Total Quality Management - Our commitment to total customer satisfaction. Ask your local Leica Geosystems agent for more information about our TQM program.

Copyright Leica Geosystems AG, Heerbrugg,  
Switzerland 2012  
Original text (788480a EN)

Pat. No.: WO 9427164, WO 9818019, WO 0244754, WO 0216964,  
US 5949531, EP 1195617, US 7030969, WO 03104748,  
Patents pending

Leica Geosystems AG  
CH-9435 Heerbrugg  
(Switzerland)  
[www.disto.com](http://www.disto.com)

- when it has to be **right**

**Leica**  
Geosystems