

# SP E E C S

PEAVEY ELECTRONICS

## DJS™ 4

### Enclosure

#### SPECIFICATIONS

**Frequency response:**  
58 Hz to 16 kHz

**Usable low frequency limit  
(-10 dB point):**  
42 Hz

**Power handling:**  
500 W continuous  
1000 W program  
2000 W peak

**Sound pressure level 1W @ 1M,  
swept sine in anechoic environment:**  
99 dB

**Maximum SPL:**  
125 dB continuous  
134 dB peak

**Horn pattern:**  
90 degrees horizontal by 45  
degrees vertical

**Transducer complement:**  
Two 15" Scorpion® Plus SP-15825  
woofers, and one 2" RX™22 titanium  
diaphragm compression driver  
tweeter

**Box tuning frequency:**  
58 Hz

**Electroacoustic crossover frequency:**  
2.8 kHz



**Crossover type:**  
Internal passive psuedo-  
three-way

**Crossover slopes:**  
6 dB/oct. (1st order) low pass,  
12 dB/oct. (2nd order) high pass  
with constant directivity horn EQ

**Nominal impedance:**  
4 Ohms

**Minimum impedance:**  
3.4 Ohms

**Input connections:**  
Two 1/4" phone jacks in parallel.

**Weight:**  
93 lbs.

**Dimensions:**  
48.875"H x 21"W x 17.75"D

**Features:**

- Dual 15" Scorpion Plus woofers
- RX22 compression driver w/overload protection
- CH®-941 high frequency horn
- Lightweight enclosure
- Built-in pocket casters for easy transport
- Specially voiced for DJ use
- Contemporary cosmetics

**3 + 2 YEAR LIMITED WARRANTY**

**NOTE:** For details, refer to the warranty statement. Copies of this statement may be obtained by contacting Peavey Electronics Corporation, P.O. Box Meridian, Mississippi 39301-2898.



Features and specifications subject to change without notice.

Peavey Electronics Corporation • 711 A Street • Meridian • MS • 39301  
(601) 483-5365 • FAX (601) 486-1278 • [www.peavey.com](http://www.peavey.com)



80305002