



DutchWest
Plate Steel Wood Stoves and Insert



Warmth. Quality. And
Famous Dutchwest Value

Dutchwest Wood



Wood Stoves Built to Warm and Built to Last. At Dutchwest, we design every one of our wood stoves to deliver superior performance, durability, and value.

Premium Steel-Cast Stoves

Style and performance – heavy 5/16" thick top; firebrick firebox lining, cast-iron door, air hood, ash lip, and base elements. Three sizes with your choice of legs or pedestal. All Cast-Steel models include convenient ash drawer. All cast iron components are made in our Vermont foundry. Brushed Nickel handle to match today's interior finishes. Convective side panels reduce side clearances.

Three Sizes:

- Small (1,000 sq. ft):
 - Leg DW1000L02; Pedestal DW1000P02
- Medium (1,500 sq. ft):
 - Leg DW1500L02; Pedestal DW1500P02
- Large (2,000 sq. ft)
 - Leg DW2000L02; Pedestal DW2000P02



Wood Insert Model DW2500X02 - The Perfect Solution to an Inefficient Masonry Fireplace.

Crafted with the same sturdy construction as our wood stoves, the Dutchwest masonry wood insert is designed for existing masonry fireplaces. Standard features include a brick-lined firebox, blower, and faceplate (44 1/8" W x 31" H) with nickel trim.

Heating capacity up to 1,500 sq. ft.



Stoves & Insert

GREEN-BURN non-catalytic combustion technology results in low exhaust emissions for clean air. More complete combustion means more heat for less wood and longer lasting fires.

Value Line of Steel Stoves

Durable and feature rich at a value price. Stylish rolled top adds durability without adding unnecessary bulk – 3/16" thick top has strength of 5/16" flat top. Cast iron doors provides a large ceramic glass viewing area. Air wash design helps maintain a clean glass. Firebrick firebox lining.



CDW247001

Mobile Home Approved Wood Stove Model CDW247001

- Heating capacity up to 1,000 sq. ft.
- HUD approved for use in mobile homes; outside air connection
- Reduced clearance convection side panels



CDW244

Small Steel Wood Stove Model CDW244

- Heating capacity up to 1,000 sq. ft.
- Features cast iron door with steel legs



CDW270007

Medium Steel Wood Stove Model CDW270007

- Heating capacity up to 1,500 sq. ft.
- Features pedestal base with ash drawer



CDW300007

Large Steel Wood Stove Model CDW300007

- Heating capacity up to 2,000 sq. ft.
- Features pedestal base with ash drawer

Dutchwest Plate Steel Wood Stoves and Insert



Model	CDW247001 Mobile Home Approved	CDW244	CDW270007	CDW300007	DW1000P02 (pedestal)	DW1000L02 (legs)	DW1500P02 (pedestal)	DW1500L02 (legs)	DW2000P02 (pedestal)	DW2000L02 (legs)
Heat Cap. Sq. ft.*	up to 1,000	up to 1,000	up to 1,500	up to 2,000	up to 1,000	up to 1,000	up to 1,500	up to 1,500	up to 2,000	up to 2,000
Heat Output BTU/hr.	19,000	26,100	29,300	32,300	26,100	26,100	29,300	29,300	32,300	32,300
Avg. Efficiency %	65.3	74.5	63.0	63.0	74.5	74.5	63.0	63.0	63.0	63.0%
Avg. Emissions g/hr.	5.0	5.3	4.4	2.7	5.3	5.3	4.4	4.4	2.7	2.7
Firebox Vol. cu. ft.	1.7	1.3	2.0	2.9	1.3	1.3	2.0	2.0	2.8	2.8
Log Length	18"	18"	22"	20"	18"	18"	22"	22"	20"	20"
Product Wt. lbs.	180	180	310	300	222	222	385	350	350	350
Shipping Wt. lbs.	210	210	330	320	270	270	395	380	385	385
Over-all Dims.	31 3/4" h 22 3/4" w 20 3/8" d	26 15/16" h 22 1/2" w 20 5/8" d	29 9/16" h 27" w 20 7/8" d	31 1/2" h 26 1/2" w 25 1/8" d	27" h 23 3/4" w 20 1/2" d	27" h 23 3/4" w 20 1/2" d	30" h 28 1/4" w 22 1/4" d	30" h 28 1/4" w 22 1/4" d	31" h 26 1/2" w 26" d	31" h 26 1/2" w 26" d
Ash Drawer	NO	NO	YES	YES	YES	YES	YES	YES	YES	YES
Clearances to Combustibles	Top	54"	56"	54 1/2"	54"	56"	54 1/2"	54 1/2"	54"	54"
	Double Single Wall Wall Pipe									
	Rear	10 1/2"	15"	13"	14"	12 1/2"	12 1/2"	9"	9"	10"
	Sides	10 1/2"	18"	17 1/2"	18 1/2"	12"	12"	11 1/2"	11 1/2"	15"
	Corner	10 1/2"	7"	11"	11"	7"	7"	7"	7"	9"
	Rear	5"	N/A	N/A	N/A	8"	8"	6"	6"	10"
Sides	2 1/2"	N/A	N/A	N/A	8 1/2"	8 1/2"	6"	6"	14"	
Corner	2 1/2"	N/A	N/A	N/A	5 1/2"	5 1/2"	4"	4"	8"	



DW2500X02

Heat Cap. Sq. ft.*	Heat Output BTU/hr.	Avg. Efficiency %	Avg. Emissions g/hr	Firebox Vol. cu. ft.	Log Length	Product Wt. lbs.	Insert Dim.	Min. Fireplace Opening
Up to 1,500	58,000	64%	4.7	1.3	20"	250	21 3/4" H 26 3/4" W 20 3/4" D	23 3/4" H 30 3/4" W 10" D Faceplate: 31" H x 44" W

See owners manual for complete dimensions and installation specifications. Units require 6" diameter flue connector.

*Note: Actual heating area will vary based on fuel, home construction and region.



ph: 1.800.525.1898

www.vermontcastings.com
www.majesticproducts.com

YOUR DEALER