VA1918wm

19" Multimedia LCD With 10,000:1 Dynamic Contrast Ratio

Multimedia, Big Screen Performance

ViewSonic's 19" VA1918wm LCD combines 10,000:1 Dynamic Contrast Ratio that produces excellent front-of-screen performance and fast 5ms ClearMotiv™ video response for blur-free fast action video into a stylish 16:10 widescreen bezel. Complementing these high performance features are integrated speakers that offer a true multimedia visual experience. The VA1918wm is the smart choice for home and small office, and education users who perform intensive graphics work or need to work in multiple documents or applications simultaneously. It's a productivity booster and entertainment enhancer. Lock in your brilliant colors and perfect screen adjustment with the OSD and power lock. Mount this stylish display on the wall to save valuable desktop space and add a touch of style to your workspace. Prepare to be impressed by the performance, style and quality of the VA1918wm.

> **10000:1 Dynamic Contrast Ratio**
> Provides for darker black levels and better overall front-of-screen performance.

> **Multimedia enhanced**
> Save desk and workspace and enjoy rich, stereo sound with built-in 2Wx2 stereo speakers.

> **16:10 Wide-screen experience**
> 16:10 wide-format screen is ideally suited to maximize natural field of vision for intense game play, HD format video, and multiple document windows.

> **sRGB Color Management**
> The sRGB color management chip technology ensures color accuracy from screen to print when used with other sRGB-compliant peripherals.

> **ClearMotiv II® 5ms video response**
> Video response as fast as 5ms enables digital HD broadcast-quality video.

Works with Windows Vista™

10,000:1 Dynamic Contrast Ratio

Multimedia

MORE THAN 2000 AWARDS

VIEWSONIC
PRODUCTS, PROGRAMS, AND SERVICES

ViewSonic®
See the difference™

VA1918wm

19" Multimedia LCD With 10,000:1 Dynamic Contrast Ratio

Model No. VS12085

LCD	Type	19" Wide Color a-Si TFT Active Matrix LCD
	Optimum Resolution	1440 X 900
	Brightness	300 cd/m² (Typ.)
	Contrast Ratio	1000:1(Typ.) / 10000:1(Dynamic Contras Ratio)
	Viewing Angles	160° (Horizontal),160° (Vertical) (CR>10)
	Response Time	5ms
	Pixel Pitch	0.285mm(H) X 0.285mm(V)
	Panel Surface	Anti-glare, hard-coating (3H)
VIDEO INPUT	Analog	RGB Analog (75 ohms, 0.7 / 1.0 Vp-p)
	Sync	Separate Sync
	Frequency	FH : 30-82kHz , Fv : 50-75Hz
COMPATIBILITY	PC	PC Compatibles (from VGA up to 1440 X 900 Non Interlaced)
	Mac	Power Mac up to 1440 X 900
CONNECTOR	Analog	15 pin mini D-sub X 1
	Audio-in	3.5 mm Audio line-in
	Power	Built-in power Adapter, 3-Pin plug
AUDIO	Speaker	2W X 2
ERGONMICS	Tilt	20 ~ -5 degrees
POWER	Voltage	100-240VAC; 50/60 Hz (Switch)
	Consumption	32W (Typ.) / 36W (Max.)
CONTROLS	Basic	[1], [2], Power, Down[▼], Up[▲]
	OnView®	Auto Image Adjust, Contrast / Brightness, Color Adjust (sRGB, 9300K, 6500K, 5400K, User Color [R,G,B]), Information, Manual Image Adjust (Horizontal Size, H/V Position, Fine Tune, Sharpness), Setup Menu(Language Select, Resolution Notice, OSD Position, OSD
OPERATING CONDITIONS	Temperature	0°C - 40°C (32°F - 104°F)
	Humidity	10-90% (Non condensed)
DIMENSIONS (W X H X D)	Physical (mm)	440.2mm X 383.4mm X 195mm (With Base)
		17.3" X 15.1" X 7.7" (With Base)
WEIGHT	Net	4.4 Kg (9.7 lbs)
REGULATIONS		UL/CUL, FCC-B (ICES-003B), CB, CE, TCO'03, TUV/GS, TUV Ergo(covers ISO13406-2 & MPRII), TUV-S, VCCI, NOM, GOST-R (4 copies), HYGIENIC, Energy Star, CCC, BSMI, PSB, C-TICK, KTL/MIC, SASO, WEEE, RoHS, Ukraine
Wall Mount		Meet VESA (100mm X 100mm) Standards

Rev. 1a

ENERGY STAR

WEEE

RoHS COMPLIANT™

TCO'03 DISPLAYS
www.tcodevelopment.com

ISO 9001:2000
FM 40187

ISO 14001:1996
FM 40968

ViewSonic Corporation`s QMS & EMS have been registered to
ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic®
See the difference™

For more product information, visit us on the web at ViewSonic.com

20080506