




- CVC5725DNV** 4-9mm Varifocal Auto Iris Lens
- CVC5725DNVW** White Housing
- CVC5825DNV** 2.8-12mm Varifocal Auto Iris Lens
- CVC5825DNVW** White Housing
- CVC5925DNV** 9-22mm Varifocal Auto Iris Lens
- CVC5925DNVW** White Housing



Features

- 1/3" Sony Super-HAD II™ CCD
- 3D-DNR (Sense-up) - Sharp Image Under Ultra Low Light Level
- Intense-IR Function - No Saturation Image, Vivid Image
- Defect Function - Elimination of White Spots
- HSBLC (High Light Suppression BLC)
- Privacy Zone
- Third-Generation DSP Chip
- ICR - Removable IR Cut Filter
- Convenient On-Screen Display (OSD) Function Controls
- 32X Digital Zoom
- Dual Voltage (24VAC / 12VDC)
- 5 year warranty

Specifications

| | |
|-----------------------------|---|
| Image Sensor | 1/3" Sony Super-HAD II™ CCD |
| Resolution..... | 600 TV Lines |
| Minimum Illumination..... | 0.000006 Lux (IR LEDs ON) |
| Lens | 4-9mm auto iris varifocal lens (CVC5725DNV) |
| | 2.8-12mm auto iris varifocal lens (CVC5825DNV) |
| | 9-22mm auto iris varifocal lens (CVC5925DNV) |
| Number of IR LEDs | 33 |
| IR Range | Up To 65' |
| White Balance | ATW / AWB / Manual / AWC SET |
| Gain Control | High, Middle, Low, Off Selectable |
| S/N Ratio | 52dB (AGC Off, Weight On) |
| Backlight..... | OFF / HSBLC / BLC Selectable |
| Effective Pixels | 768(H) x 494(V) |
| Electronic Shutter Speed... | AUTO (1/50, 1/60 sec. ~ 1/100,000 sec.) |
| OSD | Built-In |
| 3 DNR..... | Off/On (1~50 Levels Adjustable) |
| D-WDR | Indoor / Outdoor / Off |
| Sharpness | 0~31' (Level Adjustable) |
| Privacy | On/Off (8 Zones) |
| Total Pixels | 811(H) x 508(V) |
| Scanning System..... | 2:1 Interface |

| | |
|---|---|
| Synchronization | Internal / Line-Lock |
| Motion Detection..... | On/Off (4 Zones, Alarm Output) |
| Sense-Up..... | Off / Auto (Selectable Limit x2 ~ x256) |
| Mirror | Off / Mirror / V-Rev / Rotate |
| Freeze | On/Off |
| D&N Selection | Color / BW / Auto/EXT |
| Digital Zoom: | On (x32) / Off |
| Blemish Compensation..... | Auto: 128 Point/Manual:4 Point Power |
| Dual Voltage | (24VAC / 12VDC) |
| Power Consumption | 12VDC 250mA (CDS OFF) |
| | 12VDC 700mA (CDS ON) |
| | 24VAC 100mA (CDS OFF) |
| | 24VAC 250mA (CDS ON) |
| Operating Temperature/ Humidity..... | 14° F ~ 122° F, RH 95% max. |
| Storage Temperature/ Humidity..... | -4° F ~ 140° F, RH 95% max. |
| Dimensions..... | 4.8" W x 4" H x 4.8" D |
| Weight | 1.2 lbs. |

Optional Mounting Accessories



Speco Technologies is constantly developing and improving products.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 7/13/11

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880

www.specotech.com