

VL-265PIR & VL-272PIR

speco technologies®

VL-265PIR & VL-272PIR

B/W Camera in Non-Operating and Operating PIR Housing



Our 1/3" B/W CCD camera is encased in a white PIR housing. It has a .5 lux sensitivity with 420 line resolution. It features a 3.6mm wide angle pinhole lens and built-in electronic shutter. A 12V DC power supply is included. A color version of this camera can be found under model number VL-565PIR and VL-572PIR (with working PIR). A fully adjustable wall/ceiling mount is included with this unit.

Specifications

	VL-265PIR	VL-272PIR (with working PIR)
Resolution	420 lines	420 lines
Minimum Illumination	.5 lux	.5 lux
Image Device	1/3" CCD image sensor	1/3" CCD image sensor
Electronic Shutter	Auto 1/60 - 1/100,000 seconds	Auto 1/60-1/100,000 seconds
Lens	3.6mm Hor. 74°, Vert. 57°	3.6mm Hor. 74°, Vert. 57°
Operating Temperature	14° F to 122° F	14°F to 122°F
Output	Video - BNC, power- DC jack	Video - BNC, power- DC jack
Power Consumption	120 ma	130 ma
Scanning Frequency	Hori zontal 15.75 kHz vertical 60 Hz	Horizontal 15.75 kHz vertical 60 Hz
Video Output Level	1.0 Vp-p, 75 ohm	1.0 Vp-p, 75 ohm
Video S/N Ratio	Greater than 46 dB	Greater than 46 dB
Housing	White ABS plastic with mount	White ABS plastic with working PIR and mount
Power Supply	Regulated 12V DC power supply included (UL and CSA listed)	Regulated 12V DC power supply included (UL and CSA listed)
Dimensions	2"L x 2.75"W x 4.75"H	2"L x 2.75"W x 4.75"H

**Note: The PIR electronics in the VL-572PIR and VL-272PIR (working PIRs) are for local indication and activation of recording devices only. Do not connect these devices to alarm systems that will report to local police or a central station.*

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880