

COFFEE BREWER USER GUIDE

Automatic & Pour-Over Airpot Coffee Brewers


Includes Instructions for
 Brewing Coffee, Cleaning the Brewer and Deliming the Water Tank



Automatic Brewer
 Model 8773 w/optional
 8881 Airpot




Pour-Over Brewer
 Model 8774 w/optional
 8881 Airpot



BREW COFFEE

CAUTION: Water from the brew head is extremely hot. Hot water can cause serious burns.



1. Preparation

Press TANK HEAT switch to ON.
 When READY TO BREW light glows, water in tank is at proper brewing temperature.

Place one (1) genuine Bloomfield paper filter in the brew chamber.
 Add a pre-measured amount of fresh coffee grounds.
 Gently shake the brew chamber to level the bed of grounds.
 Slide the brew chamber into place under the brew head.

2. Automatic Operation

CAUTION: Prevent overflow. Always use an EMPTY airpot to brew coffee. Overflowing hot coffee can cause serious burns.

Place the appropriate *EMPTY* airpot in place under the brew chamber.

BE sure "READY TO BREW" light is glowing.

Press the "BREW" switch. The solenoid will open for an amount of time determined by the timer setting, admitting a measured quantity of water into the basin.

3. Pour-over Operation



CAUTION: Prevent overflow. Always use an EMPTY airpot to brew coffee. Overflowing hot coffee can cause serious burns.

NOTE: Any Integrity™ or Koffee-King™ brewer can be used in the pour-over mode.

Place the appropriate *EMPTY* airpot in place under the brew chamber.

BE sure “READY TO BREW” light is glowing.

Fill an airpot or server, *identical to the one being used*, with tap water. Lift the pour-over cover and pour the entire contents of the container into the pour-over opening, which will fill the basin.

4. The Brew:

Water from the basin will displace a like amount of heated water from the tank. The hot water will be forced into the brew head where it will spray over the bed of grounds.

Freshly brewed coffee will begin to fill the airpot under the brew chamber. When the flow and all dripping stops, the coffee is ready to serve.

5. Empty the Brew Basket:



CAUTION: Brew chamber and contents will be very hot. Use the handle to manipulate the hot brew chamber.

Discard the grounds and the paper filter. Rinse the brew chamber under clear water.

When the “READY TO BREW” light glows, the brewer is ready for another brew cycle.



6. Hot Water Faucet (Automatic Brewers Only):

Hot water may be drawn from the hot water faucet at any time by lifting the red handle. Hot water flow will shut off automatically when the handle is released.

IMPORTANT:

Excessive use of the hot water faucet during a brew will lower the temperature of the brew water and compromise the quality of the coffee product.



DELIME THE WATER TANK



CAUTION - CHEMICAL BURN HAZARD

Deliming chemicals may be caustic. Wear appropriate protective gloves and goggles during this procedure. Never siphon deliming chemicals or solutions by mouth.

IMPORTANT:

This operation to be performed by qualified service personnel *ONLY!*

IMPORTANT:

DO NOT spill, splash or pour water or deliming solution into or over any internal component other than the inside of the water tank.

IMPORTANT:

DO NOT allow any internal components to come into contact with the deliming solution. Take care to keep all internal components dry.

PRECAUTIONS: Disconnect brewer from electric power.
Allow brewer to cool.

FREQUENCY: As required (Brewer slow to heat)

TOOLS: Deliming Solution
Protective Gloves, Goggles & Apron
Mild Detergent, Clean Soft Cloth or Sponge
Bristle Brush, Bottle Brush
Large Sink (or other appropriate work area)

-
1. Disconnect brewer from the electrical supply. Turn off the water shut-off valve and disconnect the water supply line from the brewer inlet fitting.
 2. Disconnect faucet plumbing. Remove the tank lid assembly.
 3. Remove the water tank from the brewer body by lifting straight up. Empty all water from the tank. Set the tank back into the brewer.
 4. Mix 2 quarts of deliming solution according to the manufacturer's directions. Carefully pour the deliming solution into the water tank. Lower the lid assembly back onto the tank. Allow to sit for 30 minutes, or as directed by the chemical manufacturer.
 5. At end of soaking period, remove lid assembly from tank. Thoroughly rinse internal components of lid assembly with clear water. Using a stiff bristle brush, scrub the heating element to remove lime and calcium build-up. Rinse with clean water. Store lid assembly in a safe location.
 6. Remove the tank from the brewer and empty. Using a stiff bristle brush, scrub the interior of the water tank to remove lime and calcium build-up. Rinse with clean water.
 7. Set the tank back into the brewer. Reassemble faucet plumbing to the tank lid, and the tank lid to the water tank. Make sure the gasket is properly in place, then reinstall the hold-down strap.