




LCD MONITOR

| | | | | | | |
|---------------------|--|------|-----------|----------|------|------|
| Display size | 17" (43,18 cm) WIDE | | | | | |
| Panel Type | Active Matrix TFT | | | | | |
| Brightness | 250 cd/m ² (typ.) | | | | | |
| Contrast (typ.) | 500:1 | | | | | |
| X-Contrast (dyn.) | - | | | | | |
| Pixel pitch | 0,255(H) x 0,255(V) mm | | | | | |
| Resolution (H x V) | WXGA+ 1440 x 900 | | | | | |
| Response time | 8 ms (typ.) | | | | | |
| View angles (CR>10) | H/V 140°/130° | | | | | |
| View angles (CR>5) | | | | | | |
| Display colors | 16,2 Mio colors | | | | | |
| Display Surface | Anti-Glare | | | | | |
| Input 1 | VGA | | | | | |
| Input 2 | | | | | | |
| Input 3 | | | | | | |
| Headphone | | | | | | |
| Speakers | | | | | | |
| Supply | AC 100~240V, 50~60Hz | | | | | |
| Consumption | On: | 32 W | Stand-by: | <2 W | Off: | <1 W |
| Operation Temp/Hum | 5 ~ 35°C | | | 10 ~ 85% | | |
| Dimension (W*D*H) | 400 x 185 x 360 mm | | | | | |
| Net weight | 2,9 kg | | | | | |
| Tilt | 0°~ 20° | | | | | |
| Kensington Lock | ✓ | | | | | |
| VESA mounting | VESA Standard, 75mm | | | | | |
| On screen display | EN,TC,DE,FR,ES,IT,NL,SC,JS,KR, RU | | | | | |
| Safety | CE, FCC, BSMI, C-TICK, VCCI, CB, UL/CUL, Nemko-GS, CCC, GOST | | | | | |
| Emission | MPR II | | | | | |
| Power saving | EPA Energy Star | | | | | |
| Extras 1 | | | | | | |
| Extras 2 | | | | | | |
| Extras 3 | | | | | | |
| EAN | 4710859555359 | | | | | |
| incl Accessory | Cables (power, VGA, Audio), users manual (CD), quickstart guide (paper), warranty card | | | | | |



© HANNspree Europe GmbH. Information in this document is subject to change without notice. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. Screenshots are simulated.