COMPLIANCE INFORMATION

UL Listed C-UL Listed (Canada) CISPR22/EN55022 Class A + EN55024 CE Mark

FCC Regulations

This equipment has been tested and found to comply with the limits for a class A digital device, pursuant to part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference, in which case the user will be required to correct the interference at the user's own expense.

Canadian Regulations

This digital apparatus does not exceed the Class A limits for radio noise for digital apparatus set out on the radio interference regulations of the Canadian Department of Communications.

Le présent appareil numérique n'émet pas de bruits radioélectriques dépassant les limites applicables aux appareils numériques de la class A prescrites dans le Règlement sur le brouillage radioélectrique édicté par le ministère des Communications du Canada.

European Regulations

Warning

This is a Class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Achtuna !

Dieses ist ein Gerät der Funkstörgrenzwertklasse A. In Wohnbereichen können bei Betrieb dieses Gerätes Rundfunkstörungen auftreten, in weichen Fällen der Benutzer für entsprechende Gegenmaßnahmen werantwortlich ist.

Attention !

Ceci est un produit de Classe A. Dans un environment domestique, ce produit risque de créer des interférences radioélectriques, il appartiendra alors à l'utilsateur de prende les measures spécifiques appropriées



CAUTION: RJ connectors are NOT INTENDED FOR CONNECTION TO THE PUBLIC TELEPHONE NETWORK. Failure to observe this caution could result in damage to the public telephone network.

Der Anschluss dieses Gerätes an ein öffentlickes Telekommunikationsnetz in den EG-Mitgliedstaaten verstösst gegen die jeweligen einzelstaatlichen Gesetze zur Anwendung der Richtlinie 91/263/EWG zur Angleichung der Rechtsvorschriften der Mitgliedstaaten über Telekommunikationsendeinrichtungen einschliesslich der gegenseitigen Anerkennung ihrer Konformität.



T1/E1 Twisted-Pair Copper to Fiber

Slide-In-Module Media Converters

CSDTF10xx*-100 **USER'S GUIDE**

TRANSITION Networks CSDTF10xx-100 series media converters, designed to be installed in a PointSystem[™] Conversion Center[™] chassis, encode and decode T1 or E1 twisted-pair copper signals over duplex fiber-optic cable to extend the distance and transmission reliability of high speed T1 or E1 data traffic.

CSDTF1011-100

Provides an RJ-45 twisted pair copper connector for T1 or E1 signals and a set of RX/TX ST connectors to 850 nm multimode duplex fiber-optic cable.

CSDTF1012-100

Provides an RJ-45 twisted pair copper connector for T1 or E1 signals and an RX/TX ST connector to 1300 nm singlemode duplex fiber-optic cable.

CSDTF1013-100

Provides an RJ-45 twisted pair copper connector for T1 or E1 signals and an RX/TX SC connector to 850 nm multimode duplex fiber-optic cable.

CSDTF1014-100

Provides an RJ-45 twisted pair copper connector for T1 or E1 signals and an RX/TX SC-SM connector to 1300 nm singlemode duplex fiber-optic cable.





Provides an RJ-45 twisted pair copper connector for T1 or E1 signals and an RX/TX SC-LH connector to 1300 nm singlemode duplex fiber-optic cable.

CSDTF1022-100 (long haul)

Provides an RJ-45 twisted pair copper connector for T1 or E1 signals and an RX/TX ST connector to 1300 nm singlemode duplex fiber-optic cable.

Trademark Notice

All registered trademarks and trademarks are the property of their respective owners.

Copyright Restrictions

© 2001, 2002 TRANSITION Networks.

All rights reserved. No part of this work may be reproduced or used in any form or by any means graphic, electronic, or mechanical - without written permission from TRANSITION Networks. Printed in the U.S.A.

*In CSDTF10xx model designation, 10 represents the T1 or E1 RJ-45 connector; xx represents the selectable fiber connector installed on the media converter.

CSDTF10xx IN THE NETWORK

NOTE: THE CSDTF10xx REQUIRES A CSU BETWEEN THE MEDIA CONVERTER AND THE PUBLIC TELEPHONE NETWORK.



TECHNICAL SPECIFICATIONS

| Standards | Emissions: CISPR A | |
|-------------------|---|---|
| | T1/E1 Physical Layer: ITU-T, ANSI, AT&T, ETSI | |
| Dimensions | 2.9" x 4.8" x 1.4" | |
| Weight | 8 oz (approximate) | |
| Power Consumption | 5 watts | |
| Environment | Typical Operating Temperature*: | 0° to $50^\circ C$ (32° to 122°F) |
| | Storage Temperature: | -20° to 85°C (-4° to 185°F |
| | Humidity | 10-90%, non condensing |
| | Altitude | 0-10,000 feet |
| Warranty | Lifetime | |

*Operating temperature range for this Slide-In-Module depends on the physical characteristics and the installation configuration of the TRANSITION Networks chassis in which this Slide-In-Module will be installed. See the User's Guide *for the chassis in which this Slide-In-Module will be installed* for a discussion of temperature-related installation constraints.

| Name of Mfg: | Transition Networks | linnoapolis MNI 55244 LISA |
|------------------------------------|---|----------------------------------|
| Model: | CSDTF10xx Series Copper-1 | o-Fiber Media Converter |
| Part Number: | CSDTF1011-100, CSDTF10 CSDTF1022-100 | 12-100, CSDTF1013-100, |
| Regulation: | EMC Directive 89/336/EEC | |
| Purpose: To dec conformity with | clare that the CSDTF10xx to which the following standards. | ch this declaration refers is in |
| EN 55022:1994; | EN 55024:1998; FCC Part 15 Class | A; EN 60950 A4:1997; UL 19 |
| I, the undersigned, | hereby declare that the equipment s | becified above conforms to the |

NOTE: T1/E1 MEDIA CONVERTERS MUST BE USED IN PAIRS. A TRANSITION Networks CSDTF10xx chassis media converter can be used with another CSDTF10xx chassis media converter, a SSDTF10xx stand-alone media converter, or with a previous model TRANSITION Networks T1/E1 media converter, such as a C/T1E1-CF-01 or a T1E1-CF-01.

Features

- Media converter is framing independent (as ESF vs D4) and supports all common line codes, (AMI, B8ZS, HDB3).
- Dry relay contacts allow media converter to be tied into separate alarm circuit
- All Ones Insertion (AIS) on loss of signal at copper and/or fiber interface.

CABLE SPECIFICATIONS (continued)

Twisted-Pair Copper Cable

Twisted pair connection requires two active pairs. The two active pairs in a T1/E1 network are pins 1 & 2 and pins 4 & 5. Use only dedicated wire pairs (such as blue/white & white/blue, orange/white & white/orange) for the active pins.

Category 3 or better twisted-pair copper wire is required. Either shielded twisted-pair (STP) or unshielded twisted-pair (UTP) can be used.

T1:

| Gauge | 24 to 22 AWG |
|---------------------------------------|-----------------------------|
| Attenuation | 2.6 dB/100 meters @ 1.0 MHz |
| Differential Characteristic Impedance | 100 Ω ±10% |

E1:

Gauge24Attenuation2.Differential Characteristic Impedance12

24 to 22 AWG 2.6 dB/100 meters @ 1.0 MHz 120 Ω ±10%

Dry-Contact Relay

RJ-45 dry-contact relay opens if power, signal detect/copper or signal detect/fiber are lost.

Operational rating on pins 3 and 6: 0-30VDC maximum 1A



Switch-Selectable Configurations

T1 COPPER RJ-45

Configured as either "long haul" or "short haul" on 100 ohm cable, with a variety of selectable distance settings.

E1 COPPER RJ-45

Configured as either "long haul" or "short haul" on 120 ohm cable.

STRAIGHT-THROUGH/CROSSOVER RJ-45

Allows straight-through cable to be used where crossover-configuration cable is required.

Switch-Selectable Functions

LOOPBACK TEST FUNCTION

A loopback switch facilitates installation and network debug procedures. The path for the CSDTF10xx loopback is shown:



TRANSMIT ALL ONES FUNCTION

A selectable Transmit All Ones switch on the fiber interface and on the twisted-pair interface allows for insertion of an "all ones" pattern on that interface when *signal detect* is lost, which creates an alarm condition at the equipment connected to the interface.

INSTALLATION

CAUTION: Wear a grounding device and observe electrostatic discharge precautions when setting switch and when installing Media Converter Slide-in-Module in the Media Conversion Center. Failure to observe this caution could result in damage to, and subsequent failure of, the Media Converter Slide-in-Module.

Set Loopback Test Switch

NOTE: The Loopback Test switch, located on Media Converter Slide-in-

Module front panel, allows the network administrator to enable a loopback test for installation and network debug procedures.

Loop

Use small flatblade screwdriver or similar device to set recessed switches. Refer to drawing for switch locations.

Set 3-Position Jumper

NOTE: Jumper is located on Media Converter Slide-in-Module circuit board.

Use small needle-nosed pliers or similar device to set jumper. Refer to drawing for jumper positions.



SOFTWARE MODE

S

н

HARDWARE Converter mode is determined by 4-position switch settings below.

SOFTWARE Converter mode is determined by mostrecently-saved on-board microprocessor settings.

Set MDI/MDI-X Switch

NOTE: The MDI/MDI-X switch, located on Media Converter Slide-in-Module circuit board, allows the network administrator to use straight-through cable in installations where crossover-configuration cable is required.

Use small flatblade screwdriver or similar device to set recessed switches. Refer to drawing for switch settings.



Set 8-Position Switch

NOTE: The eight-position switch, located on Media Converter Slide-in-Module circuit board, allows the network administrator to configure the media converter for network conditions.

Use small flatblade screwdriver or similar device to set recessed switches for site installation. Refer to drawings at right for eight-position switch settings.

CABLE SPECIFICATIONS

Fiber Cable

Bit error rate: MULTIMODE

| Fiber Optic Cable Recommended: | | |
|--------------------------------|--|--|
| Optional: | | |

CSDTF1011-100

Fiber Optic Transmitter Power: Fiber Optic Receiver Sensitivity: Typical Maximum Cable Distance*: CSDTF1013-100 Fiber-optic Transmitter Power: Fiber-optic Receiver Sensitivity: Typical Maximum Cable Distance*:

62.5 / 125 µm multimode fiber 100 / 140 µm multimode fiber 85 / 125 µm multimode fiber 50 / 125 µm multimode fiber 850 nM min: -14.0 dBm max: -12.0 dBm min: -25.0 dBm max: -12.0 dBm 2 kilometers 850 nM min: -14.0 dBm max: -12.0 dBm min: -25.0 dBm max: -12.0 dBm 2 kilometers

≤10-9

SINGLEMODE

Fiber Optic Cable Recommended: CSDTF1012-100 Fiber-optic Transmitter Power: Fiber-optic Receiver Sensitivity: Typical Maximum Cable Distance*: CSDTF1014-100 Fiber-optic Transmitter Power: Fiber-optic Receiver Sensitivity: Typical Maximum Cable Distance*: CSDTF1015-100 (long haul) Fiber-optic Transmitter Power: Fiber-optic Receiver Sensitivity: Typical Maximum Cable Distance*: CSDTF1022-100 (long haul) Fiber-optic Transmitter Power: Fiber-optic Receiver Sensitivity: Typical Maximum Cable Distance*:

| 9 µm singlemode f | iber |
|-------------------|------------------|
| min: 21.0 dPm | max: 140 dPm |
| min: 25.0 dBm | max: 14.0 dBm |
| O kilomootomo | 111dX 14.0 UDITI |
| 8 Kilometers | |
| 1300 NIVI | |
| min: -21.0 dBm | max: -14.0 dBm |
| min: -27.0 dBm | max: -14.0 dBm |
| 8 kilometers | |
| 1300 nM | |
| min: -15.0 dBm | max: -5.0 dBm |
| min: -27.0 dBm | max: -14.0 dBm |
| 15 kilometers | |
| 1300 nM | |
| min: -15.0 dBm | max: -5.0 dBm |
| min: -25.0 dBm | max: -14.0 dBm |
| 15 kilometers | |

*Actual distance dependent upon physical characteristics of network installation.

FAULT ISOLATION and CORRECTION

If the media converter fails, isolate and correct the failure by determining the answers to the following questions and then taking the indicated action:

1. Is the P(o)W(e)R LED on the media converter illuminated?

NO

- Is the media converter inserted properly into the chassis?
- Is the power cord properly installed in the chassis and at the external power source?
- Does the external power source provide power?
- Contact Technical Support: (800) 260-1312.

YES

- Proceed to step 2.
- 2. Is the SDF (Signal Detect/Fiber) LED illuminated?

NO

- Check fiber cables for proper connection.
- Verify that TX and RX cables on media converter are connected to RX and TX ports, respectively, on other media converter.
- Contact Technical Support: (800) 260-1312.

YES

• Proceed to step 3.

3. Is the SDC (Signal Detect/Copper) LED illuminated?

NO

- Check twisted pair cables for proper connection.
- Check RJ-45 Pinning Switch for correct twisted pair cable configuration.
- Check integrity of device attached to media converter by twistedpair cable.
- Contact Technical Support: (800) 260-1312/(800) LAN-WANS. **YES**
- Contact Technical Support: (800) 260-1312/(800) LAN-WANS.

NOTE:

T1 must be selected (LEFT switch set #4 UP) for RIGHT switch set to have any effect.

If E1 is selected (LEFT SWITCH SET #4 DOWN), RIGHT SWITCH SET is ignored and the default is E1 $3.0V \ 120\Omega$ cable.

If T1 and short haul are selected (LEFT SWITCH SET #3 UP, #4 UP), but RIGHT SWITCH SET is not set to a valid short haul value, the short haul default is DSX-1 0'-133' cable

If T1 and long haul are selected (LEFT SWITCH SET #3 DOWN, #4 UP), but RIGHT SWITCH SET is not set to a valid long haul value, the long haul default is Odb





T1/E1 Selection

UP= T1

LEFT SWITCH SET



INSTALLATION (continued)

Install Slide-In-Module in PointSystem[™] Chassis

CAUTION: Any Slide-in-Module installation slot in which a Media Converter Slide-in-Module is NOT installed MUST have a protective plate instead. Failure to observe this caution will void Class A and/or Class B compliance.

NOTE: Install Media Converter Slide-in-Modules in any slot, in any order.

 Carefully slide Media Converter Slide-in-Module into installation slot, aligning Media Converter Slide-in-Module with installation guides.
NOTE: Ensure that Slide in Medule is firmly conted against backplane.

NOTE: Ensure that Slide-in-Module is firmly seated against backplane.

- 2. Secure Slide-in-Module by securing panel fastener screw (attached to Slide-in-Module) to chassis front.
- 3. Install protective plate at EVERY Slide-in-Module installation slot in which a Media Converter Slide-in-Module is not installed by securing attached protective plate panel fastener screw to chassis front.

Install Cable

COPPER

T1 100 OHM (RJ-45 CONNECTOR)

- 1. Locate or build twisted-pair cables that are compliant with specifications on page 10, with RJ-45 plug connectors at both ends.
- 2. Ensure that MDI/MDI-X switch is set according to network conditions.
- 3. Connect RJ-45 plug connector at one end of cable to media converter RJ-45 jack connector.
- 4. Connect RJ-45 plug connector at other end of cable to network equipment.

FIBER

 Locate or build fiber cables that are compliant with specifications on page 9, with male two-stranded TX to RX connectors installed at both ends.



- 2. Connect cable with connector installed at TX location on media converter to RX location on attached device.
- 3. Connect cable with connector installed at RX location on media converter to TX location on attached device.

Power the Slide-In-Module

NOTE: The Slide-In-Module is powered through the Conversion Center ${}^{\scriptscriptstyle \mathsf{TM}}.$

OPERATION

After installation, the media converter should function without operator intervention.

Status LEDs

Use the status LEDs to monitor media converter operation in the network.

SDC Signal Detect/Copper - Steady LED indicates twisted-pair copper link is up.

Flashing LED (once/second) indicates transmitting on link if other link is down.



- Flashing LED (5 times/second) indicates All Ones detected on Link.
- SDF Signal Detect/Fiber Steady LED indicates fiber link is up.

Flashing LED (once/second) indicates transmitting on link if other link is down.

Flashing LED (5 times/second) indicates All Ones detected on Link.

P(o)W(e)R Steady green LED indicates connection to external AC power.

Using SNMP*

Use SNMP at an attached terminal or at a remote location to:

- Monitor media converter by monitoring:
 - Media Converter Power
 - Fiber Link Status
 - Copper Link Status
 - Hardware Switch settings
 - AIS detected on Fiber
 - AIS detected on Copper
- Enter network commands that: Enable/disable Loop-back on Fiber Enable/disable Transmit All Ones on Fiber when Copper is down

Enable/disable Transmit All Ones on Copper when Fiber is down Power Down Media Converter.

*See the on-line documentation that comes with TRANSITION Networks FocalPoint^m software for applicable commands and usage.