



Model #: OR500LCDRM1U

UPC: 649532715015

MSRP: \$179.99

The Smart App Intelligent LCD Series is designed to protect office servers, PCs, graphic workstations, and commercial electronics.

The Intelligent Crystal-Blue LCD diagnostic panel gives administrators immediate, real-time information about vital UPS performance factors. LCD diagnostics include Input/Output Voltage, Battery Capacity, Estimated Runtime, Load Level, On Battery, Overload, and Silent Mode.

The OR500LCDRM1U has 6 outlets, USB/Serial communication ports, and RJ11/RJ45 network protection. Automatic Voltage Regulation (AVR) ensures that all your connected equipment is receiving clean power and maintains a safe voltage level. PowerPanel Business Edition software (included) automatically saves and closes open files and shutsdowns the PC in an intelligent and orderly manner.

CyberPower also carries a 3-year unlimited warranty, has professional Technical Support, and offers a lifetime Connected Equipment Guarantee of \$300,000.

- **Intelligent LCD Diagnostic Display:** The innovative front panel LCD can be used to display detailed information on the status of the UPS and current power conditions. The LCD displays 11 different diagnostics: Input/Output Voltage, Battery Capacity, Estimated Runtime, Load Level, On Battery, Overload, Silent Mode, and more.
- **GreenPower UPS™** - GreenPower UPS™ technology significantly reduces UPS energy costs by bypassing the AVR transformer when incoming AC power is clean. This not only dramatically reduces utility consumption, but also reduces heat dissipation and system noise.
- **Automatic Voltage Regulation (AVR)** - AVR technology will stabilize the AC signal and maintain a safe voltage level without switching to battery-mode. This conserves battery life, and delivers a cleaner signal to your connected equipment.
- **Microprocessor-based Digital Control** – Digital routing is maintained through a network of integrated circuitry and discrete values used for internal system processing, which significantly increases efficiency and responsiveness.
- **EMI/RFI** - Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or “humming” that occurs over telephone lines or stereo electronics.
- **USB Connectivity** - HID compliant USB port enables full integration with built-in power management and auto shutdown features of Windows, Linux, and Mac OS X.
- **Metal Housing** – Rigid metal construction allows for placement in areas with a demanding environment.
- **Audible Alarms** - Audible tones identify when the unit is running off battery power, unit overloads, and low battery.
- **Resettable Circuit Breaker** - Convenient unit reset switch in case of an overload.
- **3-year Warranty** - CyberPower will replace damaged units if within 3 years of purchase date. We stand behind our products and guarantee quality. CyberPower also offers a #1 rated technical support team that will assist you with product, installation, or warranty concerns --- Free of Charge!
- **ISO & Safety Certifications** - All CyberPower manufacturing facilities are ISO-9001 Quality Tested. Our products are also certified by the FCC, cUL, and UL.
- **PowerPanel Business Edition Management Software** – In the event of a power outage, PowerPanel will safely save and close your open files and shut your computer down in an orderly, intelligent manner. The software allows users to view detailed information about their electrical power and the vitals of the UPS. It includes configurable system notifications, automatic self tests, adjustable high/low voltage warnings, event/data logging, and scheduled shutdowns.
- **Windows compatibility** - Our power management software has been fully tested and is compatible with Windows 2000, 2003, XP, and Vista x32 & x64.



Technical Specifications

General	
Model #	OR500LCDRM1U
UPS Topology	Line-Interactive
Energy Saving	Yes - Green-UPS Energy Saving Technology
Input	
Voltage	90 - 140V
Frequency	57 - 63Hz
Plug Type	NEMA 5-15P
Cord Length	10 ft
Output	
VA	500
Watts	300
Automatic Voltage Regulation	Yes
On Battery Waveform	Simulated Sine Wave
Outlets - Total	6
Outlets - Battery & Surge	4 x NEMA 5-15R
Outlets - Surge-Only	2 x NEMA 5-15R
Transfer Time	4 ms
Battery	
Runtime at Full-Load	3 Minutes
Runtime at Half-Load	12 Minutes
Battery Specification	2 x 6V/7AH
Surge Protection and Filtering	
Surge Suppression	1030 Joules
Phone / Ethernet RJ11 / RJ45	1 x RJ11/45 Combo (One-in/One-out)
Coax Protection RG6	None
Management & Communications	
Indicators	Multifunction LCD Readout
USB Port	1 x HID Compliant
Serial Port	1 x DB9
Software	PowerPanel Business Edition
SNMP / HTTP Remote Monitoring	Yes [With optional RMCARD201]
Physical	
Dimensions (WxHxD)	17.25" x 1.75" x 9.25"
Weight	18 lbs.
Warranty	
Product Warranty	3-year warranty. Free Tech Support.
Connected Equipment Guarantee	Lifetime
CEG Amount	\$300,000