

XTC 1

Featuring an ALUXX SL butted aluminum frameset, the XtC series provides the aspiring racer or performance-minded trail rider the essentials for off-road riding.

MOUNTAIN PERFORMANCE HARDTAIL



SPECIFICATIONS

FRAME	SIZES	XS, S, M, L, XL
	COLORS	Red/Brushed
	FRAME	ALUXX SL Aluminum
	FORK	Marzocchi MZ Race, 100mm w/ lockout
	SHOCK	N/A
COMPONENTS	HANDLEBAR	6061Al low rise
	STEM	Alloy, 10 degree rise
	SEATPOST	Alloy 350x30.9mm
	SADDLE	WTB Silverado Race
	PEDALS	Shimano PD-M505
DRIVETRAIN	SHIFTERS	SRAM X5, trigger
	FRONT DERAILLEUR	Shimano Deore
	REAR DERAILLEUR	SRAM X7
	BRAKES	Hayes Stroker Ryde, 160F/160R
	BRAKE LEVERS	Hayes
WHEELS	CASSETTE	Shimano HG-50, 11/34 9-speed
	CHAIN	Shimano HG-73
	CRANKSET	TruVativ 5D 3.1, 22/32/42
	BOTTOM BRACKET	TruVativ Powerspline
	EXTRAS	

Specifications and availability subject to change without notice.

FRAME TECHNOLOGY

Giant's all-new XtC frames feature ALUXX SL butted alloy tuned for minimal weight and maximum strength—perfect for the XC racecourse or cruising your favorite local singletrack.

KEY UPGRADES (OVER XTC 2)

- Marzocchi MZ Race, 100mm suspension fork
- SRAM X.7 trigger shifting, X.5 rear derailleur
- Hayes Stroker Ryde disc brakes
- Kenda Small Block Eight tires

FRAME GEOMETRY

Actual Frame Size	Head Angle	Seat Angle*	Toptube**	Headtube	Chainstay	Wheelbase	Standover Height***
inches	degrees	degrees	inches	inches	inches	inches	inches
XS/14.5	70.5	74.0	21.7	4.6	16.7	41.2	30.3
S/16.0	70.5	73.5	22.6	4.6	16.7	41.8	30.6
M/18.0	70.5	73.0	23.4	5.1	16.7	42.4	31.4
L/20.0	70.5	73.0	24.2	5.7	16.7	43.2	32.4
XL/22.0	70.5	73.0	25.0	6.3	16.7	44.0	33.5

*Seat angle is actual

**Toptube is measured from the center of the headtube horizontally back to the top of the effective extension of the seattube

***Standover height is based on the largest size tire that will fit the bike, not necessarily the included size tire