


DC-8330i

8.0 MegaPixel

- ▶ 8.0 MegaPixel CCD sensor
- ▶ 3x optical zoom, 4x digital zoom
- ▶ 3.0" TFT-LCD (230K), 960 x 240 dots
- ▶ 21 scene modes

Highlights

- ▶ ASM (Aperture priority, Shutter priority, Manual exposure mode)
- ▶ Photo stabilizer
- ▶ Face Tracking
- ▶ ISO 1600
- ▶ SDHC compatible (4 GB)
- ▶ AF lamp
- ▶ Histogram



TÜV Rheinland, Germany, a worldwide leader of technical services and quality control, tested the DC-8330i and certified with it's logo a rating of 'GOOD'. In detail:

- Handling:	EXCELLENT
- Workmanship:	GOOD
- Instruction manual:	GOOD



- Handling tested
- Instruction manual tested
- Workmanship tested

DC-8330i

Technical details

► Image sensor

Sensor	8.0 MegaPixel CCD
--------	-------------------

► Optics

Lens and type	6 elements in 5 groups, (incl. 3 pcs aspherical)
Focal length	f = 6.2 (W) ~ 18.6 (T) mm
Equivalent to 35mm camera	37.5 (W) ~ 112.5 (T) mm
Brightness	F/2.8 (W), F/5.2 (T)
Shutter speed	1/2000 ~ 8 sec.

► Zoom

Digital zoom	4x
Optical zoom	3x

► Focusing

Focus range	T: 40 cm ~ Infinity, W: 15 cm ~ Infinity
-------------	---

► Exposure

Exposure compensation	-2EV to +2EV in 1/3 step, (-2.0, -1.7, -1.3, -1.0, -0.7, -0.3, 0.0, +0.3, +0.7, +1.0, +1.3, +1.7, +2.0)
Exposure meter	Center-weighted, multi, spot
ISO	Auto, 50, 100, 200, 400, 800, 1600
White balance	Daylight, cloudy, tungsten, fluorescent_H, fluorescent_L, customer
Exposure control	Automatic/manual

► Viewfinder / LCD

Colour display	3.0" TFT-LCD, 960 x 240 dots
----------------	------------------------------

► Memory

Memory internal	16 MB
Memory external	2GB (SD-card) and 4GB (SDHC)

► Resolution

Still image	3264 x 2448 (default), 3264 x 2176 (3:2), 3200 x 1800 (16:9), 2816 x 2112, 2304 x 1728, 1600 x 1200, 640 x 480
Video	848 x 480 (16:9), 640 x 480, 320 x 240, 30 fps

► File format

Still image	JPEG, EXIF 2.2, support DPOF, PictBridge compatible
Video	AVI
Audio	WAV

► Scene mode

Scene mode	Sunset, snow, soft skin, sports, soft flowing water, backlight, building, movie, portrait, party, fireworks, food, night scene, night scene portrait, Q mode, landscape, kids, text, candle, voice Rec, program
------------	--

► Flash mode

Flash light	Auto, auto w/Red-eye reduction, slow sync. w/Red-eye reduction, forced On, Off; flash range: 2.3 m (W), 1.3 m (T)
-------------	--

► Interface

USB	2.0
TV out	PAL/NTSC

► Power source

Power supply	2x AA Alkaline batteries
Auto power off	1 min., 3 min., 5 min.

► Others

Camera dimensions	approx. 95 x 61 x 24 mm (W x H x L)
Housing	Highend plastic
Weight	146 g (w/o batteries)
Menu language	English, German, Spanish, French, Italian, Portuguese, Dutch, Swedish, Greek, Czech, Polish, Turkish, Hungarian, Russian, Arabic, Romanian, Thai, Japanese, Simple Chinese, Korean, Traditional Chinese

► Accessories

	USB cable, AV cable, 2 x AA batteries, wrist strap, pouch, CD-Rom
--	--

► Logistics

Item number	06852
Bar code	4004781068521
Packaging size	8.7 x 16.1 x 22.5 cm (W x H x L)
Packaging unit	5
Weight	approx. 706 g
Weight (boxed unit)	approx. 4.1 kg
Dimensions ship box	19 x 25 x 46 cm (W x H x L)

Dealer stamp

AgfaPhoto is used under license of Agfa-Gevaert NV&Co. KG. Agfa-Gevaert NV&Co. KG does not manufacture this product or provide any product warranty or support. For service, support and warranty information, contact the distributor or manufacturer. All other brands and product names are registered trademarks of their respective owners. Product design and technical features can be changed without notice.