
Water















Instant Kitchen Convenience

- Perfectly chilled water from 36°F to 40°F
- One Year replacement warranty
- Air-cooled designed to fit under a sink
- Compact, economical and easily installed
- Stainless steel storage tank



SPECIFICATIONS AND FEATURES

CAPACITY

1.1 gallons per hour 26.4 gallons per day

TEMPERATURE RANGE

From 36°F to 40°F, perfectly chilled water

COOLING ELEMENT

120 VAC, R-134a Refrigerant

BUILT TO LAST

Insulated, stainless steel tank for long life Welded water lines to eliminate corrosion and assure leak proof operation 1 year limited warranty

TANK DIMENSIONS

HEIGHT WIDTH DEPTH 14.75" 10.3" 8.72"

Due to continued product improvement, specifications may be subject to change without notice.









Cool Water® Designer Faucets

Regatta Series

Available in Chrome (C310-CH), Brass (C310-BR), Satin Nickel (C310-SN), Biscuit (C310-BQ), White (C310-WT) and Oil Rubbed Bronze (C310-ORB)



Bainbridge Series

Available in Chrome (C320-CH), Brass (C320-BR), Satin Nickel (C320-SN), Biscuit (C320-BQ), White (C320-WT) and Oil Rubbed Bronze (C320-ORB)



Windermere Series

Available in Chrome (C330-CH), Brass (C330-BR), Satin Nickel (C330-SN), Biscuit (C330-BQ) and White (C320-WT)



Crescent Series

Available in Chrome (C340-CH), Brass (C340-BR), Satin Nickel (C340-SN) and Oil Rubbed Bronze (C340-ORB)



Montlake Series

Available in Chrome (C350-CH), Brass (C350-BR) and Satin Nickel (C350-SN)

Inline Water Filtration Systems

FM DWS 1500 FM DWS 750 NSF Certified **Filter** Systems Cleans Cleans 1500 750 Gallons Gallons of Water of Water

- Provides fresh tasting water, coffee and beverages
- Advanced filtration and contaminant absorption system reduces sediment, rust, chlorine taste and odor, led and cysts that may be present in the water supply
- Sanitary Quick Change filter cartridges for easy installation and service - no spills, no mess
- 1/4 turn quick-change filter design eliminates risk of injury and physical challenges associated with under-sink appliance maintenance